

Rueger

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Rueger Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Rueger T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunulmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
0-60°C, TGL=400mm, TWL=250mm,	Swivelling Cap Connection U TI113-611 TH1130U/0-60°C/TGL=400mm/TWL=250mm
Modell S80-TC	S80=S=T=K=N=1=2=3=7=O=R=C3=15000=350=_=5P=T S80 thermocouple sensor with mineral insulated cable S Version TC standard T Diameter measuring insert 1/4" or 6.35 mm K Type K thermocouple - measuring range: -200 ... +1100°C N Accuracy class according to ANSI MC 96.1: Standard class 1 sensor element isolated 2 measuring circuit double 3 Sheath material Inconel 600/ 2.4816 7 Cable connection not stripped O Extension cable PTFE (Teflon) R Extension cable: armored outer sheath, without anti-kink spring C3 process connection compression fitting 1/2 NPT, AISI 316 15,000 cable length Lc= 15,000 mm 350 sensor length L= 350 mm _ Without certificate 5P calibration certificate 5 points T marking with stainless steel tag without transmitter
	100=AM=074=E=255=0_160C=_=EAYW=EN Class 1 according to EN 13190 Case, connection and stem stainless steel Bayonet style case, protection IP66 100 Dial size 100 mm AM Thermometer model A, stem

ASHCROFT® Bimetal Thermometer Model A	diameter 6 mm 074 Adjustable union connection 1/2 NPT female E Every angle connection 255 Stem length 255 mm Standard instrument glass window EA External zero adjustment YW Case and ring material stainless steel 316L EN Product documentation in English Range: 0/160 °C
THERMOMETER,RUEGER,THI100A+AMU,380 MM	Thermometers, Dial, Bi metal Diameter, dial 100 mm Type, dial connection 1/2 inch NPT Material specification, case AISI 303/1.4305 Diameter, stem 6 mm Length, stem 380 mm Calibration units, scale Degrees Celsius Temperature range from 0 to 160 Manufacturer RUEGER Manufacturer's catalog No. THI100A+AMU
Pbx100xa	
Pmd150xk General Purpose Gauge	
Pbx100xa Rohrfedermanometer	
Tmi100a Amx+ Tw10412	
Tmi100a+amx	
Tmi100a + Amu	
Ppc 96x192mm	
Pbx150xa Rohrfedermanometer	
Tco075	
Pmd100xk Differential Pressure Indicator	
Typ Tmi100a + Amx, L1 = 350 Mm	
Pmd150xk	
Pbx150xa	
Pmx150xa,Ip55	
S01.1.81baba.B--X-.-.-.-.-	
Thi130a+amx	
Pmd100xk	
R1/2quot;Npt,4quot;,8x470mm	
Tmi100u	
Tta070/770	
Tmi100a + Amx, L1 = 250 Mm	
Rppy -1 - +3.5 Barg 2? Npt Female 150 Rf	
Pbx150xa,(Dial 150mm),Ip67	