



Sab Bröckskes

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Sab Bröckskes Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Sab Bröckskes T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	A¼ıklama
01410705	
01880707	
07749218	
07849213	
1880705	
1890805	
2841404	
38340720	
38669004	
3921425	
62240407	
67100507	

67450275	
7250004	
7537431-007 oem	
7742507	
CC 600 CY	
D-VIERSEN	
D-VIERSON S200 36X0,5MM2	
L0127-0305	
L0392-90101	
L07840375	
L3696-2604	
L5260-0325	
L6166-0187	
Ò404-036-700	
SAB 0784-9008	
SL 803 C	
SL 842 C	
SPECIAL 50 – 200 07649213	
T021-007-040	
T055-046-529	
T056-000-771	
T207-058-597	
T207-058-598	
T233-048-279	
T433-027-824	
T521-029-387	
T545-009-590	
T999-029-444	
TBS5 RTD PT100	500mm
TBS5 RTD PT100	200mm T810-030-411

MODEL:TBS RTD PT100	CONNECTION TYPE: RTD 3 WIRE (Main hose length 2500mm) OPERATING TEMPERATURE: 0.....+60C
MODEL:TBS RTD PT100	CONNECTION TYPE: RTD 3 WIRE (Main hose length 5200mm) OPERATING TEMPERATURE: 0.....+60C
T545-009-590 Einsteck- Widerstandsthermometer545-0002 * 066-2001	
T233-048-279 Winkel-Thermoelement 1xtyp K Mit Sonderleitung 233-0002 * 066-3024	
3696-2604	
T056-000-771 Einschraubnippel Form Asw 17; 2 Stifte G 1/4 Alange 30 Mmd=14.8	
L1631-4631	
T055-046-529 Coupling	
T531-005-200	
0784-9008	
T601-060-036	
T021-007-040 Die Verriegelung Des Kabels	
T413-035-673	Immersion thermocouple with MTE measuring insert Item 3 pc 354.00 /1 pc Designation: Immersion thermocouple with MTE measuring insert Protective tube: Form AS W.-Nr.: 1.4762 Dimension: 15 Nominal length: 400 mm Connection head: Form B Type: KE 021 Measuring insert: 2 x type K, class 1, form A Temperature range: -40...+1000°C Insert tube: 3 mm Material no.: 2.4816 Insert length: 425 mm Fastening: with threaded sleeve B 131/VA