

Salvatore Robuschi

Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Salvatore Robuschi Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Salvatore Robuschi Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.



rn	Aıklama
Fsr00006011 / Rcb 100-25a 4c22 C140 3	Centrifugal pump made of stainless steel with vortex impeller on base plate with coupling and coupling protection Version with double shaft seal. Free passage for solids up to max. 95 mm. Motor: 22 kW, 4-pin, 400 / 690V, 50 Hz, IP55, IE3, PTC Housing and impeller made of stainless steel EN1.4408-A351 CF3M-AISI 316 Stainless steel shaft EN1.4404-A351 CF3M-AISI 316L double shaft seal (back-to-back) with barrier chamber medium side: AISI 316 / CARB / PTFE engine side: CARB / SiC / VITON Intake / discharge side: DN 125 / DN 100, EN1092 PN10 (Nominal delivery: 150 m ³ / h, nominal delivery head: 22 m) (Weight approx. 330 kg without packaging)
Fsr00006022 / Rcb 100-25a 4c22 U999	Centrifugal pump made of stainless steel with vortex impeller on base plate with coupling and coupling protection Version with single seal. Free passage for solids up to max. 95 mm. Motor: 22 kW, 4-pin, 400 / 690V, 50 Hz, IP55, IE3, PTC Housing and impeller made of stainless steel EN1.4408-A351 CF3M-AISI 316 Stainless steel shaft EN1.4404-A351 CF3M-AISI 316L Shaft sealing as a single seal (according to S / N 2010002278) Intake / discharge side: DN 125 / DN 100, EN1092 PN10 (Nominal delivery: 150 m ³ / h, nominal delivery head: 22 m) (Weight approx. 330 kg without packaging)
Rsm 50-20a 4b40 M183 3	Centrifugal pump made of stainless steel with an open vortex impeller Nominal output: Q 45 m ³ / h, H 12.6 m Pump material EN 1.4408-A351 CF8M-AISI316 Motor: (P2) 4 kW, 4pol., 3 Ph. 230/400 V, 50 Hz, IP 55, IE3 GLRD CARB / SiC / VITON, DNS / DND: DN65 / DN50, EN1092 Weight: approx. 60 kg (unpacked) HS code: 84137081

Fsr0tm1068600 / Glrd (183)	Mechanical seal CARB / SiC / VITON for RSM 50-20A 4B40 M183 3 (RS4 50 20A 055 403, S / N 50651A1.2005)
Fsr0gsu0245300	BEARING HOUSING G20 RC GR2 - CAP.0,78L (BEARING HOUSING Ref. Spare parts N. 330)
Ttjgc0012000	GASKET BEARING COVER GR.2 GUARNITAL 80x115x0,3 (GASKET BEARING COVER Ref. Spare parts N. 400.2/.3)
Utmat0002700	BEARING COVER SEAL DPM NBR 35x47x7 (Ref. Spare parts N. 420.1/.2)
FSR0ECT0122000	CF8M Pos. 471 (zu RCB 100-25A 4C30 L181 3) SEAL CHAMBER COVER DOUBLE CF8M GR2 (SEAL CHAMBER COVER Ref. Spare parts N. 471)
FSR0XCBT0148500	WSH A316 RC RD RG GR2 Shaft protecting sleeve, item 524, (RG 65 25A 412 3)
Lobe Air blower	RBS 65/F UNI/ ANSI, Nozzle unit dimension DN 150, blower flow direction standard flow
Part No-320.2	Ball bearing-DE for the Pump model:RCB 100-25A 4C30L1813
Part No-504	Spacer for the pump model:RCB 100-25A 4C30L1813,
Part No-320.1	Ball bearing-NDE for the Pump model:RCB 100-25A 4C30L1813
RDL 50-25B 4B40 C181 3	Centrifugal pump according to EN22858 - 25199, PN 16 Version with drive lantern and internal flex coupling Pump housing EN 1.4408-A351 CF8M-AISI 316 Impeller EN 1.4408-A351 CF8M-AISI 316 Shaft sleeve EN 1.4404A351 CF3M-AISI 316L Wear ring EN 1.4404A351 CF3M-AISI 316L Shaft EN 1.4404-A351 CF3M-AISI 316L Housing seal SIL-C-4400 Motor: 4 kW, 230/400 V, 50 Hz, IE3, 2 pol., IE3, IP55 Mechanical seal double acting: - SiC / SiC / VITON on the medium side - Carb / SiC / VITON on the drive side Pressure / suction side: DN 80 / DN 50 Weight: approx. 120 kg (without packaging) Dimensions (lxwxh): approx. 1080 x 340 x 440 mm (without packaging) Execution according to 2010027067
RDL 65-25AR 4B55 C181 3	Centrifugal pump according to EN22858 - 25199, PN 16 Version with drive lantern and internal flex coupling Pump housing EN 1.4408-A351 CF8M-AISI 316 Impeller EN 1.4408-A351 CF8M-AISI 316 Shaft sleeve EN 1.4404A351 CF3M-AISI 316L Wear ring EN 1.4404A351 CF3M-AISI 316L Shaft EN 1.4404-A351 CF3M-AISI 316L Housing seal SIL-C-4400 Motor: 5.5 kW, 400 / 690V, 50 Hz, IE3, 2 pol., IE3, IP55 Mechanical seal double acting: - SiC / SiC / VITON on the medium side - Carb / SiC / VITON on the drive side Pressure / suction side: DN 100 / DN 65 Weight: approx. 154 kg (without packaging) Dimensions (lxwxh): approx. 1205 x 370 x 450 mm (without packaging) Execution according to 2010027068
RBS 46 / SP	Rotary piston blower stage RBS 46 / SP (formerly / F) as a replacement and identical design for the existing blower stage with s. n. 12-16127 with 3-leaf rotary lobes, helical and hardened gears and reinforced roller bearings ensure smooth running and a long service life Country of origin: Italy Customs tariff number: 84 14 80 78 Dangerous goods: No. Weight: 117 kg / 127 kg (without / with packaging) *** Dimensions: 83 cm x 45 cm x 56 cm / L x W x H *** (including pallet and packaging)
FSR00006121 / RCB 100-25A 0000 U499 3/A	Stainless steel centrifugal pump with vortex impeller ***# Pump with bare shaft end #*** - without motor, without base plate, without additional components - Version with single seal. Free passage for solids up to max. 95 mm. Housing and impeller made of stainless steel EN1.4408-A351 CF3M-AISI 316 Shaft sleeve EN1.4404-A351 CF3M-AISI 316L Shaft made of stainless steel EN1.4404-A351 CF3M-AISI 316L Shaft seal as a single seal - SiC / SiC / CHEMRAZ (R) Suction / pressure side: DN 125 / DN 100, EN1092 PN10 (Nominal delivery rate: 187.2 m ³ / h, nominal delivery head: 21 m) Weight approx. 92 kg (without packaging) Same design as pump with S / N: 2010002278
RB3186900301	BODY RBS 175 UNI CAST IRON G 250 Position: 1

RBS 165 V TyP	IT WILL BE SUPPLIED FOR BLOWER SERIES NO. 02-04416. PART NAME: HOUSING (BODY) PART NO:1
Pump see list	
ES66/3C	
ES115/4C	
Blower Filter ES 66 /3 C	
Blower Filter ES 115 /4 C	
RBB125-31B 4C37 B0001	only the blade part of the pump and the packing head are required.
1955B3	
2010028359	
RDL 50/16D 2B40 A125 3	Centrifugal pump made of stainless steel AISI316, with closed impeller 140mm, with lantern and flexible coupling, motor B5 4.0 kW, 400V, 50Hz, 2930 1 / min., IP55, mechanical seal: Tungsten carbide / tungsten carbide / EPDM, Suction nozzle DN 80, pressure nozzle DN50
RSM 50-16 A 4B30 M199 3	stainless steel horizontal centrifugal pump AISI-316, with vortex vortex impeller, freer Ball passage 40 mm, 3.0 kW, 230/400 volts, 50 Hz, 1450 rpm, mechanical seal: WC/WC/Viton
RSM 32-16 A 4B15 M199 3	stainless steel horizontal centrifugal pump AISI-316, with vortex vortex impeller, freer Ball passage 22 mm, 1.5 kW, 230/400 volts, 50 Hz, 1450 rpm, mechanical seal: WC/WC/Viton
MECHANICAL SEAL	Equipment name* CENTRIFUGAL POTABLE WATER PUMP Equipment model number* RN 65-250 TM RN 80-160-TM Equipment serial number* TBA Position number 4200 Additional information TMC T4610/GRX1S1 Manufacturer ROBUSCHI Manufacturer Part Number RB2047530000
RBS-55	SN:12-04108 Naked Blower (Flange-mounted Bare Blower)
RCB 100-25A 4C30L1813 Spacer	A.316 T.M. D43 R5LRO2, Part No-485
PUMP SEAL KIT, RIC.KIT	TEN.SERIE 3L-D22 S/S/V SKIN KB, Part.no : 364500035
RDC 50 16DR2B40 120	Pump Features: 3.1 Vertical Shaft Column Type Pump Flow rate max. : 30 m ³ /h hm max. : 20 ms Fluid : Tar water, ammonia water 85 °C max , Snail Body : ASTM A744 GR CF-8M Cover : ASTM A744 GR CF-8M Fan : ASTM A744 GR CF-8M - AISI 316 L (Stainless Steel) Pump Shaft : ASTM A744 GR CF-8M - AISI 420 (Stainless Steel) Shaft length : 1250 mm Surfaces in contact with the fluid will be ASTM A744 GR CF-8M - AISI 316 L. Motor: 380 V, 3-phase, 50 Hz, IP67 Protection Class Motor Protection: Internal contactor, internal motor protection thermal relay, dry running self-stopping due to temperature rise during Fan Type : Semi-vortex fan O-ring : Nitrile Rubber
RB2018270145	FS, LMKAS-110, Pos. 63A, RBS 7 STEEL C 75 Position: 63A Spare parts for the SN 0522103/108 position nr. 23A, 23C, 37, 63A, 78, 43, SP306
RB3205911204	STEEL P 03 PR Position: 23A Pos. 23 A-C, RBS
RB3205911204	STEEL P 03 PR Position: 23C Pos. 23 A-C, RBS
RB3256110100	STEEL Position: 37 Shaft protection sleeve,EGS,item 37,R
RB1891180954	VITON Position: 43 Sealing ring, Viton, item 43, RBS
RB2309610145	STEEL C 75 Position: 63A Spring washer, item 63A, RBS 95
RB2138801006	ALLUM.-VITON Position: 78 Oil level glass, 3/4", item 78, d
RB3156151015	PF 50 Position: SP306 Filter mat 15x440x1100, Robox Spare parts for the SN 0522109/22110 position nr. 11A, 11B, 26

RB3206310108	Gear pair, item 11A, RBS 95- 18NICRMO5 Position: 11A
RB3206320108	18NICRMO5 Position: 11B Gear pair, item 11B, RBS 95-
RB1506300125	STEEL R 70 Position: 26 NM, ss, 55x2 GUP, Pos. 26, RBS NO S/N, order created using part numbers provided by customer
RB3253090308	SPECIAL CAST IRON Piston ring, Pos45, RB(S)95-106.9 Spare parts for the SN 0520336/37 position nr. SP306
RB3155281015	PF 50 Position: SP306 Filter mat 15x280x810, Robox
RB3206310108	18NICRMO5 Position: 11A Gear pair, item 11A, RBS 95-
RB3206320108	18NICRMO5 Position: 11B Gear pair, item 11B, RBS 95-
RB000302060	CAST IRON G 250 BUSHING 3020D. DIAM 60
RB1863630301	CAST IRON G 250 PULLEY 212 5SPB
RB000302065	CAST IRON G 250 BUSHING 3020D. HOLE65
RB1863630301	CAST IRON G 250 PULLEY 212 5SPB
SLEEVE SHFT;REF:SXKBT0148500,SUPR DSS,2	SLEEVE, SHAFT; MATERIAL: SUPER DSS, MATERIAL GRADE: 2, MATERIAL SPECIFICATION: SAF 2507, APPLICATION: DIESEL PUMP; REFERENCE NO: SXKBT0148500, EQUIPMENT MANUFACTURER: SALVATORE ROBUSCHI, EQUIPMENT MODEL NO: RD10020AE401, EQUIPMENT SERIAL NO: 73391F1, EQUIPMENT TAG NO: P-8789A, P-8789B; POSITION NUMBER: 524
GASKET;TTJGC0012000,RND,400.2/.3	GASKET; SHAPE: ROUND, DIMENSIONS: ID 80 X OD 115 X THK 0.3 MM, APPLICATION: BEARING COVER, DESAL 3 PUMP; MANUFACTURER: SALVATORE ROBUSCHI AND C. SRL, MANUFACTURER PART NO: TTJGC0012000, EQUIPMENT MODEL NO: RD 65 25D E 401 3, RD 100 20A E401, EQUIPMENT SERIAL NO: 73391C1, 73391F1, EQUIPMENT TAG NO: P -8787A, P-8787B, P-8789A, P-8789B; POSITION NUMBER: 400.2/.3
RGB 65-25AR 4B55 K999 3	
RBB 125-40BR 0000 U181 4	horizontal centrifugal pump, according to ISO 5199 free shaft end, with multi-channel wheel, suction/ Pressure connection DN150/DN125, with Mechanical seal SiC/SiC/Viton, according to the attached detailed description
USIVI0083000	Shaft locking screw, grub screw, AISI-304
UTDAT0037200	Housing seal in FPM, item 412.3
UTMAT0012800	Seal for shaft protection sleeve in NBR, item 412.2
CXSPRS12CR	Housing cover with sealing chamber for back to Back mechanical seal, item 161
URATM5555200	Mechanical seal 24mm. in carbon/ceramic/FPM for RS 25 12B 030 C152, motor side
URSTM1556600	mechanical seal 24mm, Silicon carbide/silicon carbide/FPM, item 433.2
SXKAL0145500	Pump shaft, item 210
Rdb8020a4a75c1813	
Rgl5020a2a37c1813	
Rbv8016b4b30c2202	
Tipors 25 12b 020 166 / 41054b1 / Pompa	

Rdv6516a4b15c2001	
Rnv5025a6c15c2002	
Rgb6520a2a75k9997	
Hdm 40-16b 2b55 C153 3	
Hd 25 16b 030 C166	
Rsm 40-12b 2b55 L166 3	
Hd2516b030153 3	
Rdm6531c4b11b0007	
Rcpn 200-450/Tm -01	
El65/2p	400 mbar 1400 m3 / h Model : EL65/2P
Rsa 40-20a 2b92 L181 3 / S.N. : 201 0004073	
Rdl10025c8b22s0009	
Rgv12531c6c11c3303	
Rgm8025c6b22c1817	
Cpump00	
Rcv8020a4b30c2501	
Rcf 32 20a 4b40 05	