



## Samchully

Garanti: 12 ay  
 Bu ¼r¼ne ait T¼rkiye ii kapı teslim fiyat ve teslim s¼resi ieren teklifimizi almak iin [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Samchully** Markası, tedarik s¼resi iin l¼tfen bizimle iletiŐime geiniz.

*Firmamız Samchully T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*

¼r¼n	Aıklama
<a href="#">Sam-Hc-24se</a>	AUTOMATIC SELF-CENTERING WITHOUT STEPS BAR WITH PROTECTIONS FOR VERTICAL LATHES HC-SE SERIES; HC-S CYLINDER CONNECTION METRIC TEETH 1,5mm x 60 ° - 3mm x 60 ° from HC 21 EQUIPMENT: n. 1 set of sweet blocks
<a href="#">Sam-Hb18b2</a>	SET HARDENED JAWS
<a href="#">Sam-Syh-1246cck (M52x1.5)</a>	CILINDRI IDRAULICI ULTRA COMPATTI CON PASSAGGIO BARRA SERIE SYH VALVOLE DI SICUREZZA E PREDISPOSIZIONE AL CONTROLLO CORSA FORATURE D'ATTACCO POSTERIORI - CORSA NORMALE - ALTA VELOCITA' ROTAZIONE
<a href="#">Sam-Syh-1246cc/Cad (M52x2.0)</a>	
<a href="#">Sam-Mh-208v1</a>	AUTOMATIC SELF-CENTERING WITH LARGE PASSAGE BAR SERIES MH - MHT - MHF CYLINDRICAL ATTACHMENT - NORMAL STROKE METRIC TEETH 1,5mm x 60 ° - 3mm x 60 ° from MH 218 EQUIPMENT: n. 1 set of sweet blocks
<a href="#">Sam-Hb08a1</a>	SET GRIFFE TEMPRATE NR HC-08, HCH-08, HS-08, MH-208
<a href="#">SAM-CP-HS-10</a>	COVER PLUG HS-10
<a href="#">SAM-MH-208V1</a>	SELF-CENTERING AUTOMATIC WITH LARGE BAR PASSAGE SERIES MH - MHT - MHF CYLINDRICAL ATTACHMENT - NORMAL STROKE METRIC TOOTHING 1,5mm x 60 ° - 3mm x 60 ° from MH 218 EQUIPMENT: n. 1 set of candy blocks
<a href="#">HB08A1</a>	HARDENED JAWS SET HC-08, HCH-08, HS-08, MH-208

<a href="#">SH-19082 [M90 x 2.0] Rotary Cylinder</a>	
<a href="#">Mirror cover and HS10VI model mirror</a>	
<a href="#">SAM-HS-10</a>	SELF-CENTERING AUTOMATIC WITH PASSAGE NORMAL BAR SERIES HS - HST - HSF - HCH CYLINDRICAL ATTACHMENT - NORMAL STROKE METRIC TOOTHING 1,5mm x 60 ° EQUIPMENT: n. 1 set of candy blocks
<a href="#">SAM-HB10A1</a>	HARDENED JAWS SET
<a href="#">Samchully 12 " mirror dust cover</a>	
<a href="#">Model name: SD-17568 ICU1</a>	MFG. Number: 18A031 built-in lock valve and relief valve hydraulic chuck cylinder
<a href="#">SD-15452CU (M60x2)</a>	Max speed: 6,200 omw / min Max clamping force: o Pull: 63 kN o Pressure: 67kN
<a href="#">MH-210V1</a>	Power chuck Samchully 3-jaw MH-210V1, diameter ø254mm, through-hole 82mm Mount: Z-edge ø220mm, without adapter flanges max.rpm 4,500 Jaw connection V = 1.5mm * 60 ° N = 16mm Pull nut blanks *****without adapter flanges*****
<a href="#">SD-18577 M85x2.0</a>	Samchully hydraulic clamping cylinder SD-18577 M85x2.0 Mega Bore Short body open center cylinder Max RPM 5,000 Max. Pull / push: 82 / 89kN
<a href="#">SB18A2 L-180B=65 H=70 n=25 v=3.0x60°</a>	Set (3 pcs) of soft top jaws Samchully type SB18A2 L-180B = 65 H = 70 n = 25 v = 3.0x60°
<a href="#">0116023</a>	
<a href="#">0210012</a>	
<a href="#">0210017</a>	
<a href="#">0240015</a>	
<a href="#">0240022</a>	
<a href="#">0240128</a>	
<a href="#">17 0000 4660</a>	
<a href="#">20519605</a>	
<a href="#">8824-4 M4</a>	
<a href="#">8831-4/II KPL</a>	
<a href="#">BJ/TJ-TC-190</a>	
<a href="#">HB10A1</a>	
<a href="#">HCH15</a>	
<a href="#">HCH21</a>	
<a href="#">HCHF-15</a>	
<a href="#">HS-10 - 02 10 013</a>	
<a href="#">MH-208</a>	
<a href="#">MH208V1</a>	
<a href="#">MH-221</a>	
<a href="#">RTC-160</a>	

<a href="#">SB18A2</a>	
<a href="#">SD-17577BL</a>	
<a href="#">SH-10036CAD</a>	
<a href="#">SK-SDU-175XX</a>	
<a href="#">SPR-SD-17577BL-3</a>	
<a href="#">SPR-SD-17577BL-4</a>	
<a href="#">SYH-1877</a>	
<a href="#">SD-15452</a>	Samchully mega bore short body open center hydraulic cylinder
<a href="#">Y-1530 RE</a>	
<a href="#">614357E013110</a>	ASCO SENTRONIC PLUS ND. G1/4. NG6. 0-10 BAR. ATEX.
<a href="#">SYH-1245CCH</a>	Samchully top hat Max speed: 8,000 RPM Max clamping force: o Pull: 33kN o Pressure: 38kN
<a href="#">MH-208</a>	
<a href="#">MH-210, D 82 mm</a>	
<a href="#">Number: R75577A</a>	Model: SB18A2(HCHCH-21/24 MH-221)
<a href="#">SD 13546</a>	
<a href="#">Power chuck Samchully 3-jaw HC18SE</a>	Diameter ø450mm, without through hole Recording: Z-edge ø300mm Max RPM 2,710 Jaw connection V=1.5mm*60° N=25.5mm Max. clamping force 249kN Tie rod M30x3.5 This chuck is supplied as standard with 1 set of soft top jaws and 1 set of sliding blocks.
<a href="#">Modell SD-18582</a>	- Samchully hydraulisher Spannzyylinder SD-18582 M90x2.0 Mega Bore Short body open center cylinder Max. U/min 4.800 Max. pull/push: 79/85kN NOTE***: The SH-19082 cylinder is no longer manufactured and has been replaced by the SD-18582 model. We offer you these without obligation:
<a href="#">HC - 15D CNC LATHE CHUCK</a>	
<a href="#">SB18A2</a>	Set of soft cheeks Samchully L=180 B=65 H=70 n=25 v=3x60°
<a href="#">Plunger nut for Samchully HS-08</a>	
<a href="#">Drawnut for Samchully HS-08</a>	
<a href="#">Wedgeplunger for Samchully HS-08</a>	
<a href="#">PCV-100"</a>	
<a href="#">soft jaws Samchully SB18A2</a>	L=180 W=65 H=70 n=25 v=3.0x60°
<a href="#">Base jaws for Samchully MH-208V1</a>	3 pieces= 1 set
<a href="#">Samchully 3-jaw power chuck</a>	MH-208BV1 diameter ø210mm, through hole 68mm Recording: Z-edge ø170mm max. rpm 5000, Jaw connection V=1.5mm*60° N=14mm tension nut blanks
<a href="#">IC-4056</a>	
<a href="#">IC-2427</a>	
<a href="#">FIG1 HB15A1</a>	CNC Lathe triple hard feet set
<a href="#">P02481289 12" Hydraulic Cnc Lathe Chuck 3 Legs</a>	

<a href="#">P02488353 10 INCH CNC HYDRAULIC MIRROR 3 FEET</a>	
<a href="#">P02488354 8 INCH CNC HYDRAULIC MIRROR 3 FEET</a>	
<a href="#">HS-06</a>	
<a href="#">SYH-1552HA</a>	
<a href="#">SD-15452(CU)</a>	Samchully Mega-Bore Short body Open Center Hydraulic Cylinder Typ SD-15452CU
<a href="#">HS-O8VI</a>	
<a href="#">4-jaw MHF-210</a>	power chuck diameter ø254mm, through hole 82mm Hole: Z-edge ø220mm, without adapter flanges Jaw connection V=1.5mm*60° N=16mm max. rpm 4,500, Pull nut blanks (max. M90x2)
<a href="#">Adapter flanges APF08A06 for spindle nose A-6</a>	(ACCEPTANCE)
<a href="#">Thread in the tension nut (max. M90x2)</a>	
<a href="#">Mega-Bore Short body Open Center Hydraulic</a>	Cylinder Typ SD-15452CU
<a href="#">TR-120</a>	
<a href="#">S-170</a>	
<a href="#">0241112</a>	
<a href="#">Hs-10 /808010</a>	
<a href="#">Y-2035re</a>	
<a href="#">Sam-Hc-15se [m30x3.5]</a>	AUTOMATIC SELF-CENTERING WITHOUT STEPS BAR WITH PROTECTIONS FOR VERTICAL LATHES HC-SE SERIES; HC-S CYLINDER CONNECTION METRIC TEETH 1,5mm x 60 ° - 3mm x 60 ° from HC 21 EQUIPMENT: n. 1 set of sweet blocks
<a href="#">Sam-Sh-17068cck (M76x1.5/</a>	BACKI) ULTRA COMPACT HYDRAULIC LINDERS WITH BAR PASSAGE SERIES SH SAFETY VALVES AND PREPARATION TO THE STROKE CONTROL REAR ATTACK HOLES - STROKE NORMAL
<a href="#">Hch-21b Kraftspannfutter</a>	
<a href="#">Sam-Hb15n1</a>	SET HARDENED JAWS FOR HC-15, HC-18, HC-18SE
<a href="#">Mh-208v1 Spannfutter Drehmaschine</a>	
<a href="#">Mh-208 Spannfutter Drehmaschine</a>	
<a href="#">Hs-10 Patrone</a>	
<a href="#">Hs-10</a>	
<a href="#">Sam-Ap15a08-33t</a>	ADAPTER
<a href="#">Sam-Sh-15052cad</a>	Interchangeable with SH-15052CC (M60X2.0 / BACK) ULTRA COMPACT HYDRAULIC CYLINDERS WITH BAR PASSAGE SERIES SH SAFETY VALVES AND PREPARATION TO THE STROKE CONTROL REAR ATTACK HOLES NORMAL STROKE
<a href="#">Sam-Hc-15 [m30x3.5]</a>	AUTOMATIC SELF-CENTERING WITHOUT STEPS BAR SERIES HC - HCT - HCF - HCHT - HCHF CYLINDRICAL ATTACHMENT - NORMAL STROKE METRIC TEETH 1,5mm x 60 ° - 3mm x 60 ° from HC 21 EQUIPMENT: n. 1 set of sweet blocks
<a href="#">16f008 Spare Part As In The Picture Completely</a>	

Hs-08