

Schaaf

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Schaaf Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Schaaf T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
Schaaf	
03490NBR	O-Ring d=1,78 D1=53,7 D2=57,26 NBR 90°Shore A API034 40169300 DE
Air hydraulic pump HDL 3000	A37200023 0 - 3000 bar according to SCHAAF drawing A3720 with 2 useful connections M16x1.5 IT 60°DK 2 outlets with quick-release coupling sleeve SVK30 M16x1.5 AG 58° DK - external precision pressure relief valve (adjustment range 50 bar - 3000 bar) - 1 pressure gauge 0 - 3000 bar, Ø 100 mm, quality class 1.0 glycerin filled Short name: 022A3720300/10X/S3/2/XX/XDB Drawing number A3720 Index a
	Screw tensioning device SSV M64x6 Article no. B41430000 Technical data: Clamping force 1980 kN at 2922 bar hydraulic pressure Stroke 6mm max. outside diameter 166 mm Height 209mm Support diameter inside 110 mm External support diameter 141 mm consisting of: ----- Cylinder, support sleeve Pistons High pressure seal kit Hexagon socket SW 95 for tightening the main nut using an adjusting rod Ø 12 mm Adjusting rod Ø 12 mm Manual piston

B41430000	return stroke device via return elements Stroke signal band with max.stroke - max.stroke indications Venting Support sleeve attachment integrated into the cylinder (support sleeve remains rotatable) Quick-release coupling nipple type SVN30 Eyebolt ----- The surfaces of the individual parts are burnished. The SSV is fully assembled and functionally tested. Price includes 1x detailed technical documentation in German. Drawing number B4143 Index a
A06470004	High pressure hose, 4.0 m long with quick-release coupling sleeve and nipple type SVK30 / SVN30 Max. operating pressure: 3000 bar
B41170000	Screw tensioning device SSV M72x6 Technical data: ----- ----- Clamping force 2400 kN at 2875 bar hydraulic pressure Stroke 6mm max. outside diameter 185 mm Height 190mm Internal support diameter 122 mm External support diameter 155 mm consisting of: ----- Cylinder, support sleeve Pistons High pressure seal kit Adjusting rod Ø 12 mm Manual piston return stroke device via return elements Stroke signal band with max.stroke - max.stroke indications Venting Support sleeve attachment integrated into the cylinder (support sleeve remains rotatable) Rotatable angle connection with quick-release coupling nipple type SVN30 ----- The surfaces of the individual parts are burnished. The SSV is fully assembled and functionally tested. Price includes 1x detailed technical documentation in German. Drawing number B4117 Index a
B41810000	Screw tensioning device SSV M80x6 Article no. B41810000 Technical data: Clamping force 3000 kN at 2987 bar hydraulic pressure Stroke 10mm max. outside diameter 200 mm Height 202.6mm Internal support diameter 134 mm External support diameter 175 mm consisting of: ----- Cylinder, support sleeve Pistons High pressure seal kit Hexagon socket SW 115 for tightening the main nut using an adjusting rod Ø 12 mm Adjusting rod Ø 12 mm Manual piston return stroke device via return elements Stroke signal band with max.stroke - max.stroke indications Venting Support sleeve attachment integrated into the cylinder (support sleeve remains rotatable) Rotatable angle connection with quick-release coupling nipple type SVN30 Eyebolt ----- ----- The surfaces of the individual parts are burnished. The SSV is fully assembled and functionally tested. Price includes 1x detailed technical documentation in German. Drawing number B4181 Index a
A0500vs00	Set of wearing parts to the HP 1600 consisting of; 1stk U-Ring NA300 10 / 20x8 94AU925 1stk wiper AS10 / 20x5x8 88NBR 5pcs nylon ring Dia12 / Dia18x3 1stk U-Ring NI300 Dia 16 / Dia 8 x 5.5 94AU925 1stk copper sealing ring according to DIN7603A 12 / 06x1, 5 Cu 1stk seal 110x110x1
D65d10-A3173-22/307	
A52430000	
	High pressure hose 3,0m long with quick-release coupling

A06540003	sleeve and nipple Ty CVK 25-2 / CVN 25-2 customs tariff 39173100 DE
A66805200	
A06810003	High pressure hose 3,0m long with quick-release coupling sleeve and nipple Ty CVK 16 / CVN 16 customs tariff 39173100 DE
A05680003	High pressure hose 3,0m long with quick-release coupling sleeve and nipple Ty CVK 15 / CVN 15 customs tariff 39173100 DE
A42820000	
Zu0010508	
A66805300	
M36-A3874-22/307	
A66805400	