

Schoppe Faeser

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Schoppe Faeser Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Schoppe Faeser T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



| ¼r¼n | A¼ıklama |
|--|---|
| 266DSH.H.S.S.A.2.B.7-...LS..B1 | High performance differential pressure transmitter 66DSH differential pressure transmitter, basic accuracy 0.075%, static pressure up to 21 MPa / 210 bar / 3045psi 266DSH.H.S.S.A.2.B.7-...LS..B1 Sensor measuring range limits / basic accuracy H 1.6 and 160 kPa (16 and 1600 mbar, 6.4 and 642 in, H2O) / basic accuracy 0.06% Overload limit S Permissible working pressure: Standard Diaphragm material / Filling liquid S Stainless steel (AISI 316L SST) / Silicone oil (NACE) Process Flange and Adapter Material /Connections (low pressure side) A AISI 316L stainless steel / 1/4-18 NPT-f direct (horizontal) (NACE) Screws Material / Gaskets Material 2 Stainless steel (AISI 316 SST) / PTFE Housing Material / Electrical Connection B Aluminum Alloy (Barrel Type) / M20 x 1.5 Output 7 base unit with HART digital communication and 4 ...20 mA (product selection with additional order code) Integrated digital display (LCD) LS Integrated LCD display Mounting Accessories / Material B1 For pipe or wall mounting / Carbon Steel |
| 68996-2-0000-511 Used | SCHOPPE & FAESER 68996-2-0000-511 TRANSMITTER POSITION |