

Schorch

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Schorch Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Schorch T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
Electric Motor 125hp	50HZ 400V, RPM 2980, POWER 92KW, 3PHASE FOR TAG.NO.10-P-5571A/B-M TYPE: KA7315S-AB31G-Z DEGREE OF PROTECTION IP55 EXPLOSION OF PROTECT. EXNA IIT3 IEC 79-15 REF.SCHORCH CO. MOTOR COMPLETE
6035815	
7310632	
BD132S-4	
CD 160 L-4	
CD 225 M-4 X	
KN7 315X-BX01G-Z	
KN7315X-PB01Q-Z	
KB5032G-AN02	750 kW, 400V, 2polig, IMB3; IM1001, IP
Type: K85R 400X 6	VIK IEC 400X IMV1 cos φ 0,84 50Hz, 690V S1 400kW 420A 993rpm. EN 60034 JEC 34

KD1 080N-AA43 G-M	
Ersatzteile	Spindelachse
Seal Shaft For Kr7236a-UI18	
Kn5200l-Ab094-060	
Kn7 315s-Qb01d-Z	
55cxl4g7no.	
0514-Cnt-40/207	
2101081nnr	
Kp 6534b-Aa10	
Ka1 207lcb-Osb-Z	
A 132s/4b-31s+e2 (Alu-Gehã196;Use - Klemmkasten Rechts) Psn: U527041	
Mwd12 For Kr7236a-UI18	
O/Level Inspection For Kr7236a-UI18	
Kx5 315 S-Bz059 Z	
Ln7208l-Zz83z-Z	
Ka7200l-Bb39g-Z	
Cd 71 M2-4	
Kn7250s-Ab01b-Z 90 Kw	
Dg7315-Cb81h-Z	
Ka7 280s-Ba01b-Z	
Kn7 318m-Sb01d-Z	
Nde Bearing For Kr7236a-UI18	
Ring Lubricati For Kr7236a-UI18	
Kn7ã;250s-Bb01g-Z	
Heater Space For Kr7236a-UI18	
Kn7 315l-Bx01g-Z	
Lm8250m-A	
2gus000152-100 For Kr7236a-UI18	
Kr6534 G-Aa04	
Kp6534b-Aa10	

Kn7250m - Ab01b - Z
Am 132 S04
Kn7250s-Ab01b-Z 200 Kw
Ka7 250m-Ba01b-Z
Cr 6836 B ?Aa06 2300 Kw 6000 V Ip 54
Kn7317l-Ab01f-Z
Kit
Cd 63 M1-4
Kn7225m-Ab018-401 Iec 225m Imb3
Kn5200l-Pb095-2 Iec 160l
Kd1200lba49gm <p>ATB flameproof encapsulated three-phase motor 22 KW , 400 V, 4 pol., V6. Motor type: KD1200LBA49GM Motor type: KD1 Size: 200 Motor type 4 pole: L-4 Pole number electrical: 4 class efficiency 1: According to manufacturer's standard Operating mode: S1 Thermal class 1: F to B P2 power [kW]: 22 Ambient temperature max. ° C: 50 Ambient temperature min. ° C: -20 speed 1 [rpm]: 1500 Circuit 1: D Voltage 1 [V]: 400 Circuit 2: Y Voltage 2 [V]: 690 Frequency 1-2 [Hz]: 50 On / Engine Start: Direct Special version: V2A screws Type: V6 Cable Entry: DRF Type Cable entry location [on DS]: Right Cable gland type: ADE1F, brass, nickel-plated cable entry. (Number of threads): 1x M50x1,5 Degree of protection IP: 55 Combination seal: Yes Type of balance: half wedge FU mode: no Signs: Schorch Expl. Protection Gas ATEX: II 2G Ex db IIC T4 Gb Certificates ATEX_Schorch: PTB 09 ATEX 1082 X Painting: Offshore Standard Color Type / bes. Anfo: DinEN ISO 12944-2; C5; min.200µm RAL / Type: 7031</p>
Kn7250m-Abo14-152
Kn7318l-Ax03g-Z Iec Imb35
871 356 408
Efklq28-300 Bearing For Kr7236a-UI18
Ka7 280m-Bb09g-Z
Screw Bearing For Kr7236a-UI18
Kd1 180m-Aa45g-M