

Schwer Fittings



Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Schwer Fittings Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Schwer Fittings Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
Gf-125r38x10-7	Locking screw 1.4571 with hexagon socket R3 / 8 "Si8x10
Sr-594g18	Locking screw 1.4571 Viton ring G1 / 8 "D14x12
Sr-594g14	Locking screw 1.4571 Viton ring G1 / 4 "D19x17
Gf-125r12x14-7	Locking screw 1.4571 Special length R1 / 2 "S10x14
Sr-594g34	Locking screw 1.4571 Viton ring G3 / 4 "D32x21
Gf-105g1238-7	Hexagon reducing double nipple 1.4571 G1 / 2 "> G3 / 8" S24x32.5
Mi-Gs25din-4l	1.4404
u2-BV1m12HLD-4LiP	2-way low pressure ball valve (up to 1000 PSI) AISI316L 1.4404 / PTFE -30 ° C <180 ° C Functional reliability 1.5 times D12 / S22 S22 / Hex27x99.3 b12.5
u2-CVFN14ps1-4LV	Check valve (NPT) 1.4404 / Viton 1psi Functional reliability 1.5 times 1/4 "NPT IT
NPT 1/4" Fittings	leider keine Artikel nr. vorhanden
Union Tee	leider keine Artikel nr. vorhanden
NPT 1/2" Fitting	leider keine Artikel nr. vorhanden
1/2 "-12.7mm Hydraulic Green Pipe Clamp (Single)	leider keine Artikel nr. vorhanden

SK-9070S1420	T-piece for orbital welding 1.4571 D14x2.0 S19x31 / 31
IC-HLN-N18x50-4i-8	Long hexagonal double nipple 1.4401 AG1 / 8 "NPTx50.8 S7 / 16 (11.11) x50.8
SR-594M12	Screw plug 1.4571 / FKM M12x1.5 D17x17
GF-151G14-7	Welding socket 1.4571 D11x1.5 <G1 / 4 "D18x20
A-BV2F50PN40F-8i	
A-BV2F80PN40F-8i	
A-BV2G12-8i	
A-BV2G14-8i	
A-BV2GR12-8i	
A-BVHB12S77POV	
A-BVHB30S77POV	
AS-BS13-4L	
AS-BS41-4Li	
AS-N13-4Li	
AS-N41-4Li	
AS-OR13-V	
AS-OR41-V	
CL-CL1D155-2i	
CL-CL1D34-2i	
CL-CL1D505-2i	
CL-CL1D64-2i	
CL-CL1D775-2i	
CL-CL1D91-2i	
CL-CL2D505-2i	
CL-CR1-34Z505-25-H4-5	
CL-CR1-34Z505-34-H4-5	
CL-CR2-112Z64-505-4L	
CL-CR2-112Z64-505-H4-5	
CL-CR34-12Z34-25-H4-5	
CL-CS40DIN505-B	

CL-EC34-4Li
CL-EC505-4Li
CL-EC64-4Li
CL-EC775-4Li
CL-EC91-4Li
CL-FA10ISO34G38-4L
CL-FA15DIN34G12-4L
CL-HA25DIN505-4L
CL-MA10DIN34G14-4L
CL-MA15DIN34G12-4L
CL-MA1Z505G14-4L
CL-WF50DIN64-4Li
GF-10712-4i
GF-110G14-5i
GF-11516R12-7
GF-1399G12-7
GF-141FR1-7
GF-143FR34-7
MO-RBV0622
MO-RE10-54E
Pace1Press, c futlyarom PAC-P1pressSE
PAC-P1VO12L
PAC-P1VO12S
PAC-P1VO16S
PAC-P1VO20S
PAC-P1VO30S
PAC-P1VO38S
SA-DKR16G12
SR-500Z12LSi
SR-500Z16Si

[SR-500Z20Si](#)

[SR-500Z30Si](#)

[SR-500Z38Si](#)

[SR-50112S](#)

[SR-50112S-7i](#)

[SR-50116S](#)

[SR-50120S](#)

[SR-50130S](#)

[SR-50138S](#)

[SR-50512S](#)

[SR-50516S](#)

[SR-50530S](#)

[SR-50538S](#)

[SR-50612S](#)

[SR-50616S](#)

[SR-50630S](#)

[SR-50638S](#)

[SR-50712S](#)

[SR-50716S](#)

[SR-50720S](#)

[SR-50730S](#)

[SR-50738S](#)

[SR-50812S](#)

[SR-50816S](#)

[SR-50830S](#)

[SR-50838S](#)

[SR-51220S12](#)

[SR-51220S34](#)

[SR-51230S1](#)

[SR-537121612S](#)

[SR-537161216S](#)

SR-5391612S	
SR-5393830S	
SR-5401612S	
SR-5403012S	
SR-5403016S	
SR-5403812S	
SR-5403816S	
SR-5403830S	
SR-58912LS	
SR-58916S	
SR-58930S	
SR-58938S	
SR-592S12S-7227	
SR-592S16S-7227	
SR-592S20S-7227	
SR-592S30S-7227	
SR-592S38S-7227	
u2-MS-G12-4i	
u2-Tm12-4L	
V-NVG12-7	
V-NVG14-7	
V-NVZ12S-7	
CL-EC64-4Li	
SR-51216S12	Straight screw connection 1.4571 viton ring 16S<G1/2" S27x51
SR-51216S38	Straight screw connection 1.4571 incl. FKM (Viton ®) soft sealing ring DIN EN ISO 8434-1 16S>G3/8" S30x52.2
SR-50616S	Store Verschraubung 1.4571 DIN EN ISO 8434-1 16S B24/S30x46,5
SR-50716S	T-screw connection 1.4571 EN ISO 8434-1 16S S30x46.2
SR-5391612S	Straight reducing fitting 1.4571 16/12S

SR-51212S14	Straight screw connection 1.4571 viton ring 12S<G1/4" S22x45
RS-IS16PA	Pipe clamp, heavy series, Complete version V4A/PA DIN3015 Part2 16.00 73x30x48
CL-CL2D505-2i	Two-jointed clamp 1.4308 with clamping nut DIN32676 D50.5
A-BV1F15PN16F-8i	Short flanged ball valve 1.4408/PTFE15% glass fiber/FKM 15 Drive preparation according to ISO5211 Flanges according to DIN 2501 DN15 PN16 D95xL42
A-BV1F25PN16F-8i	Short flanged ball valve 1.4408/PTFE15% glass fiber/FKM 25 Drive preparation according to ISO5211 Flanges according to DIN 2501 DN25 PN16 D115xL50
A-BV1F40PN16F-8i	Short flanged ball valve 1.4408/PTFE15% glass fiber/FKM 25 Drive preparation according to ISO5211 Flanges according to DIN 2501 DN25 PN16 D115xL50
V-CVZG25S	Check valve 1.4571/FKM 25S Po 1 bar G1"<25S S46/50x78.5
V-CVZG42L	Check valve 1.4571/FKM 42 poe 1 bar G1-1/2"<42L S80/90x105.5
A-MSVG12SM-7	Pressure gauge shut-off valve 1.4571 15 Form A G1/2"
A-STMG12-7	Pressure gauge accessories 1.4571 with set screw G1/2" 4kt27x63
F-GF15-16-40-7i	Threaded flange turned bright 1.4571 DN15 PN16-40, Form B1 EN 1092-1 Rp 1/2" A95xH22>b16xf2xk65
F-GF25-16-40-7i	Threaded flange turned bright 1.4571 DN25 PN16-40, Form B1 EN 1092-1 Rp 1" A115xH28>b18xf2xk85
F-GF32-16-40-7i	Threaded flange turned bright 1.4571 DN32 PN16-40, form B1 EN 1092-1 Rp 1-1/4" A140xH30>b18xf2xk100
F-GF40-16-40-7i	Threaded flange turned bright 1.4571 DN40 PN16-40, Form B1 EN 1092-1 Rp 1-1/2" A150xH32>b18xf3xk110
F-VF65-10-16-7i	Welding flange 1.4571 DN65 PN10-16, form B1 turned bright EN 1092-1 type 11 D76.1x2.9 A185xH45>b18xf3xk145
SR-50625S	Elbow screw connection 1.4571 EN ISO 8434-1 25S B36/S46x59
SR-50642L	Elbow screw connection 1.4571 42L S60/B50x63
WF-B761x29-7Ni	Elbow, ISO 1.4571 seamless DIN2605 D76.1x2.9 D76.1xR95
SR-57125SG	Adjustable L fitting with Screw socket 1.4571 25S<G1" S46/B36x54/91
SR-57142LG	Adjustable L fitting with Screw socket 1.4571 42L<G1-1/2" S60/B50x63/104
SR-50725S	T-screw connection 1.4571 25S S46/B36x54

SR-50742L	T-screw connection 1.4571 42L S60/B50x63
SR-56825SG	Adjustable T-barrel fitting with Screw socket 1.4571 25S<G1" S46/B36x54/91
SR-56842LG	Adjustable T-barrel fitting with Screw socket 1.4571 42L G11/2"8 50x63
SR-51025S1	Straight screw connection 1.4571 25S<G1" S41x47
SR-51025S112	Straight screw connection 1.4571 25S<G1-1/2" S55x50
SR-51042L112	Straight screw connection 1.4571 42L<G1-1/2" S55x42
SR-53025S	Straight screw connection 1.4571 25S inside G1"DIN/ISO228 SW46x62
SR-5431234	Reducing socket 1.4571 viton ring AG1/2"<IG3/4" S36x46
SR-543121	Reducing socket 1.4571 viton ring AG1/2"<IG1" S41x49
SR-54334112	Reducing socket 1.4571 viton ring AG3/4"<IG1-1/2" S60x57
SR-5431112	Reducing socket 1.4571 viton ring AG1"<IG1-1/2" S60x59
GF-105134-7	Hexagon reducing double nipple 1.4571 R1">R3/4" S36x45.5
GF-105112114-4i	Hexagon reducing double nipple 1.4408 R1-1/2">R1-1/4" S50x54, R1-1/2">R1-1/4"
GF-149CR1-7	Screw connection, external thread on both sides 1.4571/1.4408 conical sealing R1" S55x90
SA-BE9025S25*	Hose connector with shaft 90° 1.4571 25S>DN25
HOS-PT125	PTFE hose, smooth PTFE DN 25 DN 25 A notice: Please check length!
SA-DKRF25G1	Hose connector DKR FG 1.4571 G1">DN25 SW41x68
SA-DKRF25G1	Hose connector DKR FG 1.4571 G1">DN25 SW41x68
HOS-PT125	PTFE hose, smooth PTFE DN 25 DN 25 A notice: Please check length!
SA-DKR25G1	Hose connector DKR 1.4571 G1">DN25 SW41x73.5
SA-AGR16R12	Hose connector AGR conical 1.4571 R1/2" SW22x66.5
QC-FCG112IB-4LPV	High-pressure coupling, shutting off on both sides: Coupling 1.4404/FKM/PTFE DN40 DIN ISO 7241-1B G1-1/2" S65x126
QC-MCG112IB-4LV	High-pressure coupling, shutting off on both sides: Plug 1.4404/FKM DN40 DIN ISO 7241-1B G1-1/2" S65x126
SA-AGR40G112	Hose connector EGR cylindrical 1.4571 G 1 1/2">DN40
GF-130G12-4i	Angle 90° 1.4408 G1/2" L28
Stainless Steel - 1"-14 UNS Vented Cap, 3/8" NPT	Grease Fitting

A-BV3DN50-8i	3-part ball valve 1.4408 DN50 with welding ends on both sides
A-BVHBG1477POV	High-pressure block ball valve 1.4571/POM/FKM G1/4" S22/26x69
GF-115645R212-5i	Screw-in hose nipple 1.4408 di64.5<R2-1/2" S78x99
HOSE HEAD 2"1/2 CODE:GF-11560R212-7 SCHWER	STAINLESS 2"1/2x60 MM
MANOMETER HOSE 1500MM M16X2 AISI 316Ti PN 630BAR	755 DN2 1500
Liste am anhang	
SR-5146L18	Straight screw connection 1.4571 6L<1/8NPT S14/B12x31.5
HyF-LCWM880µm	Screw-in filter V4A/V4 M8x1.25 4x5
KF-SF40x70-4L	Small flange 1.4404 DN 40 DIN 28403/ISO 2861 D55 D55x70
HyF-LCWM880µm	Screw-in filter V4A/V4 M8x1.25 4x5
GF-100R11440-7	Weld nipple 1.4571 DIN EN 10226 D42.4x3.25>R1-1/4" D42.4x40
MANOMETER HOSE 1000MM M16X2	AISI 316Ti PN 630BAR 755 DN2 1000
MANOMETER HOSE 1500MM M16X2	AISI 316Ti PN 630BAR 755 DN2 1500
MANOMETER HOSE 2000MM M16X2	AISI 316Ti PN 630BAR 755 DN2 2000
MANOMETER HOSE 2500MM M16X2	AISI 316Ti PN 630 BAR 755 DN2 2500
Ref.Sr-594g14 S.S.	PLUG G1/4"
T-Rm35x25-7000mm	PIPE STAINLESS STEEL T-Rm35x25-7000mm SCHWER
Gf-147cr112i40-7	screw Externally threaded hose connection 1.4571 / 1.4408 conical sealing R1-1 / 2 "> di40 S75x146
A-Bveg12-8i	One-piece ball valve 1.4408 / PTFE G1 / 2 "S25x60
Gf-11613g38-7	HOSE ADAPTER STAINLESS STEEL G3/8" - di 13 mm (HOSE DN12) SCHWER GF-11613G38-7 (OR EQUIVALENT PART)
A-Dag112-8i	Dirt catcher 1.4408 40 G1-1 / 2 "H79,5xL = 120
Gf-107112-4i	Hexagon double nipple 1.4408 R1-1 / 2 "S50x54
A-Ftg112-5i	Check valve 1.4408 Straight seat design DIN / ISO 228 G11 / 2 "S58x120
Wf-T213x29-7e	TEE, IMPERIAL 1.4571 21,3x2,9 SCHWER WF-T213x29-7E
Sr-594g12	1.4571 G 1/2" DIN 228 SCHWER SR-594G12 (OR EQUIVALENT PART)

A-Fah20-240vj3	Electric Actuator Model J3S20 Standard SCS000109 SW14
Gf-143cr12-7	UNION, OUTSIDE THREAD 1.4571 G 1/2" SCHWER GF-143CR12-7
Rs-179a4060-2	Screw thread hose clamp 1.4301 W4 version DIN3017-A B9, d40-60
Gf-113g112-7	Hexagon bolt 1.4571 G1-1 / 2 "D55x33
Wf-B35x2-7n	ELBOWS STAINLESS STEEL WF-B35x2-7N SCHWER (OR EQUIVALENT PART)
A-Dtg12-4l	Hose tap 1.4404 08 G1 / 2 "D28x99
Mr-Rsmg100 0-10	Bourdon tube safety gauge 1.4301 / 1.4571 / glycerine filling NG100 display range 0-10 bar, G1 / 2 "below,
134 G 38-4 I	
Gf-10712-7	HEXAGONAL COUPLING 1.4571 G 1/2" SCHWER GF-10712-7
Gf-113g12-7	Hexagon bolt 1.4571 G1 / 2 "D26x26
Cvd25s (Ex 550-25s)	
Wf-B213x2	ELBOW STAINLESS STEEL Ø48,3x3,2 SCHWER WF-B213x2 (OR EQUIVALENT PART)
Gf-110g34-4i	PROJE 2328 POZ- 10 FEMALE HEXAGONAL CAP STAINLESS STEEL G 3/4" SCHWER GF-110G34-4i
T-Rz483x32	PIPE STAINLESS STEEL Ø48,3x3,2-5000mm SCHWER T-Rz483x32 (OR EQUIVALENT PART)
Wf-B483x32	ELBOW STAINLESS STEEL Ø48,3x3,2 SCHWER WF-B483x32 (OR EQUIVALENT PART)
Gf-134g12-7	Tee 1.4571 15 G1 / 2 "D30xL32
H0s-1sn40	di=38.1mm; D=50.1mm; l=3m H0S-1SN40 HOSE
134 G 12-4 I	
Gf-141cr114-7	Screw connection, internal external thread 1.4571 / 1.4408 DN32 conical sealing R / G1-1 / 4 "S70x83
Gf-134g112-4i	Tee 1.4408 DN40 G1-1 / 2 "D57x50
Gf-131g112-4i	Store 90 ° 1.4408 R / G1-1 / 2 "L68 / 48
A-Bv3g112-8i	3-piece ball valve 1.4408 G1-1 / 2 "S..x123
Gf-149cr112-7	Screw connection, male thread on both sides 1.4571 / 1.4408 conical sealing R1-1 / 2 "S75x112
Gf-131g114-4i	Store 90 ° 1.4408 R / G1-1 / 4 "L62 / 46
Ref.Sr-594g12 S.S.	PLUG G1/2"

Gf-145cr12-7	UNION, OUTSIDE THREAD - WELDING END 1.4571 G 1/2" SCHWER GF-145CR12-7
Gf-106g11212-7	Hexagon Reducer 1.4571 AG / IG G1-1 / 2 "> G1 / 2" S50x30
Ref.Sr-594g114 S.S	PLUG G1 1/4"