

## Senotec



Garanti: 12 ay  
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Senotec** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

*Firmamız Senotec T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*

¼r¼n	A¼ıklama
<a href="#">130 54</a>	Level probe R3T-5/7 L10W PTFE, SI = 65mm, d = 18mm, cable cross exit with metal angled connector Manufacturer: Binder series 682 Package: 18x24x11cm net weight: 0.5 kg gross weight: 0.8 kg
<a href="#">Sensor R2t-3/5I20</a>	Art nr. 130 61 Your model description: 50058351
<a href="#">110 95</a>	
<a href="#">11015</a>	
<a href="#">130 118</a>	
<a href="#">130 18</a>	
<a href="#">130 19</a>	
<a href="#">130 58</a>	
<a href="#">130 77</a>	
<a href="#">20 022 05 / CLC 22-L05</a>	
<a href="#">20 028 99</a>	
<a href="#">30 033 20</a>	
<a href="#">30 045 60</a>	
<a href="#">30 080 05</a>	
<a href="#">4-008-40-0247</a>	

<a href="#">4-008-40-259</a>	
<a href="#">C3W 4-4/4</a>	
<a href="#">CLC40-L05</a>	
<a href="#">CLS45-LO5H</a>	
<a href="#">CLS-60</a>	
<a href="#">CLS80-LO5H</a>	
<a href="#">R3E-816L12</a>	
<a href="#">R3T-5/7 L10W</a>	
<a href="#">SVK44-L50M0</a>	
<a href="#">R2T-3/5L20</a>	130 61 Capazitive level sensor Capazitive level sensor Sensor length: 50 mm Cable cross exit Cable length: approx.1990 mm Active zone: 25 mm Weight: 0,170 kg Country of origin: Germany Customs tariff no.: 90268020
<a href="#">CLS-33</a>	
<a href="#">30 080 60</a>	CLS 80-L60 Switching amplifier Supply voltage: 18...30 V/DC Connection: Cable 4x0,25mm <sup>2</sup> length: 6,0m Output: 2 x PNP-NO
<a href="#">CLS 90-M12 Homag</a>	30 090 00H Switching amplifier Supply voltage: 18...30 V/DC Connection: 4 pin connector M12x1 Output: 2 x PNP-NO Low Level / High Level Weight: 0,245 kg Homag Teilenummer: 4-008-40-0256
<a href="#">D1Q-2x3/13L12</a>	130 141 Capazitive level sensor for two levels Sensor length: 130 mm Cable cross exit Cable length: approx.1200 mm Active zone: 2 x 30mm Lowlevel / Highlevel Weight: 0,190 kg Country of origin: Germany Customs tariff no.: 90268020 (Use with switching amplifier 4-008-40-0256)
<a href="#">30 090 00H</a>	CLS 90-M12 Homag Switching amplifier Supply voltage: 18...30 V/DC Connection: 4 pin connector M12x1 Output: 2 x PNP-NO Low Level / High Level Weight: 0,245 kg Country of origin: Germany Customs tariff number: 85365080 Homag Teilenummer: 4-008-40-0256
<a href="#">130 11 Type R3e-5/12</a>	
<a href="#">130 61 Teflonsonde R2t-3/5I20 Sl=50mm Mit Kabelquerausgang, Kl=2m</a>	
<a href="#">130 18 Sensorteflonsonde R2q L20 5/10sl 100mm, Kabelquerausgang, 2m</a>	
<a href="#">130 61</a>	Level probe
<a href="#">R4t-1/6</a>	
<a href="#">ClS80-L05h</a>	

<a href="#">30 033 05</a>
<a href="#">130 104p R3e 8 16l12</a>
<a href="#">130 54 R3t 5 7 L10w</a>
<a href="#">Clc 40 Sm8</a>
<a href="#">Clc 28-L15</a>
<a href="#">Clc40-Sm8</a>
<a href="#">20 040 05 Clc40-L05</a>
<a href="#">130 58 Teflonsonde R6g-5/17sl 170mm, Mb Mit Gew. D M18, Mb L=60mm</a>
<a href="#">130 11 Teflonsonde R3e-5/12 Sl=120mm, Montagebereich V2a Mit Knickschutzfeder</a>
<a href="#">R3e-8/16l12</a> Art nr. 130 104 Level probe R3E-8 / 16L12 Sl = 160mm, mounting area V2A Material: PTFE; Cable length 1100mm with anti-kink spring Package: 18x24x11cm net weight: 0.2 kg gross weight: 0.3 kg Customs number: 85365080 Country of Origin: Germany
<a href="#">13011 Teflonsonde R3e-5/12sl=120mm, Montagebereich V2amit Knickschutzfeder</a>
<a href="#">30 045 05 Schaltverstã196;Rker Cls 45- L05 18-30 V/Dc</a>
<a href="#">130 20</a>
<a href="#">Fullstandssonde R3e-8/16l12</a>
<a href="#">Svk 44 , By 30 045 05 Type Cls 45-L05</a>
<a href="#">10 055 00</a>
<a href="#">20 028 99 Schaltverstã196;Rker Clc 28- Ima</a>
<a href="#">Clc 28-L50</a>
<a href="#">130 54 R3t-5/7 L10w</a>
<a href="#">130 54 Teflonsonde R3t-5/7 L10w</a>
<a href="#">10 055 100</a>
<a href="#">Csv41 Csv41-Gt;Cls 33-L05 18-30 V/Dc (Nachfolgemodell Fur Csv41)</a>
<a href="#">130 104</a>
<a href="#">130 61 R2t-3/5l20</a>

<a href="#">130 19 Teflonsonde R2q-5/8 Sl 86,5mm, Mb Mit Gew. D=m18,Kabelqueraus</a>
<a href="#">Csv55 (10 055 00) Adhesive Level Sensor Signal Booster</a>
<a href="#">Cls 33-L05 18-30 V/Dc</a>
<a href="#">130 11 Teflonsonde R3e-5/12sl=120mm, Montagebereich V2amit Knickschutzfeder</a>
<a href="#">130 99</a>
<a href="#">20 040 08</a>
<a href="#">30 045 05 Type Cls 45-L05</a>
<a href="#">130 61 Sensor</a>
<a href="#">Cls45-L05h</a>
<a href="#">130 58 Teflonsonde R6g-5/17 Sl 170mm, Mb Mit Gew. D M18, Mb L=60mm</a>
<a href="#">130 11 Teflonsonde R3e-5/12 Sl=120mm, Montagebereich V2a</a>
<a href="#">Svk44 Adhesive Level Control Module</a>
<a href="#">Cls 33-L05</a>
<a href="#">130 94</a>
<a href="#">130 61 Teflon-Sonde R2t-3/5l20sl=50mm Kabel Mit Einem Ausgang, Kl=2m</a>
<a href="#">Clc 28-Ima (20 028 99)</a>
<a href="#">Csv41ce</a>
<a href="#">R3e-5/12 Artikel-Nr 130 11</a>
<a href="#">Cls 45-L05 18-30 V/Dc</a>
<a href="#">130 11 (R3e-5/12)</a>
<a href="#">20 022 05</a>
<a href="#">130 20 Teflonsonde R3ew-3/8</a>
<a href="#">130 104 Type R3e-8/16l12</a>
<a href="#">10 055 00 Schalerverstaerker Csv 55110-240 V/Ac, 50-60 Hzzeitverzoegerung, Kl=1,5m</a>
<a href="#">R2q-5/10l20 Sensor</a>

<a href="#">30 045 05</a>	Successor of SVK 44! Switching amplifier CLS 45-L05 18-30 V / DC Connecting cable LIYCY 4x0,25mm <sup>2</sup> Length = 0.5m
<a href="#">30 033 05 (Cls 33-L05)</a>	
<a href="#">130 19 Teflonsonde R2q-5/8sl 86,5mm, Mb Mit Gew. D=m18,Kabelqueraus</a>	
<a href="#">Clc22 Adhesive Level Sensor Signal Booster</a>	
<a href="#">Cls 45-L50 30 045 50</a>	
<a href="#">Rpk-3/6l6</a>	
<a href="#">Clc 22-L05 (Art.-Nr. 20 022 05)</a>	
<a href="#">Clc40-L05 18-30 V/Dc</a>	
<a href="#">R2t-3/5l20 130 61teflonsonde R2t-3/5l20sl=50mm Mit Kabelquerausgang, Kl=2m</a>	
<a href="#">130 99 Sl 60mm, Kabellõ;Nge 530mm Material: Ptfе</a>	
<a href="#">130 61</a>	
<a href="#">Clc 40-Sm8</a>	
<a href="#">R2q 5/10 L20</a>	
<a href="#">11015 M161028-1 Type C3q-6/10</a>	
<a href="#">130 11</a>	
<a href="#">130 104p R3e-8/16l12</a>	
<a href="#">Svk 44 M0h3</a>	
<a href="#">Cls 33 L05</a>	
<a href="#">30 060 05</a>	
<a href="#">130 61 Teflonsonde R2t-3/5l20sl=50mm Mit Kabelquerausgang, Kl=2m</a>	
<a href="#">30 033 225</a>	
<a href="#">Rpk-3/6l6 Level Sensorseries R 130 99</a>	
<a href="#">R3e-5/12</a>	
<a href="#">R2q-5/10 Sensoren</a>	
<a href="#">Clc 28 Ima</a>	
<a href="#">130 72</a>	
<a href="#">Clc28-Ima</a>	



Yursat DıŐ Tic. M¼nendislik  
Yeni Karaman Mah. Sanayi Cad. 4. Kantar Sok. Asya Plaza Kat:5 No:505  
Osmangazi/BURSA  
+90 224 2400304  
[info@yursat.com.tr](mailto:info@yursat.com.tr)  
[www.yursat.com.tr](http://www.yursat.com.tr)

---