



Sensopart

Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Sensopart Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Sensopart Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

| rn | Aıklama |
|--|---|
| 740-21021 Ft 18-2 Rm-Ps-L4 | Diffuse sensor, 400mm, metal housing, red light, PNP, metal connector M12 4-pin. |
| FT 50 RLH-PAL4 | Laser photoelectric proximity switch with background suppression, SN 30-150 mm, PNP antiv., 2.5 kHz, IP67, connector M12 4-pin Net weight of the item: 0.043 KG Country of origin: DE Stat. Lot number: 85365019 |
| L4-2m-G-PUR | Accessories, M12 connection cable, 2 m, straight PUR, 4 pole |
| MS F 50 | Accessories, bracket, fastening set (Bracket and screws) for F50 |
| UT 20-240-PSM4 | Ultrasonic button PNP, 240 mm, connector M8 4-pin, teach-in |
| V10-OB-S1-W6 | VISOR V10 object sensor, standard, max. 8 jobs with 32 detectors each, position tracking, 5 Detector types, focal length 6mm, white LEDs, 8 IO Channels, Ethernet, EtherNet / IP, Profinet Net weight of the item: 0.688 KG (per unit: 0.344 KG) Country of origin: DE Stat. Lot number: 85365019 |
| FT 92 IL-PSL4 | Laserdistanzsensoren Reichweite 6 m, 1 x PNP -MSP F 90 Bracket Fx90 (V2A / 1.4301 -L4-2m-G-PUR Accessories, M12 connection cable, 2 m, straight PUR, 4 pole INCLUDED |
| | Reflective light scanner energetic, 800 mm, red light, LED, |

| | |
|--|--|
| FT 25-R-PNSL-M4 | auto-detect, teach-in, connector M8 4-pin, IP 67 & IP 69, IO-Link |
| FR 25-R-PS-M4 | 606-11000 Reflection light barrier, 6m, red light, LED, PNP, teach-in, connector M8 4-pin, IP67 & IP69K There is a new variant for this product: 606-11042 FR 25-R-PNSL-M4 This offers additional functions via IO-Link. |
| FT 25-RA-170-PSU-M4M | 604-41002 Measuring range 30 ... 200mm, resolution 50µm red light, analog 1 ... 10 V, teach-in, PNP, N.O./N.C, metal plug M8x1, 4-pole For this product there is a new variant 604-41009 FT 25-RA-170- PNSUL-M4M This offers additional functions via IO-Link. |
| FT 25-RA-170-PNSUL-M4M | "Measuring range 30 ... 200mm, resolution 50µm Red light, analog 1 ... 10 V, teach-in, Auto-Detect, N.O./N.C, metal plug M8x1, 4-pin, IO-Link *****SUCCESSORS WITH IO-LINK |
| UT 20-700-AIM4 | Ultrasonic sensor with analog output, Working range 120-700 mm, Scanning range limit 1000 mm, 4-20 mA, M8 connector, 4-pin, teach-in |
| FT 25-RLH-PS-M4 | Diffuse reflection sensor with background suppression, 120mm, Laser, PNP, teach-in, connector M8 4-pin, IP67 & IP69K There is a new variant for this product: 609-11015 FT 25-RLH-PNSL-M4 This offers additional functions via IO-Link. |
| FT 25-RLH-PNSL-M4 | Diffuse reflection sensor with background suppression, 150 mm, laser, Automobile- Detect, teach-in, connector M8 4-pin, IP 67 & IP 69, IO-Link |
| MS F20 | Fastening set for F 20, (Bracket and screws) |
| K4-2m-G-PUR | Connection cable M8 connection cable - 4-pin 2m - straight - PUR |
| FT 25-C1-GS-M4M | RGB color sensor, 12 +/- 3mm, 10 kHz, push-pull, Teach-in, metal connector M8 4-pin, IP67 & IP69K There is a new variant for this product: 607-21040 FT 25-C1-GSL-M4M |
| FT 25-C1-GSL-M4M | RGB color sensor, 12 +/- 3mm, 10 kHz, push-pull, teach-in, Metal connector M8 4-pin, IP 67 & IP 69, IO-Link |
| V20-OB-A2-R12 | VISOR V20 object sensor, Advanced, 255 jobs with 255 detectors each, position tracking, 6 detector types, Focal length 12mm, red LEDs, 10 IO channels, Encoder input, interface to IO-Box, RS422, RS232, Ethernet, EtherNet / IP, Profinet |
| FT 50 RLA-100-PL5 | Distance sensor, 70 ... 170 mm, resolution 0.1% MBE 1 x PNP, N.C./N.O. 4 ... 20 mA, connector M12 5-pin |
| MS F 50 | Accessories, bracket, fastening set (Bracket and screws) for F50 |
| L5-2m-G-PUR | L5-2m-G-PUR, M12, F 5pol. 2000 Straight PUR Connection cable, 2m, M 12, straight, PUR, 5-pin f. F 40, Fx 92 |
| | Laser photoelectric proximity switch with Background suppression, red light, Laser class 1, SN = 10..70mm, PNP, |

| | |
|--|--|
| FT 10-RLH-PS-KM4 | 1000Hz, IP67, molded plug (Pigtail) M8 4-pin, 200mm cable, Teach-in There is a new variant for this product: 600-11165 FT 10-RLH-PNSL-KM4 This offers additional functions via IO-Link |
| FT 10-RLH-PNSL-KM4 (Alternative) | FT 10-RLH-PNSL-KM4 180.50 EUR 1,805.00 EUR "Laser diffuse reflection sensor with Background suppression, red light, Laser class 1, SN = 10 # 70 mm, Auto-Detect, 1000 Hz, IP 67, Cable tail 200 mm with connector M8 4-pin, Teach-in, IO-Link " |
| MS F 10 | Fastening set (bracket and screws) for F10 |
| MFT 12 PP4 | Mains and switching devices, SmartPlug, timer, PNP in / PNP out, plug M12x1 100ms, drop-out delay Net weight of the item: 0.026 KG Country of origin: DE Stat. Lot number: 85365019 |
| 30 RZ 12/1000-MSL LS | Fiber optic button Glass fibers for FMS sensors, light switches with metal helix, 100mm, radial Light emission, button |
| FR 25-RGO-PS-M4M | Reflective light barrier with autocollimation principle for Detection of transparent objects, 2m, red light, LED, PNP, Teach-in, metal plug M8 4-pin, IP67 & IP69K There is a new variant for this product: 606-11052 FR 25-RGO-PNSL-M4M This offers additional functions via IO-Link. |
| 041-01303 | |
| 506-11000 | |
| 518-51505 | |
| 533-11037 | |
| 540-51622 | |
| 543-11023 | |
| 543-11043 | |
| 551-11000 | |
| 551-11010 | |
| 558-41000 | |
| 572-51008 | |
| 572-51062 | |
| 573-52007 FE 50 I-PAL4 | |
| 579-50010 | |
| 580-51406 | |
| 600-11002 | |
| 600-11003 | |

| |
|---|
| 600-11036 |
| 604-41008 |
| 606-11012 |
| 606-11016 |
| 607-21010 |
| 607-21018 + 902-50805 + 558-41000 |
| 607-21025 |
| 608-11000 |
| 608-11019 |
| 608-11044 |
| 609-11005 |
| 609-11009 |
| 609-11017 |
| 609-31001 |
| 623-11000 |
| 623-11031 |
| 623-11038 |
| 631-91080 |
| 690-51541 |
| 690-51561 |
| 690-51562 |
| 706-11000 |
| 741-11014 |
| 742-51000 |
| 823-11010 |
| 832-11008 |
| 832-11010 |
| 832-11012 |
| 902-5080 |
| 902-51612 |

| | |
|--|---|
| 902-51799 | |
| 974-51281 | |
| 978-06547 | |
| 978-06548 | |
| 979-06242 | |
| 979-06274 | |
| 979-51628 | |
| 996-51467 | |
| FE 20 R-PSM4 | |
| FR 25-RL-PS-M4M | Reflection light barrier, 13m, laser, PNP, Teach-in, metal connector M8 4-pin, IP67 & IP69K There is a new variant for this product: 609-31018 FR 25-RL-PNSL-M4M This offers additional functions via IO-Link. |
| FS 20 R-M4 | |
| FT 55-RH-PS-L4 | |
| FT 25-RH-PS-M3M | 608-11012 Diffuse mode sensor with background suppression, 200mm, red light, LED, PNP, teach-in, metal connector M8 3-pin, IP67 & IP69K There is a new variant 608-11055 FT for this product 25-RH-PNSLM3M This offers additional functions via IO-Link |
| FT 25-RH-PNSL-M3M (alternative for pos1) | 608-11055 Diffuse mode sensor with background suppression, 200mm, red light, LED, auto-detect, teach-in, metal connector M8 3-pin, IP67 & IP69K, IO-Link |
| FT 50 RH-PAL4 | 572-51004 Diffuse mode sensor with background suppression, SN 30-300 mm, PNP antiv., 1 kHz, IP67, connector M12 4-pin, F 50 Item net weight: 0.129KG (per unit: 0.043KG) |
| FSE 18-2 IM-PS-L4 | One-way light barrier, 10m, S+E, metal threaded sleeve, Infrared, PNP, metal connector M12 4-pin Item net weight: 0.112KG |
| FT 18-2 IDM-PS-L4 | Reflex light barrier, 800mm, metal threaded sleeve, Infrared, PNP, metal connector M12 4-pin Item net weight: 0.825KG (per unit: 0.075KG) Country of Origin: TW Stat. Commodity number: 85365019 |
| FT 25-RHD-PS-M4 | Diffuse mode sensor with background suppression, 400mm, Red light, LED, PNP, teach-in, connector M8 4-pin, IP67 & IP69K There is a new variant 608-11042 FT for this product 25-RHD-PNSLM4 This offers additional functions via IO-Link |
| FT 25-RHD-PNSL-M3M | Diffuse mode sensor with background suppression, 400mm, Red light, LED, auto-detect, teach-in, metal connector M8 3-pin, IP67 & IP69K, IO-Link |

| | |
|--|--|
| K4-2m-G-PUR | connection cable M8 connection cable - 4-pin 2m - Straight - PUR |
| MS F20 | Fastening set for F 20, (brackets and screws) |
| FT 25-RH-PNSL-M4 | Diffuse mode sensor with background suppression, 200mm, red light, LED, auto-detect, teach-in, connector M8 4-pin, IP67 & IP69K, IO link |
| 979-06184 18/30 RZ 2/500-PVC LS=10 | |
| FR 25-R-PNSL-M4M | 606-11046 |
| FR 25 RG0 | |
| FT 50 RH-PAL4 | 572-51004 Diffuse mode sensor with background suppression, SN 30-300 mm, PNP antiv., 1 kHz, IP67, connector M12 4-pin, F 50 |
| FT 50 RH-PAL4 | Diffuse mode sensor with background suppression, SN 30-300 mm, PNP antiv., 1 kHz, IP67, connector M12 4-pin, F 50 |
| MS F 50 | 579-50000 Accessories, bracket, fastening set (brackets and screws) for F50 |
| L4-2m-G-PUR | 902-50805 Accessory, M12 connection cable, 2 m, straight PUR, 4 pin |
| L5-2m-G-PUR | 902-51652 L5-2m-G-PUR, M12,F 5pol. 2000 Straight PUR Connection cable, 2m, M 12, straight, PUR, 5-pin f. F 40, Fx 92 |
| LL 18 R-24-L4 | 525-51156 Digital TTL control (trigger) up to 500 kHz Opening angle 45° Easy hand focusing M18 male thread for easy and versatile attachment LED power indicator M12 connector ensures optimal connection Electrically insulated housing |
| K4-2m-G-PUR | 902-50801 connection cable M8 connection cable - 4-pin 2m - Straight - PUR |
| MS F20 | 558-41000 Fastening set for F 20, (brackets and screws) |
| FT 25-RLH-PNSL-M4 | 609-11015 Background suppression sensor, 150 mm, laser, Automobile- Detect, teach-in, 4-pin M8 connector, IP 67 & IP 69, IO-Link |
| FT 25-RH-PNSL-M4 | "Reflection sensor with background suppression, 200mm, red light, LED, auto-detect, teach-in, connector M8 4-pin, IP67 & IP69K, IO link" |
| K4-2m-G-PUR | 558-41000 connection cable M8 connection cable - 4-pin 2m - Straight - PUR |
| MS F20 | 902-50801 Fastening set for F 20, (brackets and screws) |
| FGL 30-RK-30-PS-M4 | 832-11002 fork light barrier, plastic, Fork width 30 mm, fork depth 34 mm, Red light, teach-in, 2000 Hz, PNP, Connector M8 4-pin |

| | |
|--|--|
| FGL 50-RK-50-PS-M4 | 832-11006 fork light barrier, plastic, Fork width 50 mm, fork depth 54 mm, Red light, teach-in, 2000 Hz, PNP, Connector M8 4-pin |
| Nr. 606-11043 - FR 25-R-PNSL-K4. | |
| IT 12 NBM-PSL4 | 996-51481 Inductive sensor made of stainless steel/ full metal with increased switching distance 10mm, M12 non-flush, PNP N.O., Connector M12 4-pin |
| MA 12 | 041-01305 |
| L4-2m-G-PUR | 902-50805 Accessory, M12 connection cable, 2 m, straight PUR, 4 pin |
| FT 18-2 IDM-PS-L4 | Reflex light barrier, 800mm, metal threaded sleeve, Infrared, PNP, metal connector M12 4-pin |
| FT 25-R-NS-M4M | 607-21007 Diffuse mode sensor energetic, 800mm, red light, LED, NPN, teach-in, metal connector M8 4-pin, IP67 & IP69K |
| FMS 18-34 U | 510-51587 Photo sensor Universal Light barrier for light guide adaptation, M18, Infrared, 1000Hz, PNP N.O./N.C., Cable Item net weight: 0.247KG Country of origin: DE Stat. Commodity number: 85365019 |
| 740-21029 Ft 18-2 Idm-Ps-L4 | |
| MA 18 | 041-01304 |
| FT 18-2 IDM-PS-L4 | Reflex light barrier, 800mm, metal threaded sleeve, Infrared, PNP, metal connector M12 4-pin Item net weight: 0.375KG (per unit: 0.075KG) |
| 606-11012 FR 25-RF-PS-M4 | Retro-reflective sensor, 3m, red light, LED, PNP, fixed setting, connector M8 4-pin, IP67 & IP69K |
| 607-21000 FT 25-R-PS-M4 | Diffuse mode sensor energetic, 800mm, red light, LED, PNP, teach-in, connector M8 4-pin, IP67 & IP69K There is a new variant for this product: 607-21027 FT 25-R-PNSL-M4 |
| FT 18-2 IDM-PS-L4 | 740-21029 Reflex light barrier, 800mm, metal threaded sleeve, Infrared, PNP, metal connector M12 4-pin |
| FR 25 R PS M4 | |
| FMS 30-35 U INFRARED 10 | |
| 30 RZ 12/1000-MCS | |
| 30 RZ 12/1000-MSC LS=16 | 979-06318 30 RZ 12/1000-MSC LS=16 fiber optic button glass fibers for FMS sensors, light scanner with metal coil, 100mm, radial Light exit, button |
| ft 18-2 idmps-l4 | |
| FT 10-RLH-PNSL-KM4 | Laser diffuse reflection sensor with background suppression, red light, Laser class 1, SN = 10 # 70 mm, Auto-Detect, 1000 Hz, IP 67, Cable tail 200 mm with M8 4-pin connector, teach- |

| | |
|---|---|
| | in, IO-Link |
| FT 10-BF3-PS-KM3 | 2...50mm, blue light, HGA, fixed focus, PNP, cable tail 200mm with M8 3-pin connector |
| FSE 18-2 IM-PS-L4 | Through-beam light barrier, 10m, S+E, metal threaded sleeve, infrared, PNP, Metal connector M12 4-pin |
| FMS 30-35 U | 544-51323 Light barrier for fiber optic adaptation, infrared, 100Hz, PNP N.O., VMA, cable |
| 30 RZ 12/1000-MSC LS=16 | 30 RZ 12/1000-MSC LS=16 fiber optic button glass fibers for FMS sensors, light scanner with metal coil, 100mm, radial Light exit, button |
| 606-11000 FR 25-R-PS-M4 | Reflective light barrier, 6m, red light, LED, PNP, teach-in, connector M8 4-pin, IP67 & IP69K There is a new variant for this product: 606-11042 FR 25-R-PNSL-M4 This offers additional functions via IO-Link. |
| 608-11000 FT 25-RHD-PS-M4 | Diffuse reflection sensor with background suppression, 400 mm, red light, LED, PNP, teach-in, connector M8 4-pin, IP67 & IP69. There is a new variant for this product 608-11042 FT 25-RHD-PNSL-M4 This offers additional functions via IO-Link |
| 602-71004 FE 10-RL-PS-KM4 | Laser through-beam sensor, receiver, red light, laser class 1, SN=4000mm, PNP, 4000Hz, IP67, molded connector (pigtail) M8 4-pin, 200mm cable, teach-in |
| FR 25-RGO-PS-M4 | Reflection light barrier with autocollimation principle for detecting transparent objects, 2m, red light, LED, PNP, teach-in, connector M8 4-pin, IP67 & IP69K There is a new variant for this product: 606-11054 FR 25-RGO-PNSL-M4 |
| FR 85-2 ILLG-S1L5 | |
| FR 25-RGO-PNSL-M4 | |
| FT 50 RLA-220-S1L8 | |
| FR 25-RGO-PS-KM4-X04 | |
| 820-41001 | |
| 608-11004 Schalter Sensopart Ft 25-Rh-Ps-M4 | |
| 545-01000 | IP68 OVERHOUSING, STAINLESS STEEL DOES NOT INCLUDE FA45 |
| 609-11005 Ft 25-Rlh-Ps-M4 | |
| Fgl5-Ik-50-Ps-K4 | |
| Fr55-Rlap-70-2pnsi-L8 | |
| Lb86rd-24-Kfl5 | |
| 580-51406, Fls 18-L4fls 18-L4 | |

| | |
|--|---|
| 532-51035 Mg3a | (LR 100 WD-24-KFL5) RINGLIGHT, DIFFUSE, 100 MM, WHITE |
| 574-41014 | |
| 580-51398, Fs 18 RI-L4fs 18 RI-L4 | |
| 552-11007, Fe 23 R-Ps-M4fe 23 R-Ps-M4 | |
| 609-11002 | |
| 580-51416, Fle 18 Wfle 18 W | |
| 604-41003 | |
| 600-11012 | |
| 18/30r04/1000-Si | |
| P/N: 621-11004 Type: Fr 55-R-Ns-K4 | |
| 537-91011 | |
| P/N: 535-91006 Type: V10-Ob-A1-I6 | |
| 697-01052 | |
| 697-01037 | |
| Ft50rlhd-Nak4 | |
| Ft90ila-S2-Q12 | |
| Ft25-RIh-Ps-M3 | |
| 620-11002 | |
| 605-21013, Fe 25-R-Ns-M4mfe 25-R-Ns-M4m | |
| Fms18-34u-60 | |
| 591-91003 | (FT 91 ILA-S2-Q12) DIFFUSE 0.5M-6M, 5MM RES., LASER, ANALOG, 2XPNP, 4-20MA / SERIAL, PLUG M16 12 PINS |
| 996-50325 | |
| Fr55-RI-Ns-K4 | |
| Idt6-2b-Ps-K3 | |
| 536-91042 | |
| Art.No. 608-11000, Type: Ft 25-Rhd-Ps-M4 | |
| 042-12825 / Ma 18 A | |
| Vision V10-A Model | |
| | |

| | |
|--|---|
| 96905910 (Vk5575ube91970) | |
| 978-08577 | |
| 18/30 Lz 1/500-Si Ls=10 | |
| It12-8n-Ns-K3 | |
| 532-51071 | |
| Llk1rm3pe-1m | |
| 540-51319 | |
| 522-91088 | EYESIGHT, VGA, RED LIGHT, RED NOTCH FILTER, CCD-MONO, LIGHT VER., 6MM LENS, ETHERNET / RSXXX |
| 552-11009, Fe 23 R-Ns-M4fe 23 R-Ns-M4 | |
| 041-01304 | |
| 525-51156, LI 18 R-24-L4II 18 R-24-L4 | |
| Ut18-270-Ail4 | |
| 690-51541 Ultraschallsensor Um 18-60-250-Cd-Hp | |
| 580-51408 | |
| 525-51137 | |
| Lr56r-24-Kfl5 | |
| 750-11005 | |
| 620-21000, Fe 55-R-Ps-L4fe 55-R-Ps-L4 | |
| 690-51566 | |
| 18/30rz2/1000-Sils=10 | |
| Ft10-Bf2-Ns-Km3 | |
| 532-51005 | (LR 70 R-24-KFL5) RINGLIGHT, 70 MM, RED |
| 606-11015 | |
| K3-2m-G-Pur | |
| V10c-All-A2-W25 | |
| 553-11013 | |
| 902-51664 | |
| 622-21007 | |
| Fr20rlo-Psk4 | |

| | |
|---|---|
| 600-11132 | |
| 605-21014, Fe 25-RI-Ps-M4mfe 25-RI-Ps-M4m | |
| 979-06254 | |
| 902-51794 | |
| Fms30-34b | |
| V10c-Eye-A2-W6 | |
| 996-50274 | |
| V10-Cr-A1-R6 | |
| Fms184u | |
| 532-51034 | (LR 70 WD-24-KFL5) RINGLIGHT, DIFFUSE, 70 MM, WHITE |
| 543-11002 | |
| Mspf50 | |
| 742-51004, Fse 18-2 Im-Ps-L4fse 18-2 Im-Ps-L4 | |
| Lb625rk24a353I5 | |
| 978-06405 | |
| Mft12pp4 | |
| 532-51009 | (LR 132 WW-24-KFL5) RINGLIGHT, ANGLE, 132 MM, WHITE |
| Ft10-Bf2-Ns-K4 | |
| Lr70rid-24-Kfl5 | |
| 623-11007 | |
| Ft10-Rf1-Ns-Km4 | |
| 902-51632 | |
| 552-11004, Fs 23 R-M4fs 23 R-M4 | |
| 996-09444 | |
| Fs55-RI-L4 | |
| Fm18500-4x | |
| 532-51069 | |
| 551-11011 | |
| 690-51541 / Um18-60/250-Cd-Hp | |
| Llk2slr10pe-2m | |

| | |
|--|---|
| 902-51792 | |
| 535-91022 | |
| Llk2lv6pe-1m | |
| 30lz42000sils | |
| 718-51400 | |
| 623-11022 | |
| 600-11146 | |
| 601-61005, Fs 10-RI-Km3fs 10-RI-Km3 | |
| Fgl120-Ik-50-Ps-M3 | |
| 535-91073 | (V10C-CO-A2-W6) V10 COLOR ADVANCED OBJECT SENSOR, 736X480, 6MM WHITE, RS422/RS232, ETHERNET/ETHERNET/IP |
| 535-91104 | |
| Fms200-01 | |
| 974-09617 Lichtleiter 30 Ql 0,2x10/1000-Si | |
| Lb44wd-24-Kfl5 | |
| 551-11025 | |
| 979-06656 | |
| 978-08195 | |
| Mbd-F-10 | |
| Ft20-R-Psm4 | |
| Ft10-Rf2-Ps-Km3 | |
| 604-41000 | |
| 978-06488 | |
| Cusb-Rs485-0.7m | |
| 927-81003 | INFRARED, MEASURING FIELD 150MM, RANGE 2100MM, RESOLUTION 7 MM, 0-10 V |
| 978-06453 | |
| 536-91011 | |
| 522-91095 | EYESIGHT, VGA, WHITE LIGHT, CCD-COLOR, ADVANCED VER., 6MM LENS, ETHERNET / RSXXX |

| | |
|---|---|
| 522-91080 | EYESIGHT, VGA, WHITE LIGHT, CCD-MONO, LIGHT VER., 6MM LENS, ETHERNET / RSXXX |
| 527-51139 | |
| Ft18-2id-Ps-K4 | |
| 526-51516, Lo C 25lo C 25 | |
| 522-91053 | VGA, WHITE LIGHT, CCD-MONO, OBJECT DETECTION, 12MM LENS, HIGH END, ETHERNET/RS422 |
| 979-08345 | |
| Ft20rh-Psm4 | |
| 741-11015 | |
| 532-51004 | |
| Fs 20 R-M4 / By Fs 25-R-M4m | |
| V10-Tcbox-101 | |
| 18/30I2/500-Msc | |
| Fms3024ul460 | |
| 996-51486 | |
| Ft25-Rlh-Ps-M3m / 609-11007 | |
| 543-11010 | |
| 978-06382 | |
| 718-51403 | |
| Fr25-Rlo2-Ps-K4 | |
| It12bm-Psl4 | |
| Ft 25-R-Ps-M4m | |
| 902-51844 | |
| 571-50005 | |
| 693-11012 | |
| 902-51773 | |
| 580-51411, Fle 18-L4-15fle 18-L4-15 | |
| Fgl80r-Psm3 | |
| 532-51014 | |
| 690-10102 | |
| V10-Cr-A1-I25 | |

| | |
|---|---|
| 979-08342 | |
| 572-51004 Sensor Ft 50 Rh-Pal4 | |
| 518-51505 Optischer Sensorfmh 18-L4 , Reflexions-Lichttaster Mit Hga, M12- Stecker 4-Polig, Bis 120mm | |
| 522-91084 | EYESIGHT, VGA, WHITE LIGHT, CCD-MONO, ADVANCED VER., 12MM LENS, ETHERNET / RSXXX |
| 978-06428 | |
| 591-91008 | |
| Cusb-Rs232 | |
| 978-06459 | |
| 978-06383 | |
| 574-41030 | 80 . 300MM, 0.215MM, LASER, ANALOG, 1 X NPN, NC/NO , 4 TO 20MA, PLUG M12 5 PINS |
| 978-06412 | |
| Imt18-8b-Ns-L4 | |
| 831-81000 | (FG40 I-PSM3) 40 X 80MM, PNP N.O., PLUG M8 3 PINS |
| 902-51610 | |
| Ft-10-RIh-Ps-Km4 | |
| 551-11022 | |
| 591-91011 | |
| 696-51478 | |
| Ft91-Ila-S2-Q12 | (591-91003) DIFFUSE 0.5M-6M, 5MM RES., LASER, ANALOG, 2XPNP, 4-20MA / SERIAL, PLUG M16 12 PINS |
| 579-50000 | |
| 522-91085 | EYESIGHT, VGA, CCD-MONO, ADVANCED VER., C-MOUNT LENS, ETHERNET / RSXXX |
| R1 | |
| Lms10-S22 | |
| 611-51002, Fs/Fe 10-RI-Ps-K4fs/Fe 10- RI-Ps-K4 | |
| K4-2m-W-Pur | |
| 611-51005, Fs/Fe 10-RI-Ns-Km4fs/Fe 10-RI-Ns-Km4 | |

| | |
|---|--|
| 600-11104 | |
| Fr51rl-Pal4 | |
| 551-71000 | |
| 606-11000 Fr 25 R-Ps-M4 | |
| 532-51021 | |
| Fr91ila-S2-Q12 | |
| 607-21011 | |
| 917-16000 | |
| 532-51030 | (LR 70 WID-24-KFL5) RINGLIGHT, INDIRECT, DIFFUSE, 70 MM, WHITE |
| 532-51015 | (LR 130 WI-24-KFL5) RINGLIGHT, INDIRECT, 130 MM, WHITE |
| Fr 23 R-Psm4 | |
| 558-41001 | |
| 996-09972 | |
| 97908045 (R1/500pvc) | |
| Lb1000irk24a353I5 | |
| 532-51018 | (LF 36 WD-24-KFL5) AREALIGHT, DIFFUSE, 36 MM, WHITE |
| Fs25-R-M4m | |
| 522-91128 | VGA, CCD-MONO, CODEREADER, C-CS MOUNT LENS, HIGH END., QUALITY PARAMETERS, ETHERN./RS422 |
| 605-21017, Fe 25-Rf-Ns-M4fe 25-Rf-Ns-M4 | |
| 611-51006, Fs/Fe 10-RI-Ps-Km3fs/Fe 10-RI-Ps-Km3 | |
| 979-08337 | |
| 526-51531, Lof-Pf-30,5x0,5lof-Pf-30,5x0,5 | |
| Ft25-W1-Gs-M4m | |
| 572-51062 Sensor Ft 50 RIhd-Pal4 | |
| 601-61004, Fs 10-RI-Km4fs 10-RI-Km4 | |
| 978-08551 | |
| 572-51051 | |
| 573-52002, Fs 50 I-K4fs 50 I-K4 | |

| | |
|---|---|
| 572-51011 | |
| It8-1b5-Ps-K3 | |
| Cl12fg-S-5m-Pur | |
| 741-11022 | |
| 996-09973 | |
| 978-06437 | |
| 978-06364 | |
| 902-50690 | |
| Fs10-RI-Km4 | |
| Ft10-RIhr-Ps-Km4 | |
| 978-51649 / 18/30 Lzx 1/400-260 Si Ls=11 | |
| 742-51000 Sensopart Fse 18-1 I-Ps- L4einweglichtschranke, M18,Sn=8000 Mm, Pnp, Stecker M12-4pol | |
| Cl8-Fg-S-10m-Pur | |
| 543-11011 | |
| 532-51037 | (LR 100 RD-24-KFL5) RINGLIGHT, DIFFUSE, 100 MM, RED |
| 573-52005, Fe 50 I-Psvk4fe 50 I-Psvk4 | |
| 536-91026 | |
| 607-21010 Ft 25-Rgb1-Gs-Kl4 | |
| Ci L4mg/Rj45g-Gs-5m-Pur | |
| Lr50ww-24-Kfl5 | |
| 904-51564 | |
| 609-21003 | |
| Fr25-Rgo-Ns-M4 | |
| Is46-12 | |
| 525-51150 | |
| Fe25-R-Ns-K4 | |
| 575-11000 | |
| 832-11009 | |
| 620-11000, Fs 55-R-L4fs 55-R-L4 | |

| | |
|---|--|
| 535-91027 | |
| Fr25-R-Ps-K4 | |
| Fr 25-R-Ps-M4 | Reflection light barrier, 6m, red light, LED, PNP, teach-in, M8 4-pin connector, IP67 & IP69K There is a new version for this product: 606-11042 FR 25-R-PNSL-M4 This offers additional functions via IO-Link. Product information can be found at www.sensopart.de Net weight of the item: 0.022 KG Country of origin: DE Stat. Product number: 85365019I |
| 978-06527 | |
| Lf100ard-24-Kfl5 | |
| 591-91000 | (FT 90 ILA-S2-Q12) DIFFUSE 0.5M-12M, 4MM RES., LASER, ANALOG, 2XPNP, 4-20MA / SERIAL, PLUG M16 12 PINS |
| 979-06185 | |
| 532-51020 | (LF 100 WD-24-KFL5) AREALIGHT, DIFFUSE, 100 MM, WHITE |
| 620-11003, Fs 55-RI-K4fs 55-RI-K4 | |
| 526-51514 | |
| 697-01058 | |
| 902-51735 | CONVERTER, RS422 / PROFIBUS |
| V10-Ob-A1-I12 | |
| 18/30Iz3/1500-Pvcls=14 | |
| Fe55-RI-Ns-L4 | |
| 681-50956 | |
| 602-71005, Fe 10-RI-Ns-Km4fe 10-RI-Ns-Km4 | |
| 510-51589 | |
| 996-50641 | |
| Cl12/3fw-S-20m-Pur | |
| 620-21003, Fe 55-R-Ps-K4fe 55-R-Ps-K4 | |
| Imt30-15n-Ns-K3 | |
| Ut 20-150-Aim4 | |
| 580-51410, Fle 18-L4fle 18-L4 | |
| K4-2m-G-Pur (902-50801) | cable M8 connection cable - 4-pin 2m - straight - PUR Net weight of item: 0.280 KG (per unit: 0.070 KG) Country of origin: CZ Stat. Product number: 85444290 |
| 527-51136, Lpt S5Ipt S5 | |

| | |
|--|--|
| 927-81001 | INFRARED, MEASURING FIELD 100MM, RANGE 2100MM, RESOLUTION 7 MM, 0-10 V |
| 621-11026 | |
| Ft25-R-Ps-Km4 | |
| 690-51567 | |
| V20-Eye-A2-W 12 | |
| Ft10-B-Rlf2-Ns-K4 | |
| 540-51605, Fms 30-34 U-54fms 30-34 U-54 | |
| Lpt45cmI5I | |
| Fr25-Rgo-Ps-M4 | |
| Kd12b-PsI4 | |
| 532-51008 | (LR 90 WW-24-KFL5) RINGLIGHT, ANGLE, 90 MM, WHITE |
| Ft18-2 Rwmpl4 | |
| 623-11006 | |
| 18/30r15/500-Si | |
| 620-11002, Fs 55-RI-L4fs 55-RI-L4 | |
| 99609905 | |
| 979-08051 | |
| 580-51406 Fls 18-L4 Laser- Einweglichtschranke, M12,Sender, Stecker M 12 4-Pol | |
| 608-11039 | |
| 30rz4/250-Sils= 16 | |
| 979-06184 | |
| 567-71003 | |
| V10c-Eye-A2-W 12 | |
| 522-91055 | VGA, RED LIGHT, CCD-MONO, OBJECT DETECTION, 6MM LENS, HIGH END, ETHERN./RS422 |
| 697-01006 | |
| 18/30lz1/750-Sils= 10 | |
| 571-50004 | |

| | |
|--|---|
| 8340f410p1f7a2h142-2a | |
| Ft50-C-1-Ps1-L8 | |
| Fr25-Rgo2-Ns-K4 | |
| 720-50766 | |
| 688-51090 | |
| 532-51012 | (LR 90 RW-24-KFL5) RINGLIGHT, ANGLE, 90 MM, RED |
| R5 (Refl.51x61),Standard | Accessories, reflector 51 x 61mm; 2 mounting holes |
| 609-11005 Schalter Sensopart Ft 25-RIh-Ps-M4 | |
| 740-21016 | |
| 604-41002 | |
| 903-05142 | |
| 902-51736 | |
| FMS 30-35 U | 544-51323 Light barrier for light guide adaptation, Infrared, 100Hz, PNP N.O., VMA, Kab |
| RI250 | |
| Ft55-Rh-Ps-L4 | |
| Ft50rla-100-PI5 | |
| 606-11016 Optischer Sensorfr 25-Rgo-Ps-M4m | |
| 535-91050 | |
| Ft10-B-RIf1-Ps-Km4 | |
| K4-10m-G-Pur | |
| 996-09397 | |
| Aerp 150 B90 Ae 2,5mt | |
| P/N: 551-11010 Type: Ft 20 Ih-Psm4 | |
| 1830rx21000si X | |
| V10-Cr-A1-W12 | |
| Fe10-RI-Ps-K4 | |
| Fle18w-L4-15 | |
| 697-01005 | |
| 571-50001 | |

| | |
|---|---|
| 979-08415 | |
| Art.No. 575-11000, Type: Ft 50 C-1-PsI8 | |
| 558-41006 | |
| 902-51835 | |
| 535-91041 | |
| Ft55b-Rh-Ps-L4 | |
| 904-51533 | |
| V10-All-A2-R25 | |
| 535-91096 | |
| 611-51001, Fs/Fe 10-RI-Ns-E4fs/Fe 10-RI-Ns-E4 | |
| 038-12401 | |
| 902-50683 | |
| 532-51007 | (LR 74 WW-24-KFL5) RINGLIGHT, ANGLE, 74 MM, WHITE |
| 605-21004, Fe 25-RI-Ns-K4fe 25-RI-Ns-K4 | |
| Fr18-2iw-Ps-L4 | |
| 902-50808 | |
| 979-50544 | |
| Ft50rlh-Nak4 | |
| 840-11002 | |
| 580-51415, Fle 18 W-L4-15fle 18 W-L4-15 | |
| 605-21012, Fe 25-R-Ps-M4mfe 25-R-Ps-M4m | |
| V20-So-A2-C | |
| P/N: 830-11007 Type: Fgl 180 R-Psm3 | |
| 605-11002, Fs 25-RI-K4fs 25-RI-K4 | |
| 927-81001 , Type Fcp 100-I7-2100-Psu-L | |
| Ft10-Rh-Ns-E4 | |
| Ft88r-Ga-L4 | |
| 904-51565 | |

| | |
|--|--|
| 602-71003, Fe 10-RI-Ns-K4fe 10-RI-Ns-K4 | |
| 927-81000 | INFRARED, MEASURING FIELD 100MM, RANGE 2100MM, RESOLUTION 5 MM, 0-10 V |
| 979-51457 | |
| Mbst2 | |
| 902-51813 | |
| 580-51400 | |
| 609-31010 | |
| 540-51622 Fm 30-800-3 X Sp-L4-X01 (Ndt)fotosensor Mit L4-Stecker | |
| L4-10m-G-Pur | |
| 750-11004 | |
| 579-50010 Ms F 55 Befestigungswinkel Set (L-Form, V2a/1.4301) | |
| 996-51481 | |
| Ft20r-Nsm3 | |
| 918-10001 | |
| Mfc12pp4 | |
| Fe25-RI-Ns-M4m | |
| 97951295 | |
| 553-11000 | |
| 902-51716 | |
| 30I4/500-Si | |
| 532-51011 | (LR 74 RW-24-KFL5) RINGLIGHT, ANGLE, 74 MM, RED |
| Aerp 150 B90 | |
| 978-06439 | |
| 532-51036 | (LR 70 RD-24-KFL5) RINGLIGHT, DIFFUSE, 70 MM, RED |
| 693-11007 | |
| 600-11030 | |
| Kd08b-Pom3 | |
| 535-91023 | |
| 97806798 (L12/500msc) | |

| | |
|---|--|
| Kl06nb-Nom3 | |
| 978-06949 | |
| 996-09394 | |
| 608-11004 | |
| 978-06797 | |
| 902-51688 | |
| 18/30r31000s1 | |
| V10-AII-A2-I12 | |
| 750-11001 | |
| 902-51641 | |
| 522-91067 | VGA, RED LIGHT, CCD-MONO, CODEREADER, 6MM LENS, HIGH END, ETHERN./RS422 |
| Fr 20 RIo-Psm4 | |
| V10-Ob-A1-W6 | |
| R3-2Ik1 | |
| 979-08081 | |
| 605-11001, Fs 25-R-K4fs 25-R-K4 | |
| 553-51004 | |
| 605-21017 | |
| K3-5m-G-Pur | |
| 97908050 | |
| 18/30r1/500si | |
| Fe10-RI-Ns-Km4 | |
| 522-91083 | EYESIGHT, VGA, WHITE LIGHT, CCD-MONO, ADVANCED VER., 6MM LENS, ETHERNET / RSXXX |
| 53051589 (Fms30-44ug-60) | |
| 527-51135 | |
| 904-51588 | |
| 18/30r2/500-Si | |
| 604-41010 | |
| 979-08049 | |

| | |
|---|--|
| 741-11011 | |
| Fr 20 RI -Psm 4 Sensor | |
| Fr 25-RI-Ps-M4m | Reflection light barrier, 13m, laser, PNP, Teach-in, metal connector M8 4-pin, IP67 & IP69K There is a new version for this product: 609-31018 FR 25-RL-PNSL-M4M This offers additional functions via IO-Link. Product information can be found at www.sensopart.de Net weight of the item: 0.050 KG (per unit: 0.025 KG) Country of origin: DE Stat. Product number: 85365019 |
| Fms18-34u | |
| Art.No. 968-11000, Type Mft 12 Pp4 | |
| 522-91097 | EYESIGHT, VGA, CCD-COLOR, ADVANCED VER., C-MOUNT LENS, ETHERNET / RSXXX |
| 697-01047 | |
| K2ade | |
| 609-31013 | |
| 537-91015 | |
| 567-71001 | |
| K4-5m-W-Pur | |
| 904-51543 | |
| 602-71002, Fe 10-RI-Ps-K4fe 10-RI-Ps-K4 | |
| 532-51013 | (LR 132 RW-24-KFL5) RINGLIGHT, ANGLE, 132 MM, RED |
| 544-51323 | |
| Ut20-240-Nsm4 | |
| Fms30-34ut | |
| 042-12820 | |
| 571-50009 | |
| Lms13-S22 | |
| 697-01010 | |
| Fs/Fe10-RI-Ns-E4 | |
| Fse18-2im-Ps-L4 | |
| Rf775x500mm | |
| 902-51654 | |

| | |
|---|--|
| 902-51797 | |
| 623-11012 | |
| 821-11013 | |
| Ft12r-Psk3 | |
| Lb1000rk24a353I5 | |
| 551-21018 | |
| Ft92ila-PsI5 | |
| 904-51590 | |
| 609-21004 | |
| 994-51132 | |
| Ma45I | |
| 18/30I1/750-Si | |
| 902-51604 | |
| 580-51446 | |
| 551-11023 | |
| 575-11016 | |
| 532-51076 | |
| K3-10m-G-Pur | |
| 591-91001 | (FR 90 ILA-S2-Q12) RETRO 0.5M-250M, 2MM RES., LASER, ANALOG, 2XPNP, SSI / SERIAL, PLUG M16 12 PINS |
| 522-91052 | VGA, WHITE LIGHT, CCD-MONO, OBJECT DETECTION, 6MM LENS, HIGH END, ETHERNET/RS422 |
| Fr20rl-Nsk4 | |
| 720-50767 | |
| Ft55-RI2h-Ps-L4 | |
| 526-51515, Lo C 16lo C 16 | |
| FI20r-Psm3 | |
| 522-91093 | EYESIGHT, VGA, RED LIGHT, RED NOTCH FILTER, CCD-MONO, ADVANCED VER., 6MM LENS, ETHERNET / RSXXX |
| 681-50917 | |
| Fgl30-Ik-30-Ns-M4 | |
| 30rz12/1000-Sils=16 | |

| | |
|---|--|
| Ft25-RIh-Ps-KI4 | |
| 902-50805 | |
| 600-11010 | |
| Ft20rh-Psm3 | |
| 536-91012 | |
| Imt8-2b-Ps-M3 | |
| 903-50314 | |
| 555-31000 | |
| 532-51024 | (LF 200 WD-24-KFL5) AREALIGHT, DIFFUSE, 200 MM, WHITE |
| Fl70ra-Nsd-K5 | |
| 543-11030, Lr 0,5lr 0,5 | |
| Mfw12nn4 | |
| 741-11008 | |
| 832-11024 | |
| 533-01027, Pv-Aw1010.4tx Depv-Aw1010.4tx De | |
| Soda Caustica | |
| 904-51532 | |
| Fms-30-44ul-4-60 | |
| 974-09617 | |
| 602-71008, Fe 10-RI-Ns-Km3fe 10-RI-Ns-Km3 | |
| Ft25-Rhd-Ns-M4 | |
| 681-50942 | |
| 543-11021 | |
| 522-91065 | VGA, WHITE LIGHT, CCD-MONO, CODEREADER, 12MM LENS, HIGH END, ETHERN./RS422 |
| Is518-02 | |
| 690-51542 | |
| 18/30 Lz 1/1000-Si Ls=10 | |
| Vk-5575u-05 | |
| 623-11035 | |

| | |
|---|---|
| Ft25-RI-Ps-Km4 | |
| 532-51017 | (LR 130 RI-24-KFL5) RINGLIGHT, INDIRECT, 130 MM, RED |
| Fr55-R-Ps-L4 | |
| Ms F 20 | 558-41000 Fastening set for F 20 , (Bracket and screws) |
| 996-51449 | |
| Fms30-44ug-56 | |
| Fr20rg-Nsm3 | |
| FI70r-Ns-K4 | |
| 902-51694 | |
| 571-50006 | |
| 742-51007, Fse 18-2 Im-Ns-K4fse 18-2 Im-Ns-K4 | |
| 532-51078, Lb 1000 Irk 24 A35 3I5Ib 1000 Irk 24 A35 3I5 | |
| 951-50008 | |
| 951-50001 | |
| Fr-18-1 I-PsI4 | |
| 978-06545 | |
| V20c-Eye-A2-C | |
| Is48-12t | |
| V10-Cr-S2-I25 | |
| 830-11005 | |
| 693-11006 | |
| Ft20rl-Psk4 | |
| 526-51353, Ex2cex2c | |
| 823-11010 Lichtschrinke Fr 88-R-Pav-L5 | |
| Llk1rvv6pe-1m | |
| 902-51657 | |
| Ft10-Rf3-Ps-Km3 | |
| 30Iz4/500-Mscls=16 | |
| 978-06543 | |

| | |
|---|---|
| Cil8mgk/L4mgk-S-02m-Pvc | |
| 528-51106 | LINE SENSOR, ANALOGUE OUTPUT 4 . 20MA |
| 952-50001 | |
| 580-51408, Fls 18 W-L4fls 18 W-L4 | |
| 978-08215 | |
| 697-01033 | |
| 609-11012 | |
| Imt30-15n-Ps-L4 | |
| K3-10m-W-Pl-Pur | |
| 18/30r3/500-Si | |
| 18/30rz1/500-Mscls=10 | |
| 978-06406 | |
| 621-11023 | |
| 742-51005, Fse 18-2 Im-Ns-L4fse 18-2 Im-Ns-L4 | |
| Rd4 | |
| 527-51139, Lpf S1lpf S1 | |
| 551-11003 | |
| Cl12/3fg-S-5m-Pur | |
| 30I4/2000-Msc | |
| 532-51059 | |
| Fr20r-Nsm3 | |
| Art.No.740-21029 Ft 18-2 Idm-Ps-L4 | |
| 681-50957 | |
| 525-51126 | LUMINARY, USABLE AEREA 420MM, IP 67 |
| 600-11103 | |
| 532-51025 | (LF 200 RD-24-KFL5) AREALIGHT, DIFFUSE, 200 MM, RED |
| 978-08236 | |
| Ft 25-Rh-Ps-M4m (608-11014) | Diffuse reflection sensor with background suppression, 200 mm, red light, LED, PNP, metal plug M8, 4-pin, IP67 & IP69K For this product there is a new variant 608-11053 FT 25-RH PNSLM4M This offers additional functions via IO-Link. Further Product information can be found at www.sensopart.de Net weight of item: 0.084 KG (per unit: 0.021 KG) Country of |

| | |
|---|--|
| origin: DE Stat. Product number: 85365019 | |
| R50bc | |
| Is-530-04-S | |
| Ft 20 R-Psm4 | |
| Fr10-RI-Ns-K4 | |
| K4-2m-G-Pur | 902-50801 Connection cable, M8 connection cable - 4-pin 2m - straight - PUR |
| 591-91012 | |
| 580-51405, Fe 12 RI-Nsl4fe 12 RI-Nsl4 | |
| 532-51006 | |
| Mg 2 A | |
| 580-51407, Fls 18fls 18 | |
| Ft18-2id-Ps-L4 | |
| 902-51840 | |
| 18/30I3/750-Msc | |
| 978-06478 | |
| 902-51681 | |
| 600-11134 | |
| 041-01304 Ma 18 (Montagewinkel Fm 18) | |
| 572-51004 | |
| 608-11034 | |
| Is34-52 | |
| Ft12 R-Psl4 | |
| 580-51412, Fle 18fle 18 | |
| Fmsa668232 | |
| 690-51167 | |
| 611-51003, Fs/Fe 10-RI-Ns-K4fs/Fe 10-RI-Ns-K4 | |
| Fr18-2rm-Ns-L4 | |
| Ut18-270-Psl4 | |
| Fe25-RI-Ns-K4 | |

| | |
|--|---|
| 18/30rz3/250sils=14 | |
| Fr25-Rl-Ps-M3m | |
| 681-50955 | |
| 552-11007 | |
| 697-01036 | |
| Ft10-Rlhr-Ns-Km3 | |
| 832-11018 | |
| 902-50801 K4-2m-G-Pur(M8-Kabel F 4p2000 Gerade Pu | |
| 979-06274 Fiber Optic Cable18/30 Rz 2/500-Pvc-2v2a | |
| 609-21012 | |
| 620-21000 | |
| 605-11006, Fs 25-R-M4mfs 25-R-M4m | |
| Ft 25-Rlh-Ps-M4 | |
| Ft10-Rf1-Ns-Km3 | |
| Fr50rl-Psvk4 | |
| V10-Ob-A1-I6 | |
| 608-11000 Ft 25-Rhd-Ps-M4 | |
| Fe50i-Pal4 | |
| 525-51143 | |
| Lf36wd-24-KfI5 | |
| 821-11013 Lichtschanke Ft 88-Ih-Pa-L5 | |
| Ms F 20 (Fixing Set F 20 | Fixing set for F 20, (Bracket and screws) |
| 978-06407 | |
| 902-51817 | |
| 533-01010, Lof-Lp-Ir850-30,5x0,5lof-Lp- Ir850-30,5x0,5 | |
| 821-11010 | |
| Imt8-2n-Ps-K3 | |
| 750-11006 | |

| | |
|---|---|
| Ut20-150-Aum4 | |
| 902-51830 | |
| Ft55-Rh-Ps-K4 | |
| 978-06653 | |
| 978-51688 | |
| Fs10-RI-K4 | |
| 97908058 | |
| 574-41032 | |
| 608-11004 Ft25-Rh-Ps-M4 | |
| 620-21001, Fe 55-R-Ns-L4fe 55-R-Ns-L4 | |
| 99509516 | |
| 996-09399 | |
| Fr25-RI-Ps-K4 | |
| 571-50003 | |
| Fr20-R-Psm4 | |
| 551-21007 | |
| 697-01019 | |
| R5-8/L | |
| Mft12pp4t:... | |
| Lvlf6-M3 | |
| 902-51715 | |
| 741-11025 | |
| 526-51519, Lot-Tec-M55lot-Tec-M55 | |
| 979-06147 | |
| 611-51006 | |
| Ft50c-1-Psl8 | |
| 580-51409, Fls 18 Wfls 18 W | |
| 30rz4/1000-Mscls=16 | |
| 522-91126 | VGA, WHITE LIGHT, CCD-MONO, CODEREADER, 6MM LENS, HIGH END., QUALITY PARAMETERS, ETHERN./RS422 |
| 979-06647 | |

| | |
|---|---|
| 904-51641 | |
| Ft25-Rh-Ns-M3m | |
| 535-91102 | |
| 18/30-R-3/250-Si | |
| 555-31006 | |
| Llk2lz | |
| Ut12-370-Ail4 | |
| Ut | |
| Is48-01 | |
| 601-61002, Fs 10-RI-K4fs 10-RI-K4 | |
| 830-11010 | |
| Ft18-2rw-Ns-K4 | |
| Fse18-2im-Ps-K4 | |
| 607-21025 Sensorft 25-Rgb1-Gs-M4m-X07 | |
| 522-91054 | VGA, CCD-MONO, OBJECT DETECTION, C-CS MOUNT LENS, HIGH END, ETHERNET/RS422 |
| 573-52004, Fe 50 I-Psvl4fe 50 I-Psvl4 | |
| Imt18-8b-Ns-K3 | |
| 979-08414 | |
| 742-51006, Fse 18-2 Im-Ps-K4fse 18-2 Im-Ps-K4 | |
| 522-91129 | VGA, RED LIGHT, CCD-MONO, CODEREADER, 6MM LENS, HIGH END., QUALITY PARAMETERS, ETHERN./RS422 |
| Fl70ra-Psd-K5 | |
| Ms F20 (558-41000) | (Bracket and screws) Net weight of item: 0.052 KG (per unit: 0.013 KG) Country of origin: DE Stat. Lot number: 76041090 |
| 605-21016, Fe 25-Rf-Ps-M4fe 25-Rf-Ps-M4 | |
| 832-11019 | |
| 602-71006 | |
| 832-11000 | |
| 600-11105 | |

| | |
|--|---|
| Is34-51 | |
| 697-01038 | |
| Fms30/34-U | |
| 522-91089 | EYESIGHT, VGA, RED LIGHT, RED NOTCH FILTER, CCD-MONO, LIGHT VER., 12MM LENS, ETHERNET / RSXXX |
| 740-21034 | |
| Ft55-Bh-Ns-L4 | |
| 33lv122w | |
| Rf-50kl | |
| 623-11000 Sensopart Ft55-Rh-Ps-L4 | |
| 553-11010 | |
| 575-11014 | |
| 902-51821 | |
| 974-09617 30 Ql 0,2x10/1000 Si, Querschnittswandler, 1000mm, Silikon, 10mm Lichtaustritt | |
| 605-21001 | |
| 979-06320 | |
| 903-05142 / Mb 10 (Z-Halterung) | |
| 611-51004, Fs/Fe 10-RI-Ps-Km4fs/Fe 10-RI-Ps-Km4 | |
| Cil4fgk/L8fgk-S-02m-Pvc | |
| Is58-13s | |
| Fav 30-01 | |
| 551-11005 | |
| 522-91035 | VGA, WHITELIGHT, CCD-COLOR, COLOR, 12MM LENS, HIGH END, ETHERNET/RS422 |
| Ft10-B-Rlf2-Ps-Km3 | |
| Mft12nn4t:.. | |
| 553-11000 Sensor Fr 20 Rpsm4 | |
| Ft88rh-Pa-L5 | |
| 740-21026 | |
| 552-21000 | |

| | |
|---|---|
| 623-11014 | |
| P/N: 742-51004 Type: Fse 18-2 Im-Ps-L4 | |
| 606-11030 | |
| 30rx2/310-Si | |
| 522-91081 | EYESIGHT, VGA, WHITE LIGHT, CCD-MONO, LIGHT VER., 12MM LENS, ETHERNET / RSXXX |
| 605-21003, Fe 25-R-Ns-K4fe 25-R-Ns-K4 | |
| Lr132rw-24-KfI5 | |
| Fr20rg1-Nsm4 | |
| V20-Ob-A2-C | |
| 996-09421 | |
| SaI-12-Rk12-5/A3 Conec | |
| Fr50rl-Nsvk4 | |
| 572-51002 | |
| P/N: 606-11000 Type: Fr 25-R-Ps-M4 | |
| Ft25-Rvd-Pns-M4m | |
| Ft50ih-Pak4 | |
| 690-51569 | |
| 522-91056 | VGA, RED LIGHT, CCD-MONO, OBJECT DETECTION, 12MM LENS, HIGH END, ETHERN./RS422 |
| 567-71002 | |
| Fe 20 R-Psm4 / By Fe 25-R-Ps-M4m | |
| 605-21015, Fe 25-Rl-Ns-M4mfe 25-Rl-Ns-M4m | |
| Lr130wi-24-KfI5 | |
| 18/30r3/750-Msc | |
| 606-11023 | |
| 522-91058 | VGA, WHITE LIGHT, CCD-MONO, OBJECT DETECTION, 6 MM LENS, LIGHT, ETHERNET |
| Umt30-6000-2psd-L5 | |
| Ft10-Rlh-Ps-K4 | |

| | |
|---|--|
| 690-51164 | |
| 580-51417 | |
| 608-11040 | |
| 532-51077, Lb 625 Irk 24 A35 3I5Ib 625 Irk 24 A35 3I5 | |
| Is56-11t | |
| Is530-44-S | |
| Ft25-Bf2-Ns-K4 | |
| 572-51029 | |
| 591-91000 Ft 90 Ila-S2-Q12 | |
| Is530-41 | |
| Fr10-RI-Ps-E4 | |
| 740-21022 | |
| L8f-10m-W-Pur | |
| 978-08231 | |
| 902-51695 | |
| 904-51644 | |
| 902-51831 | |
| Ut20-240-Aum4 | |
| 996-09396 | |
| V20-AII-A2-R12 | |
| 831-81002 | (FG 120 I-PSM3) 120 X 80MM, PNP N.O., PLUG M8 3 PINS |
| 532-51019 | (LF 51 WD-24-KFL5) AREALIGHT, DIFFUSE,51 MM, WHITE |
| C L12fg-S-5m-Pur | |
| Imt18-8b-Ps-L4 | |
| 602-71006, Fe 10-RI-Ps-Km3fe 10-RI-Ps- Km3 | |
| Cl12/3fw-S-5m-Pur | |
| 580-51413 | |
| Imt18-5b-Ns-L4 | |
| 97908491 | |
| 18/30rz2/250sils= 10 | |

| | |
|---|---|
| 750-11002 | |
| Ft50rh-Nal4 | |
| Ft10-RIh-Ps-Km3-X07 | |
| 903-05141 | |
| 978-08234 | |
| 522-91082 | EYESIGHT, VGA, CCD-MONO, LIGHT VER., C-MOUNT LENS, ETHERNET / RSXXX |
| Fms30-44ul-4-60 | |
| Ft50rh-Psvl4 | |
| 951-50009 | |
| 978-06426 | |
| Fr25-RI-Ns-Km4 | |
| 621-11001 | |
| 979-06199 | |
| 902-50679 | |
| 532-51038 | (LD 50 WD-24-KFL5) RINGLIGHT, DOME, DIFFUSE, 50 MM, WHITE |
| 527-51140, Lpf S2lpf S2 | |
| 607-21004 | |
| 575-11018 | |
| 527-51134, Lpt 45 Cml 5llpt 45 Cml 5l | |
| Lb180rd-24-Kfl5 | |
| 978-06420 | |
| Ft55-R-Ps-L4 | |
| 979-06196 | |
| 606-11005 | |
| 522-91127 | VGA, WHITE LIGHT, CCD-MONO, CODEREADER, 12MM LENS, HIGH END., QUALITY PARAMETERS, ETHERN./RS422 |
| Q12-3m-W-Pvc | |
| 048-12932 | |
| Fs25-RI-M4m | |

| | |
|---|--|
| Sq12t-02 | |
| 527-51138, Lpt 45llpt 45l | |
| 527-51143, Etssets | |
| R100bc | |
| P/N: 536-91012 Type: V20-Ob-A2-R12 | |
| 660-01000 | |
| 532-51032 | (LR 70 RID-24-KFL5) RINGLIGHT, INDIRECT, DIFFUSE, 70 MM, RED |
| Fgl30-Rk-30-Ns-M4 | |
| 543-11031, Lr 1lr 1 | |
| Mbd-S94 | |
| 904-51570 | (RL700) REFLECTOR |
| Fa-46-305-Wcc-Obo12es6 | VISION SENSOR AND LEADS WHITE LIGHT GUI 2 |
| FT 50 RLA 220 PL5 | 574-41029 Distance sensor, 80...300mm, resolution 0.1% MBE, 1 x PNP, N.C./N.O. 4...20 mA, plug M12 5-pin |
| 573-52007, Fe 50 I-Pal4fe 50 I-Pal4 | |
| 620-11001, Fs 55-R-K4fs 55-R-K4 | |
| 591-91009 | |
| V10-AII-A2-R12 | |
| Fe10-RI-Ps-Km3 | |
| Lb180wd-24-Kfl5 | |
| Sal-45s-S8.36-12d-Rs4.2-5/Gaf/025 | |
| 18/30rz1/1000-Mscls=10 | |
| 742-51004 | |
| 532-51039 | (LD 50 RD-24-KFL5) RINGLIGHT, DOME, DIFFUSE, 50 MM, RED |
| Ft50rlh-Psvk4 | |
| 3311/500msc | |
| Imt8-2n-Ns-K3 | |
| 978-08549 | |
| 902-51652 | |
| 608-11015 | |
| 528-51105 | LINE SENSOR, ANALOGUE OUTPUT 0 . 10 V |

| | |
|---|--|
| 904-51562 | |
| 978-06370 | |
| Ft-10-B-Rlf2-Ps-Km4 | |
| 574-41034 | |
| Fr25-R-Ps-M3m | |
| 580-51440, Fle 18wm-L4-X01fle 18wm-L4-X01 | |
| 522-91062 | VGA, RED LIGHT, CCD-MONO, OBJECT DETECTION, 12MM LENS, LIGHT, ETHERNET |
| 522-91094 | EYESIGHT, VGA, RED LIGHT, RED NOTCH FILTER, CCD-MONO, ADVANCED VER., 12MM LENS, ETHERNET / RSXXX |
| Ft20r-Nsm4 | |
| 605-11008, Fs 25-Rf-M4fs 25-Rf-M4 | |
| Mspf20-11 | |
| 697-01045 | |
| 522-91034 | VGA, WHITELIGHT, CCD-COLOR, COLOR, 6MM LENS, HIGH END, ETHERNET/RS422 |
| Imt30-15b-Ns-K3 | |
| V10-Cr-A1-C | |
| Ft50-RIh-PaI4 | |
| 681-50945 | |
| Fr-25-RI-Ns-M4m | |
| V20-Ob-A2-W12 | |
| 904-51585 | |
| Ft50 Rla-40sl4s* 574-41003 | |
| Ft50rla-70-L8 | |
| K2r-25 | |
| 740-21030 | |
| 580-51399, Fe 18 RI-Ns-L4fe 18 RI-Ns-L4 | |
| 543-11032, Lr 10lr 10 | |
| 742-51006 | |

| | |
|---|--|
| 522-91036 | VGA, CCD-COLOR, COLOR, C-CS MOUNT LENS, HIGH END, ETHERNET/RS422 |
| 551-21001 | |
| Fs10-RI-Km3 | |
| 510-51590 Fms 18-34 UI4-60m18infrarot, 5000hz, Pnp/Npn N.O., Stecker M12 4-Poliglichtleitersensoren | |
| 974-51281 30 Qlx 1,0x15/750-Si, X = 12.01.06 | |
| 555-31007 | |
| Ms-F-10 | |
| 979-08063 | |
| 535-91094 | |
| 551-21004 | |
| 608-11030 | |
| 522-91130 | VGA, RED LIGHT, CCD-MONO, CODEREADER, 12MM LENS, HIGH END., QUALITY PARAMETERS, ETHERN./RS422 |
| 555-31004 | |
| 602-71008 | |
| Is-512-44-S | |
| 705-21001 | |
| 978-08202 | |
| 601-61000, Fs 10-RI-E4fs 10-RI-E4 | |
| Ft 55-RI2h-Ps-L4 Sensor | Laser reflection light scanner with background suppression, Red light, PNP, IP67, connector M12, laser class 1 Item net weight: 0.171 KG (per unit: 0.057 KG) Country of origin: DE Stat. Product number: 85365019 |
| 580-51401, Fs 12 RI-L4fs 12 RI-L4 | |
| 996-51454 | |
| P/N: 605-11006 Type: Fs 25-R-M4m | |
| Ft10-Rf3-Ns-Km4 | |
| 622-21009 | |
| 704-21001 | |
| 978-06379 | |
| Lpfs2 | |

| | |
|---|---|
| P/N: 571-50009 Type: Fr 50 RI-Pal4 | |
| 536-91005 | |
| 978-06444 | |
| 573-52003, Fe 50 I-Pak4fe 50 I-Pak4 | |
| 572-51026 | |
| 681-50895 | |
| 580-51414, Fle 18 W-L4fle 18 W-L4 | |
| 532-51023 | (LF 100 RD-24-KFL5) AREALIGHT, DIFFUSE, 100 MM, RED |
| L8fs-2m-G-Pur | |
| 580-51446, Fls 18wm-L4-X02fls 18wm-L4-X02 | |
| Is56-12 | |
| 602-71001, Fe 10-RI-Ns-E4fe 10-RI-Ns-E4 | |
| 606-11009 | |
| P/N: 540-51321 Type: Fms 30-34-Un | |
| 522-91059 | VGA, WHITE LIGHT, CCD-MONO, OBJECT DETECTION, 12 MM LENS, LIGHT, ETHERNET |
| 978-06462 | |
| 978-08239 | |
| Ft-160-Rh-Pal4 | |
| Art.No. 571-50009 [fr 50 RI-Pal4] | |
| Ld50wd-24-Kfl5 | |
| Ft12rf-Psl4 | |
| 525-51144 | |
| 968-21000 | |
| Fl70r-Ns-M4 | |
| Fls18 | |
| Is518-03 | |
| 535-91089 | |
| 510-51587 (Fms1834u) | |
| 536-91001 | |

| |
|--|
| Ft 18-2-Rwmps-L4 740-21025 |
| 741-11006 |
| 527-51137, Lpt 45 pt 45 |
| 18/30rz2/250mscls=14 |
| V20-Eye-A2-C |
| 580-51402, Fe 12 RI-Psl4fe 12 RI-Psl4 |
| 99609429 |
| P/N: 605-21012 Type: Fe 25-R-Ps-M4m |
| 18/30r15/1000-Si |
| Fr18-2iw-Ps-K4 |
| Fe88r-Nav-L5 |
| 979-06236 |
| P/N: 572-51008 Type: Ft 50 Rlh-Pal4 |
| 607-21012 |
| 571-50012 |
| 571-50033 |
| 607-21005 |
| 902-51624 |
| 580-51447, Fle 18wm-L4-X02fle 18wm-L4-X02 |
| 740-21025 |
| Fr88r-Pav-L5 |
| 518-51505 Sensopart Fmh 18-L4 , Reflexions-Lichttaster Mit Hga, M12-Stecker 4-Polig, Bis 120mm |
| 962-50577 |
| Ft 18-2 Rm-Ps-L4 |
| 510-51590 |
| Ft50rlh-Nal4 |
| Fls18wm-L4-X02 |
| 978-06402 |
| Ft18-2rwm-Ps-L4 |

| | |
|---|---|
| 621-11010 | |
| 522-91096 | EYESIGHT, VGA, WHITE LIGHT, CCD-COLOR, ADVANCED VER., 12MM LENS, ETHERNET / RSXXX |
| 97808207 | |
| 978-06550 | |
| Idt4-0b8-Ps-K3 | |
| 996-09428 | |
| 605-11007, Fs 25-RI-M4mfs 25-RI-M4m | |
| 697-01030 | |
| 996-09438 | |
| 979-06162 | |
| Fr10-RI-Ns-Km3 | |
| 522-91061 | VGA, RED LIGHT, CCD-MONO, OBJECT DETECTION, 6MM LENS, LIGHT, ETHERNET |
| 575-11009 | |
| 18/30rz3/2000-Mscls=10 | |
| 917-16003 | |
| 543-11015 | |
| 42-10034 | |
| 718-51404 | |
| Ft55-R-Ns-L4 | |
| Lf51wd-24-KfI5 | |
| 605-21007, Fe 25-RI-Ps-K4fe 25-RI-Ps-K4 | |
| 978-06404 | |
| 18/30r1/500-Si | |
| 97908062 | |
| 693-11004 | |
| 30r12/2000-Si | |
| 543-11033, Lr 20lr 20 | |
| Ft25-C1-Gs-M4m | |

| | |
|---|--|
| 532-51022 | (LF 51 RD-24-KFL5) AREALIGHT, DIFFUSE, 51 MM, RED |
| 974-09623 | |
| 526-51513, Lo C 8lo C 8 | |
| 620-21004, Fe 55-R-Ns-K4fe 55-R-Ns-K4 | |
| Ft10-B-Rlf2-Ns-E4 | |
| P/N: 623-11006 Type: Ft 55-Rlh2-Ps-L4 | |
| 620-21006, Fe 55-RI-Ps-L4fe 55-RI-Ps-L4 | |
| Fr23r-Ps-M4 | |
| 606-11032 | |
| 978-06440 | |
| 527-51132, Lpt 45 Cml 5lpt 45 Cml 5 | |
| V20-All-P2-W12 | |
| 927-81004 | INFRARED, MEASURING FIELD 300MM, RANGE 2100MM, RESOLUTION 7 MM, 0-10 V |
| 30I12/2000-Msc | |
| Fms3024ug60 | |
| 741-11005 | |
| 903-50313 | |
| Ft20rh-Psk4 | |
| Idt6-2b-Ns-M3 | |
| Ft 25-Rhd-Ps-M4m (608-11016) | Diffuse reflection sensor with background suppression, 400mm, Red light, LED, PNP, teach-in, metal connector M8 4-pole, IP67 & IP69K For this product there is a new variant 608-11044 FT 25-RHD PNSLM4M |
| 978-08567 | |
| Loc50 | |
| 21000pvclr | |
| 532-51031 | (LR 100 WID-24-KFL5) RINGLIGHT, INDIRECT, DIFFUSE, 100 MM, WHITE |
| 741-11024 | |
| 608-11008 | |
| V10-Ob-A1-R6 | |

| | |
|---|--|
| FqI120-Rk-50-Ps-M3 | |
| 525-51127 | |
| Ft25-Ra-60-Nsu-M4m | |
| 543-11011, Lr 5lr 5 | |
| 525-51152 | |
| 740-21033 | |
| Fr23r-Psk4 | |
| Ft92il-Ps-KI4 | |
| 902-51843 | |
| Ft12rh-Psl4 | |
| 522-91064 | VGA, WHITE LIGHT, CCD-MONO, CODEREADER, 6MM LENS, HIGH END, ETHERN./RS422 |
| 902-50693 | |
| 533-01028, Pv-Aw1010.4tx Enpv- Aw1010.4tx_En | |
| Fr12r-Psl4 | |
| 18/30lz2/2000-Mscls=14 | |
| 979-06655 | |
| 968-11009 | |
| 18/30rz3/500-Pvcls=14 | |
| 703-11003 | |
| 741-11026 | |
| 57251004 | |
| 536-91006 | |
| 048-02144 | |
| 572-51007 | |
| 974-09617 Sensopart 30 QI 0,2x10/1000 Si, Querschnittswandler, 1000mm, Silikon, 10mmlichtaustritt | |
| 600-11145 | |
| 620-21007 | |
| 553-51006 | |

| | |
|---|---|
| Fr20rg-Psm4 | |
| 99509515 | |
| Is530-42 | |
| 902-51800 | |
| 902-51647 | |
| Mspf20-2 | |
| 902-50689 | |
| 535-91052 | |
| Fr20rg1psm4 | |
| 705-11000 | |
| Is512-42 | |
| 810-50007 | |
| It30nbm-Psl4 | |
| 602-71000, Fe 10-RI-Ps-E4fe 10-RI-Ps-E4 | |
| 611-51007, Fs/Fe 10-RI-Ns-Km3fs/Fe 10-RI-Ns-Km3 | |
| 526-51514, Lo C 12lo C 12 | |
| 740-21042 | |
| 591-91002 | (FR 91 ILA-S2-Q12) RETRO 0.5M-50M, 4MM RES., LASER, ANALOG, 2XPNP, SSI / SERIAL, PLUG M16 12 PINS |
| 30rz4/250-Mscls=16 | |
| 978-06455 | |
| 544-51324 / Fms 30-35 UI5 | |
| 533-01013, Mp Ppc 10,4mp Ppc 10,4 | |
| 506-11000 Lichttasterft12rh-Psl4 | |
| 581601 | |
| 622-21018 | |
| 740-21015 | |
| Ft10-Rf2-Ns-K4 | |
| Imt18-8n-Ps-K3 | |
| 573-52006, Fs 50 I-L4fs 50 I-L4 | |
| | |

| | |
|---|--|
| P/N: 600-11002 Type: Ft 10-Rh-Ps-Km4 | |
| Lr32r-24-Kfl5 | |
| Ma18a | |
| 831-81001 | (FG80 I-PSM3) 80 X 80MM, PNP N.O., PLUG M8 3 PINS |
| 580-51410 | |
| 532-51002 | (LR 70 W-24-KFL5) RINGLIGHT, 70 MM, WHITE |
| 979-06197 | |
| 608-11041 | |
| 696-51473 | |
| 927-81002 | INFRARED, MEASURING FIELD 150MM, RANGE 2100MM, RESOLUTION 5 MM, 0-10 V |
| Fe20r-Psk4 | |
| 517-51396 | |
| 574-41003 | |
| Fgl30-Rk-30-Ns-M3 | |
| 526-51515 | |
| 606-11011 | |
| L4-2m-G-Pur | |
| 996-09488 | |
| Fr50r-Nak4 | |
| 535-91021 | |
| 522-91068 | VGA, RED LIGHT, CCD-MONO, CODEREADER, 12MM LENS, HIGH END, ETHERN./RS422 |
| 522-91060 | VGA, WHITE LIGHT, CCD-MONO, OBJECT DETECTION, C-CS MOUNT LENS, LIGHT, ETHERNET |
| Ft50rlh-Nsvl4 | |
| L4s-2m-G-Pvc, M12 | |
| 574-41028 | 30 . 100MM, 68.36 MM, LASER, ANALOG, 1 X NPN, NC/NO , 4 TO 20MA, PLUG M12 5 PINS |
| 718-51398 | |
| 551-11017 | |
| 580-51400, Fe 18 RI-Ps-L4fe 18 RI-Ps-L4 | |
| Imt30-10b-Ps-L4 | |

| | |
|---|---|
| Ft 55b-Rh-Ps-L4 Schalter Lichtschränke | |
| 902-51796 | |
| Fr10-R-Ps-Km4 | |
| 902-51628 | |
| 681-50880 | |
| Fgl220-R-Psm3 | |
| 978-06541 / 30 Lz 12/1000-Si Ls=16 | |
| 543-11024 - Mg 3a | |
| 522-91066 | VGA, CCD-MONO, CODEREADER, C-CS MOUNT LENS, HIGH END, ETHERN./RS422 |
| 979-06250 | |
| 526-51116, Lo C 75lo C 75 | |
| 697-01020 | |
| Umt30-350-A-Iud-L5 | |
| 902-51757 | |
| 526-51525, Lo C 35lo C 35 | |
| 602-71004, Fe 10-RI-Ps-Km4fe 10-RI-Ps-Km4 | |
| 696-51470 | |
| Ft10-RIh-Ns-Km3 | |
| 30rz12/500-Mscls=20 | |
| Pf30-T | |
| 525-51122 | |
| Ft10-Bf3-Ns-Km4 | |
| 18/30rp2/1000-Si | |
| 611-51000, Fs/Fe 10-RI-Ps-E4fs/Fe 10-RI-Ps-E4 | |
| 18/30lz2/500-Sils=10 | |
| 996-51455 | |
| 551-21021 | |
| 697-01009 | |
| Fgl80-Rk-50-Ns-M4 | |

| | |
|---|------------------------------------|
| 526-51519 | INFINITY. |
| 697-01017 | |
| 978-06652 | |
| 551-71002 | |
| 555-31002 | |
| P/N: 608-11000 Type: Ft 25-Rhd-Ps-M4 | |
| Ft | |
| Lk25r-24-Kfl5 | |
| R3-2lk | |
| 533-01015, Lof-Bp-R635-30,5x0,5lof-Bp-R635-30,5x0,5 | |
| 902-50801 | |
| V10-Eye-A1-R12 | |
| 527-51135, Lpt W 50lpt W 50 | |
| P/N: 571-50000 Type: Fr 50 R-Pak4 | |
| 832-11021 | |
| Fr25-Rgo-Ps-M4m | |
| 608-11024 | |
| Fr25-R-Ps-M3 | |
| 979-06150 | |
| It10-4n-Ps-K3 | |
| 978-51680 | |
| 525-51121 | LUMINARY, USABLE AEREA 98MM, IP 54 |
| 978-06460 | |
| 605-21001, Fe 25-R-Ps-K4fe 25-R-Ps-K4 | |
| 18/30r3/1500-Msc | |
| 600-11009 | |
| 526-51113, Lo C 50lo C 50 | |
| K2l-202 | |
| 580-51403, Fe 12 RI-Po-L4fe 12 RI-Po-L4 | |

| | |
|---|--|
| 722-01003 | |
| 57251000 | |
| 978-08216 | |
| 580-51439, Fls 18wm-L4-X01fls 18wm-L4-X01 | |
| 740-21028 | |
| 18/30rz3/250mscls=10 | |
| 532-51033 | (LR 100 RID-24-KFL5) RINGLIGHT, INDIRECT, DIFFUSE, 100 MM, RED |
| 510-51602 | |
| Ft25-Ra-170-Nsu-M4m | |
| Fgl50-R-Psm3 | |
| 979-06648 | |
| Ft50c-3-Psl8 | |
| 623-11037 | |
| 038-12399 | |
| 681-50903 | |
| Fms18-34ul4-54 | |
| 901-05096 | |