



Sensopart

Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Sensopart Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Sensopart Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
740-21021 Ft 18-2 Rm-Ps-L4	Diffuse sensor, 400mm, metal housing, red light, PNP, metal connector M12 4-pin.
FT 50 RLH-PAL4	Laser photoelectric proximity switch with background suppression, SN 30-150 mm, PNP antiv., 2.5 kHz, IP67, connector M12 4-pin Net weight of the item: 0.043 KG Country of origin: DE Stat. Lot number: 85365019
L4-2m-G-PUR	Accessories, M12 connection cable, 2 m, straight PUR, 4 pole
MS F 50	Accessories, bracket, fastening set (Bracket and screws) for F50
UT 20-240-PSM4	Ultrasonic button PNP, 240 mm, connector M8 4-pin, teach-in
V10-OB-S1-W6	VISOR V10 object sensor, standard, max. 8 jobs with 32 detectors each, position tracking, 5 Detector types, focal length 6mm, white LEDs, 8 IO Channels, Ethernet, EtherNet / IP, Profinet Net weight of the item: 0.688 KG (per unit: 0.344 KG) Country of origin: DE Stat. Lot number: 85365019
FT 92 IL-PSL4	Laserdistanzsensor Reichweite 6 m, 1 x PNP -MSP F 90 Bracket Fx90 (V2A / 1.4301 -L4-2m-G-PUR Accessories, M12 connection cable, 2 m, straight PUR, 4 pole INCLUDED
	Reflective light scanner energetic, 800 mm, red light, LED,

FT 25-R-PNSL-M4	auto-detect, teach-in, connector M8 4-pin, IP 67 & IP 69, IO-Link
FR 25-R-PS-M4	606-11000 Reflection light barrier, 6m, red light, LED, PNP, teach-in, connector M8 4-pin, IP67 & IP69K There is a new variant for this product: 606-11042 FR 25-R-PNSL-M4 This offers additional functions via IO-Link.
FT 25-RA-170-PSU-M4M	604-41002 Measuring range 30 ... 200mm, resolution 50µm red light, analog 1 ... 10 V, teach-in, PNP, N.O./N.C, metal plug M8x1, 4-pole For this product there is a new variant 604-41009 FT 25-RA-170- PNSUL-M4M This offers additional functions via IO-Link.
FT 25-RA-170-PNSUL-M4M	"Measuring range 30 ... 200mm, resolution 50µm Red light, analog 1 ... 10 V, teach-in, Auto-Detect, N.O./N.C, metal plug M8x1, 4-pin, IO-Link *****SUCCESSORS WITH IO-LINK
UT 20-700-AIM4	Ultrasonic sensor with analog output, Working range 120-700 mm, Scanning range limit 1000 mm, 4-20 mA, M8 connector, 4-pin, teach-in
FT 25-RLH-PS-M4	Diffuse reflection sensor with background suppression, 120mm, Laser, PNP, teach-in, connector M8 4-pin, IP67 & IP69K There is a new variant for this product: 609-11015 FT 25-RLH-PNSL-M4 This offers additional functions via IO-Link.
FT 25-RLH-PNSL-M4	Diffuse reflection sensor with background suppression, 150 mm, laser, Automobile- Detect, teach-in, connector M8 4-pin, IP 67 & IP 69, IO-Link
MS F20	Fastening set for F 20, (Bracket and screws)
K4-2m-G-PUR	Connection cable M8 connection cable - 4-pin 2m - straight - PUR
FT 25-C1-GS-M4M	RGB color sensor, 12 +/- 3mm, 10 kHz, push-pull, Teach-in, metal connector M8 4-pin, IP67 & IP69K There is a new variant for this product: 607-21040 FT 25-C1-GSL-M4M
FT 25-C1-GSL-M4M	RGB color sensor, 12 +/- 3mm, 10 kHz, push-pull, teach-in, Metal connector M8 4-pin, IP 67 & IP 69, IO-Link
V20-OB-A2-R12	VISOR V20 object sensor, Advanced, 255 jobs with 255 detectors each, position tracking, 6 detector types, Focal length 12mm, red LEDs, 10 IO channels, Encoder input, interface to IO-Box, RS422, RS232, Ethernet, EtherNet / IP, Profinet
FT 50 RLA-100-PL5	Distance sensor, 70 ... 170 mm, resolution 0.1% MBE 1 x PNP, N.C./N.O. 4 ... 20 mA, connector M12 5-pin
MS F 50	Accessories, bracket, fastening set (Bracket and screws) for F50
L5-2m-G-PUR	L5-2m-G-PUR, M12, F 5pol. 2000 Straight PUR Connection cable, 2m, M 12, straight, PUR, 5-pin f. F 40, Fx 92
	Laser photoelectric proximity switch with Background suppression, red light, Laser class 1, SN = 10..70mm, PNP,

FT 10-RLH-PS-KM4	1000Hz, IP67, molded plug (Pigtail) M8 4-pin, 200mm cable, Teach-in There is a new variant for this product: 600-11165 FT 10-RLH-PNSL-KM4 This offers additional functions via IO-Link
FT 10-RLH-PNSL-KM4 (Alternative)	FT 10-RLH-PNSL-KM4 180.50 EUR 1,805.00 EUR "Laser diffuse reflection sensor with Background suppression, red light, Laser class 1, SN = 10 # 70 mm, Auto-Detect, 1000 Hz, IP 67, Cable tail 200 mm with connector M8 4-pin, Teach-in, IO-Link "
MS F 10	Fastening set (bracket and screws) for F10
MFT 12 PP4	Mains and switching devices, SmartPlug, timer, PNP in / PNP out, plug M12x1 100ms, drop-out delay Net weight of the item: 0.026 KG Country of origin: DE Stat. Lot number: 85365019
30 RZ 12/1000-MSL LS	Fiber optic button Glass fibers for FMS sensors, light switches with metal helix, 100mm, radial Light emission, button
FR 25-RGO-PS-M4M	Reflective light barrier with autocollimation principle for Detection of transparent objects, 2m, red light, LED, PNP, Teach-in, metal plug M8 4-pin, IP67 & IP69K There is a new variant for this product: 606-11052 FR 25-RGO-PNSL-M4M This offers additional functions via IO-Link.
041-01303	
506-11000	
518-51505	
533-11037	
540-51622	
543-11023	
543-11043	
551-11000	
551-11010	
558-41000	
572-51008	
572-51062	
573-52007 FE 50 I-PAL4	
579-50010	
580-51406	
600-11002	
600-11003	

600-11036
604-41008
606-11012
606-11016
607-21010
607-21018 + 902-50805 + 558-41000
607-21025
608-11000
608-11019
608-11044
609-11005
609-11009
609-11017
609-31001
623-11000
623-11031
623-11038
631-91080
690-51541
690-51561
690-51562
706-11000
741-11014
742-51000
823-11010
832-11008
832-11010
832-11012
902-5080
902-51612

902-51799	
974-51281	
978-06547	
978-06548	
979-06242	
979-06274	
979-51628	
996-51467	
FE 20 R-PSM4	
FR 25-RL-PS-M4M	Reflection light barrier, 13m, laser, PNP, Teach-in, metal connector M8 4-pin, IP67 & IP69K There is a new variant for this product: 609-31018 FR 25-RL-PNSL-M4M This offers additional functions via IO-Link.
FS 20 R-M4	
FT 55-RH-PS-L4	
FT 25-RH-PS-M3M	608-11012 Diffuse mode sensor with background suppression, 200mm, red light, LED, PNP, teach-in, metal connector M8 3-pin, IP67 & IP69K There is a new variant 608-11055 FT for this product 25-RH-PNSLM3M This offers additional functions via IO-Link
FT 25-RH-PNSL-M3M (alternative for pos1)	608-11055 Diffuse mode sensor with background suppression, 200mm, red light, LED, auto-detect, teach-in, metal connector M8 3-pin, IP67 & IP69K, IO-Link
FT 50 RH-PAL4	572-51004 Diffuse mode sensor with background suppression, SN 30-300 mm, PNP antiv., 1 kHz, IP67, connector M12 4-pin, F 50 Item net weight: 0.129KG (per unit: 0.043KG)
FSE 18-2 IM-PS-L4	One-way light barrier, 10m, S+E, metal threaded sleeve, Infrared, PNP, metal connector M12 4-pin Item net weight: 0.112KG
FT 18-2 IDM-PS-L4	Reflex light barrier, 800mm, metal threaded sleeve, Infrared, PNP, metal connector M12 4-pin Item net weight: 0.825KG (per unit: 0.075KG) Country of Origin: TW Stat. Commodity number: 85365019
FT 25-RHD-PS-M4	Diffuse mode sensor with background suppression, 400mm, Red light, LED, PNP, teach-in, connector M8 4-pin, IP67 & IP69K There is a new variant 608-11042 FT for this product 25-RHD-PNSLM4 This offers additional functions via IO-Link
FT 25-RHD-PNSL-M3M	Diffuse mode sensor with background suppression, 400mm, Red light, LED, auto-detect, teach-in, metal connector M8 3-pin, IP67 & IP69K, IO-Link

K4-2m-G-PUR	connection cable M8 connection cable - 4-pin 2m - Straight - PUR
MS F20	Fastening set for F 20, (brackets and screws)
FT 25-RH-PNSL-M4	Diffuse mode sensor with background suppression, 200mm, red light, LED, auto-detect, teach-in, connector M8 4-pin, IP67 & IP69K, IO link
979-06184 18/30 RZ 2/500-PVC LS=10	
FR 25-R-PNSL-M4M	606-11046
FR 25 RG0	
FT 50 RH-PAL4	572-51004 Diffuse mode sensor with background suppression, SN 30-300 mm, PNP antiv., 1 kHz, IP67, connector M12 4-pin, F 50
FT 50 RH-PAL4	Diffuse mode sensor with background suppression, SN 30-300 mm, PNP antiv., 1 kHz, IP67, connector M12 4-pin, F 50
MS F 50	579-50000 Accessories, bracket, fastening set (brackets and screws) for F50
L4-2m-G-PUR	902-50805 Accessory, M12 connection cable, 2 m, straight PUR, 4 pin
L5-2m-G-PUR	902-51652 L5-2m-G-PUR, M12,F 5pol. 2000 Straight PUR Connection cable, 2m, M 12, straight, PUR, 5-pin f. F 40, Fx 92
LL 18 R-24-L4	525-51156 Digital TTL control (trigger) up to 500 kHz Opening angle 45° Easy hand focusing M18 male thread for easy and versatile attachment LED power indicator M12 connector ensures optimal connection Electrically insulated housing
K4-2m-G-PUR	902-50801 connection cable M8 connection cable - 4-pin 2m - Straight - PUR
MS F20	558-41000 Fastening set for F 20, (brackets and screws)
FT 25-RLH-PNSL-M4	609-11015 Background suppression sensor, 150 mm, laser, Automobile- Detect, teach-in, 4-pin M8 connector, IP 67 & IP 69, IO-Link
FT 25-RH-PNSL-M4	"Reflection sensor with background suppression, 200mm, red light, LED, auto-detect, teach-in, connector M8 4-pin, IP67 & IP69K, IO link"
K4-2m-G-PUR	558-41000 connection cable M8 connection cable - 4-pin 2m - Straight - PUR
MS F20	902-50801 Fastening set for F 20, (brackets and screws)
FGL 30-RK-30-PS-M4	832-11002 fork light barrier, plastic, Fork width 30 mm, fork depth 34 mm, Red light, teach-in, 2000 Hz, PNP, Connector M8 4-pin

FGL 50-RK-50-PS-M4	832-11006 fork light barrier, plastic, Fork width 50 mm, fork depth 54 mm, Red light, teach-in, 2000 Hz, PNP, Connector M8 4-pin
Nr. 606-11043 - FR 25-R-PNSL-K4.	
IT 12 NBM-PSL4	996-51481 Inductive sensor made of stainless steel/ full metal with increased switching distance 10mm, M12 non-flush, PNP N.O., Connector M12 4-pin
MA 12	041-01305
L4-2m-G-PUR	902-50805 Accessory, M12 connection cable, 2 m, straight PUR, 4 pin
FT 18-2 IDM-PS-L4	Reflex light barrier, 800mm, metal threaded sleeve, Infrared, PNP, metal connector M12 4-pin
FT 25-R-NS-M4M	607-21007 Diffuse mode sensor energetic, 800mm, red light, LED, NPN, teach-in, metal connector M8 4-pin, IP67 & IP69K
FMS 18-34 U	510-51587 Photo sensor Universal Light barrier for light guide adaptation, M18, Infrared, 1000Hz, PNP N.O./N.C., Cable Item net weight: 0.247KG Country of origin: DE Stat. Commodity number: 85365019
740-21029 Ft 18-2 Idm-Ps-L4	
MA 18	041-01304
FT 18-2 IDM-PS-L4	Reflex light barrier, 800mm, metal threaded sleeve, Infrared, PNP, metal connector M12 4-pin Item net weight: 0.375KG (per unit: 0.075KG)
606-11012 FR 25-RF-PS-M4	Retro-reflective sensor, 3m, red light, LED, PNP, fixed setting, connector M8 4-pin, IP67 & IP69K
607-21000 FT 25-R-PS-M4	Diffuse mode sensor energetic, 800mm, red light, LED, PNP, teach-in, connector M8 4-pin, IP67 & IP69K There is a new variant for this product: 607-21027 FT 25-R-PNSL-M4
FT 18-2 IDM-PS-L4	740-21029 Reflex light barrier, 800mm, metal threaded sleeve, Infrared, PNP, metal connector M12 4-pin
FR 25 R PS M4	
FMS 30-35 U INFRARED 10	
30 RZ 12/1000-MCS	
30 RZ 12/1000-MSC LS=16	979-06318 30 RZ 12/1000-MSC LS=16 fiber optic button glass fibers for FMS sensors, light scanner with metal coil, 100mm, radial Light exit, button
ft 18-2 idmps-l4	
FT 10-RLH-PNSL-KM4	Laser diffuse reflection sensor with background suppression, red light, Laser class 1, SN = 10 # 70 mm, Auto-Detect, 1000 Hz, IP 67, Cable tail 200 mm with M8 4-pin connector, teach-

	in, IO-Link
FT 10-BF3-PS-KM3	2...50mm, blue light, HGA, fixed focus, PNP, cable tail 200mm with M8 3-pin connector
FSE 18-2 IM-PS-L4	Through-beam light barrier, 10m, S+E, metal threaded sleeve, infrared, PNP, Metal connector M12 4-pin
FMS 30-35 U	544-51323 Light barrier for fiber optic adaptation, infrared, 100Hz, PNP N.O., VMA, cable
30 RZ 12/1000-MSC LS=16	30 RZ 12/1000-MSC LS=16 fiber optic button glass fibers for FMS sensors, light scanner with metal coil, 100mm, radial Light exit, button
606-11000 FR 25-R-PS-M4	Reflective light barrier, 6m, red light, LED, PNP, teach-in, connector M8 4-pin, IP67 & IP69K There is a new variant for this product: 606-11042 FR 25-R-PNSL-M4 This offers additional functions via IO-Link.
608-11000 FT 25-RHD-PS-M4	Diffuse reflection sensor with background suppression, 400 mm, red light, LED, PNP, teach-in, connector M8 4-pin, IP67 & IP69. There is a new variant for this product 608-11042 FT 25-RHD-PNSL-M4 This offers additional functions via IO-Link
602-71004 FE 10-RL-PS-KM4	Laser through-beam sensor, receiver, red light, laser class 1, SN=4000mm, PNP, 4000Hz, IP67, molded connector (pigtail) M8 4-pin, 200mm cable, teach-in
FR 25-RGO-PS-M4	Reflection light barrier with autocollimation principle for detecting transparent objects, 2m, red light, LED, PNP, teach-in, connector M8 4-pin, IP67 & IP69K There is a new variant for this product: 606-11054 FR 25-RGO-PNSL-M4
FR 85-2 ILLG-S1L5	
FR 25-RGO-PNSL-M4	
FT 50 RLA-220-S1L8	
FR 25-RGO-PS-KM4-X04	
820-41001	
608-11004 Schalter Sensopart Ft 25-Rh-Ps-M4	
545-01000	IP68 OVERHOUSING, STAINLESS STEEL DOES NOT INCLUDE FA45
609-11005 Ft 25-Rlh-Ps-M4	
Fgl5-Ik-50-Ps-K4	
Fr55-Rlap-70-2pnsi-L8	
Lb86rd-24-Kfl5	
580-51406, Fls 18-L4fls 18-L4	

532-51035 Mg3a	(LR 100 WD-24-KFL5) RINGLIGHT, DIFFUSE, 100 MM, WHITE
574-41014	
580-51398, Fs 18 RI-L4fs 18 RI-L4	
552-11007, Fe 23 R-Ps-M4fe 23 R-Ps-M4	
609-11002	
580-51416, Fle 18 Wfle 18 W	
604-41003	
600-11012	
18/30r04/1000-Si	
P/N: 621-11004 Type: Fr 55-R-Ns-K4	
537-91011	
P/N: 535-91006 Type: V10-Ob-A1-I6	
697-01052	
697-01037	
Ft50rlhd-Nak4	
Ft90ila-S2-Q12	
Ft25-RIh-Ps-M3	
620-11002	
605-21013, Fe 25-R-Ns-M4mfe 25-R-Ns-M4m	
Fms18-34u-60	
591-91003	(FT 91 ILA-S2-Q12) DIFFUSE 0.5M-6M, 5MM RES., LASER, ANALOG, 2XPNP, 4-20MA / SERIAL, PLUG M16 12 PINS
996-50325	
Fr55-RI-Ns-K4	
Idt6-2b-Ps-K3	
536-91042	
Art.No. 608-11000, Type: Ft 25-Rhd-Ps-M4	
042-12825 / Ma 18 A	
Vision V10-A Model	

96905910 (Vk5575ube91970)	
978-08577	
18/30 Lz 1/500-Si Ls=10	
It12-8n-Ns-K3	
532-51071	
Llk1rm3pe-1m	
540-51319	
522-91088	EYESIGHT, VGA, RED LIGHT, RED NOTCH FILTER, CCD-MONO, LIGHT VER., 6MM LENS, ETHERNET / RSXXX
552-11009, Fe 23 R-Ns-M4fe 23 R-Ns-M4	
041-01304	
525-51156, LI 18 R-24-L4II 18 R-24-L4	
Ut18-270-Ail4	
690-51541 Ultraschallsensor Um 18-60-250-Cd-Hp	
580-51408	
525-51137	
Lr56r-24-Kfl5	
750-11005	
620-21000, Fe 55-R-Ps-L4fe 55-R-Ps-L4	
690-51566	
18/30rz2/1000-Sils=10	
Ft10-Bf2-Ns-Km3	
532-51005	(LR 70 R-24-KFL5) RINGLIGHT, 70 MM, RED
606-11015	
K3-2m-G-Pur	
V10c-All-A2-W25	
553-11013	
902-51664	
622-21007	
Fr20rlo-Psk4	

600-11132	
605-21014, Fe 25-RI-Ps-M4mfe 25-RI-Ps-M4m	
979-06254	
902-51794	
Fms30-34b	
V10c-Eye-A2-W6	
996-50274	
V10-Cr-A1-R6	
Fms184u	
532-51034	(LR 70 WD-24-KFL5) RINGLIGHT, DIFFUSE, 70 MM, WHITE
543-11002	
Mspf50	
742-51004, Fse 18-2 Im-Ps-L4fse 18-2 Im-Ps-L4	
Lb625rk24a353I5	
978-06405	
Mft12pp4	
532-51009	(LR 132 WW-24-KFL5) RINGLIGHT, ANGLE, 132 MM, WHITE
Ft10-Bf2-Ns-K4	
Lr70rid-24-Kfl5	
623-11007	
Ft10-Rf1-Ns-Km4	
902-51632	
552-11004, Fs 23 R-M4fs 23 R-M4	
996-09444	
Fs55-RI-L4	
Fm18500-4x	
532-51069	
551-11011	
690-51541 / Um18-60/250-Cd-Hp	
Llk2slr10pe-2m	

902-51792	
535-91022	
Llk2lv6pe-1m	
30lz42000sils	
718-51400	
623-11022	
600-11146	
601-61005, Fs 10-RI-Km3fs 10-RI-Km3	
Fgl120-Ik-50-Ps-M3	
535-91073	(V10C-CO-A2-W6) V10 COLOR ADVANCED OBJECT SENSOR, 736X480, 6MM WHITE, RS422/RS232, ETHERNET/ETHERNET/IP
535-91104	
Fms200-01	
974-09617 Lichtleiter 30 Ql 0,2x10/1000-Si	
Lb44wd-24-Kfl5	
551-11025	
979-06656	
978-08195	
Mbd-F-10	
Ft20-R-Psm4	
Ft10-Rf2-Ps-Km3	
604-41000	
978-06488	
Cusb-Rs485-0.7m	
927-81003	INFRARED, MEASURING FIELD 150MM, RANGE 2100MM, RESOLUTION 7 MM, 0-10 V
978-06453	
536-91011	
522-91095	EYESIGHT, VGA, WHITE LIGHT, CCD-COLOR, ADVANCED VER., 6MM LENS, ETHERNET / RSXXX

522-91080	EYESIGHT, VGA, WHITE LIGHT, CCD-MONO, LIGHT VER., 6MM LENS, ETHERNET / RSXXX
527-51139	
Ft18-2id-Ps-K4	
526-51516, Lo C 25lo C 25	
522-91053	VGA, WHITE LIGHT, CCD-MONO, OBJECT DETECTION, 12MM LENS, HIGH END, ETHERNET/RS422
979-08345	
Ft20rh-Psm4	
741-11015	
532-51004	
Fs 20 R-M4 / By Fs 25-R-M4m	
V10-Tcbox-101	
18/30I2/500-Msc	
Fms3024ul460	
996-51486	
Ft25-Rlh-Ps-M3m / 609-11007	
543-11010	
978-06382	
718-51403	
Fr25-Rlo2-Ps-K4	
It12bm-Psl4	
Ft 25-R-Ps-M4m	
902-51844	
571-50005	
693-11012	
902-51773	
580-51411, Fle 18-L4-15fle 18-L4-15	
Fgl80r-Psm3	
532-51014	
690-10102	
V10-Cr-A1-I25	

979-08342	
572-51004 Sensor Ft 50 Rh-Pal4	
518-51505 Optischer Sensorfmh 18-L4 , Reflexions-Lichttaster Mit Hga, M12- Stecker 4-Polig, Bis 120mm	
522-91084	EYESIGHT, VGA, WHITE LIGHT, CCD-MONO, ADVANCED VER., 12MM LENS, ETHERNET / RSXXX
978-06428	
591-91008	
Cusb-Rs232	
978-06459	
978-06383	
574-41030	80 . 300MM, 0.215MM, LASER, ANALOG, 1 X NPN, NC/NO , 4 TO 20MA, PLUG M12 5 PINS
978-06412	
Imt18-8b-Ns-L4	
831-81000	(FG40 I-PSM3) 40 X 80MM, PNP N.O., PLUG M8 3 PINS
902-51610	
Ft-10-RIh-Ps-Km4	
551-11022	
591-91011	
696-51478	
Ft91-Ila-S2-Q12	(591-91003) DIFFUSE 0.5M-6M, 5MM RES., LASER, ANALOG, 2XPNP, 4-20MA / SERIAL, PLUG M16 12 PINS
579-50000	
522-91085	EYESIGHT, VGA, CCD-MONO, ADVANCED VER., C-MOUNT LENS, ETHERNET / RSXXX
R1	
Lms10-S22	
611-51002, Fs/Fe 10-RI-Ps-K4fs/Fe 10- RI-Ps-K4	
K4-2m-W-Pur	
611-51005, Fs/Fe 10-RI-Ns-Km4fs/Fe 10-RI-Ns-Km4	

600-11104	
Fr51rl-Pal4	
551-71000	
606-11000 Fr 25 R-Ps-M4	
532-51021	
Fr91ila-S2-Q12	
607-21011	
917-16000	
532-51030	(LR 70 WID-24-KFL5) RINGLIGHT, INDIRECT, DIFFUSE, 70 MM, WHITE
532-51015	(LR 130 WI-24-KFL5) RINGLIGHT, INDIRECT, 130 MM, WHITE
Fr 23 R-Psm4	
558-41001	
996-09972	
97908045 (R1/500pvc)	
Lb1000irk24a353I5	
532-51018	(LF 36 WD-24-KFL5) AREALIGHT, DIFFUSE, 36 MM, WHITE
Fs25-R-M4m	
522-91128	VGA, CCD-MONO, CODEREADER, C-CS MOUNT LENS, HIGH END., QUALITY PARAMETERS, ETHERN./RS422
605-21017, Fe 25-Rf-Ns-M4fe 25-Rf-Ns-M4	
611-51006, Fs/Fe 10-RI-Ps-Km3fs/Fe 10-RI-Ps-Km3	
979-08337	
526-51531, Lof-Pf-30,5x0,5lof-Pf-30,5x0,5	
Ft25-W1-Gs-M4m	
572-51062 Sensor Ft 50 RIhd-Pal4	
601-61004, Fs 10-RI-Km4fs 10-RI-Km4	
978-08551	
572-51051	
573-52002, Fs 50 I-K4fs 50 I-K4	

572-51011	
It8-1b5-Ps-K3	
Cl12fg-S-5m-Pur	
741-11022	
996-09973	
978-06437	
978-06364	
902-50690	
Fs10-RI-Km4	
Ft10-RIhr-Ps-Km4	
978-51649 / 18/30 Lzx 1/400-260 Si Ls=11	
742-51000 Sensopart Fse 18-1 I-Ps- L4einweglichtschranke, M18,Sn=8000 Mm, Pnp, Stecker M12-4pol	
Cl8-Fg-S-10m-Pur	
543-11011	
532-51037	(LR 100 RD-24-KFL5) RINGLIGHT, DIFFUSE, 100 MM, RED
573-52005, Fe 50 I-Psvk4fe 50 I-Psvk4	
536-91026	
607-21010 Ft 25-Rgb1-Gs-Kl4	
Ci L4mg/Rj45g-Gs-5m-Pur	
Lr50ww-24-Kfl5	
904-51564	
609-21003	
Fr25-Rgo-Ns-M4	
Is46-12	
525-51150	
Fe25-R-Ns-K4	
575-11000	
832-11009	
620-11000, Fs 55-R-L4fs 55-R-L4	

535-91027	
Fr25-R-Ps-K4	
Fr 25-R-Ps-M4	Reflection light barrier, 6m, red light, LED, PNP, teach-in, M8 4-pin connector, IP67 & IP69K There is a new version for this product: 606-11042 FR 25-R-PNSL-M4 This offers additional functions via IO-Link. Product information can be found at www.sensopart.de Net weight of the item: 0.022 KG Country of origin: DE Stat. Product number: 85365019I
978-06527	
Lf100ard-24-Kfl5	
591-91000	(FT 90 ILA-S2-Q12) DIFFUSE 0.5M-12M, 4MM RES., LASER, ANALOG, 2XPNP, 4-20MA / SERIAL, PLUG M16 12 PINS
979-06185	
532-51020	(LF 100 WD-24-KFL5) AREALIGHT, DIFFUSE, 100 MM, WHITE
620-11003, Fs 55-RI-K4fs 55-RI-K4	
526-51514	
697-01058	
902-51735	CONVERTER, RS422 / PROFIBUS
V10-Ob-A1-I12	
18/30Iz3/1500-Pvcls=14	
Fe55-RI-Ns-L4	
681-50956	
602-71005, Fe 10-RI-Ns-Km4fe 10-RI-Ns-Km4	
510-51589	
996-50641	
Cl12/3fw-S-20m-Pur	
620-21003, Fe 55-R-Ps-K4fe 55-R-Ps-K4	
Imt30-15n-Ns-K3	
Ut 20-150-Aim4	
580-51410, Fle 18-L4fle 18-L4	
K4-2m-G-Pur (902-50801)	cable M8 connection cable - 4-pin 2m - straight - PUR Net weight of item: 0.280 KG (per unit: 0.070 KG) Country of origin: CZ Stat. Product number: 85444290
527-51136, Lpt S5Ipt S5	

927-81001	INFRARED, MEASURING FIELD 100MM, RANGE 2100MM, RESOLUTION 7 MM, 0-10 V
621-11026	
Ft25-R-Ps-Km4	
690-51567	
V20-Eye-A2-W 12	
Ft10-B-Rlf2-Ns-K4	
540-51605, Fms 30-34 U-54fms 30-34 U-54	
Lpt45cmI5I	
Fr25-Rgo-Ps-M4	
Kd12b-PsI4	
532-51008	(LR 90 WW-24-KFL5) RINGLIGHT, ANGLE, 90 MM, WHITE
Ft18-2 Rwmpl4	
623-11006	
18/30r15/500-Si	
620-11002, Fs 55-RI-L4fs 55-RI-L4	
99609905	
979-08051	
580-51406 Fls 18-L4 Laser- Einweglichtschranke, M12,Sender, Stecker M 12 4-Pol	
608-11039	
30rz4/250-Sils= 16	
979-06184	
567-71003	
V10c-Eye-A2-W 12	
522-91055	VGA, RED LIGHT, CCD-MONO, OBJECT DETECTION, 6MM LENS, HIGH END, ETHERN./RS422
697-01006	
18/30lz1/750-Sils= 10	
571-50004	

8340f410p1f7a2h142-2a	
Ft50-C-1-Ps1-L8	
Fr25-Rgo2-Ns-K4	
720-50766	
688-51090	
532-51012	(LR 90 RW-24-KFL5) RINGLIGHT, ANGLE, 90 MM, RED
R5 (Refl.51x61),Standard	Accessories, reflector 51 x 61mm; 2 mounting holes
609-11005 Schalter Sensopart Ft 25-RIh-Ps-M4	
740-21016	
604-41002	
903-05142	
902-51736	
FMS 30-35 U	544-51323 Light barrier for light guide adaptation, Infrared, 100Hz, PNP N.O., VMA, Kab
RI250	
Ft55-Rh-Ps-L4	
Ft50rla-100-PI5	
606-11016 Optischer Sensorfr 25-Rgo-Ps-M4m	
535-91050	
Ft10-B-RIf1-Ps-Km4	
K4-10m-G-Pur	
996-09397	
Aerp 150 B90 Ae 2,5mt	
P/N: 551-11010 Type: Ft 20 Ih-Psm4	
1830rx21000si X	
V10-Cr-A1-W12	
Fe10-RI-Ps-K4	
Fle18w-L4-15	
697-01005	
571-50001	

979-08415	
Art.No. 575-11000, Type: Ft 50 C-1-PsI8	
558-41006	
902-51835	
535-91041	
Ft55b-Rh-Ps-L4	
904-51533	
V10-All-A2-R25	
535-91096	
611-51001, Fs/Fe 10-RI-Ns-E4fs/Fe 10-RI-Ns-E4	
038-12401	
902-50683	
532-51007	(LR 74 WW-24-KFL5) RINGLIGHT, ANGLE, 74 MM, WHITE
605-21004, Fe 25-RI-Ns-K4fe 25-RI-Ns-K4	
Fr18-2iw-Ps-L4	
902-50808	
979-50544	
Ft50rlh-Nak4	
840-11002	
580-51415, Fle 18 W-L4-15fle 18 W-L4-15	
605-21012, Fe 25-R-Ps-M4mfe 25-R-Ps-M4m	
V20-So-A2-C	
P/N: 830-11007 Type: Fgl 180 R-Psm3	
605-11002, Fs 25-RI-K4fs 25-RI-K4	
927-81001 , Type Fcp 100-I7-2100-Psu-L	
Ft10-Rh-Ns-E4	
Ft88r-Ga-L4	
904-51565	

602-71003, Fe 10-RI-Ns-K4fe 10-RI-Ns-K4	
927-81000	INFRARED, MEASURING FIELD 100MM, RANGE 2100MM, RESOLUTION 5 MM, 0-10 V
979-51457	
Mbst2	
902-51813	
580-51400	
609-31010	
540-51622 Fm 30-800-3 X Sp-L4-X01 (Ndt)fotosensor Mit L4-Stecker	
L4-10m-G-Pur	
750-11004	
579-50010 Ms F 55 Befestigungswinkel Set (L-Form, V2a/1.4301)	
996-51481	
Ft20r-Nsm3	
918-10001	
Mfc12pp4	
Fe25-RI-Ns-M4m	
97951295	
553-11000	
902-51716	
30I4/500-Si	
532-51011	(LR 74 RW-24-KFL5) RINGLIGHT, ANGLE, 74 MM, RED
Aerp 150 B90	
978-06439	
532-51036	(LR 70 RD-24-KFL5) RINGLIGHT, DIFFUSE, 70 MM, RED
693-11007	
600-11030	
Kd08b-Pom3	
535-91023	
97806798 (L12/500msc)	

Kl06nb-Nom3	
978-06949	
996-09394	
608-11004	
978-06797	
902-51688	
18/30r31000s1	
V10-All-A2-I12	
750-11001	
902-51641	
522-91067	VGA, RED LIGHT, CCD-MONO, CODEREADER, 6MM LENS, HIGH END, ETHERN./RS422
Fr 20 Rlo-Psm4	
V10-Ob-A1-W6	
R3-2Ik1	
979-08081	
605-11001, Fs 25-R-K4fs 25-R-K4	
553-51004	
605-21017	
K3-5m-G-Pur	
97908050	
18/30r1/500si	
Fe10-RI-Ns-Km4	
522-91083	EYESIGHT, VGA, WHITE LIGHT, CCD-MONO, ADVANCED VER., 6MM LENS, ETHERNET / RSXXX
53051589 (Fms30-44ug-60)	
527-51135	
904-51588	
18/30r2/500-Si	
604-41010	
979-08049	

741-11011	
Fr 20 RI -Psm 4 Sensor	
Fr 25-RI-Ps-M4m	Reflection light barrier, 13m, laser, PNP, Teach-in, metal connector M8 4-pin, IP67 & IP69K There is a new version for this product: 609-31018 FR 25-RL-PNSL-M4M This offers additional functions via IO-Link. Product information can be found at www.sensopart.de Net weight of the item: 0.050 KG (per unit: 0.025 KG) Country of origin: DE Stat. Product number: 85365019
Fms18-34u	
Art.No. 968-11000, Type Mft 12 Pp4	
522-91097	EYESIGHT, VGA, CCD-COLOR, ADVANCED VER., C-MOUNT LENS, ETHERNET / RSXXX
697-01047	
K2ade	
609-31013	
537-91015	
567-71001	
K4-5m-W-Pur	
904-51543	
602-71002, Fe 10-RI-Ps-K4fe 10-RI-Ps-K4	
532-51013	(LR 132 RW-24-KFL5) RINGLIGHT, ANGLE, 132 MM, RED
544-51323	
Ut20-240-Nsm4	
Fms30-34ut	
042-12820	
571-50009	
Lms13-S22	
697-01010	
Fs/Fe10-RI-Ns-E4	
Fse18-2im-Ps-L4	
Rf775x500mm	
902-51654	

902-51797	
623-11012	
821-11013	
Ft12r-Psk3	
Lb1000rk24a353I5	
551-21018	
Ft92ila-PsI5	
904-51590	
609-21004	
994-51132	
Ma45I	
18/30I1/750-Si	
902-51604	
580-51446	
551-11023	
575-11016	
532-51076	
K3-10m-G-Pur	
591-91001	(FR 90 ILA-S2-Q12) RETRO 0.5M-250M, 2MM RES., LASER, ANALOG, 2XPNP, SSI / SERIAL, PLUG M16 12 PINS
522-91052	VGA, WHITE LIGHT, CCD-MONO, OBJECT DETECTION, 6MM LENS, HIGH END, ETHERNET/RS422
Fr20rl-Nsk4	
720-50767	
Ft55-RI2h-Ps-L4	
526-51515, Lo C 16lo C 16	
FI20r-Psm3	
522-91093	EYESIGHT, VGA, RED LIGHT, RED NOTCH FILTER, CCD-MONO, ADVANCED VER., 6MM LENS, ETHERNET / RSXXX
681-50917	
Fgl30-Ik-30-Ns-M4	
30rz12/1000-Sils=16	

Ft25-RIh-Ps-KI4	
902-50805	
600-11010	
Ft20rh-Psm3	
536-91012	
Imt8-2b-Ps-M3	
903-50314	
555-31000	
532-51024	(LF 200 WD-24-KFL5) AREALIGHT, DIFFUSE, 200 MM, WHITE
FI70ra-Nsd-K5	
543-11030, Lr 0,5lr 0,5	
Mfw12nn4	
741-11008	
832-11024	
533-01027, Pv-Aw1010.4tx Depv-Aw1010.4tx De	
Soda Caustica	
904-51532	
Fms-30-44ul-4-60	
974-09617	
602-71008, Fe 10-RI-Ns-Km3fe 10-RI-Ns-Km3	
Ft25-Rhd-Ns-M4	
681-50942	
543-11021	
522-91065	VGA, WHITE LIGHT, CCD-MONO, CODEREADER, 12MM LENS, HIGH END, ETHERN./RS422
Is518-02	
690-51542	
18/30 Lz 1/1000-Si Ls=10	
Vk-5575u-05	
623-11035	

Ft25-RI-Ps-Km4	
532-51017	(LR 130 RI-24-KFL5) RINGLIGHT, INDIRECT, 130 MM, RED
Fr55-R-Ps-L4	
Ms F 20	558-41000 Fastening set for F 20 , (Bracket and screws)
996-51449	
Fms30-44ug-56	
Fr20rg-Nsm3	
FI70r-Ns-K4	
902-51694	
571-50006	
742-51007, Fse 18-2 Im-Ns-K4fse 18-2 Im-Ns-K4	
532-51078, Lb 1000 Irk 24 A35 3I5Ib 1000 Irk 24 A35 3I5	
951-50008	
951-50001	
Fr-18-1 I-PsI4	
978-06545	
V20c-Eye-A2-C	
Is48-12t	
V10-Cr-S2-I25	
830-11005	
693-11006	
Ft20rl-Psk4	
526-51353, Ex2cex2c	
823-11010 Lichtschrinke Fr 88-R-Pav-L5	
Llk1rvv6pe-1m	
902-51657	
Ft10-Rf3-Ps-Km3	
30Iz4/500-Mscls=16	
978-06543	

Cil8mgk/L4mgk-S-02m-Pvc	
528-51106	LINE SENSOR, ANALOGUE OUTPUT 4 . 20MA
952-50001	
580-51408, Fls 18 W-L4fls 18 W-L4	
978-08215	
697-01033	
609-11012	
Imt30-15n-Ps-L4	
K3-10m-W-Pl-Pur	
18/30r3/500-Si	
18/30rz1/500-Mscls=10	
978-06406	
621-11023	
742-51005, Fse 18-2 Im-Ns-L4fse 18-2 Im-Ns-L4	
Rd4	
527-51139, Lpf S1lpf S1	
551-11003	
Cl12/3fg-S-5m-Pur	
30I4/2000-Msc	
532-51059	
Fr20r-Nsm3	
Art.No.740-21029 Ft 18-2 Idm-Ps-L4	
681-50957	
525-51126	LUMINARY, USABLE AEREA 420MM, IP 67
600-11103	
532-51025	(LF 200 RD-24-KFL5) AREALIGHT, DIFFUSE, 200 MM, RED
978-08236	
Ft 25-Rh-Ps-M4m (608-11014)	Diffuse reflection sensor with background suppression, 200 mm, red light, LED, PNP, metal plug M8, 4-pin, IP67 & IP69K For this product there is a new variant 608-11053 FT 25-RH PNSLM4M This offers additional functions via IO-Link. Further Product information can be found at www.sensopart.de Net weight of item: 0.084 KG (per unit: 0.021 KG) Country of

origin: DE Stat. Product number: 85365019	
R50bc	
Is-530-04-S	
Ft 20 R-Psm4	
Fr10-RI-Ns-K4	
K4-2m-G-Pur	902-50801 Connection cable, M8 connection cable - 4-pin 2m - straight - PUR
591-91012	
580-51405, Fe 12 RI-Nsl4fe 12 RI-Nsl4	
532-51006	
Mg 2 A	
580-51407, Fls 18fls 18	
Ft18-2id-Ps-L4	
902-51840	
18/30I3/750-Msc	
978-06478	
902-51681	
600-11134	
041-01304 Ma 18 (Montagewinkel Fm 18)	
572-51004	
608-11034	
Is34-52	
Ft12 R-Psl4	
580-51412, Fle 18fle 18	
Fmsa668232	
690-51167	
611-51003, Fs/Fe 10-RI-Ns-K4fs/Fe 10-RI-Ns-K4	
Fr18-2rm-Ns-L4	
Ut18-270-Psl4	
Fe25-RI-Ns-K4	

18/30rz3/250sils=14	
Fr25-Rl-Ps-M3m	
681-50955	
552-11007	
697-01036	
Ft10-Rlhr-Ns-Km3	
832-11018	
902-50801 K4-2m-G-Pur(M8-Kabel F 4p2000 Gerade Pu	
979-06274 Fiber Optic Cable18/30 Rz 2/500-Pvc-2v2a	
609-21012	
620-21000	
605-11006, Fs 25-R-M4mfs 25-R-M4m	
Ft 25-Rlh-Ps-M4	
Ft10-Rf1-Ns-Km3	
Fr50rl-Psvk4	
V10-Ob-A1-I6	
608-11000 Ft 25-Rhd-Ps-M4	
Fe50i-Pal4	
525-51143	
Lf36wd-24-KfI5	
821-11013 Lichtschanke Ft 88-Ih-Pa-L5	
Ms F 20 (Fixing Set F 20	Fixing set for F 20, (Bracket and screws)
978-06407	
902-51817	
533-01010, Lof-Lp-Ir850-30,5x0,5lof-Lp- Ir850-30,5x0,5	
821-11010	
Imt8-2n-Ps-K3	
750-11006	

Ut20-150-Aum4	
902-51830	
Ft55-Rh-Ps-K4	
978-06653	
978-51688	
Fs10-RI-K4	
97908058	
574-41032	
608-11004 Ft25-Rh-Ps-M4	
620-21001, Fe 55-R-Ns-L4fe 55-R-Ns-L4	
99509516	
996-09399	
Fr25-RI-Ps-K4	
571-50003	
Fr20-R-Psm4	
551-21007	
697-01019	
R5-8/L	
Mft12pp4t:...	
Lvlf6-M3	
902-51715	
741-11025	
526-51519, Lot-Tec-M55lot-Tec-M55	
979-06147	
611-51006	
Ft50c-1-Psl8	
580-51409, Fls 18 Wfls 18 W	
30rz4/1000-Mscls=16	
522-91126	VGA, WHITE LIGHT, CCD-MONO, CODEREADER, 6MM LENS, HIGH END., QUALITY PARAMETERS, ETHERN./RS422
979-06647	

904-51641	
Ft25-Rh-Ns-M3m	
535-91102	
18/30-R-3/250-Si	
555-31006	
Llk2lz	
Ut12-370-Ail4	
Ut	
Is48-01	
601-61002, Fs 10-RI-K4fs 10-RI-K4	
830-11010	
Ft18-2rw-Ns-K4	
Fse18-2im-Ps-K4	
607-21025 Sensorft 25-Rgb1-Gs-M4m-X07	
522-91054	VGA, CCD-MONO, OBJECT DETECTION, C-CS MOUNT LENS, HIGH END, ETHERNET/RS422
573-52004, Fe 50 I-Psvl4fe 50 I-Psvl4	
Imt18-8b-Ns-K3	
979-08414	
742-51006, Fse 18-2 Im-Ps-K4fse 18-2 Im-Ps-K4	
522-91129	VGA, RED LIGHT, CCD-MONO, CODEREADER, 6MM LENS, HIGH END., QUALITY PARAMETERS, ETHERN./RS422
Fl70ra-Psd-K5	
Ms F20 (558-41000)	(Bracket and screws) Net weight of item: 0.052 KG (per unit: 0.013 KG) Country of origin: DE Stat. Lot number: 76041090
605-21016, Fe 25-Rf-Ps-M4fe 25-Rf-Ps-M4	
832-11019	
602-71006	
832-11000	
600-11105	

Is34-51	
697-01038	
Fms30/34-U	
522-91089	EYESIGHT, VGA, RED LIGHT, RED NOTCH FILTER, CCD-MONO, LIGHT VER., 12MM LENS, ETHERNET / RSXXX
740-21034	
Ft55-Bh-Ns-L4	
33lv122w	
Rf-50kl	
623-11000 Sensopart Ft55-Rh-Ps-L4	
553-11010	
575-11014	
902-51821	
974-09617 30 Ql 0,2x10/1000 Si, Querschnittswandler, 1000mm, Silikon, 10mm Lichtaustritt	
605-21001	
979-06320	
903-05142 / Mb 10 (Z-Halterung)	
611-51004, Fs/Fe 10-RI-Ps-Km4fs/Fe 10-RI-Ps-Km4	
Cil4fgk/L8fgk-S-02m-Pvc	
Is58-13s	
Fav 30-01	
551-11005	
522-91035	VGA, WHITELIGHT, CCD-COLOR, COLOR, 12MM LENS, HIGH END, ETHERNET/RS422
Ft10-B-Rlf2-Ps-Km3	
Mft12nn4t:..	
553-11000 Sensor Fr 20 Rpsm4	
Ft88rh-Pa-L5	
740-21026	
552-21000	

623-11014	
P/N: 742-51004 Type: Fse 18-2 Im-Ps-L4	
606-11030	
30rx2/310-Si	
522-91081	EYESIGHT, VGA, WHITE LIGHT, CCD-MONO, LIGHT VER., 12MM LENS, ETHERNET / RSXXX
605-21003, Fe 25-R-Ns-K4fe 25-R-Ns-K4	
Lr132rw-24-KfI5	
Fr20rg1-Nsm4	
V20-Ob-A2-C	
996-09421	
SaI-12-Rk12-5/A3 Conec	
Fr50rl-Nsvk4	
572-51002	
P/N: 606-11000 Type: Fr 25-R-Ps-M4	
Ft25-Rvd-Pns-M4m	
Ft50ih-Pak4	
690-51569	
522-91056	VGA, RED LIGHT, CCD-MONO, OBJECT DETECTION, 12MM LENS, HIGH END, ETHERN./RS422
567-71002	
Fe 20 R-Psm4 / By Fe 25-R-Ps-M4m	
605-21015, Fe 25-Rl-Ns-M4mfe 25-Rl-Ns-M4m	
Lr130wi-24-KfI5	
18/30r3/750-Msc	
606-11023	
522-91058	VGA, WHITE LIGHT, CCD-MONO, OBJECT DETECTION, 6 MM LENS, LIGHT, ETHERNET
Umt30-6000-2psd-L5	
Ft10-Rlh-Ps-K4	

690-51164	
580-51417	
608-11040	
532-51077, Lb 625 Irk 24 A35 3I5Ib 625 Irk 24 A35 3I5	
Is56-11t	
Is530-44-S	
Ft25-Bf2-Ns-K4	
572-51029	
591-91000 Ft 90 Ila-S2-Q12	
Is530-41	
Fr10-RI-Ps-E4	
740-21022	
L8f-10m-W-Pur	
978-08231	
902-51695	
904-51644	
902-51831	
Ut20-240-Aum4	
996-09396	
V20-AII-A2-R12	
831-81002	(FG 120 I-PSM3) 120 X 80MM, PNP N.O., PLUG M8 3 PINS
532-51019	(LF 51 WD-24-KFL5) AREALIGHT, DIFFUSE,51 MM, WHITE
C L12fg-S-5m-Pur	
Imt18-8b-Ps-L4	
602-71006, Fe 10-RI-Ps-Km3fe 10-RI-Ps- Km3	
Cl12/3fw-S-5m-Pur	
580-51413	
Imt18-5b-Ns-L4	
97908491	
18/30rz2/250sils= 10	

750-11002	
Ft50rh-Nal4	
Ft10-RIh-Ps-Km3-X07	
903-05141	
978-08234	
522-91082	EYESIGHT, VGA, CCD-MONO, LIGHT VER., C-MOUNT LENS, ETHERNET / RSXXX
Fms30-44ul-4-60	
Ft50rh-Psvl4	
951-50009	
978-06426	
Fr25-RI-Ns-Km4	
621-11001	
979-06199	
902-50679	
532-51038	(LD 50 WD-24-KFL5) RINGLIGHT, DOME, DIFFUSE, 50 MM, WHITE
527-51140, Lpf S2lpf S2	
607-21004	
575-11018	
527-51134, Lpt 45 Cml 5llpt 45 Cml 5l	
Lb180rd-24-Kfl5	
978-06420	
Ft55-R-Ps-L4	
979-06196	
606-11005	
522-91127	VGA, WHITE LIGHT, CCD-MONO, CODEREADER, 12MM LENS, HIGH END., QUALITY PARAMETERS, ETHERN./RS422
Q12-3m-W-Pvc	
048-12932	
Fs25-RI-M4m	

Sq12t-02	
527-51138, Lpt 45llpt 45l	
527-51143, Etssets	
R100bc	
P/N: 536-91012 Type: V20-Ob-A2-R12	
660-01000	
532-51032	(LR 70 RID-24-KFL5) RINGLIGHT, INDIRECT, DIFFUSE, 70 MM, RED
Fgl30-Rk-30-Ns-M4	
543-11031, Lr 1lr 1	
Mbd-S94	
904-51570	(RL700) REFLECTOR
Fa-46-305-Wcc-Obo12es6	VISION SENSOR AND LEADS WHITE LIGHT GUI 2
FT 50 RLA 220 PL5	574-41029 Distance sensor, 80...300mm, resolution 0.1% MBE, 1 x PNP, N.C./N.O. 4...20 mA, plug M12 5-pin
573-52007, Fe 50 I-Pal4fe 50 I-Pal4	
620-11001, Fs 55-R-K4fs 55-R-K4	
591-91009	
V10-AII-A2-R12	
Fe10-RI-Ps-Km3	
Lb180wd-24-Kfl5	
Sal-45s-S8.36-12d-Rs4.2-5/Gaf/025	
18/30rz1/1000-Mscls=10	
742-51004	
532-51039	(LD 50 RD-24-KFL5) RINGLIGHT, DOME, DIFFUSE, 50 MM, RED
Ft50rlh-Psvk4	
3311/500msc	
Imt8-2n-Ns-K3	
978-08549	
902-51652	
608-11015	
528-51105	LINE SENSOR, ANALOGUE OUTPUT 0 . 10 V

904-51562	
978-06370	
Ft-10-B-Rlf2-Ps-Km4	
574-41034	
Fr25-R-Ps-M3m	
580-51440, Fle 18wm-L4-X01fle 18wm-L4-X01	
522-91062	VGA, RED LIGHT, CCD-MONO, OBJECT DETECTION, 12MM LENS, LIGHT, ETHERNET
522-91094	EYESIGHT, VGA, RED LIGHT, RED NOTCH FILTER, CCD-MONO, ADVANCED VER., 12MM LENS, ETHERNET / RSXXX
Ft20r-Nsm4	
605-11008, Fs 25-Rf-M4fs 25-Rf-M4	
Mspf20-11	
697-01045	
522-91034	VGA, WHITELIGHT, CCD-COLOR, COLOR, 6MM LENS, HIGH END, ETHERNET/RS422
Imt30-15b-Ns-K3	
V10-Cr-A1-C	
Ft50-RIh-PaI4	
681-50945	
Fr-25-RI-Ns-M4m	
V20-Ob-A2-W12	
904-51585	
Ft50 Rla-40sl4s* 574-41003	
Ft50rla-70-L8	
K2r-25	
740-21030	
580-51399, Fe 18 RI-Ns-L4fe 18 RI-Ns-L4	
543-11032, Lr 10lr 10	
742-51006	

522-91036	VGA, CCD-COLOR, COLOR, C-CS MOUNT LENS, HIGH END, ETHERNET/RS422
551-21001	
Fs10-RI-Km3	
510-51590 Fms 18-34 UI4-60m18infrarot, 5000hz, Pnp/Npn N.O., Stecker M12 4-Poliglichtleitersensoren	
974-51281 30 Qlx 1,0x15/750-Si, X = 12.01.06	
555-31007	
Ms-F-10	
979-08063	
535-91094	
551-21004	
608-11030	
522-91130	VGA, RED LIGHT, CCD-MONO, CODEREADER, 12MM LENS, HIGH END., QUALITY PARAMETERS, ETHERN./RS422
555-31004	
602-71008	
Is-512-44-S	
705-21001	
978-08202	
601-61000, Fs 10-RI-E4fs 10-RI-E4	
Ft 55-RI2h-Ps-L4 Sensor	Laser reflection light scanner with background suppression, Red light, PNP, IP67, connector M12, laser class 1 Item net weight: 0.171 KG (per unit: 0.057 KG) Country of origin: DE Stat. Product number: 85365019
580-51401, Fs 12 RI-L4fs 12 RI-L4	
996-51454	
P/N: 605-11006 Type: Fs 25-R-M4m	
Ft10-Rf3-Ns-Km4	
622-21009	
704-21001	
978-06379	
Lpfs2	

P/N: 571-50009 Type: Fr 50 RI-Pal4	
536-91005	
978-06444	
573-52003, Fe 50 I-Pak4fe 50 I-Pak4	
572-51026	
681-50895	
580-51414, Fle 18 W-L4fle 18 W-L4	
532-51023	(LF 100 RD-24-KFL5) AREALIGHT, DIFFUSE, 100 MM, RED
L8fs-2m-G-Pur	
580-51446, Fls 18wm-L4-X02fls 18wm-L4-X02	
Is56-12	
602-71001, Fe 10-RI-Ns-E4fe 10-RI-Ns-E4	
606-11009	
P/N: 540-51321 Type: Fms 30-34-Un	
522-91059	VGA, WHITE LIGHT, CCD-MONO, OBJECT DETECTION, 12 MM LENS, LIGHT, ETHERNET
978-06462	
978-08239	
Ft-160-Rh-Pal4	
Art.No. 571-50009 [fr 50 RI-Pal4]	
Ld50wd-24-Kfl5	
Ft12rf-Psl4	
525-51144	
968-21000	
Fl70r-Ns-M4	
Fls18	
Is518-03	
535-91089	
510-51587 (Fms1834u)	
536-91001	

Ft 18-2-Rwmps-L4 740-21025
741-11006
527-51137, Lpt 45 pt 45
18/30rz2/250mscls=14
V20-Eye-A2-C
580-51402, Fe 12 RI-Psl4fe 12 RI-Psl4
99609429
P/N: 605-21012 Type: Fe 25-R-Ps-M4m
18/30r15/1000-Si
Fr18-2iw-Ps-K4
Fe88r-Nav-L5
979-06236
P/N: 572-51008 Type: Ft 50 Rlh-Pal4
607-21012
571-50012
571-50033
607-21005
902-51624
580-51447, Fle 18wm-L4-X02fle 18wm-L4-X02
740-21025
Fr88r-Pav-L5
518-51505 Sensopart Fmh 18-L4 , Reflexions-Lichttaster Mit Hga, M12-Stecker 4-Polig, Bis 120mm
962-50577
Ft 18-2 Rm-Ps-L4
510-51590
Ft50rlh-Nal4
Fls18wm-L4-X02
978-06402
Ft18-2rwm-Ps-L4

621-11010	
522-91096	EYESIGHT, VGA, WHITE LIGHT, CCD-COLOR, ADVANCED VER., 12MM LENS, ETHERNET / RSXXX
97808207	
978-06550	
Idt4-0b8-Ps-K3	
996-09428	
605-11007, Fs 25-RI-M4mfs 25-RI-M4m	
697-01030	
996-09438	
979-06162	
Fr10-RI-Ns-Km3	
522-91061	VGA, RED LIGHT, CCD-MONO, OBJECT DETECTION, 6MM LENS, LIGHT, ETHERNET
575-11009	
18/30rz3/2000-Mscls=10	
917-16003	
543-11015	
42-10034	
718-51404	
Ft55-R-Ns-L4	
Lf51wd-24-KfI5	
605-21007, Fe 25-RI-Ps-K4fe 25-RI-Ps-K4	
978-06404	
18/30r1/500-Si	
97908062	
693-11004	
30r12/2000-Si	
543-11033, Lr 20lr 20	
Ft25-C1-Gs-M4m	

532-51022	(LF 51 RD-24-KFL5) AREALIGHT, DIFFUSE, 51 MM, RED
974-09623	
526-51513, Lo C 8lo C 8	
620-21004, Fe 55-R-Ns-K4fe 55-R-Ns-K4	
Ft10-B-Rlf2-Ns-E4	
P/N: 623-11006 Type: Ft 55-Rlh2-Ps-L4	
620-21006, Fe 55-RI-Ps-L4fe 55-RI-Ps-L4	
Fr23r-Ps-M4	
606-11032	
978-06440	
527-51132, Lpt 45 Cml 5lpt 45 Cml 5	
V20-All-P2-W12	
927-81004	INFRARED, MEASURING FIELD 300MM, RANGE 2100MM, RESOLUTION 7 MM, 0-10 V
30I12/2000-Msc	
Fms3024ug60	
741-11005	
903-50313	
Ft20rh-Psk4	
Idt6-2b-Ns-M3	
Ft 25-Rhd-Ps-M4m (608-11016)	Diffuse reflection sensor with background suppression, 400mm, Red light, LED, PNP, teach-in, metal connector M8 4-pole, IP67 & IP69K For this product there is a new variant 608-11044 FT 25-RHD PNSLM4M
978-08567	
Loc50	
21000pvclr	
532-51031	(LR 100 WID-24-KFL5) RINGLIGHT, INDIRECT, DIFFUSE, 100 MM, WHITE
741-11024	
608-11008	
V10-Ob-A1-R6	

FqI120-Rk-50-Ps-M3	
525-51127	
Ft25-Ra-60-Nsu-M4m	
543-11011, Lr 5lr 5	
525-51152	
740-21033	
Fr23r-Psk4	
Ft92il-Ps-KI4	
902-51843	
Ft12rh-Psl4	
522-91064	VGA, WHITE LIGHT, CCD-MONO, CODEREADER, 6MM LENS, HIGH END, ETHERN./RS422
902-50693	
533-01028, Pv-Aw1010.4tx Enpv- Aw1010.4tx_En	
Fr12r-Psl4	
18/30lz2/2000-Mscls=14	
979-06655	
968-11009	
18/30rz3/500-Pvcls=14	
703-11003	
741-11026	
57251004	
536-91006	
048-02144	
572-51007	
974-09617 Sensopart 30 QI 0,2x10/1000 Si, Querschnittswandler, 1000mm, Silikon, 10mmlichtaustritt	
600-11145	
620-21007	
553-51006	

Fr20rg-Psm4	
99509515	
Is530-42	
902-51800	
902-51647	
Mspf20-2	
902-50689	
535-91052	
Fr20rg1psm4	
705-11000	
Is512-42	
810-50007	
It30nbm-Psl4	
602-71000, Fe 10-RI-Ps-E4fe 10-RI-Ps-E4	
611-51007, Fs/Fe 10-RI-Ns-Km3fs/Fe 10-RI-Ns-Km3	
526-51514, Lo C 12lo C 12	
740-21042	
591-91002	(FR 91 ILA-S2-Q12) RETRO 0.5M-50M, 4MM RES., LASER, ANALOG, 2XPNP, SSI / SERIAL, PLUG M16 12 PINS
30rz4/250-Mscls=16	
978-06455	
544-51324 / Fms 30-35 UI5	
533-01013, Mp Ppc 10,4mp Ppc 10,4	
506-11000 Lichttasterft12rh-Psl4	
581601	
622-21018	
740-21015	
Ft10-Rf2-Ns-K4	
Imt18-8n-Ps-K3	
573-52006, Fs 50 I-L4fs 50 I-L4	

P/N: 600-11002 Type: Ft 10-Rh-Ps-Km4	
Lr32r-24-Kfl5	
Ma18a	
831-81001	(FG80 I-PSM3) 80 X 80MM, PNP N.O., PLUG M8 3 PINS
580-51410	
532-51002	(LR 70 W-24-KFL5) RINGLIGHT, 70 MM, WHITE
979-06197	
608-11041	
696-51473	
927-81002	INFRARED, MEASURING FIELD 150MM, RANGE 2100MM, RESOLUTION 5 MM, 0-10 V
Fe20r-Psk4	
517-51396	
574-41003	
Fgl30-Rk-30-Ns-M3	
526-51515	
606-11011	
L4-2m-G-Pur	
996-09488	
Fr50r-Nak4	
535-91021	
522-91068	VGA, RED LIGHT, CCD-MONO, CODEREADER, 12MM LENS, HIGH END, ETHERN./RS422
522-91060	VGA, WHITE LIGHT, CCD-MONO, OBJECT DETECTION, C-CS MOUNT LENS, LIGHT, ETHERNET
Ft50rlh-Nsvl4	
L4s-2m-G-Pvc, M12	
574-41028	30 . 100MM, 68.36 MM, LASER, ANALOG, 1 X NPN, NC/NO , 4 TO 20MA, PLUG M12 5 PINS
718-51398	
551-11017	
580-51400, Fe 18 RI-Ps-L4fe 18 RI-Ps-L4	
Imt30-10b-Ps-L4	

Ft 55b-Rh-Ps-L4 Schalter Lichtschränke	
902-51796	
Fr10-R-Ps-Km4	
902-51628	
681-50880	
Fgl220-R-Psm3	
978-06541 / 30 Lz 12/1000-Si Ls=16	
543-11024 - Mg 3a	
522-91066	VGA, CCD-MONO, CODEREADER, C-CS MOUNT LENS, HIGH END, ETHERN./RS422
979-06250	
526-51116, Lo C 75lo C 75	
697-01020	
Umt30-350-A-Iud-L5	
902-51757	
526-51525, Lo C 35lo C 35	
602-71004, Fe 10-RI-Ps-Km4fe 10-RI-Ps-Km4	
696-51470	
Ft10-RIh-Ns-Km3	
30rz12/500-Mscls=20	
Pf30-T	
525-51122	
Ft10-Bf3-Ns-Km4	
18/30rp2/1000-Si	
611-51000, Fs/Fe 10-RI-Ps-E4fs/Fe 10-RI-Ps-E4	
18/30lz2/500-Sils=10	
996-51455	
551-21021	
697-01009	
Fgl80-Rk-50-Ns-M4	

526-51519	INFINITY.
697-01017	
978-06652	
551-71002	
555-31002	
P/N: 608-11000 Type: Ft 25-Rhd-Ps-M4	
Ft	
Lk25r-24-Kfl5	
R3-2lk	
533-01015, Lof-Bp-R635-30,5x0,5lof-Bp-R635-30,5x0,5	
902-50801	
V10-Eye-A1-R12	
527-51135, Lpt W 50lpt W 50	
P/N: 571-50000 Type: Fr 50 R-Pak4	
832-11021	
Fr25-Rgo-Ps-M4m	
608-11024	
Fr25-R-Ps-M3	
979-06150	
It10-4n-Ps-K3	
978-51680	
525-51121	LUMINARY, USABLE AEREA 98MM, IP 54
978-06460	
605-21001, Fe 25-R-Ps-K4fe 25-R-Ps-K4	
18/30r3/1500-Msc	
600-11009	
526-51113, Lo C 50lo C 50	
K2l-202	
580-51403, Fe 12 RI-Po-L4fe 12 RI-Po-L4	

722-01003	
57251000	
978-08216	
580-51439, Fls 18wm-L4-X01fls 18wm-L4-X01	
740-21028	
18/30rz3/250mscls=10	
532-51033	(LR 100 RID-24-KFL5) RINGLIGHT, INDIRECT, DIFFUSE, 100 MM, RED
510-51602	
Ft25-Ra-170-Nsu-M4m	
Fgl50-R-Psm3	
979-06648	
Ft50c-3-Psl8	
623-11037	
038-12399	
681-50903	
Fms18-34ul4-54	
901-05096	