

## Sensotec

Garanti: 12 ay  
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Sensotec** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

*Firmamız Sensotec T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*



¼r¼n	A¼ıklama
<a href="#">Al312cn</a>	SENSOR MODEL 34 250LBS 60-160 DEGREE
<a href="#">060-F491-01</a>	TRANSDUCER MODEL FP2000 0.10% ACCURACY 2.5PSID
<a href="#">Bp217</a>	
<a href="#">Tq3662</a>	TORQUE WATCH GAUGE, ACCURACY:+/-10%, TORQUE MAX:0.1IN-OZ, TORQUE MIN:0.01IN-OZ ROHS COMPLIANT: NA
<a href="#">Lkw50kz</a>	DIGITAL FORCE INDICATOR, LOAD CAPACITY:50LB, LOAD CELL OUTPUT:FORCE, LOAD CELL FORCE MAX:50LBF, SUPPLY VOLTAGE MAX:9VDC, TRANSDUCER FUNCTION:LOAD CELL
<a href="#">Al131ep</a>	LOAD CELL, CABLE TYPE:FLUOROPOLYMER, LOAD CAPACITY:50000LB, LOAD CELL OUTPUT:VOLTAGE, OPERATING TEMPERATURE RANGE:-5 C TO +105 C, LINE CELL LINEARITY:0.5%, L
<a href="#">V-Bp513ug-2j-3d-5f-9e-14a</a>	PRESSURE TRANSDUCER 30INCH HGV 4-20MA 1/4IN G FM
	(PRICE/EA) LOAD CELL, LOAD CAPACITY:50LB, SUPPLY VOLTAGE:10VDC, OPERATING TEMPERATURE MIN:-5 C,

<a href="#">Al111bn</a>	OPERATING TEMPERATURE MAX:105 C, CELL OUTPUT MV / V:3
<a href="#">Lkw25kz</a>	DIGITAL FORCE INDICATOR, LOAD CAPACITY:25LB, LOAD CELL OUTPUT:FORCE, LOAD CELL FORCE MAX:25LBF, SUPPLY VOLTAGE MAX:9VDC, TRANSDUCER FUNCTION:LOAD CELL
<a href="#">Rf/7673-03</a>	
<a href="#">73171101</a>	CEMENT
<a href="#">060-H417-01</a>	PRESSURE TRANSDUCER
<a href="#">90002141</a>	
<a href="#">41/571-01</a>	LOAD CELL 100LBS
<a href="#">060957504</a>	PRESSURE TRANS
<a href="#">Al111dr</a>	LOAD CELL, CABLE TYPE:FLUOROPOLYMER, LOAD CAPACITY:5000LB, LOAD CELL OUTPUT:VOLTAGE, OPERATING TEMPERATURE RANGE:-5 C TO +105 C, LINE CELL LINEARITY:0.1%, LO
<a href="#">Ap121br</a>	PRESSURE SENSOR, SENSING ACCURACY:0.1%, OPERATING PRESSURE MAX:100PSI, SENSOR OUTPUT:VOLTAGE, PORT SIZE:1/4, PORT STYLE:NPT, PRESSURE MEASURE TYPE:GA
<a href="#">41057205</a>	LOAD CELL
<a href="#">Lkw10kz</a>	DIGITAL FORCE INDICATOR, LOAD CAPACITY:10LB, LOAD CELL OUTPUT:FORCE, LOAD CELL FORCE MAX:10LBF, SUPPLY VOLTAGE MAX:9VDC, TRANSDUCER FUNCTION:LOAD CELL
<a href="#">Lkw500kz</a>	DIGITAL FORCE INDICATOR, LOAD CAPACITY:500LB, LOAD CELL OUTPUT:FORCE, LOAD CELL FORCE MAX:500LBF, SUPPLY VOLTAGE MAX:9VDC, TRANSDUCER FUNCTION:LOAD CE
<a href="#">060-J500-01</a>	TRANSDUCER SINGLE CHANNEL 1AMP 30VDC PROGRAMMABLE
<a href="#">Sns-R3100-Za</a>	
<a href="#">A-105a</a>	
<a href="#">Nacr-Ni(K) ,Type-K</a>	
<a href="#">060-0571-01</a>	LOAD CELL 100LB
<a href="#">Al311ar</a>	LOAD CELL, CABLE TYPE:FLUOROPOLYMER, LOAD CAPACITY:1000G, LOAD CELL OUTPUT:VOLTAGE, OPERATING TEMPERATURE RANGE:-5 C TO +105 C, LINE CELL LINEARITY:0.15%, LO
<a href="#">Tq651c3</a>	GAUGE, TORQUE WATCH 15N-MM TO 285N-MM 2%, TORQUE RANGE N-M:15N-MM TO 265N-MM, TORQUE RANGE FT-LB:0.01LB-FT TO 0.208LB-FT, ACCURACY %:2%, ACCURACY:+/-2
<a href="#">Termocupla Tipo S Doble Termopozo</a>	

<a href="#">Al322ar</a>	LOAD CELL, CABLE TYPE:BRAIDED SHIELD, LOAD CAPACITY:1000G, LOAD CELL OUTPUT:VOLTAGE, OPERATING TEMPERATURE RANGE:-5 C TO +105 C, LINE CELL LINEARITY:0
<a href="#">Al111br</a>	LOAD CELL, CABLE TYPE:FLUOROPOLYMER, LOAD CAPACITY:100LB, LOAD CELL OUTPUT:VOLTAGE, OPERATING TEMPERATURE RANGE:-5 C TO +105 C, LINE CELL LINEARITY:0.1%, LOA
<a href="#">Tq651c2</a>	TORQUE WATCH GAUGE, ACCURACY:+/-2%, TORQUE MAX:20IN-OZ, TORQUE MIN:1IN-OZ ROHS COMPLIANT: NA
<a href="#">060-E286-02</a>	
<a href="#">Tq9402</a>	TORQUE WATCH GAUGE, ACCURACY:+/-2%, TORQUE MAX:100IN-OZ, TORQUE MIN:15IN-OZ ROHS COMPLIANT: NA
<a href="#">Al322bn</a>	LOAD CELL, CABLE TYPE:BRAIDED SHIELD, LOAD CAPACITY:50LB, LOAD CELL OUTPUT:VOLTAGE, OPERATING TEMPERATURE RANGE:-5 C TO +105 C, LINE CELL LINEARITY:0.
<a href="#">Ap142bn,1b,2t,5b,6i</a>	MODEL A-5, ABSOLUTE PRESSURE, 50PSI, 30 TO 130 DEG F. (0 TO 55 DEG.C) TEMPERATURE COMPENSATION, VEHICLE VOLTAGE AMPLIFIER (0 TO 10 VDC) WITH 15 TO 28 V
<a href="#">060-9613-01-02</a>	
<a href="#">81205-20 Miniatur-Drucksensor Messbereich 20 Bar</a>	
<a href="#">Al322bl</a>	LOAD CELL, CABLE TYPE:BRAIDED SHIELD, LOAD CAPACITY:25LB, LOAD CELL OUTPUT:VOLTAGE, OPERATING TEMPERATURE RANGE:-5 C TO +105 C, LINE CELL LINEARITY:0.
<a href="#">Al111ej</a>	LOAD CELL 32VDC 20MA 60-160F 15000LB
<a href="#">Al111dv</a>	LOAD CELL, CABLE TYPE:FLUOROPOLYMER, LOAD CAPACITY:10000LB, LOAD CELL OUTPUT:VOLTAGE, OPERATING TEMPERATURE RANGE:-5 C TO +105 C, LINE CELL LINEARITY:0.1%, L
<a href="#">Al111cr</a>	LOAD CELL, CABLE TYPE:FLUOROPOLYMER, LOAD CAPACITY:500LB, LOAD CELL OUTPUT:VOLTAGE, OPERATING TEMPERATURE RANGE:-5 C TO +105 C, LINE CELL LINEARITY:0.1%, LOA
<a href="#">Tje/6321-01</a>	TRANSDUCER 0-2PSI
<a href="#">Ae213qa,52j,58em</a>	
<a href="#">809901</a>	LOAD CELL
<a href="#">060-H032-01-01</a>	
	DIGITAL FORCE INDICATOR, LOAD CAPACITY:250LB, LOAD CELL OUTPUT:FORCE, LOAD CELL FORCE MAX:250LBF,

<a href="#">Lkw250kz</a>	SUPPLY VOLTAGE MAX:9VDC, TRANSDUCER FUNCTION:LOAD CE
<a href="#">811fmg108309</a>	TRANSDUCER
<a href="#">34</a>	
<a href="#">Fpg1bj25b6m</a>	PRESSURE SENSOR, SENSING ACCURACY:0.1%, OPERATING PRESSURE MAX:15PSI, SENSOR OUTPUT:CURRENT, PORT SIZE:1/4, PORT STYLE:NPT, PRESSURE MEASURE TYPE:GAG
<a href="#">651-X-4mcald</a>	651-X-4M CALIBRATED
<a href="#">Al311an4a</a>	(PRICE/EA) LOAD CELL, LOAD CAPACITY:250G, SUPPLY VOLTAGE:5VDC, OPERATING TEMPERATURE MIN:-5 C, OPERATING TEMPERATURE MAX:105 C, CELL OUTPUT MV / V:20
<a href="#">060-F642-01</a>	PRESSURE TRANSMITTER WING UNION 424
<a href="#">Lkw5kkz</a>	DIGITAL FORCE INDICATOR, LOAD CAPACITY:5000LB, LOAD CELL OUTPUT:FORCE, LOAD CELL FORCE MAX:5000LBF, SUPPLY VOLTAGE MAX:9VDC, TRANSDUCER FUNCTION:LOAD
<a href="#">060-0574-03-01</a>	PANCAKE LOAD CELL MODEL 41 RANGE 10000LBS 10VDC
<a href="#">Al311bl</a>	LOAD CELL, CABLE TYPE:FLUOROPOLYMER, LOAD CAPACITY:25LB, LOAD CELL OUTPUT:VOLTAGE, OPERATING TEMPERATURE RANGE:-5 C TO +105 C, LINE CELL LINEARITY:0.15%, LOA
<a href="#">060-F441-04</a>	PNEUMATIC PRESSURE TRANSDUCER 1500PSI G9-32VDC
<a href="#">9940c-Kcn2x05-Fv</a>	
<a href="#">Al311cn</a>	LOAD CELL, CABLE TYPE:FLUOROPOLYMER, LOAD CAPACITY:250LB, LOAD CELL OUTPUT:VOLTAGE, OPERATING TEMPERATURE RANGE:-5 C TO +105 C, LINE CELL LINEARITY:0.15%, LO
<a href="#">Fdw1as-1aj-2d-5c-6q</a>	TRANSDUCER MODEL FP2000 0.10% ACCURACY 2.5PSID
<a href="#">Ap121cv</a>	PRESSURE SENSOR, SENSING ACCURACY:0.1%, OPERATING PRESSURE MAX:1000PSI, SENSOR OUTPUT:VOLTAGE, PORT SIZE:1/4, PORT STYLE:NPT, PRESSURE MEASURE TYPE:G
<a href="#">Al322br</a>	LOAD CELL, CABLE TYPE:BRAIDED SHIELD, LOAD CAPACITY:100LB, LOAD CELL OUTPUT:VOLTAGE, OPERATING TEMPERATURE RANGE:-5 C TO +105 C, LINE CELL LINEARITY:0
<a href="#">Wp9000</a>	
<a href="#">Aa123</a>	
<a href="#">Lkw10kkz</a>	DIGITAL FORCE INDICATOR, LOAD CAPACITY:10000LB, LOAD CELL OUTPUT:FORCE, LINE CELL LINEARITY:0.2%, LOAD CELL FORCE MAX:10000LBF, SUPPLY VOLTAGE MAX:9VD
<a href="#">By136hu</a>	TRANSDUCER LVDT MODEL MDLC

<a href="#">Al111eI</a>	(PRICE/EA) LOAD CELL, LOAD CAPACITY:20000LB, SUPPLY VOLTAGE:10VDC, OPERATING TEMPERATURE MIN:-5 C, OPERATING TEMPERATURE MAX:105 C, CELL OUTPUT MV / V
<a href="#">060-9189-02tjg</a>	PRESSURE TRANSDUCER HIGH PSI
<a href="#">32</a>	
<a href="#">060-F203-01-01</a>	