

## Sensus (Brand Of Xylem)

Garanti: 12 ay  
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Sensus (Brand Of Xylem)** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

*Firmamız Sensus (Brand Of Xylem) T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*



¼r¼n	A¼ıklama
<a href="#">159610 WASSERZÄHLER DURCHFLUSSZÄHLER</a>	
<a href="#">03008513</a>	
<a href="#">03112382</a>	
<a href="#">03112392</a>	
<a href="#">88129882</a>	
<a href="#">88189800</a>	
<a href="#">AN130</a>	
<a href="#">AN130F</a>	
<a href="#">MSTMK612</a>	
<a href="#">PTHHX01A</a>	
<a href="#">S420F</a>	

<a href="#">S620F01E</a>	
<a href="#">Typ WP QF QN 60, DN 100</a>	
<a href="#">YREGU10700</a>	
<a href="#">WP-Dinamic 125 Puls</a>	
<a href="#">Regulator Sensus 243-12-2 2"NPT</a>	Part number: 243-050-840-006 Connection: 2" NPT Orifice: 1/2 " Main Spring: 3.1/2" – 6.1/2" W.C. CE mark: NO
<a href="#">MSTMM</a>	<p>Woltmann water meter MeiStream DN150 Compliance fee Catalog number MSTMMGH5 Nominal diameter (DN) DN 150 Product type counter Pressure rating PN40 Length 300 mm Drilling pattern EN 1092 PN25 Coating cobalt blue (cold)/tin RAL5013 Metrology 2014/32/EU (MID) Module H1 Nominal flow Q3 = 250 m<sup>3</sup>/h Class / Ratio (measuring ratio) R63 Installation position horizontal/vertical (H/V) Temperature marking T 50 TVO KTW+W270 (standard) Material cover surface GGG40/VA BMF Mechanical counter Unit m<sup>3</sup> Housing/ME additional flow straightener (SGR) Sampled pointer Not specified Woltmann dry runner with encapsulated counter. Counter rotatable. Measuring vane parallel to the pipe axis. * universal installation position (version "plus" only horizontal) * standard HRI AMR interface for remote reading or M-Bus * optional: e-register with integrated radio readout . Special design features: * "floating impeller" for maximum measuring accuracy * Measuring inserts (cold water) compatible with type WP-Dynamic * Available in all common lengths (WP and WS). * very high resilience * minimized wear * unique measuring range * Flood-proof according to protection class IP 68</p>
<a href="#">MSTMI00A</a>	<p>Woltmann water meter MeiStream DN80 225mm Q3_63 R63 PN16 Installation position horizontal/vertical, cold water up to 50 °C Compliance fee Catalog number MSTMI001 Nominal diameter (DN) DN 80 Product type counter Pressure rating PN16 Length 225 mm Drilling pattern EN 1092 PN16 Coating cobalt blue (cold)/tin RAL5013 Metrology 2014/32/EU (MID) Module H1 Nominal flow Q3 = 63 m<sup>3</sup>/h Class / Ratio (measuring ratio) R63 Installation position horizontal/vertical (H/V) Temperature marking T 50 TVO KTW+W270 (standard) Mechanical counter Unit m<sup>3</sup> Housing/ME additional flow straightener (SGR) Sampled pointer Not specified Woltmann dry runner with encapsulated counter. Counter rotatable. Measuring vane parallel to the pipe axis. * universal installation position (version "plus" only horizontal) * standard HRI AMR interface for remote reading or M-Bus * optional: e-register with integrated radio readout . Special design features: * "floating impeller" for maximum measuring accuracy * Measuring inserts (cold water) compatible with type WP-Dynamic * Available in all common lengths (WP and WS). * very high resilience * minimized wear * unique measuring range * Flood-proof according to protection class IP 68 Technical data according to list sheet LB 1010, LB 1020, LB 1060, LB 1080</p>
<a href="#">03008513 Anschlussverschraubung, Messingg2" X R1 1/2"</a>	

