



Sgm Lektra

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye ii kapı teslim fiyat ve teslim s¼resi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Sgm Lektra Markası, tedarik s¼resi iin l¼tfen bizimle iletiŐime geiniz.

Firmamız Sgm Lektra T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	Aıklama
Mce121705726	
Model: RPMAGN0150E1B1A3E1	Serial: FM0102002288 DN 150 PN 16 Meter: 1907660
3.1	
306A008 L= 2m	
400A046B-TC26	
400A072B TC22	
400A076B	
490S020C L=550 mm	
490S020C L=580mm	
490S021C	
AGRITHER10A1A	
CLS2 B33B02L0A400	
CLS2B41L01I0A000A	
CLS4B73B11H46A	
CLS7B41F11N74B	
CLT4 B22 F01 D42 A	
CLT4 H99Z99H46A L=1200mm	
CLT4B00L75H46A	

CLT4B22L75H46A	
CLT4F22B12H46A	
CLT4F22B12H46C	
CLT4F30D21H46A	
CLT7B22L11N74B	
FP10R06KL4	
KTU51B4A	
LEKTA RAL 13	
METER4F4D	
Mod TT1A0L05A0	
MU002112686	
MUX02AA	
PMAGY0050B2B1A0A1	
PRFRNK7HS0N3	
PTU50C0U	
PTU51E0T	
RL6G71D38	
RL6G73C38 L=500mm	
RL6G73C38, L=320mm	
RL6G73D38	
TT1A0L06B0	
TT1E0L07B0	
VL601SGM	
VL611SGM	
CLS2B42L0111A000A	"42L"
CLS4	Base: ON/OFF capacitive level control Suitable for conductive and non-conductive liquids Top and lateral side metallic tank-installation Setting by VL601SGM keyboard/display removable module (TL41R) opt. (F) Version: Compact, with SS316 dissipator between head and connection (46) Electronic: TL41R ON-OFF, supply 24Vdc/Vac - 36 Vac 50Hz, Relay output SPDT - with removable display (L) Housing for electronic preamplifier: PC with blind cap and osmotic filter, IP67 (73) Process connection: CLAMP 1" ½ / SS316 (B) Electrode type and insulation: PTFE partially insulated SS316

	rod (Ø 10mm) (40) L= Electrode length: 350 (C) L1 = non sensitive part (rod): SS316 / 140mm
Code KPTDF5A40	
RSL 100 - Diapason level switch for liquids	Level Screw 1/2 inch 24volt the length 10cm
PTU51E0T Level transmitter	(PTU51) Base: Ultrasonic - for measurement in liquids, muds, acids and granulates. Range: 0,3 ÷ 6m; IP67 / IP68 proof Housing in polypropylene (PP) Calibration by VLW60T/VLW602/VLW90M units, via MODBUS or via BLUETOOTH (opt.) with Android APP Power supply 20÷30Vdc - Output 4÷20mA + MODBUS Temperature range -20 ÷ +60°C (E) Version: With SS316 male connector / IP67 (0) Process connection / Sensor material: G 1" / PP + n.1 1" BSP/ PP fixing bolt (T) Accessories: IP67 female connector in SS316 with 5m cable
Flowmeter0f4l	
400a042b Tc22	
400a072b Tc 22 Compact Capacitance Level Transmitter	
Ptu51e0t Ultrasonic Sensor 0,3-6m 4-20ma	
400a043b S/N: Mk001045 Old Code, New Code 400a073b	
Clt4f30l21h46a Sensor	
525b003a	
Clt4a00l21h46a	
Clt4a00l21h46a Mc0121311869	
Clt4f22l12h46c	
Smart1b4a , By Ktu51b4a	
Smart1b4a	
3.1 Zertifikat	
11.04.2019490s021c-Tc22	
490s002c L= 550 Mm	
VI611 Display	
400a076b Tc26 Sensor	
Rtd Pt100-0`_100c-Ds	
Clt4f22b12h46c Capacitive Rod Probe For Liquids And Dust	

400a072b Tc 22	
Cl4f30d21h46a Capacitive Sensor	
400a072b Sensortc22	
Agrither10a1a	
Mux02ex	
Smart3b4a	
400a072b Sensor Tc22	
Sgm-100s-M1c	
Cls1d33b73o0o00b	
Kpldnnfag10	
400a046b-Tc26 Obsolete, Replaced By 400a076b Tc26 Sensor	
Cls2b41I01i0a000a	
Cl7b22d11n74b Capacitance Sensors	
Tt1c0I06b0 L= 17,5 M	
Spthba4nn2n	HART pressure transmitter (SPT) Base: IP67 - Working temperature range: -40 ÷ +85°C Power supply: 12÷42Vdc (2-wire) 4÷20mA HART - Fully sealed welding (H) Accuracy: ± 0,075% (B) Measure range: 0 - 0,6kPa ÷ 6kPa (0 - 6 ÷ 60mbar) gauge p. Max overload 0,2bar Range limits -6 ÷ +6kPa (-60 ÷ +60 mbar) (A) Housing / membrane / filling liquid: Aluminum / SS316L / silicone oil (4) Process connection: ½" G male SS316 thread (N) Special functions: None (N) Fixing bracket for panel and pipe mounting (2"): None (2) Display: Backlit LCD (N) Certification: None
Ptu51eqt	
Rwl51pag Paasmxa	
Rl6b75d38	
Sla2x10taan	
400a073b	
Vlw601	
Pmagf0125e1b1a0a2	
Rl6g71d38 Sensor	
Swing2c1c0 - Transmitter	
Tc-21	

521 Smart
Rpl52pbafcbuma
Dn20..Dn100 (S1) Ultrasonic Sensors
Kptdf5a40
Ptu05b0a Obsolete, Replaced By Ptu51f0t
Cls1h34d99z0z00z
Clt4f22l21h46a
Rpmagn0050b2b1a0e1
Sgm-200hs1-A
400a072b Tc22 Capacitance Level Transmitter
Ptu10 A-O-A
Ptsaoa2a
Clt7b22l11n74b Capacitance Sensors
Cls2b41l11b1a700c
Sgm-100fwam1na
Vlw601a4a
400a072b
Ptu51
Vlw90m2c1b1a
Vlw90m
490s021c-Tc22 Sensor
Smag62 Dn 50
Clt4f22d21h46a S/N S2005389
Rl6b75d3
Tt1c0l06b0 L= 20,0 M
Ptu10a0a - Ultraschall-F¼llstandssensor
Smart 1b4h - Old Model Name, New Model Name Is Smart1b4a
Kplcntfag09 Level Sensor
400a042b-Tc22 Sensor 24 Vdc

[Cl4 H99z99h46a L=1200mm Sensor](#)

[Kplcntfag09](#)