

Sick

Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Sick** Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Sick Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.



rn

Aıklama

Type: installation Execution: Absolute multiturn Communication interface: HIPERFACE® Sine / cosine periods per revolution:

| | |
|--|--|
| Srs/Srm50, Srm50-Hfa0-K21 | 1,024 Safety-related system: no Mechanical interface: cone shaft, spring plate support, 9 mm Connection type: connector, 8-pin, radial Technology: optical |
| Mat. Nr.:1026820 | Safety laser scanner S300 Standard, S30B-2011BA Protective field range: 2 m Scan angle: 270 ° Number of fields: 3 |
| 1040965 | Inductive proximity sensors IME, IME18-08BPSZC0K Housing design: short design Switching distance Sn: 8 mm Installation in metal: flush Electrical version: DC 3-wire Switching output: PNP Switching function: normally open Connection type: M12 connector, 4-pin Country of origin: HU; Stat. Product number: 85365019 |
| 1065887 | Small light barriers G10, GL10-P4212 Switching distance max ..: 0.08 m ... 15 m, 0.08 m ... 12 m Sensor principle: reflection light barrier Detection principle: double lens Switching output: PNP Switching mode: light / dark switching Connection type: M12 connector, 4-pin Light transmitter: PinPoint-LED Setting: potentiometer Included in delivery: BEF-G10DC01 mounting bracket, P250 reflector Country of origin: MY; Stat. Product number: 85365019 EC dual use / export list number: non; |
| 1047361 | Mid-range distance sensors Dx50, DL50-P1123 Measuring range: 200 mm ... 50,000 mm, on reflective tape #Diamond Grade " Minimum response time: 15 ms Analog output type: current output Digital output: 1 x PNP Light transmitter: laser, red Laser class: 1 (IEC 60825-1: 2014, EN 60825-1: 2014) Multi-function input (MF): 1 x |
| Afm60b-S1kz000s06 Absolute Encoder | 1075531 004096 steps x 4096 rev., 4.5 ... 32V, SSI / Gray, Sin / Cos 1024 periods, Cable 12-wire, universal, 1m with struck M23,17-pol. plug with customer-specific pin assignment |
| Absolute Encoder Baumer Eal580-Bnc.5wpt. | .18130.A PROFIN. |
| S300 FRONT SCREEN 2039248 | |
| LFV200-XATGACPV | 6036381 Level sensors LFV200, Process connection: G 1 A PN 64 Output signal: contactless switch Probe length: 67 mm Materials in contact with media: stainless steel 1.4404 Housing material: stainless steel 1.4404, PEI Connection type: valve plug DIN 43650 Process temperature: -40 ° C ... +150 ° C Approvals: WHG |
| IME12-02BPSZC0S | Inductive proximity sensors 1040732 Housing design: standard Switching distance Sn: 2 mm Installation in metal: flush Electrical version: DC 3-wire Switching output: PNP Switching function: normally open Connection type: M12 plug, 4-pin |
| IME12-04BPSZC0S | Inductive proximity sensors 1040764 Housing design: standard Switching distance Sn: 4 mm Installation in metal: flush Electrical version: DC 3-wire Switching output: PNP Switching function: normally open Connection type: M12 plug, 4-pin |
| PL80A | 1003865 Reflectors Angular, PL80A Description: Rectangular, screwable Dimensions: 80 mm 80 mm Ambient temperature, operation: -20 ° C ... +65 ° C |
| Range -10 +10 mbar,output 4-20 mA, | |

| | |
|---|--|
| 24vdc | |
| VFS 60 - 2048 | Encoder VFS 60 - 2048 - TTL 4.5- 32V fully programmed and assembled with connector |
| 1040970 | IME, IME18-08BPOZC0S |
| T40-E0121K | Contactless safety switches T4000 Direct, T40-E0121K System part: sensor Coding: Uniquely coded Connection type detail: connector, M12, 8-pin LED: yes |
| AFS/AFM60 | 1059034 Absolut-Encoder AFS / AFM60 PROFINET, AFM60A-BENB018x12 Singleturn or multiturn design: multiturn Resolution max .: 18 bit x 12 bit (262,144 x 4,096) Mechanical design: blind hollow shaft Shaft diameter: 12 mm Communication interface: PROFINET Connection type: plug, 1x, M12, 4-pin, axial, socket, 2x, M12, 4-pin, axial Programming interface: Via PLC engineering tool |
| IQ20-07BPSDU2S | 6045180 Inductive proximity sensors IQV, IQ20-07BPSDU2S Switching distance Sn: 7 mm Installation in metal: flush Cuboid shape (W x H x D): 20 mm x 32 mm x 8 mm Electrical version: DC 3-wire Switching output: PNP Switching function: normally open Connection type: cable, 3-core, 2 m |
| P250F | 5308843 Reflectors Fine triple reflectors, P250F Description: Feintripel, screw-on, suitable for laser sensors Dimensions: 52 mm 62 mm Ambient temperature, operation: -30 ° C ... +65 ° C |
| LMS1xx, LMS141-15100 Security Prime | 1070409 2D LiDAR sensors Working range: 0.5 m ... 40 m Opening angle: 270 ° Degree of protection: IP67 Color: Gray (RAL 7032) Integrated application: Field evaluation with flexible fields, security-specific parameterization, Easy Teach lite and pro Connection type: 1 x M12 round connector Scanning frequency: 25 Hz, 50 Hz |
| MZT7-03VPS-KWB | |
| W12-3, WTB12-3P2431 | 1041411 Small light barriers Switching distance max .: 20 mm ... 350 mm Sensor principle: photoelectric proximity switch Switching output: PNP Switching type: light / dark switching Connection type: M12 connector, 4-pin Light transmitter: LED Type of light: Visible red light Setting: potentiometer, 5 turns Included in delivery: 2 x clamp holders BEF-KH-W12, including screws |
| MZT7-03VPS-KWP | |
| IME12-04BPOZCOK-1040767 END/KAP | |
| S30A-6011DA | Safety laser scanner 1019600 S3000 Professional, S30A-6011DA Protective field range: 5.5 m Scan angle: 190 ° Number of fields: 24 |
| VFS60A-BHPZ0-S01 | |
| SLA-ML4V5 3W8 1001019 | |
| 1064607 | Miniature photoelectric switches W2S-2, WTB2S-2P3160 Switching distance max .: 1 mm ... 66 mm Sensor principle: photoelectric proximity switch Detection principle: background suppression Switching output: PNP Switching type: light |

| | |
|---|--|
| | switching Connection type: Cable with connector M8, 3-pin, 200 mm Light transmitter: PinPoint-LED Setting: none Communication interface: - |
| G6, GSE6-P1212 | Miniature photoelectric switches Switching distance max .: 0 m ... 15 m Sensor principle: one-way light barrier Switching output: PNP Switching type: light / dark switching Connection type: cable, 3-core, 2 m Light transmitter: PinPoint-LED Type of light: Visible red light Housing material: ABS / PC Setting: potentiometer Included in delivery: Stainless steel mounting bracket (1.4301 / 304) BEF-W100-A |
| 2054.1041114 | 2D LiDAR sensors LMS1xx, LMS111-10100 Working range: 0.5 m ... 20 m Opening angle: 270 ° Degree of protection: IP67 Color: Gray (RAL 7032) Integrated application: field evaluation with flexible fields Connection type: 1 x M12 round connector Scanning frequency: 25 Hz, 50 Hz |
| 6035499 | Round light barriers V18V, VS / VE18-4P3140V Switching distance max .: 0 m ... 20 m Sensor principle: one-way light barrier Switching output: PNP Switching type: light / dark switching Connection type: M12 plug, 4-pin Light transmitter: LED Setting: none |
| LUT1B-31325 | |
| Move mechanics stainless %15 steel for DHSP-T | 2043925 (Move mechanics SS for DHSP-T) |
| SRM50S-HFZ0-S22 | |
| TiM3xx, TIM320-1131000 | 2D LiDAR sensors 1062219 Area of application: indoors Integrated application: field evaluation with flexible fields Measuring principle: HDDM+ Working range: 0.05 m ... 4 m Angular resolution: 1° Number of field sets: 16 Digital outputs: 3 (PNP, additional 1 x "Device Ready") Connection type: 1 x 12-pin M12 device connector (0.8 m) |
| LMS511-22100 Heavy Duty | + laser scanner power cable |
| STE-1204-GE01 | |
| DT50-2B215552 | |
| YF2A15-100VB5XLEAX | |
| IMB 18-12 NPSVCOS (PNP) 1070173 | |
| DOS-1204-GX 6026528 | |
| 6052361 | miniature light barriers W100-2, WL100-2P3439 Switching distance max.: 0.01 m ... 7.2 m Sensor principle: Reflection light barrier Detection principle: double lens Switching output: PNP Switching type: light/dark switching Connection type: M8 plug, 3-pin Light emitter: LED Adjustment: potentiometer Included in delivery: mounting bracket BEF-W100-A, reflector P250 |
| 1002314 | reflectors Square, PL30A Description: Rectangular, screwable Dimensions: 30mm 82mm Ambient operating temperature: -20 °C ... +65 °C |

| | |
|---|--|
| 5M3-BEH-K04-096 | 1038155 incremental encoder DFS60, DFS60B-BHEK04096 Mechanical design: blind hollow shaft 15 mm Communication interface: 10 V ... 32 V, HTL, push-pull Connection type: cable, 8-wire, universal, 1.5 m Pulses per revolution: 4,096 Country of origin: DE; Stat. Commodity number: 90314990 EU dual use / export list number: non; US ECCN: non |
| MBA810ZIN2-N00650-N-XXXXX | Digital rotary paddle switch - Parameters adjustable - maintenance free - wear-free - insensitive to vibrations. MBA810ZIN2-N00650-N-XXXXX MBA810 supply voltage: 115V to 230V 50Hz Z with certificate for dust Ex Zone 20/21 I process connection: Flange DN 125 PN 6, stainless steel N Pressure in the container: - 0.5 ... + 3 bar 2 Temperature in the container: up to 200 °C N Angle bracket for horizontal assembly, reinforced, stainless steel Diving depth: 650 mm N toggle wing Ø 12 x 100 mm 2 Process temperature up to 200°C N Shaft with 90° angle, reinforced, stainless steel Immersion depth: 600 mm N Toggle paddle, stainless steel MBA200 |
| DFS60B-BHEK04096 | INCREMENTAL ENCODER DFS60, DFS60B-BHEK04096 Mechanical design: blind hollow shaft 15 mm Communication interface: 10 V ... 32 V, HTL, push-pull Connection type: cable, 8-wire, universal, 1.5 m Pulses per revolution: 4,096 |
| FX3-CPU000000 FLEXISOFT CONTROLLER | 1043783 Security systems for AGVs and AMRs Safe EFI-pro system, FX3-CPU000000 Module: main module Configuration and diagnostic interface: RS-232 Type of connection: tension spring terminals Protective varnish for increased environmental requirements: no Scope of delivery: Main module without system plug, safety instructions, operating instructions to download |
| FX3-MPL000001 FLEXISOFT MEMORY PLUG | 1043700 connectors and cables Miscellaneous connectors and cables, FX3-MPL000001 Description: System plug: Power supply for the Flexi Soft system and Saving the system configuration (without EFI-enabled devices) Connection technology: screw terminals |
| FX3-XTIO84002 FLEXISOFT 8IN/4OUT | 1044125 Security systems for AGVs and AMRs Safe EFI-pro system, FX3-XTIO84002 Module: I/O module Secure inputs: 8 Safe exits: 4 Flexi Loop compatible: yes Type of connection: tension spring terminals Protective varnish for increased environmental requirements: no |
| i110RP313 | |
| WTB27X-3P1811 | |
| WLL190T-2P434 | FIBER GAIN Article number: 6032553 fiber optic sensors WLL190T-2, WLL190T-2P434 Switching distance max.: 2 ... 4 m Switching type: light/dark switching Connection type: M8 plug, 4-pin Degree of protection: IP66 Setting: menu-driven, teach-in button, line |
| LL3-TH08-3 | LIGHT GUIDE HEAT RESIST. Article number: 5328051 light guide LL3, LL3-TH08-3 For fiber optic sensor: GLL170(T), WLL180T Functional principle detail: Consisting of a transmitter and a receiver Material, fiber: glass Material, jacket: stainless steel Material, light guide head: brass Thread diameter (housing): M4 Light guide length: 3,000 mm |

| | |
|--|---|
| MRA-F130-110D2 CABLE MECHANISM | Cable mechanism, MRA-F130-110D2 Description: HighLine cable mechanism for servo flange with 6 mm shaft, Measuring range 0 m ... 10 m Scope of delivery: without encoder |
| A3M60B-S4PB013X13 ABSOLUTE ENCODER | 1038826 Absolute encoder A3M60 PROFIBUS, A3M60B-S4PB013x13 Singleturn or multiturn version: multiturn Max. resolution: 13 bits x 13 bits (8192 x 8192) Mechanical design: solid shaft clamping flange 10 mm x 19 mm Communication interface: PROFIBUS DP, DPV0, programmable Connection type: plug, 2x, M12, 5-pin, axial, socket, 1x, M12, 5-pin, axial Programming interface: Via PLC engineering tool |
| SICK END.SEN. IME18-08BPSZC08(1040966) | Inductive proximity sensors IME, IME18-08BPSZC0S Housing design: Standard Sensing distance Sn: 8 mm Installation in metal: Flush Electrical design: DC 3-wire Switching output: PNP Switching function: normally open Connection type: M12 plug, 4-pin |
| IME18-08BPSZC0S 1040966 | Inductive proximity sensors IME, IME18-08BPSZC0S Housing design: Standard Sensing distance Sn: 8 mm Installation in metal: Flush Electrical design: DC 3-wire Switching output: PNP Switching function: normally open Connection type: M12 plug, 4-pin |
| IQ40-40NPPKC0K 1071552 | Inductive proximity sensors IQG, IQ40-40NPPKC0K Sensing distance Sn: 40 mm Installation in metal: non-flush Block shape (W x H x D): 40 mm x 40 mm x 66 mm Electrical design: DC 4-wire Switching output: PNP Switching function: complementary Connection type: M12 plug, 4-pin |
| IME18-08BPSZC0K -1040965 | Inductive proximity sensors IME, IME18-08BPSZC0K Housing design: Short design Sensing distance Sn: 8 mm Installation in metal: Flush Electrical design: DC 3-wire Switching output: PNP Switching function: normally open Connection type: M12 plug, 4-pin |
| YF2A15-050VB5XLEAX PVC/5*0,34/GR/US | 2096240 connectors and cables Connecting leads, YF2A15-050VB5XLEAX Connection type head A: socket, M12, 5-pin, straight, A-coded Type of connection Head B: Open cable end Approvals: CE, UL Signal type: sensor/actuator line Cable: 5 m, 5-core, PVC Description: Sensor/actuator cable, unshielded Area of application: chemical area |
| IP67 1063132 | Photoelectric sensor RT-P2233 sensor/detection principle: sensor with reflection from the object, background suppression response distance: 60 ... 900mm type of radiation: infrared light Operating voltage: 10 ... 30V DC switching output: PNP Switching type: dark Connection type: cable with M12 connector, 4-pin, 300mm Degree of protection: IP67 1063132 SICK |
| Transmitter M20S-02150A122 24-28 | ,8V DC 10-55Hz 3,7W 0 - 55° C 0 - 25M 48 x 40MM 1018186 SICK |
| LFP2500-G1NMB | level sensors 1065361 LFP Inox, LFP2500-G1NMB Process connection: G 3/4 A Probe length: 2,500 mm Application type/design: Standard Output signal: 1 x PNP + 1 x PNP/NPN + 4 mA ... 20 mA / 0 V ... 10 V Connection type: circular connector M12 x 1, 5-pin Process temperature: -20 °C ... +150 °C Materials in contact with media: 1.4404 (Ra ≤ 0.8 µm), PEEK Housing design: With viewing window made of PMMA (acrylic glass) |

| | |
|---|---|
| 1019229 - WT34-B410 | Compact light barriers 1019229 W34, WT34-B410 Sensor principle: diffuse reflection sensor Detection principle: background suppression Switching output: NPN, PNP Switching type: light switching, dark switching Connection type: M12 plug, 4-pin Light emitter: LED Adjustment: potentiometer Communication interface: - |
| Control Panel for MCU of dusthunter art No: | 2061514-0000 |
| WL100L-F2231 REFLEXIONS-LS | 6030710 miniature light barriers W100 Laser, WL100L-F2231 Switching distance max.: 0.08 m ... 12 m Sensor principle: Reflection light barrier Detection principle: double lens Switching output: PNP Switching type: light/dark switching Connection type: M8 plug, 4-pin Light emitter: laser Adjustment: potentiometer Laser class: 1 Included in delivery: stainless steel mounting bracket (1.4301/304) BEF-W100-A, reflector P250F |
| IME18-08BPSZC08(1040966) | |
| IME18-08BPSZC08(1040966) | |
| IQ40-40NPP-KC0K 6037073 | |
| IME18-08BPSZCOK 1040965 | |
| DOL-1205-G05M (6009868) | |
| IME08-02BPSZW2K | Inductive proximity sensors IME, IME08-02BPSZW2K Housing design: Short design Sensing distance Sn: 2 mm Installation in metal: Flush Electrical design: DC 3-wire Switching output: PNP Switching function: normally open Connection type: cable, 3-wire, 2 m |
| IME18-08BPSZW2S | Inductor. Article number: 1040968 Inductive approximation sensors Ime, ime18-08bpszw2s Housing form: standard design Switch distance SN: 8 mm Installation in metal: flush Electrical version: DC 3 ladder Switch output: PNP Switch function: closer Connection type: line, 3-caded, 2 m |
| DME4000-211 | DISTANCE MEASUREMENT UNIT Artikelnummer: 1029790 Long range distance sensors DME4000, DME4000-211 Measuring range: 0.15 m ... 130 m, on "Diamond Grade" reflective foil Repeatability: 2mm Accuracy: ±5mm Output Time: 1ms Communication interface: SSI Connection type: plug, M16, 8-pin Current consumption: At 24 V DC < 250 mA |
| DBS36E-BBAK01000 INCREMENTAL ENCODER | Article number: 1060528 incremental encoder DBS36/50, DBS36E-BBAK01000 Mechanical design: blind hollow shaft 8 mm Communication interface: 4.5V ... 5.5V, TTL, RS-422 Connection type: cable, 8-wire, universal, 1.5 m Pulses per revolution: 1,000 |
| 1001019 | |
| DFS60B-S4EA05000 | Part Nr: 1037275 INCREMENTAL ENCODER DFS60, DFS60B-S4EA05000 Mechanical design: solid shaft clamping flange 10 mm x 19 mm Communication interface: 10 V ... 32 V, HTL, push-pull Connection type: plug, M23, 12-pin, radial Pulses per revolution: 5,000 |

| | |
|--|---|
| A3M60B-BEP | Absolut-Encoder Article number: 1052509 Scope of delivery: 1 x A3M60B-BEPB013X13 (1038825), 1 x STE-1205-WQ (6041428), 1 x DOS-1205-W (6009720), 1 x DOS-1205-WQ (6041429) Special feature: sales set |
| IME18-08BPSZW2S | 1040968 Inductive proximity sensors IME, IME18-08BPSZW2S Housing design: Standard design Sensing distance Sn: 8 mm Installation in metal: Flush Electrical design: DC 3-wire Switching output: PNP Switching function: normally open Connection type: cable, 3-wire, 2 m |
| DT500-A111 DISTANCE SENSOR BUTTON | 1026515 Long range distance sensors Dx500, DT500-A111 Measuring range: 0.2 m ... 30 m, 90% remission 0.8 m ... 15 m, 6% remission Repeatability: 1mm Accuracy: ±3mm Type of analog output: current output Power Consumption: Typ. 3w Heating: no |
| AFM60A-S1NB018X12 ABSOLUTE ENCODER | Absolute encoder AFS/AFM60 Ethernet, AFM60A-S1NB018x12 Singleturn or multiturn version: multiturn Max. resolution: 18 bits x 12 bits (262,144 x 4,096) Mechanical design: solid shaft servo flange 6 mm x 10 mm Communication interface: PROFINET, programmable Connection type: Plug, 1x, M12, 4- pin, axial Socket, 2x, M12, 4-pin, axial Programming interface: Via PLC engineering tool |
| WL100-2P4439 | REFLEXIONS-LS miniature light barriers W100-2, WL100-2P4439 Functional principle: Reflection light barrier Functional principle detail: double lens Switching output: PNP Switching type: light/dark switching Connection type: M8 plug, 4-pin Light emitter: LED Adjustment: potentiometer Communication interface: - Included in delivery: mounting bracket BEF-W100-A, reflector P250 |
| GL6-P4212 | REFLEXIONS-LICHTSCH. miniature light barriers G6, GL6-P4212 Switching distance max.: ≤ 6 m Functional principle: Reflection light barrier Functional principle detail: double lens Switching output: PNP Switching type: light/dark switching Connection type: M8 plug, 4-pin Light emitter: PinPoint LED Type of light: Visible red light Housing material: ABS/PC Adjustment: potentiometer Included in delivery: P250 reflector, stainless steel mounting bracket (1.4301/304) BEF-W100-A |
| WL9M4-3P2232 | REFLEXIONS-LICHTSCH. Small light barriers W9, WL9M4-3P2232 Functional principle: Reflection light barrier Functional principle detail: autocollimation Switching output: PNP Switching type: light/dark switching Connection type: M8 plug, 4-pin Light emitter: PinPoint LED Setting: teach-in button Communication interface: - |
| SKS36-HFA0-K02SKS36-HFA0-K02 | 1034095 MOTORFEEDBACK HIPERFACE® rotary motor feedback systems SKS/SKM36, SKS36-HFA0-K02 Communication interface: HIPERFACE® Execution: absolute single turn Type: built-in Sine/cosine periods per revolution: 128 Safety-related system: no Mechanical design: conical shaft, spring plate support Type of connection: plug, 8-pin, radial Technology: Optical Operating temperature range: -20 °C ... +110 °C |
| WE260-S270 | |
| WSE280-2H4331 THROUGH-BEAM SENS. | |

| | |
|--|--|
| EKS36-0KF0108A | |
| GRTE18S-P2317 | |
| WTB26P-24861120A00Z2ZZZZZZZZZ1 | 1115766 Compact light barriers W26, WTB26P-24861120A00 Switching distance min. / max.: 30 mm / 1,600 mm Functional principle: reflection light scanner Functional principle detail: background suppression Switching output: PNP Connection type: M12 plug, 4-pin Light transmitter: PinPoint LED Light type: Visible red light Housing material: VISTAL® Setting: Teach-in button, cable, potentiometer, push-turn element Communication interface: IO-Link V1.1 Smart Sensor: Enhanced Sensing, Efficient Communication, Smart Task Smart Task Name: Basic Logic |
| 2049526 | Printed-circuit board assembly |
| E10-P123 | e10-p123-25 For rational and permanent labeling of all types of products made of metal, plastic, wood, etc. The marking system is characterized above all by its robust and industrial-grade design according to the following specification: Marking head Hand-held device with pistol-shaped handle X-axis with linear guide and ball-bearing slide, drive via Rack, Y-axis swivel drive via rack Rubberized front panel for position fixation with V recess and Quick adjustment for workpiece distance Labeling area 120 x 25 mm, LED lighting Electromagnetic needle drive with needle guide and 60 mm embossing needle made of carbide Embossing up to 62 HRC material hardness possible max. 5 mm height compensation, depending on the embossing force Noise development 76 dB (measured at medium embossing force and speed on sheet steel) 7.5 m control cable to the control unit with cable bending protection Weight 3.7 kg Control unit Integrated membrane keyboard, high-resolution color display (480x272 pixels) USB interface, special USB driver is required |
| C4C-SA18030A10000 LIGHTCURTAIN | Safety light curtains deTec, C4C-SA18030A10000 deTec variant: deTec4 Core System part: transmitter Area of application: standard industrial environment Safety level: Type 4, PL e, SIL3 Resolution: 30mm Range: 15m Protective field height: 1,800 mm Connection type: M12 plug, 5-pin Protection class: IP65, IP67 Scope of delivery: transmitter |
| C4C-EA18030A10000 LIGHTCURTAIN | Safety light curtains deTec, C4C-EA18030A10000 deTec variant: deTec4 Core System part: receiver Area of application: standard industrial environment Safety level: Type 4, PL e, SIL3 Resolution: 30mm Range: 15m Protective field height: 1,800 mm Connection type: M12 plug, 5-pin Protection class: IP65, IP67 Scope of delivery: receiver, test rod with a diameter corresponding to the resolution of the Safety light curtain, safety instructions, assembly instructions, operating instructions for download |
| C4C-SA09010A10000 LIGHTCURTAIN | Safety light curtains deTec, C4C-SA09010A10000 deTec variant: deTec4 Core System part: transmitter Area of application: standard industrial environment Safety level: Type 4, PL e, SIL3 Resolution: 14mm Range: 10m Protective field height: 900 mm Connection type: M12 plug, 5-pin Protection class: IP65, IP67 Scope of delivery: transmitter |
| | Safety light curtains deTec, C4C-EA09010A10000 deTec variant: deTec4 Core System part: receiver Area of application: standard |

| | |
|---|--|
| C4C-EA09010A10000 LIGHTCURTAIN | industrial environment Safety level: Type 4, PL e, SIL3 Resolution: 14mm Range: 10m Protective field height: 900 mm Connection type: M12 plug, 5-pin Protection class: IP65, IP67 Scope of delivery: receiver, test rod with a diameter corresponding to the resolution of the Safety light curtain, safety instructions, assembly instructions, operating instructions for download |
| YF2A15-100UB5M2A15 PUR/5*0,34/BK/US | Connectors and cables Connecting cables, YF2A15-100UB5M2A15 Connection type head A: Socket, M12, 5-pin, straight, A-coded Connection type head B: plug, M12, 5-pin, straight, A-coded Approvals: CE, UL Signal type: sensor/actuator cable Cable: 10 m, 5-wire, PUR, halogen-free Description: Sensor/actuator cable, unshielded Area of application: oil/lubricant area, drag chain operation, robots |
| YF2A15-050UB5M2A15 PUR/5*0,34/BK/US | Connectors and cables Connecting cables, YF2A15-050UB5M2A15 Connection type head A: Socket, M12, 5-pin, straight, A-coded Connection type head B: plug, M12, 5-pin, straight, A-coded Approvals: CE, UL Signal type: sensor/actuator cable Cable: 5 m, 5-wire, PUR, halogen-free Description: Sensor/actuator cable, unshielded Area of application: oil/lubricant area, drag chain operation, robots |
| DSC-1205T000025KM0 T-VERBINDER M12* 5 | Distributor T-distributor, DSC-1205T000025KM0 Connection type head A: Socket, M12, 5-pin, A-coded Connection type head B: plug, M12, 5-pin, A-coded Connection type head C: M12 socket A-coded Description: T-splitter for simultaneous connection to transmitter and receiver, divides the line coming from the control cabinet between the transmitter and receiver Note: 5-pin |
| S30A-7111CP S3000 PN | Security laser scanner S3000 PROFINET IO Advanced, S30A-7111CP Version: Sensor without system plug Protective field range: 7 m Scan angle: 190° Number of fields: 8 Transmission medium for PROFINET IO: copper cable |
| S3000 MOUNTING KIT HEAVY DUTY | Mounting brackets and plates Mounting bracket, heavy duty mounting kit Description: Mounting bracket, heavy duty, with protective cover Floor installation, adjustment around the longitudinal and transverse axes using an alignment plate, Height adjustment possible. Tilt angle ± 5°. There are no additional brackets necessary. Material: steel Details: Steel, painted (RAL 1021) Color: RAL 1021 (rapeseed yellow) Packaging unit: 1 piece |
| SX1A-A0000L S3000 PN SYS-PLUG | Connectors and cables Other connectors and cables, SX1A-A0000L Connection type head A: system plug Description: Without cable, for S3000 PROFINET IO Advanced and Professional, Not for use with incremental encoders, integrated configuration memory |
| LEITUNG,STEC/BUC 0M30 RJ45PP/M12 | Connectors and cables Other connectors and cables, RJ45PP/M12 adapter cable Cable: 0.3 m Description: Shielded, for connecting the RJ-45 port on Safety laser scanner with M12 standard connectors |
| DSL-8U04G02M025KM1 VERBINDUN.LTG M 8* 4 | Connectors and cables Connection cables, DSL-8U04G02M025KM1 Connection type head A: plug, M8, 4-pin, straight Connection type head B: male, USB-A, straight Cable: 2 m, 4-wire, PVC Description: Unshielded, configuration cable |

| | |
|--|---|
| | with integrated RS-232 converter to USB to connect a sensor configuration connector (M8, 4-pin) to the USB interface of a PC |
| REF-IRF-56 REFL.FOLIE 50.0* 60.0 | 5314244 Reflectors Reflective film, REF-IRF-56 Accessory group: reflectors Accessory family: reflective film Description: Self-adhesive Dimensions: 50mm 60mm Operating ambient temperature: -20 ¼C ... +60 ¼C |
| AFM60A-S4PM262144 | 1037512 Absolute encoder AFS/AFM60 SSI, AFM60A-S4PM262144 Singleturn or multiturn version: Multiturn Resolution max.: 18 bit x 12 bit (262,144 x 4,096) Mechanical design: solid shaft clamping flange 10 mm x 19 mm Communication interface: SSI, programmable Connection type: cable, 8-wire, universal, 5 m Programming interface: Via handheld programming tool, via SOPAS |
| PGT-08-S PROGRAMMING TOOL | 1036616 Programming and configuration tools, PGT-08-S Description: USB programming device, for programmable SICK encoders AFS60, AFM60, DFS60, VFS60, DFV60 and cable pull encoders with programmable encodersv |
| AFM60B-S4AM004096 ABSOLUTE ENCODER | 1058001 Absolute encoder AFS/AFM60 SSI, AFM60B-S4AM004096 Singleturn or multiturn version: Multiturn Resolution max.: 13 bit x 12 bit (4,096 x 4,096) Mechanical design: solid shaft clamping flange 10 mm x 19 mm Communication interface: SSI, non-programmable Connection type: cable, 8-wire, universal, 5 m |
| IME18-08BPSZC0S | 1040966 Inductive proximity sensors IME, IME18-08BPSZC0S Housing design: standard design Sensing distance Sn: 8 mm Installation in metal: Flush Electrical version: DC 3-wire Switching output: PNP Switching function: normally open Connection type: M12 plug, 4-pin |
| GTB10-P4211 | Small light barriers G10, GTB10-P4211 Functional principle: reflection light scanner Functional principle detail: background suppression Switching output: PNP Switching type: light/dark switching Connection type: M12 plug, 4-pin Light transmitter: PinPoint LED Setting: potentiometer Communication interface:- |
| WL280-2P1131 | Compact light barriers W280-2, WL280-2P1131 Functional principle: retro-reflective light barrier Functional principle detail: double lens Switching output: PNP Switching type: light/dark switching Connection type: cable, 3-wire, 2 m Light transmitter: LED Setting: potentiometer Communication interface:- Included in delivery: BEF-W280 mounting bracket, P250 reflector |
| WT34-B410 | Compact light barriers W34, WT34-B410 Functional principle: reflection light scanner Functional principle detail: background suppression Switching output: NPN, PNP Switching type: light switching, dark switching Connection type: M12 plug, 4-pin Light transmitter: LED Setting: potentiometer Communication interface:- |
| WL100-2P3439 | Miniature photoelectric sensors W100-2, WL100-2P3439 Functional principle: retro-reflective light barrier Functional principle detail: double lens Switching output: PNP Switching type: light/dark switching Connection type: M8 plug, 3-pin Light transmitter: LED Setting: potentiometer Communication interface:- Included in delivery: mounting bracket BEF-W100-A, reflector P250 |

| | |
|--|--|
| PGT-08-S PROGRAMMING TOOL | programming device, for programmable SICK encoders AFS60, AFM60, DFS60, VFS60, DFV60 and pulley encoders with programmable encoders |
| DSL-3D08-G0M5AC2 LTG,ST/DS 0M5 M23/SUB-D | Connectors and cables Connection cables, DSL-3D08-G0M5AC2 Connection type head A: Socket, M23, 12-pin, straight Connection type head B: plug, D-Sub, 9-pin, straight Signal type: SSI Cable: 0.5 m, 8-core, PUR, halogen-free Description: SSI, shielded, programming cable for programming tool PGT-08-S and PGT-10-S Note: Suitable for use with SSI interface, not for use with Interface SSI + Incremental or SSI + Sin/Cos suitable., Programming adapter cable for programming tool PGT-10-Pro and PGT-08-S |
| STE-2312-G LTG.STE. M23 12P.GE | Connectors and cables Assembleable connectors, STE-2312-G Connection type head A: plug, M23, 12-pin, straight Signal type: HIPERFACE®, SSI, incremental, RS-422 Description: HIPERFACE®, shielded, M23 connector SSI Incremental RS-422 Connection technology: solder connection |
| BEF-FA-020-036 FLANSCHADAPTER | flanges Mounting flange, BEF-FA-020-036 Description: Flange adapter centering collar D20 to D36 Scope of delivery: flange adapter, screws for encoder mounting (3 pieces M3 x 14 cylinder head) |
| SKS36-HFA0-S05 | Motor feedback systems rotary HIPERFACE® SKS/SKM36, SKS36-HFA0-S05 Communication interface: HIPERFACE® Version: Absolute single turn Type: built-in Sine/cosine periods per revolution: 128 Safety-related system: no Mechanical design: conical shaft, spring plate support Connection type: plug, 8-pin, radial Technology: Optical Operating temperature range: -20 °C ... +110 °C Special feature: Without side fastening screws, delivered in Revolving packaging (020-240-000-710), operating instructions 8013452 not included Scope of delivery, |
| DME5000-117 DISTANCE MEASURING UNIT | Long-range distance sensors DME5000, DME5000-117 Measuring range: 0.15 m ... 70 m, on "Diamond Grade" reflective film Repeatability: 0.5mm Accuracy: ±2mm Output time: 2 ms Communication interface: HIPERFACE® Connection type: connector, 1 x M12, 4-pin, 1 x M12, 8-pin Current consumption: At 24 V DC < 250 mA |
| DS50-P1122 DISTANCE SENSOR | Mid-range distance sensors Dx50, DS50-P1122 Measuring range: 200 mm ... 10,000 mm, 90% reflectance 200 mm ... 6,000 mm, 18 % reflectance 200 mm ... 4,000 mm, 6% reflectance Minimum response time: 20 ms Digital output: 2 x PNP Light transmitter: laser, red Laser class: 1 Multifunctional input (MF): 1 x |
| RT-P3231 | 1063131 |
| WL18-3P430 | 1025911 |
| DME5000-117 Distance Measuring | |
| DS50-P1122 | |
| PGT-08-S | |
| AD-ATM60-KA3PR | Bus-Adapter KR3, 3 x PG IP67 |
| VTE18-3F4740 | |

| | |
|--|---|
| LMS111-10100S09 | |
| KUP-1012-B BELLOWS COUPLING | 5312984 Shaft adaptation Shaft couplings, KUP-1012-B Description: Bellows coupling, shaft diameter 10 mm / 12 mm, maximum shaft offset: radial +/- 0.25 mm, axial +/- 0.4 mm, angular +/- 4°; max. speed 10,000 rpm, -30° to +120° Celsius, max. torque 120 Ncm; material: bellows made of stainless steel, clamping hubs made of aluminum |
| DOS-3XM12-W (2058177) | |
| DOS-1204-G 4-Pin M12(6007302) | |
| DOL-1204-G05MRN (6058476) | |
| DOS-1205-W (6009720) | |
| WS/WE45-P260S01 (1016031) | |
| IME12-04BPSZC0K (1040763) | |
| IME30-15BPSZC0K (1041029) | |
| DL100-11AA2101 (1059957) | |
| IM12-10NPS-ZC1 (6027514) | |
| UM18-51111 (6028965) | |
| IME12-04BPPZC0S (1060232) | |
| DS50-P1112 (1047402) | |
| GRTE18-P1142 (1066548) | |
| AFM60B-S1AA004096 ABSOLUTE ENCODER | 1037868 Absolute encoder AFS/AFM60 SSI, AFM60B-S1AA004096 Singleturn or multiturn version: multiturn Max. resolution: 12 bit x 12 bit (4,096 x 4,096) Mechanical version: solid shaft servo flange 6 mm x 10 mm Communication interface: SSI, not programmable Connection type: connector, M23, 12-pin, radial |
| AFM60B-S1AA004096 ABSOLUTE ENCODER | Absolute encoder AFS/AFM60 SSI, AFM60B-S1AA004096 Singleturn or multiturn version: multiturn Max. resolution: 12 bit x 12 bit (4,096 x 4,096) Mechanical version: solid shaft servo flange 6 mm x 10 mm Communication interface: SSI, not programmable Connection type: connector, M23, 12-pin, radial |
| IQ40-40NPPKC0K | 1071552 |
| PBS-RB010SG1SSNAMA0ZS02 | 6063038 |
| IME18-08BPSZC0K | 1040965 |
| GRL18S-F2336 | Light sensors and light barriers GR18, GRL18S-F2336 Functional principle: reflection light barrier Functional principle detail: With minimum distance to the reflector (double lens system) Switching output: PNP Switching type: Dark switching Connection type: M12 connector, 3-pin Light transmitter: PinPoint LED Setting: None Communication interface: - Included in delivery: Fastening nut (2 x) |

| | |
|---|---|
| GRL18S-F2336 | Light sensors and light barriers GR18, GRL18S-F2336 Functional principle: reflection light barrier Functional principle detail: With minimum distance to the reflector (double lens system) Switching output: PNP Switching type: Dark switching Connection type: M12 connector, 3-pin Light transmitter: PinPoint LED Setting: None Communication interface: - Included in delivery: Fastening nut (2 x) |
| 6026473 Sick Induktiver Sensor Iq80-50bpp-Kco | |
| Eks36-0kf0b018a | Motor feedback systems rotary HIPERFACE DSL® EKS / EKM36, EKS36-0KF0B018A Type: installation Communication interface: HIPERFACE DSL® Mechanical interface: torque arm Connection type: Plug 4-pin Safety-related system: no Resolution per revolution: 18 bit Country of origin: DE; Stat. Product number: 90314990 EC dual use / export list number: non; |
| 6052379 | |
| 7029163 | |
| Iq40-20bppk0s | |
| 1040696 Wt4-3p3441s38 | |
| 6008900 Stecker Mit Kabel 2 Meter (Eckig) | |
| 2073484 | |
| 1019248 | |
| 7122797 | |
| 1028936 | |
| 1064461 Scanner | |
| 1036028 | |
| 1026538 Sensorkt5w-2p1116d | |
| 1063923 | |
| 6044999 | |
| 2064574 | |
| Wl12-3p2431 | |
| 1209148 | |
| 1026834 | |
| Wl45-P260 | |
| 1019253 Lichtschanke Ws/We34-V230 | |
| 1016629 | |
| Wt14-2p432so8 | |

| |
|---|
| 2076544 |
| Dt50-N1113 Abstandssensor |
| Re27-Sa05I |
| Dos-1204-W |
| Dbv50e-22eka2000 |
| 1052595 |
| Wlf18-3v930 |
| 6047606 Thts-1aat11006mz |
| 2105497 Kabel |
| Wl11-2p2430 |
| Srs50-Hza0-S36 Encoder Motor Feedback |
| 2071778 Dos-2312-Ready-To-Gs02montage Steck -Steckverbinder |
| 6054714 Ultraschall-Sensor |
| 5311210 Pl10f Reflektor |
| Al20e-Pm331s01 |
| P/N: 7102162, Type: Dol-Ms10-G05mma3 |
| 1052866 |
| 7101656 Dgs35-1h408192inkrementelles Wegmess |
| 6055955 |
| 6036082 Wl8g-P2231s01 Lichtschranke |
| Bef-W280 Montagewinkel K. V. Optischen |
| 2045739 |
| 6010543 |
| 6022774 |
| 6024788 Ws/We140-2p132 Sensordie Bestimmungen Optoelektronnyj |
| Wl12l-2b530s03 |
| 1018975 |
| Clv620-2000s01 Scanner |
| Ds35-?15221 Abstandssensor |
| 1046894 Inductive Sensor Ime 18-08-Nppzc0s (No/Nc) |

| |
|---|
| 5310602 |
| Dme4000-321 |
| P/N: 1057792, Type: Ttk50-Hxi0k02 |
| Wtb4t-3n1264 |
| 6041752 |
| 6022083 Ste-1205-G Stecker Gerade(Papst) |
| Ws/We100I-F223 |
| Dme4000-211s06 |
| 1068866 |
| 6022012 |
| 1043006 Kt5w-Sensor 2b1116kontrastierenden Markierungen |
| Dfs60b-Bhak01024 |
| 6024791 Ws/We140-2p430 Through-Beam Sens.Sensorbestimmungen |
| P/N: 1063567, Type: Ttk70-Hxj0-K02 |
| 6009719 Anschluss Typ Dos-1205-G, M12, 5-Polig |
| Dt35-B15551 Sensor |
| 1040984 Stellungsgeber |
| Im18-08n-N-Zwo |
| 6013533 |
| 1025326 |
| 6063340 Sensor Lichtschranke. Typ: Gll170t-B432 |
| 6013254 Sensor |
| 1059031 Encoder Absolute Afm60a- Bhnb018x12 |
| 2025238 |
| 6030715 |
| S30b-2011da Agv Sensor - |
| 1062542 |
| 6036841 Wfl120-95b416 Geschlitzsensoren |

| |
|--|
| 6010192 |
| 1052700 |
| 6049678 Ufn3-70b413 |
| 6007988 Dos-1612-W Steckdose (Ready-To -Montage) |
| Dt500-A211 |
| I12-Sb213 |
| 6032451 |
| 1026244 Kt3l-P3216 |
| 1040747 Ime12-Induktiver 04npszc0ksensor |
| 6034414 Ssl-2j04-G02meanschlusskabel Mitstecker Und Stecker |
| 1036354 Encoder Dfs60e-Beek01024 |
| 6022083 |
| 1016910 Magnetischer Zylindersensortyp: Mzt 1-03 Vps-Kp 0al: N Eccn: |
| 6025907 Dol-1205-G05mcstarthilfekabel Mitweiblicher Teil |
| Im12-04nps-Zqd Induktiver Stellungsgeber |
| 5321625 |
| 5304812 Leichter Reflektor |
| 1037729 |
| Wll170-2p162 |
| 1028669 |
| 6022083 Connector M12 Sick Ste-1205-G |
| 1026538 |
| 1071843 Iq40-15bpp-Kko |
| 6048407 |
| 1036074 |
| 1037909 |
| Dol-1204-G02m |
| 1027770 Wl27-2f440 |

| |
|--|
| 2085763 (Ex.2077728) |
| 1207969 |
| Srm50-Hwa0-K21 |
| 6052362 |
| Dos-1204-Gz Stecker |
| 2045890 Spring Terminal Set |
| 6011971 |
| Pl40a Reflektor 41 X 60 |
| 1036077 |
| 1053411 |
| 6058497 |
| 1040736 Induktiver Sensor Ime12-02bpoz0s |
| 1030001 |
| Wtb9-3n1161 |
| M40e-034000rr0 |
| 1016934 |
| 6009932 Ste-1204-G Stecker M12 4-Pin., Luftlinie, "papa" |
| 1041290 Barcodescanner, Clv650-0000 |
| 1099335 |
| 1036081 |
| Icr620s-T11503 Barcodeleser |
| 1085373 |
| 1026515 |
| 1207795 Sensor |
| 1040856 |
| 5308445 Bef-W n-M30 Befestigungssystem |
| Bef-Ha-M18r |
| 1053167 |
| 1072273 |
| 4026324 |

| |
|---|
| 1059925 |
| 6044736 Optischer Sensor |
| P/N: 7102161, Type: Dol-Ms10-G03mma3 |
| 1057655 |
| 1030009 |
| Wtb12-3p1111 |
| 1019251 |
| 1062420 |
| T4000-1kba |
| 1053126 Dfs60b- Bdea01000inkrementelles Wegmess |
| Dt20-N130b0960 Optischer Sensor |
| We12-2p430 |
| Uc4-11341 |
| 1026820 |
| 2029245 |
| Dmt10-2-1213 |
| 1053168 |
| 1062110 |
| 1070720 |
| Im30-22bps-Zc1 |
| 2025264 |
| 1070814 |
| Dme 4000-111 Long-Range- Distanzsensoren |
| 6022084 Ste-1204-W Stecker M12, 4-Pin - Ecke (Papa) |
| Wt12l-2b550-T01 |
| 1065661 |
| Kt3w-P1116 |
| 1016592 |
| Lm31l/450 |
| 1029951 |

| | |
|---|---------|
| 6024916 | |
| 1022603 | |
| 1053131 | |
| C4c-Ea12030a10000 | |
| M40z-043000tr0 | |
| 6030710 Sensor | |
| 1040966 Sensor Ime18-08bpszc0s | |
| 6048061 Photoelectric Sensor | |
| 1028097 Sensor Wtb4-3p3161 | |
| Vfs60a-Bhpz0-S01 | Encoder |
| Ime18-08nnszw2s | |
| ??-3583? 100 ??? 16 ??? | |
| Wl36-R230 | |
| Bef-Dsdt | |
| 1044369 Optischer Sensor | |
| Drehgeber Dgs35-1h408192, Lines - 8192, 5vdc | |
| 5327812 Sensor | |
| 1033490 | |
| We12l2p430 | |
| Bef-W170 | |
| 6041818 Optic Sensor Vl180 - 2p41131 | |
| 1037981 Encoderdfs60bbdcc01024 | |
| 1051889 Wtb9m4-3p2261 | |
| 58072117 | |
| C20e-045304 | |
| 6039094 Wll180t- N432fiberoptikoptoelektronische Sensoren | |
| P/N: 1053558 | |
| 2068147 | |
| 1041986 Barcodeleser Clv631-6000 | |
| 1016806 Reflektor Pl560dg665 Mm X 665 Mm | |

| |
|--|
| Dfs60b-S4pk10000 Drehgeber |
| 5313885 Bef-W 280 Wannensicherungswinkel |
| 1033548 |
| 1012720 Reflektor PI40a |
| Srm50-Hfa0-K21 previous material number: 6CF-KR0-202-000 Motor feedback systems rotary HIPERFACE® SRS / SRM50, SRM50-HFA0-K21 Type: installation Communication interface: HIPERFACE® Mechanical interface: Spring plate support Spring plate support Connection type: Plug 8-pin radial Safety-related system: no Resolution per revolution: 4,096 Country of origin: HU; Stat. Product number: 90318020 EC dual use / export list number: non; US ECCN: non |
| P/N: 7102165, Type: Dol-MS10-G30mma3 |
| Ars60-A4b00360 |
| 7900099 |
| 4035439 |
| Dos-1612-G Stecker |
| 1003865 Reflektorpl80a |
| P/N: 1053007 |
| Btf08-A1am |
| 1033532 L230-Linear P580c2s00000endlosregler |
| 2013942 Montageplatte |
| 1036087 |
| 1082138 Kontrastsensoren , Ktm- Wp11172p |
| Kt10w-2p1115 Contrast Sensor Sick |
| 6025911 |
| S30a-4011da S3000s |
| 210802 Ultraschallsensortyp: Um 18- 51111artikel-Nr.: 6028965 |
| Atm60-A4a0-K06 |
| 6 009 867 Kabel Dol-1204-W05m |
| 1059555 |
| Lms511-11100 |
| Mm12-60aps-Zck ? Dos-1204-W x Sensor |

| |
|--|
| 1025245 |
| 20227180 |
| VI184p3240 (Ex.VI180p430) |
| Msle02-25011 Satz |
| 1034263 |
| 1040853 Induktiver Sensor |
| 1070871rzt7-03zws-Kw0 |
| 1036924 Endlosregler Df60b-Tepk1000 |
| Ps95w-24v |
| 1019280 |
| 6011048 Wt150-P162reflexions- Lichttaster Mit Hintergrundausblendung |
| Strl-Xas Opto Sensor |
| We27-2d430 Dc10 |
| 1041263 |
| Foto-Elektrischer Sensor Wtf12-3p2431 |
| Ds50-P1112 |
| 6037481 Sensick V180-2 Vte180-2n41147 (Npn) |
| 1036193 |
| 1036456 |
| Dol-2312-G03mma3 |
| Dol-1204-W10mm |
| 1069860 |
| WI260-P230 |
| 1036455 |
| 2075254 |
| 1036100 |
| 1017910 PI240dg Reflektierendeplatte |
| 6028626 |
| 6044701 |
| Iq80-50bpp-Kc0 |

| |
|--|
| 1018250 Sensor Lichtschanke Sick Wt12I-2b530 |
| 1052438 |
| 6022083 Ste-1205-G Ready-To -Montage Steck -Steckverbinder |
| 1051529 |
| 1047314 Sensor Dt50-P2113 |
| .Srm50-Hwz0-S35. |
| P/N: 1053765 |
| Iq40-20bppkcok |
| 1041385 Sensor |
| Dme4000-211 |
| Atm60-A1a-12x12 4096 |
| 6034576 |
| 6052615 |
| P/N: 7102160, Type: Dol-Ms10-G1m5ma3 |
| Wtb12-Sensor 3p2441optoelektronnyj |
| 1060534 Inkrementaler Drehgeber Dbs36e-Bbek01024 |
| 2096215 Kabel Patch Yg2a15-020vb5xleax |
| 1037697 Endlosregler |
| 2096239 |
| Im18-08nps-Zwb |
| C40e-S113 |
| Ste-1205-Wq |
| 1200126 |
| 6038659 |
| 1060294 |
| 1088196 Encoder Dfs60a-S1pk10000 |
| 1036014 |
| 1053258 Kt5w-2p1156s41 |
| 1019254 Sensor Ws/We-B430, |
| 1 040 950 |

| |
|--|
| Mb320-0008 |
| 2095888 Yf8u14-020va3xleax |
| 5308050 LI3-Tb01 |
| 1041411 Sensor Lichtschanke Wtb12-3p2431 |
| WI100I-F2231 |
| 1071200 |
| Lp10 -01000444 |
| 6041802 |
| WI14-2p431 |
| 1036992 Vfs60a-Thpz0-S01motorfeedback-Sensorposition Pulse |
| 6032638 |
| 1063375 |
| 1066198 |
| 6024920 |
| 1040838 Induktiver Sensorime081b5psztos |
| 6021353 |
| 1206482 |
| I17-Sa213 Elektromechanischer Schalter |
| Ars60-F4a00360 |
| 2062450 |
| Im12-08nps-Zc1 |
| 6036831 Wfl30-60b416 Fork Sensor |
| 6029507 |
| 6058483 |
| Gtb10-P4411s01 |
| ?4?-??03030?10000 Sender |
| 2095888 |
| 1029200 |
| Bef-Wn-Dx50 |
| P/N: 1069972, Type: Vfs60e-Bjck01000 |

| |
|--|
| P/N: 1059513, Type: Vfs60b-Bhaj02048 |
| 1003865 Reflektor PI80a |
| 6009867 |
| 10410763 |
| Bef-Wn-W45 (2011480) |
| C4mt-03634abb03de0 |
| 6027511 |
| Srs50-Hza0-S21 |
| 1041376 Sensor |
| 6036923 |
| 2023797 |
| C41e-0301ag300 |
| 1052684 DI100-Sensor 21aa2101entfernung Ssi |
| 1041390 Sensor 4m Palletizer WI11g- 2b2531 |
| Am164-81a000000037 |
| 1040976 |
| ???-301-???? ???1 0,25/0,6/0,6 |
| 2013353 Dol-1612-5m-2 Ltg,Rd.Dose/Aeh 5m0 12a |
| 6013117 Sensor Vte18-4p8212 |
| 1023547 |
| 5308050 Lwl-Kabel |
| We24-2b230 2021160 Receiver, PNP / NPN, H / D |
| 1203241 M40e-63a503rb0 Multiple Beam System Mehrstrahl-Sicherheitssystem |
| WI9-2p121 |
| 6058495 |
| 6058505 |
| 4019634 |
| 1046763 Spl-S280pps1w04 |
| 6009868 |

| |
|---|
| 1079051 Dbs60e-S4ec00100 Incremental Encoder |
| Dks40-E5I00200 Endlosregler |
| 6020688 Optischer Sensor WI150-P420 |
| Wlg4s-3p2232 Sensor |
| DI100-22aa2101 Sensor Distanz |
| 1018253 |
| 6052374 Wt100-Sensor 2p4439optisch |
| 5312981 |
| Ime12-04bpszcok |
| Srs50-Hwa0-K21 |
| 1041404 |
| Fx3-Xtio84002 |
| 6058476 |
| VI18-3p3140 Photoelectric Sensor 6013527 |
| 6034414 |
| Dol-1608-G10ma |
| 5326523 PI30f Reflektor |
| Kabel Zum Sensor |
| 1072836 |
| 1041132 Sensor Wse4-3f2131,Reflex |
| 1052446 |
| 1041456 Sensor WI12g-3b2531 |
| 6011992 Induktiver Sensor |
| 1042046 |
| Ime18-08bpszc0s Induktiver Schalter |
| 2019649 |
| 1019237 Lasersensorwt34-B440 |
| Mps-032tstp0 |
| WI100-P3330 |
| 2045643 |

| |
|---|
| 1066556 |
| 1036108 |
| Ih03-0b6ns-Vu1 |
| 1046399 |
| 1071746 |
| Dt20-P214b |
| Dsl-0612g01m075km0 |
| 1036759 Dfs60b- S1pm10000inkrementelles Wegmess |
| Mhl15-P3236 Optischer Sensor |
| Vs/Ve 18-4p3240 |
| Dfs60b-S4pc10000 Endlosregler |
| 1067186 2d-Lidar-Sensortyp: Ld-Lrs3611 |
| 1044124 Fx3-Xtdi80002 Controllersicherheit |
| 1045104 |
| 6048393 |
| 6024907 |
| 5313025 |
| 6052386 Sensorminiatur-Lichtschranken, WI100-2p4429 |
| 1081712 Sensorcfs50-Aaz00s13 |
| 6011047 Optischer Sensor Wt150-460 |
| 2029227 |
| Tsp-1qag10606mzs |
| 6022082 Stecker Ste-1205-W Sick |
| 6007302 Dos-1204-G Stecker M12 4pin |
| WI11-B560 |
| Im020bm45vb8 |
| 1060232 |
| 6009974 |
| ??-3583? 63 ??? 16 ??? |
| Gtb6-N4211 |

| |
|--|
| 6028454 Sensor Wf50-40b416 |
| 1065640 |
| 6043823 |
| Wt12l-2b530 P/N 1018250 |
| 1082456 |
| 1040895 Sensoren Sick |
| 1036490 |
| 1051434 Vfs60a-Thpz0-S03 Programmierbare Encoder |
| 6025910 |
| Obs-W45 |
| 1048117 |
| 6021125 |
| 1062094 |
| Ws/We45-R260 |
| Dos-0803-G |
| 1027763 |
| M40s-025010ar0 |
| 1037235 |
| 1064593 |
| 6010185 Optischer Sensor |
| 6054708 Uc4-13346 Ultraschallsensor |
| 1000131 |
| 1027858 |
| 1012719 Pl20a Reflektoren |
| Kt5w-2p1126 |
| 2014457 |
| 6044736 Wl280-2p2431lichtschanke |
| 1058622 |
| 6024878 Sicherheitsrelais Ue42-2hd2d2 |
| 2095963 |
| Iq08-04npskw2s |

| |
|---|
| Wsg-Dsdt |
| Wtb4sc-3p2232 Pnp Sensor |
| S30a-6011ba |
| 1003865 Pl80a |
| 1036787 Inkremental-Encoder, Dfs60b-Bhpk10000 |
| Dme4000-115 |
| 1076983 Lichtschanke Grl18-P2452 |
| 1043784 Fx3-Cpu130002 Controllersicherheit |
| Wtz72r610 |
| 1204147 |
| 6034574 |
| Dt50-2b215252 |
| 1018665 |
| 1025912 |
| 1027775 |
| 1041390 Sensor 4m Wl11g-2b2531 |
| Od1-B035c15a14 |
| 6029832 |
| 1036090 |
| Dme4000-227 |
| 6048401 |
| Wtb27-3p1111 |
| 1026538 Kontrastreicher Fotosensor Kt5w-2p1116d |
| 6024915 Ue48-2os2d2 Sicherheitsrelais |
| 6022774 Sensor |
| 100 1019 |
| 1039017 |
| 6025907 |
| C40s-1503ca010 |
| 1040749 |

| |
|--|
| 6022742 Sensor |
| Mhl15-P3236 |
| 1048152 |
| 2079314 |
| 1051072 |
| P/N: 1053168 |
| 1043006 Sensor Kt5w-2b1116 |
| Wl24-2b333 |
| 6028359 Ste-1204-Gn Stecker (Fertigezur Montage) |
| 6022369 |
| Wl100-N4439 |
| 6028422 Dos-1208-G Socket Pg9 M12-8p M12-Stecker |
| 1052427 |
| 6048420 Um18-218161101ultraschall- Sensoren |
| 6027931 |
| 6020478 |
| 1031556 Winkel-Sensor Ars60-F4a00360 (1031556) Verbindet Sich Von Der Spielmarke |
| 2031079 Werkzeug |
| 1078126 |
| Drs60-D4a01024 |
| 2024896 |
| Wtb250-2p2451 Optischer Sensor |
| Ie12-F1 |
| 1016019 |
| 6033211 Sensorwtb8-P1111 |
| 1029791 Dme4000-212 |
| 6026473 |
| 1027770 |
| Olm200-1002 |

| |
|--|
| 1026052 Sensor Lichtschanke Wt14-2p422 Dc10_30v Class2 500mm |
| 1003122 |
| 6036923 Um30-213118 Stellungsgeberultraschall |
| 1017405 |
| 6009932 |
| C4c-Ea04510a10000 |
| Wl34- R240 |
| 1202667 Transmitter - M40s-025003ea0 |
| Wl280-2p2431 |
| Kt5w-2n2116d |
| 1019237 |
| 1019249 |
| Clv430-6010 |
| Dfs60e-S4ea00360 |
| Im30-15bps-Zc1 |
| 6011050 Optischer Sensor |
| 2096357 Anschlusskabel |
| 1036354 Dfs60e-Beek01024 Inkrementaler Drehgeber |
| Srm50-Hxa0-K22 |
| Wtr2-P511 |
| 6022880 E100-B2a22s10a Steuerungsblock |
| 6032861 |
| Dfs60a-S4pa65536 |
| 6032676 Modul Relaisausgang Ue410-4ro4 |
| 1016932 |
| 6027577 |
| 1035242 |
| 1043783 Fx3-Modul Cpu000000flexisoft |
| Motor feedback systems rotary HIPERFACE DSL® EKS / EKM36, |

| | |
|--|--|
| Ekm36-0kf0b018a | EKM36-0KF0B018A Type: installation Communication interface: HIPERFACE DSL® Mechanical interface: torque arm Connection type: Plug 4-pin Safety-related system: no Resolution per revolution: 18 bit Country of origin: DE; Stat. Product number: 90318020 EC dual use / export list number: non; |
| Wtr2-P521s09 | |
| 6048416 Uc12-12231 Stellungsgeber Ultraschall | |
| 6009382 | |
| Pbs-Rb250sg1ssnamaoz | |
| 6009873 | |
| ??-Ea09030a10000 | |
| 1025896 | |
| Yf8u13-C60ua1m2a13 Verbindungskabel Mit Steckern | |
| WI9-3p1130 | |
| 2022544 | |
| 1200129 | |
| 1030013 | |
| Skm36-Hfa0-K02 | |
| 6036917 Sensor | |
| 1035239 | |
| 1061396 | |
| Wt18-3p610 | |
| 6 009 869 Kabel Dol-1205-W05m | |
| 1018044 | |
| 6020312 Im12-02bds-Zc1 | |
| Wf80-60b410 | |
| 2034324 | |
| Ar60 1015741 Befestigung | |
| 1031556 Ars60-Absolute F4a00360wegmess | |
| 1018587 Sensor Typ: Kt5w-2p1126 | |
| 1325354 | |
| 7028790 Netzteil Und Netzwerkkabel | |

| |
|---|
| 1015993 Sensor |
| Um30-213112 |
| 6037782 |
| 6058156 |
| 1010994 Einweg-Lichtschranketyp: Ws/We 45-R 250 |
| 6012640 |
| 6010542 |
| 6028431 Sensor |
| WI24-2b230s02 Sensor |
| 1036121 |
| 2045891 |
| 1002314 Reflektor PI30a |
| Dt35-B15552 |
| 2055634 |
| 1041725 Scanner Lms400-2000 |
| 6041423 |
| Dme4000-214 |
| C40s 0603ca010 |
| 1037395 Srs50-Hza0-S21 Systemfeedback |
| 1046135 |
| P31267 |
| Drs60-Eam01000 |
| 1058182 Wse9I-3p2237 Photoelectric Switch Lichtschranke |
| WI9g-3n1234s02 |
| 1040870 |
| 2042516 |
| 1045096 Sensor |
| 6049679 Schlitzsensor |
| 1053183 |
| WII160-F122 |
| |

| |
|---|
| 6020598 |
| 1057643 Kt5w-2p2156s42 |
| 1046449 Wlg4s-3p3432vlichtschanke |
| P/N: 6037423, Type: Mvm-04m-2mc-Mklb |
| 6052613 Kabel |
| Wt24-2r210 |
| 1063542 Dfs60e-S1ec01000incremental Encoder |
| 1070847 Rzt7-03zrs-Kp0-Sensorposition Magnetisch |
| 1038186 Endlosregler |
| 1059455 |
| 2055427 Bef-Slg-Set1 |
| Cdb620-001 |
| 6012820 |
| Wtb9l3p2261 |
| 1017857 |
| 6009383 Dol-1204-W02mstarthilfekabel Mitweiblicher Teil |
| 1060544 Dbs36e-S3ek01000 Inkrementaler Drehgeber |
| 6009869 |
| 5333571 Madenschraube |
| Ktm Wp11181p |
| 1059039 Absolut-Encoder, Afm60a- S4nb018x12 |
| 1019311 |
| F8u13-C60ua1m2a1 |
| 1050768 |
| Bef-Wg-W12 |
| 6036918 Ultraschallsensor |
| 1044458 |
| Ime08-02bpszt0k Sensor |
| 6036644 |
| 5313019 |

| |
|--|
| Gr18sg-E233z 1061927 Optischer Sensor |
| Dfs60e-S4ea01024 Endlosregler |
| 1211474 |
| 23444 |
| C40s-1501da010 |
| 5326704 Kup-0810-D |
| Wt36r230 |
| 1037855 |
| 1074296 Dbs60e-Thezd0s18 Incremental Encoder |
| 1209147 |
| Wtb4-3p3161 |
| 1056428 |
| 1037799 Endlosregler (Ident.Nr1037799) |
| 6032669 Ue410-Mu4t5 Controllersicherheit |
| 1059401 |
| LI3-Db01 Glasfaserkabel |
| 1040966 Ime18-08bpszc0sinduktiver Stellungsgeber |
| S30a-4011 |
| 1051521 Encoder Dfs60e-Thek01024 |
| 6 009 868 Kabel Dol-1205-G05m |
| WI100p4409 |
| 6009720 |
| 6021175 |
| 1044369 Abstandssensor |
| 1081580 |
| 1052592 |
| WI250-2p2431 |
| 1040764 Ime12-04bpszc0sinduktive Sensorenproximity |
| K-SI30-02000-080-1 |

| |
|--|
| 1036453 |
| 1213213 C2c-Ea12030a10000lightcurtain Receiverlicht Schleier Sicherheit |
| We27-2f430 Dc10 |
| 1026049 |
| 7900097 Induktiver Sensor Sick Im18- 12nps-Zc1 |
| 1047396 |
| 6037824 Gabelsensoren, Wfm50-60p321 |
| 6027538 Dos-2312-G |
| Olm100-1001 |
| 6010785 Dol-0803-G02m Kabel 2 M Mitanschluss 8 Mm 3 Pin |
| P/N: 1053167 |
| 1028487 |
| 1040738 |
| 1046317 |
| 6036385 |
| Bkss20805 |
| 1064990 |
| 5308074 LI3-Db01 Glasfaseranschlusskabel |
| Dme4000-121 |
| Pr-Ste-1205-G |
| 1028100 Der Optische Sensor Wtb4- 3p2261 |
| 1018666 |
| Bef-Khs-K01 |
| VI180-2p42433 Fotosensor |
| Wt45-P 250 |
| 1044075 Fx0-Gpro00000 Controllersicherheit |
| 1022243 |
| Wtv4-3p3441 |
| Dol-1205-W05m |

| | |
|--|---|
| 2096244 | |
| We272f450505 | |
| 1040898 | |
| 6029831 Sensor | |
| Lfv310-Daftvxmtx 6041204 | |
| 1046012 | |
| Vte180-2n42482 Sensor | |
| Wt12-2p440 1 016 150 Dc 10..30v | |
| Pgt-01-S Programmer | |
| 6030928 Ssl-2j04-G10me Starthilfekabel | |
| 6053042 | |
| 6029280 | |
| Sks36-Hfa0-S05 | previous material number: 6CK-100-200-012 SKS36-HFA0-S05 MOTOR FEEDBACK HIPERFACE 128 sin / cos periods *** RoHS compliant according to EU Directive 2005/95 (from date code 08/36) Country of origin: DE; Stat. Product number: 90314990 EC dual use / export list number: non; US ECCN: non |
| Bcg05-A1nm0155 | |
| 1052684 Distanzsensor DI100-21aa2101 | |
| Wtb4-3p2161 | |
| 1041060 3. Ime30-20nnoz2s | |
| Srs50-Hta0-K21 | |
| 2022547 Dol-0612g10m075km0 M26*12 | |
| 6025906 | |
| 1026538 Kt5w-2p1116d Kontrastsensor | |
| Wt12-2p440 Sensor | |
| 1092617 | |
| 2108625 | |
| M40z-025023tb0 | |
| 6063342 | |
| 1203240 M40s-63a503aa0 Multiple Beam System Mehrstrahl-Sicherheitssystem | |
| Dme4000-313 | |

| | |
|---|---------------|
| 1200130 | |
| 6037662 Sensor Um30-214111 | |
| Wt34-R240 | |
| 1040780 | |
| 1000382 Reflektor | |
| 1042040 | |
| 1047581 Dt50-P1114 Distanz Sensor | |
| L21s-21ma1a | 19/K028940- 1 |
| 1058853 | |
| Im04-0b6ps-Zu1 | |
| Wt18-3p410-50-700 Sensor | |
| Pbs-Rb1x0sgess0bma0z | |
| 6027538 Dos-2312-G P/N 6027538 | |
| 6060127 | |
| 6009873 Dol-0804-Stecker Mit W05m Kabel 5m | |
| Wl160p132 | |
| 6049456 | |
| 1040767 | |
| Atm60-Pah13x13 | |
| 1048379 | |
| 1082138 Sick Sensor Ktm-Wp11172p | |
| 1059958 Optischer Abstandssensordl100- 11ha2101 | |
| 2058653 Bef-Ah-Traeger Fuer Dx100dl100 | |
| 5306535 | |
| 6011050 | |
| 5311137 | |
| S30a-6011ca | |
| 2029205 Dol-2312- G30mma1starthilfekabel Mitweiblicher Teil | |
| 1071845 1071845 Iq40- 20bpokk0sinduktive Sensorenproximity | |

| | |
|---|---|
| 1036750 | |
| Ws27-2d450s05 | |
| 6044336 Pressure Sensorpbs-Cb2x5sg1ssnama0z | |
| 1028153 WI4-3f3130 Photovoltaiksensör | |
| Srs50-Hfa0-K21 | previous material number: 6CF-KR0-102-000 Motor feedback systems rotary HIPERFACE® SRS / SRM50, SRS50-HFA0-K21 Type: installation Communication interface: HIPERFACE® Mechanical interface: Spring plate support Spring plate support Connection type: Plug 8-pin radial Safety-related system: no Resolution per revolution: 1 Country of origin: HU; Stat. Product number: 90314990 EC dual use / export list number: non; US ECCN: non |
| 1064706 | |
| Dos1204-G Stecker Female Connector | |
| DI100-21aa2112 | |
| Ws27-2d450505 | |
| 1023890 S30a-7011ba Laser-Scannersicherheit | |
| 1017428 Sensor Im12-02bps-Zck | |
| 1048152 Sensor Al20e-Pm331s01 | |
| 6036919 Ultraschallsensoren , Um30-214113 | |
| 2045890 Spring Set Terminal | |
| 1040774 Sensor Ime12-04bnszw2s | |
| Bef-Mu-M08n Sensor | |
| 6020683 Optischer Sensor Mit Spiegel | |
| 1035240 | |
| 1059958 | |
| 6034484 Ue410-Mdi3 Controllersicherheit | |
| 4069422 | |
| Clv620-0000 | |
| 1036664 | |
| Wt45-P200s03 | |
| 1041689 | |
| 6028958 Sensor | |
| 1056708 | |

| |
|---|
| Srm50-Hza0-S25 |
| 1060992 |
| 2095609 Kabel Patch Yf2a14-100ub3xleax |
| 1036747 |
| Wtb27-3p2411 Sensor |
| 7902925 |
| 2023616 |
| 2096356 |
| 1028153 Sensor |
| C41s-0301aa300 |
| 1211505 |
| 1036923 Encoder Dfs60b-Tdpk10000 |
| 6026211 |
| 4051184 |
| 2092035 |
| 1028161 Sensor Ws4-3d3130 |
| 1053765 |
| 1036109 |
| 1041404 Wtf12-3p2431 Lichtschanke |
| 6030704 |
| M40s-034000ar0 |
| Wl12-P1331 |
| Wt34-B410 |
| 7101661 |
| 1046396 |
| 1218660 Optoelektronische Sensor. Typ: Wla16p-24162100a00 |
| C4mt-12034abb03fe0 |
| Lbst32900 |
| Afm60a-Benb018x12 Encoder |
| Bl16010 |
| P/N: 1059306 |

| |
|--|
| 6035225 Typ: Imf18-08nppvc0sp/N: 6035225al: N Eccn |
| WII190t-2n432 |
| 7028790 |
| Wtf4s-3p3231s08photoe.Prox.Switch |
| WI9-2p330s10 Lichtschanke |
| Imb08-04npovt0k |
| I110-Ra223 |
| 1058230 |
| 6010190 10-30 |
| Cable5m |
| 1049042 Sensor Lichtschanke Sick Wtb9- 3p1111 |
| Wt100-P3430 |
| 6052628 |
| P/N: 1057793, Type: Ttk50-Hxq0k02 |
| 2073483 |
| WI34-B430-S03 Sensor |
| 1034094 Skm36-Hfa0-K02 Sensor- Feedback-System (Encoder)al: N Eccn |
| 1058701 |
| 1070849 |
| 1070814 Sensor Mzt1-03vps-Kp0 |
| M40e-025010rr0 |
| 6020112 Induktiver Sensor |
| Bef-25mmeaku4 |
| Dos-1205-G Cable Connector 6009719 |
| 7902138 |
| WII6-P122 |
| 1025575 Light-Grid |
| 6011033 |
| 1036094 |
| Ste-1204-G Stecker Male Connector |

| | |
|--|--|
| 1044120 Wse12-3p2411s36 | |
| 6036916 | |
| Btf13-P1hm0525 | |
| 1211473 | |
| 1018669 | |
| C40e-1501da010 | |
| 6011050 Miniatur-Lichtschranken, Wt150-P460 | |
| 1026036 | |
| 6027538 Stecker (Kabel-Teil) Sick: Typ Dos-2312-G | |
| 7020046 | |
| Vtf18-3f1640 | |
| 1028232 Sensor | |
| 5308074 | |
| Wtt12l-B2562 | |
| Wl272p630 (01015108) | |
| Wf240b410 | |
| C40e-0603da040 | |
| 1018045 Kt5w-2n1116 Sensor Kontrast. Tags | |
| 1070852 | |
| 6051061 | |
| 1040764 | |
| 6025067 | |
| 1213212 Sicherheits-Lichtschranke2c-Sa12030a10000 | |
| Wlg4s-3p2232 Lichtschranke | |
| Ds500-P111 | Long-range distance sensors Dx500, DS500-P111 Measurement object: natural objects Measuring range: 0.2 m, 0.8 m ... 30 m, 15 m, 90% remission, 6% remission Repeatability: 1 mm Accuracy: ± 3 mm Laser class: 2 (IEC 60825-1: 2014, EN 60825-1: 2014) corresponds to 21 CFR 1040.10 and 1040.11 with Exception of the deviations according to "Laser Notice No. 50 "from June 24, 2007 |
| Fx3-Mpl000001 | |

| |
|--|
| Dol-1205-G05m |
| 6044760 |
| Wtb27-3p2413 |
| 6028411 |
| 1081580 Lichtschranketyp:HI18-P4a3aas06 |
| P/N: 7102163, Type: Dol-MS10-G10mma3 |
| 1019227 |
| Dme3000-232p |
| Wt27-2f410 |
| Dol-1205-G10m |
| 2046459 |
| Zt2-P4228 Sensor Lichtschanke |
| 1218698 Klein-Lichtschrannen, Wtb16p-24161220a00 |
| 1029861 |
| 1081580 Lichtschranketyp:VI180-2p42436 |
| 6032866 Dol-1208-G02mac1 C |
| C40s-S113 |
| 2029216 |
| 6013675 |
| WI 160-F440 9634f |
| 6035225 Induktiver Sensor Imf18-08nppv0s 6035225 Dc-10-30v, Ia=200ma |
| 1371167 |
| 1040748 Ime 12-04npszc-0s Np1029 |
| WI150-N132 1330f Sensor |
| WI-272f440 |
| 1037006 |
| 6009383 |
| Clv-650-0000 |
| Fx3-Cpu00000 |
| C4p-Sa04530a001200 |

| |
|--|
| Um30-213111 Ultraschallsensor |
| 6013110 Sensor |
| 6020993 Dol-1208-G05mastarthilfekabel Mitweiblicher Teil |
| 6021354 |
| 6033186 WI8g-P2131 (6 033 186 1537h) Mit Anschlusskabel |
| 6025907 Dol-1205-G05mc Mit Steckerkabel 5m0 |
| Wtbs-3p3464v |
| 6025909 |
| 1045093 Der Optische Sensor Sick Wtb4s- 3p2235v |
| Wte280-2n4331 |
| Wtb27-3v2411s02 |
| 1053535 |
| 6024798 |
| Vtf18-4p1440 Optischer Sensor |
| Ste-1204-Ge01 |
| WI280-2r4331 Optischer Endschalter |
| 2030645 |
| Ds500-P511 Codice 1040479 |
| 1036112 |
| Dme4000-124 |
| 1052108 |
| 1018252 WI12I-2b530 Reflexions-Lichtsch |
| Wse12-3p2431 |
| 7047654 |
| 7x03 |
| 6053761 Sensor Wfs3-40p01cs01 |
| 6041804 Sensor |
| Wtb4s- 3p2131photoe.Prox.Switchlichtschranke |
| Bef-W 100-A |

| |
|---|
| 6037503 |
| Kt5g-2n111 |
| We272p630 |
| 7074065 Der Optische Sensor Grs18-D2421 |
| 6007363 |
| Im08-01b-N-Zw0 Induktiver Stellungsgeber |
| ???-102-111?-?-0,15/0,15 |
| Vs/Ve18-4p3240 |
| 6036918 Sensorum30-213113 |
| 7902077 Dos-0803-G-Steckdose (Ready-To -Montage) |
| Dme3000111 |
| 6020757 Hirschmann Cable Socket M26x22+fe, Gerade |
| Idec Hs7a Safety Sensor |
| 1037612 |
| 6026008 |
| 1213202 C2c-Licht Sa04530a10000schleier Sicherheit |
| 1018651 |
| 6039745 Bcg05-K1km01pp Mit Drehgeberseilzug Trommel |
| 2025268 |
| 1040012 Dt20-P214b Verschiebungs- Sensoren |
| 6022751 |
| 6037472 Anschlusskabel Mit Stecker Stl- 1204-W05mc |
| P250f |
| Bef-W4-B |
| Yg2a14-020vb3xleax |
| Grte 18s-F234z Optischer Sensor |
| 1025492 Elg3-0930p511 Eco-Lichtgrid |
| 1058175 |

| |
|---|
| 6051030 |
| Um12-1192261 |
| 1052684 Sensor |
| 5308048 |
| Clv632-0000 Scanner |
| 1016911 Sensor |
| Iq40-40nppkc0k Sensor |
| Dfs60b-Bzpz0-S01 |
| 2045601 |
| 6042565 Anschlusskabel |
| C2c-Ea03030a10000 |
| 6052360 Stellungsgeber Sick, WI100- P1439 Retro-Refl. Sens |
| Reflektor |
| 1023002 |
| Gtb10-P4211 Sensor |
| 1047402 |
| P/N: 1058957, Type: Vfs60b-Beek01024 |
| Im04-0b6ps-Zu1 Sensor |
| Wt150-P460 Sensor |
| Im30-15bp0-Zc1 |
| 1060544 Endlosregler |
| 2031895 |
| 1049061 WI9-3p2462 Lichtschrankensensor |
| Wtb9l-3p2261 |
| 1063175 Rt- B2221multifunktionsoptoelektronische Sensoren |
| Rt-P3231 Optischer Sensor |
| 1036560 |
| 5304812 Reflektor P250 |
| 6005698 |
| 6 009 872 Kabel Dol-0804-G05m |

| |
|---|
| 1062251 |
| 1041385 Sensor 10m Conveyor Line Wl11-2p2430 |
| Ime18-05bpszc0k |
| 1034308 Btf13-P1hm2025 |
| 1010994 |
| Bracket |
| 5308445 |
| 1015741 |
| 6025901 |
| Wt24-2v540s10 |
| 2096215 Yg2a15-020vb5xleaxstarthilfekabel |
| 1213213 C2c-Ea12030a10000 Lightcurtain Receiver Licht Schleier Sicherheit |
| 6052386 |
| 1017810 Sensor Kt5w-2p1123 |
| 1059333 "photo Electric Sensor,Make-Sickmodel-Gtb6-P511 |
| 1017815 Sensor Lichtschanke Wt24-2b420s08 |
| Wll170-2p132 Lwl Lichtschanke |
| Dt500-P111 |
| Wt27-2f430 |
| Ue403-A0930 |
| 1040769 |
| 1057064 |
| 6058145 |
| PI80a |
| Bef-Wg-W 24 |
| 1023971 |
| 1051521 Dfs60e-Thek01024 Inkrementaler Drehgeber |
| 7902926 |

| |
|---|
| 1016933 Wt24-2b410 |
| LI3-Tw01-3 |
| Drs60-E4I00500 |
| Iq40-15bpp-Kk1 |
| Dme4000-323 |
| 5306531 |
| 6033209 |
| 1018045 |
| 2019659 |
| 1211506 |
| 6024912 Sicherheitsrelais |
| 6033207 Wtb8-P2131 Stellungsgeberoptoelektronnyj |
| 1007167 Nt6-03025 Kontrast-Sensoren |
| Im12-04nps-Zc1 |
| P250f Reflektor |
| Dt35-B15551 Laser Sensor |
| LI3-Tr02 |
| We9-3p3430 |
| PI80 |
| 6037819 Wfm30-40p321 Fork Sensor Position Sensor |
| 1071153 Lichtschranke |
| 1050589 |
| 1047578 Lichtschranke |
| P/N: 1053509 |
| Vfs60a-Bgpz0-S01 |
| Dfs60b-Bdpl10000 |
| 5308843 P250f |
| We27-2f450s05 |
| 1017860 |
| Wt160-P460 Proximity/Reflex Sensor |

| |
|--|
| 1040966 Ime18-08bpszc0sinduktive Sensorenproximity |
| 6041819 Stellungsgeber Optoelektronnyi |
| 2033559 Einweg-Lichtschranketyp: We27- 3p2430 |
| 1033490 Sicherheitsschalterttyp: Eg342- 81b001012059 |
| 1030009 Atm60-Absolute Aaa12x12multi- Turn-Drehgeber |
| 1072806 |
| 1213212 C2c-Sa12030a10000 Lightcurtain Transm.Licht Schleiersicherheit |
| C4mt-06034abb03fe0 |
| Um18-20012 |
| Ste-1205-Ga |
| 1044124 |
| C20s-045104 |
| 1022602 |
| 6012829 Sensor Vtf18-4p1212 |
| Tr4-Sdm01c Schalter Notaus 6044638 |
| 6026558 |
| Ws100I-D2231 Lasersensor |
| 1040872 |
| 1036640 |
| 1075436 |
| 1076666 |
| 1019256 |
| 6033948 |
| Dol-1202-W10mc |
| Ime08-04nnszw2k Induktiver Sensor |
| P/N: 1070947, Type: Vfs60b-Tgek02048 |
| 1059632 |
| 6033207 Wtb8-P2131 Stellungsgeberoptoelektrisch |
| |

| |
|---|
| 1051547 |
| Im18-12nps-Zc1 Sensor |
| 1051547 Dt20-Sensoren P214bs03bias |
| 2095608 |
| PI30a |
| 1041411 Stellungsgeber Optoelektronnyi Wtb12-3p2431 |
| 6038697 |
| 1200060 Sperre Luminous M40s- 025003aa0 |
| 6033225 |
| 6011971 Induktiver Sensor |
| 1040839 |
| Dg90-5f1xb0l20g00 |
| 6023153 |
| 7902127 |
| 6039206 |
| 6035491 |
| Ws/We260-S270 |
| 4051185 Ref-Plus-R50 |
| 6008899 |
| Iq40-40nppkc0k |
| Dt35-B15251 |
| Dol-1204-W02m |
| Cdd-40p |
| Dme4000-212 |
| 1088335 |
| 6026216 Optischer Sensor-Typ: Vt12t- 2p430 |
| 1066552 |
| 6037323 Connector Dos-0804-G |
| 2096166 |
| 1052446 Gse6-P4111 Einweg- Lichtschranke |

| |
|--|
| 1047984 Lichtschanke Sicherheit |
| 2027180 |
| 1037091 Lampe |
| 2016408 |
| 1016031 |
| M40e-062200rr0 |
| 1098439 |
| 6021127 Induktiver Sensorim18-08n-N-Zw0 |
| Iq12-04bpskt0s Sensor |
| 1041411 |
| 6028442 Wf120-60b410 Geschlitzsensoren |
| 1041411 Klein-Lichtschraken, Wtb12-3p2431 |
| Lut8u-11401 |
| 6037668 |
| 5322547 Kabel Lwl Model LI3-Tv06 |
| Lms111-10100 |
| 5304812 Yi2a14-100ub3xleaxstarthilfekabel |
| 1049042 Wtb9-3p1111lichtschanke |
| 6048405 |
| 2065702 |
| 1026244 Kt3l-P3216 Kontrast-Sensoren |
| T4000-Dnac |
| 6021080 Wll170a-V430glasfaserlichtschanke |
| 5311129 |
| 7045173 |
| Dme4000-319 |
| 6049678 |
| Dfs60b-S4pk10000 |
| 1047581 |

| |
|---|
| 1036101 |
| M12 |
| E34-1-Ar |
| Wtb12-2p2411-1041422 |
| 1036255 |
| Vs18-0d3140 |
| 6032636 |
| 1071278 |
| 2021722 Ws12l-2d430-Sensorposition Optoelektronnyj |
| 6021123 |
| Dt60-P111b |
| 6038991 Dol-0803-G03mc Cab.,Fem.St 3m0 M8-3p |
| 2015069 |
| 1018295 |
| 1043784 Controller Sicherheit Fx3-Cpu1 |
| 6037833 |
| 1025910 |
| Clv422-2010s02 |
| 6024917-Ue10-3os2d0 |
| 1028226 Farbsensor |
| 6025681 |
| DI100-21aa2109 Entfernungsmesser Zur Positionierung |
| 1062523 |
| 1054131 |
| 1202707 |
| Dme4000-111s05 |
| Pbs-Rb010sg1ssnd5a0z |
| Wll180t-P434 |
| 6026216 |
| 1078041 Dfs60e-Tjek01024inkrementelles |

| |
|--|
| Wegmess |
| 6009720 Anschluss Typ Dos-1205-W, M12, 5-Polig |
| 6033290 Sensor |
| 6020223 Induktiver Sensor |
| 1028123 |
| Dfs60b-S4aa00500 Endlosregler |
| Wt100-N1432 Lichtschanke |
| Ime08-02bpszt0s |
| Dt50-N1113 |
| VI180-2n41131 Lichtschanke |
| 6049678 Sensor Ufn3-70b413 |
| 2056155 |
| 1040731 |
| 1019247 |
| 1028934 Sicherheits-Scanner S30a- 4011ba |
| 1033876 |
| Grtb18s-P1112v |
| Wtb12-3n2431 Lichtschanke |
| Kt8I-P3656 |
| Ws4-3d2130 |
| M4000 M40z-025000bro |
| 1023547 Einheit Sicherheit |
| 5321089 PI20chem Reflektor |
| WI9g-3n1234s02 Sensor |
| 1019245 |
| 6009503 |
| 6013458 |
| 6041807 |
| 1017910 PI240dg Reflektor |
| 5312984 |
| 1017910 Reflektor |

| |
|---|
| 6036629 |
| 2071329 |
| 6043920 Wfs3-40n415 |
| LI3-Db01 |
| Ste-0803-G |
| S30a-4011ba |
| Wswe160p132 |
| 1036767 Dfs60b- Bdpa10000inkrementelles Wegmess |
| Wt89-3p211 |
| Iq06-03bpsku3s |
| 6039866 |
| 1036924 |
| 2071331 |
| Nav350-3232 |
| 6011991 Induktiver Sensor |
| Dol-2321-G03mpa4 |
| Ws/We100-2n3439 |
| 1204132 |
| 6030709 |
| 6027944 |
| Wl12-2p730 |
| 1036083 |
| PI560dg |
| 1069073 |
| 5308077 |
| 6036918 Um30-213113 Ultraschallsensoren |
| 2050205 |
| 6009990 Wll160-F420lichtschanke Schalterglasfaser |
| 6027429 |
| 1034223 |

| |
|---|
| 6 007 302 Dos-1204-G Stecker M12 4pin |
| 6044705 |
| 6058474 Dol-1204-W02mrn Starthilfekabel |
| 1057656 Ds35-B15821 Abstandssensor |
| P/N: 1053574 |
| 6022758 Sensor |
| Dol-1205-G05mc |
| Iq80-60npp-Kk0 |
| 1036107 |
| 6052626 |
| Bgs-DI10cp |
| 1200122 |
| WI12-3p243 Sensor |
| 2071330 |
| 6026473 Induktiver Sensoriq80-50bpp-Kc0 |
| 2095609 Yf2a14- 100ub3xleaxstarthilfekabel |
| 1050912 |
| 6020110 Induktiver Sensor |
| Dfs60b-Tepk 10000 Drehgeber |
| Dme4000-311 |
| P/N: 1055346 |
| 7047620 |
| C45s-0303aa220 |
| Ime18-08bnszw2k Induktiver Sensor |
| 2058653 Traeger |
| 6010189 Optischer Sensor |
| 1054728 Sensor |
| 6010542 Kabel |
| P/N: 2031071, Type: Dol-2308-G05mjb2 |
| Dol-0612g20m075 Km0 2022549 Stecker Und Kabel |

| | |
|---|---|
| 1040982 | |
| Wt12lb550 | |
| 1052967 Pgt-10-S-Programmer | |
| Bef-Khz-Pt1 | |
| 6035499 | |
| 6039095 Wll180t- P434fiberoptikoptoelektronische Sensoren | |
| 202407 | |
| 1070871 Rzt7-03zws-Kw0 Magn.Cylinder Sens. Stellungsgeber Magnetische | |
| 6022009 | |
| 1045672 | |
| C2c-Sa03030a10000 | |
| 1049061 Sensor Lichtschanke Sick WI9- 3p2462 | |
| 6025036 | |
| LI3-Tb02 | |
| Dol-0804-G02m Kabel 2m Gerader Stecker M8 4 Pin | |
| 1074817 Dbs60e- Thfn01024inkrementelles Wegmess | |
| 1012720 Pl40a Reflektoren | |
| Mm12-60aps-Zck Sensor Mit Dos-1204-Wx | |
| 6051101 Ue410-Mu300s01safety-Unit | |
| Mlgs5-1450i812 Modular Light Grid | |
| 6007303-Dos-1204-W | |
| 2029215 | |
| 1059901 | |
| Dfs25a-Azaaz000s10 | |
| Dt35-B15251 Sensor | |
| Vfs 60 - 1024 - Ttl 4,5- 32v | Encoder VFS 60 - 1024 - TTL 4.5- 32V fully programmed and assembled with plug |
| 1036616 Pgt-08-S-Toolsprogrammierung Undkonfiguration | |

| |
|--|
| Dme3000-111p |
| Ag Wtb11-2p2461 1044442 |
| Elg3-1050p521 |
| 1019229 Wt34-B410 Photoelektrischen Schalter |
| 2058653 |
| 1012719 |
| Range-E50414 |
| 6027931 Lichtschanke Vse 18l-4p324 6027931 (Satz Vs187-0d314 + Ve18l- 4p324) |
| 6036919 Sensor |
| C4c-Sa18030a10000 - 1211509 |
| 1045093 |
| 6033181 Sensor |
| 6032868 |
| 1055038 Encoder |
| 1058215 Lichtschanke Grse18s-P2336 Photoelectric Switch |
| Ue10-3os4d0 Safety Relays Ue10-3ospart Number: 1028303 |
| 6027580 |
| 1036129 |
| Wl27-3p2451 |
| Wt36-R710 |
| 18sp1347 |
| 4036657 |
| 1059510 |
| 2066614 Bef-1shabpku4 Befestigungssatzset |
| 1022293 |
| 1015798 |
| Wt14-2p432so8 Sensick Sensor |
| 1037808 |

| | |
|--|------------------------------------|
| 1049070 Sensor Lichtschanke Sick WI9-2n131 | |
| 1016934 Wt24-2b440 | |
| P/N: 1056742 | |
| Btf13-P1hm3025 Endlosregler Mit Seilzug-Mechanismus Komplett | |
| 6050248 | |
| 6039751 Absolute Wegmessacs/Acm36 | |
| 6029282 Type Dsl-1205-G0m6c; Lead Number / Cross Section 5-Polig; Material Polyurethan | |
| 6010754 | |
| 1056180 | |
| 6036923 Ultraschallsensoren, Um30-213118 | |
| 6011050 Optischer Sensor Wt150-P460 | |
| 6043440 | |
| 1036992 | |
| 1019253 | |
| 1069503 Grte18s-P1362 | |
| Dos-1208-Ga | |
| Dx50, Dt50-P1113 | 1044369 Mid-range distance sensors |
| 1040763 Ime 12-04 Bpszocok | |
| Ime12-04bnszc0k | |
| Bef-Ah-Dme Halterung | |
| Wt34-R210 | |
| 1016629 Kt5w-2p1113 | |
| Kt8l-P3656 Sensor-Kontrast | |
| 1045651 | |
| 6020976 | |
| Dme Dme5000-211s08 Sensor | |
| 185220 | |
| 6036555 Leitungsdosetyp: Dol-1212-G 02 Ma S 01 | |
| 1034650 | |

| |
|---|
| 6052361 WI100-2p3439 |
| 1036722 |
| 1062253 |
| Dos-1205-G Stecker Female Connector |
| 1036907 Dfs60b-Tdpa10000 |
| Im12-02bps-Zc1 |
| WI12-3p2431 Sensor |
| 1062201 |
| 1055020 |
| 6025814 Induktiver Sensor Iq-15bpp-Kk1 |
| 1053007 |
| 1061394 |
| 6026564 Ws190I-D430 Through-Beams. Send. |
| 2041834 Kabel. M12/D-Sub, 2 M |
| 1030015 |
| 1026031 Sensor |
| Dme4000-111 |
| E33-1-Ar |
| WI170p420 |
| 7900013 Induktiver Sensor |
| 1019431 Sicherheits- Lichtschrankepns125-124 |
| 1036084 |
| P/N: 6037417, Type: Mvm-01m-2mc-Mklb |
| 6037668 Um30-215112 Stellungsgeberultraschall |
| Dol-1208-G20mac1 |
| 1037921 |
| 7020476 |
| 1214002 MIg05s-0895a10802 Lightgrid |
| 1041323 |
| 6037661 |

| |
|---|
| 1018045 Kt5w-Sensoren 2n1116kontrast |
| 1040766 |
| Dfs60e-Bdea01024 |
| Vt12t-2p430 Sensor |
| 1052952 |
| 6042005 |
| Drs60-C4a02048 |
| 1028097 |
| 7900007 |
| 5304819 |
| 4040006 |
| Lte090-351 |
| 6048391 |
| 1052591 |
| 6036106 |
| 1023546 S30a-6011ba Laserscannersicherheit |
| 1040954 |
| 1036749 |
| P/N: 1057250 |
| 1017860 W124-2b430 Optischer Sensor |
| Dme4000-112 |
| Dfs60b-Bdea00s26 |
| 1037013 |
| Wt250-P460 |
| 6026558 Reflexions-Lichtschanke Typ: WI 190I-P430 |
| P/N: 6037415, Type: Mvm-0m5-2mc-Mklb |
| 1040763 Sensor |
| Dme4000-122 |
| DI50-P1123 |
| P41f Reflektor |
| 2068148 |

| |
|---|
| 1082728 |
| 6013551 |
| 1037168 Inkrementaler Drehgeber |
| Rzt7-03zrs-Kw0 |
| M20z02550a121 |
| Dol-0612g7m5075km0 |
| P/N: 1033532, Type: L230-P580c2s00000 |
| 1012719 Reflektor PI20a |
| 6009990 Sensor Lichtschanke |
| C4000 C40s-0704ca010 |
| 1200124 |
| Wt34-V220 |
| 2073486 |
| 6036159 |
| 6024915 |
| 1063129 Sensor |
| 1058174 Sensor Lichtschanke. Typ: WI9I-3p2232 |
| 1036924 Encoder Df60b-Tepk1000 |
| 6051509 |
| PI100 5321625 Reflektor |
| 6026528 |
| 1040619 |
| 6049454 |
| 1040755 |
| Wt150p162 |
| 1017875 Lichtschanke Ws/We24-2b440 |
| 1038000 |
| 1023891 |
| 6010190 Sensor WI170-P430 |
| Dfs60b-Bhak02048 |
| A3m60b-S4pb013x13 Absolute Encoder |

| |
|---|
| 1038826 |
| 1047162 |
| 7900227 Sensor, Iq80-60npp-Kk0 |
| Wttl2l-B2538 Lichtschanke |
| 6024893 Sicherheitsrelais Ue43-2mfd2 |
| L28s-3d2431 |
| Wt42p431538 |
| 6033269 Ste-1208-G Stecker, St.Cab.Sh 8p. Connector |
| 1037384 |
| Lut1u-11331 |
| 1038826 |
| 6026224 Sensoren Optoelektronische Vs/Ve12-2p430 |
| 6048387 |
| P/N: 1057260 |
| P/N: 1054741 |
| 6012021 Vt18-204470s01sensor |
| 1025994 Lichtschanke |
| Dt60-P1115 |
| 1050529 Endlosregler |
| Wlg4s-3 Sensor |
| Bef-Ah-Dx100 Halterung Zur Positionierung |
| 1057075 |
| Ue402-A0010 |
| 1036075 |
| Wtb12-2p410 |
| 6009872 Dol-0804-G05m-Kabel M8, 4-X Polig, 5 M |
| Im12-04nps-Zuk |
| 1051484 Dfs60b-Thpm00s06 Incremental Encoder |
| 1028224 Cs810p1112 Sensoren Farbe |

| |
|---|
| 6036833 Sensor |
| 6020993 |
| 1036115 |
| 1044275 |
| 1047984 Lichtschanke |
| 1019254 |
| 5320565 |
| Wt27I-2f430 |
| 1084501 |
| P/N: 1069457 |
| Dfs60e-Beck01000 |
| DI100-11aa2101 |
| L28e-3p2431 |
| P/N: 6037422, Type: Mvm-3m5-2mc-Mklb |
| I16-Sa113 Notschalter |
| 1031558 Ars60-Absolute F1a00360wegmess |
| 1036752 |
| 1057772 |
| DoI-1205-W02mc (6025909) |
| 1036025 |
| 1090909 Dbs60e-B5epd1024 |
| 1035384 Dks40-E5I00200inkrementelles Wegmess |
| P/N: 1054143, Type: Vfs60b-Bhaj01024 |
| 1063175 Sensor Sensick WI14-2p431 |
| P/N: 1053525 |
| 2103523 |
| 2052248 |
| 1028232 Optischer Sensor Kt10w-P1115 |
| 1030014 |
| Sek37-Hfa0-S01 |

| |
|---|
| 1067980 |
| WI9-3p2230-1049059 |
| 1078888 Dfs60b-S4wa00050 Incremental Encoder |
| 1030001 Absolute Multi-Turn-Drehgeber |
| 6027522 |
| C45e-0103ag220 |
| 6052361 |
| 1028170 Sensor We4-3f3130 |
| 6 009 866 Kabel Dol-1204-G05m |
| WI27-3p2430 |
| 2029246 |
| 6034669 Ultraschallsensor Uc4-13341 |
| Dt500-A111 |
| Im18-05bpo-Zc1 Induktiver Sensor |
| Imf12-04bpcvc0s Induktiver Sensor |
| WI260-F270 |
| 1059760 |
| 1040968 Ime18-08bpszw2sinduktive Sensorenproximity |
| 1072798 |
| 7900099 Sensor, Im18-12npo-Zc1 |
| 1025911 Optischer Sensor WI18-3p430 |
| 1045655 |
| W100I-E2141 |
| 1098784 |
| 1067293 1067293 Csm-Wn11122psensoren Farbe |
| 1048418 DI50-P2225 Distanz Sensoroptoelektronnyj |
| 1213213 Sicherheits-Lichtschranke C2c-Ea12030a10000 |
| Cm30-25npp-Ec1 |
| 6025905 |

| |
|---|
| 6049679 |
| WI9-2p631 |
| 1213203 C2c-Licht Ea04530a10000schleier Sicherheit |
| P/N: 1053485 |
| Dme4000-315s02 |
| 6022701 Ws160-G440 Through- Beamsens. |
| 5308076 Linse |
| Ad-Ssig-Pa |
| 6032637 |
| 2029204 |
| 7900600 |
| 1025380 Rzt1 |
| 1034094 Skm36-Hfa0-K02-Sensor- Feedback-System (Encoder) |
| 6037663 |
| 1036111 |
| 7902124 |
| 6036158 Kabel |
| 1034318 Btf13-C1hm0525seilzug-Encoder |
| 1207923 |
| Ufn3-70p415 |
| 1036488 |
| 1018256 Sensor |
| 1053483 |
| 1037456 |
| 6025903 |
| 6036927 Induktiver Sensor |
| Strl Xdaf0ac5 Opto Sensor |
| 1041290 Bar Code Scannersclv650-0000 |
| 1218660 |
| L230-P58000000001 |

| |
|---|
| 1092136 |
| 6008900 |
| Wt100-2p3439 |
| 6043834 |
| 1064694 |
| 1041390 |
| 7102651 Hd32-Do124e0512inkrementaler Drehgeber |
| 5315124 |
| Wtb11-2p2461 Sensor Photoelectric Sensors |
| 1018593 |
| 6049579 |
| 6027448 |
| 6052386 Sensor |
| 1055909 Encoder Dfs60e-Bhek01024 |
| 1066557 |
| 5325915 |
| Im12-04bps-Zc1 |
| Mht15-P2319 |
| 1057324 Adapter-Schnittstelle |
| 1041456 |
| M2000 Standard |
| 1027790 |
| 1036767 Dfs60b-Bdpa10000inkrementaler Encoder |
| Dme4000-113 |
| Mics3-Acaz90pz1p01 |
| Ref-Irf2000r25 Reflektierendes Band |
| 1059631 Sensor Lichtschranke Gl6-N4211 (4pin, M8) |
| 1035483 |
| 6012643 |
| 5319981 Ref-Plus-R50 |

| |
|--|
| 6058494 |
| 6011050 Wt150-P460sensor |
| 1025624 |
| 1046537 |
| 6030709 Photoelectric Sensor |
| We4s-3p2430v Sensor |
| 2011435 |
| WI100-N1439 |
| 1036616 |
| 5315124 P250h Reflektoren |
| 1036105 |
| P/N: 1056153 |
| 6035460 |
| 1072489 |
| 1018586 Kontrastsensoren , Kt5w-2p1216 |
| 6058157 Sensor |
| 6027430 |
| 1067295 |
| 5305850 |
| 1026538 Sensor Kontrastierenden Markierungen |
| 1081581 |
| 1019250 WI34-R240-Photovoltaiksensor |
| Ue403 Ue403-A0930 1026287 Sicherheitsrelais |
| 1025994 Sensor Lichtschranke Sick Wtb27-3p2411 |
| 7902077 Steckverbinder Zick Dos-0803-G |
| 1027777 |
| PI240dg Reflektor |
| Wt18-3p410 |
| 6041425 |
| 6036645, Lot 1336905018f Sensor Typ |

| |
|---|
| Od2-P250w150 |
| 1057651 |
| 1026287 Ue403-A0930, Ip65, |
| 6020223 |
| 6024790 |
| 1036723 |
| 6036920 Sensor Um30-215113 |
| Mzt8-03vps-Kp0 |
| 5306091 |
| 1040739 |
| 1041411 Wtb12-3p2431 Sensor Die Bestimmungen Optoelektronnyj |
| 1052448 |
| 6028357 Dos-1204-Gn Steckdose(Einbaufertige) |
| Vse1802p42437 Sensor Lichtschanke |
| Dos-0804-G |
| 6041680 |
| 6052625 |
| 6041377 Drucksensoren Pbs- Rb016sgess0bma0z |
| 6020219 |
| 1019239 Lichtschanke Wt34-R240 |
| 1030038 |
| 2095895 |
| 1037785 Typ: Vfs60a-Tgpz0- S03motorfeedback |
| 1038186 |
| 1044508 Sensor Sensick Wl14-2p432so8 Bestell. - Nr. 1 045 104 |
| Vfs60e-Bdez0-S01 |
| Wtf12-3p2431 Sensor |
| Im30-40nps-Zc1 |
| 1049078 |

| |
|---|
| 1041411 Sensor Wtb12-3p2431 |
| 6036384 |
| P/N: 1053719 |
| Wll170-2p430 |
| C4c-Sa04510a10000 |
| 1044508 |
| Kt5w-2p1113 Optischer Sensor |
| 6048416 Ultraschallsensortyp: Um18-212161101 |
| Mra-F130-405d2 Encoder Accessory 6029789 |
| 6052614 Kabel |
| 1045650 |
| 1207236 |
| 1018961 Sensor |
| Ime08-05npszt0ss01 Induktiver Sensor |
| 6007302 Anschluss Typ Dos-1204-G, M12, 4-Polig |
| 4 019 634 Band Reflektierend Ref-Dg-K |
| 6049678 Ufn3-Ultraschall 70b413schlitzsensor |
| 1040722 |
| 1030009 Endlosregler |
| 1016131 Lichtschranke Wt12-2p420 |
| 1047616 Dt50-P1124 Distancesensor Abstandssensor |
| 6009382 Steckverbinder Dol-1204-G02m |
| 1029949 |
| 6037322 |
| 6036830 Wfl15-60b416 |
| 1008836 |
| P/N: 1055979 |
| 1030013 Atm60-Absolute P4h13x13multi-Turn-Drehgeber |

| |
|--|
| 1040748 Ime12-04npszcos |
| 6042724 Drucksensoren Pbt-Rb010sgtsenama0z |
| 2039248 |
| 1064697 |
| 1049054 WI9-3p1162 |
| 1200127 |
| 6029832 Ultraschallsensoren , Uc12-12231 |
| S30a-7011ca |
| 1050615 |
| Wtb27-3p2411 |
| 2021463 |
| 1040966 Ime18-08bpszc0s Induktiver Stellungsgeber |
| 2033560 |
| WI24-2b230s02 Der Optische Sensor WI24/2r240+pl80a |
| 1036096 |
| 2045642 |
| 6010186 WI170-P420-Positions-Sensoroptoelektronnyj |
| 1019230 |
| 6053253 Sensor |
| 1036746 |
| 1028224 |
| 6020977 |
| 1019291 |
| 1022202 |
| T4000-1rba01 |
| 1016591 |
| Iq80-50bpp-Kc0 Induktiver Sensor |
| 6013693 Stellungsgeber Vs/Ve18-4p3212 Through-Beam |

| |
|---|
| 1061790 Anschlusseinheit |
| 6025908 |
| 5310252 |
| C40e 0603cb010 |
| Rtz1-03zrs-Kp0 |
| 2048440 Connectoh M23,12-Pin:Typ Dsl-3d08-G0m5ac2 |
| 1041114 |
| Wtb140-P430 |
| 1024086 |
| Wl140-2p330-10490559 |
| Wtb11-2p2431 Sensor |
| 2050022 |
| 1046534 |
| 2095838 |
| 1047118 |
| 2060626 |
| 6020320 |
| 1037661 Encoder Afm60b-S4aa032768 |
| Wtb27-3s1541 |
| 6024910 |
| 6029832 Sensor Uc12-12231 |
| Dfs60e-Bdec01250 |
| Dt50 P2113 |
| 1059504 |
| 6044336 |
| 1200115 |
| Im30-20nps-Zc1 Sensor |
| 2029202 |
| 1052967 |
| Ime12-04bpszcok 1040763 |
| Iq10-03bpskw2s |

| |
|---|
| 4031053 |
| 2032127 |
| 7902078 Stecker Dol-1612-5m-3 |
| Wf2-40b410 |
| 1003865 Pl80a Reflektor, 100% Kunststoff |
| 2071327 |
| 1041422 Wtb12- 3p2411lichtschrankeschalter |
| Im08-2n5ns-Zc1 |
| 1019232 |
| 1040734 |
| P/N: 1069902, Type: Vfs60b-Tbaj65536 |
| 1025911 |
| 1017047 Sensor |
| Gtb6-N1212 |
| Dfs60b-Bhea08192 |
| 1026820 S30b 2011ba |
| 1207250 |
| Gte10-P4211 Sensor |
| Wl150-P122 |
| Wll180t-L432 |
| Srm50-Hza0-S50 |
| Mba220zka1n1-A00150-D-XXXXXXX |
| 1008562 |
| 1036616 Pgt-08-S-Tools Programmier-Und Konfigurationssoftware |
| 1058882 Sensor |
| 6028440 Gabelsensoren, Wf50-60b410 |
| 6012062 |
| 6049453 |
| Wl8g-P2231s01 |
| 6044699 |
| |

| |
|--|
| 7900085 Sensor |
| WI9 2p431 |
| 1041458 |
| WI45-R260 |
| 1019239 |
| VI 18-4p3240 |
| 1047616 Distanzsensor Dt50-P1124 |
| 1085344 Sicherheitsrelais |
| P/N: 6037421, Type: Mvm-03m-2mc-Mklb |
| 1200128 |
| 1052107 |
| 6044892 Ste-1208-Ga01 Coonec.,St. Shield M12-8p Kabel Stecker |
| 1041422 |
| 2027171 |
| Sfm60-Hmkt4k02 |
| Fx0-Gent00000 |
| 5315172 Reflektor P25 |
| 1211470 |
| Dbs36e-S3ek00100 Inkrementelles Wegmess |
| 1043783 |
| 1046010 Kt6w-Sensor 2n5116kontrastierenden Markierungen |
| Ws/We34-B430 |
| Ste-0804-G |
| 106544 1803-0094 Endlosregler Dbs26e- S3ek01000 |
| P/N: 2031072, Type: Dol-2308-G10mjb2 |
| Dos-1612-W |
| 1034893 |
| 6013258 |
| 1045652 |
| 1002314 |

| |
|---|
| Wi 130t-P340 Adapter Sensor |
| Dol-0803-W02mc |
| 2059368 |
| 1213209 C2c-Ea09030a10000 Lightcurtain Receiver Licht Schleier Sicherheit |
| 6032326 |
| 2039302 |
| 2_1045104 Sensor Sensick Wt14-2p432so8 |
| Srm50-Hfz0-S22 |
| 1051710 |
| We280-2r4331 |
| Pls109-317 |
| Ch12dob5c |
| Wl12-2b560s37 |
| 1070872 Sensor Rzt7-03zws-Kwb |
| 1027744 |
| 6010190 |
| Srs50-Ffa0-S21 |
| Bef-Khs-H01 |
| 6058496 |
| 1036150 |
| 1041030 |
| 6012147 |
| 5321097 |
| 1018256 |
| 6044699 Sensor |
| 1028934 Sicherheits-Scanner |
| 6053043 |
| 1016629 Sensor |
| Wfl 80-60b416 Sensor |
| 2073485 |
| 1047405 |

| |
|--|
| 1204146 |
| 6024915 Relais Ue48 Sicherheits-2os2d2 / Safety Relay |
| 1036102 |
| VI180-2p-32436 |
| 1018252 |
| Wte11-2p2432 |
| S30a4011da |
| 1052109 |
| 1059752 |
| 1034650 Dks40-E5j00100inkrementelles Wegmess |
| 1040791 |
| 7902077 Rosette Dos-0803-G |
| 6054286 |
| Dfs60b-Teek00100 Inkrementaler Drehgeber |
| 6011038 |
| 4019634 Reflektoren |
| 1037632 |
| Wtb4s-3n1361 |
| Kt10w-P1115 |
| Wtb26i-34161120a00 Kompakt- Lichtschranken |
| 1037112 |
| Dme4000-315 |
| 6022758 Optischer Sensor |
| 6028627 |
| 5312983 |
| 6027519 |
| Wt160-F420 |
| 1041438 Stellungsgeber Wl12-2p730 |
| 1044369 |

| | |
|--|---|
| 2044417 | |
| 1018587 | |
| 6027529 Cable W. Shield . 4*2*0,15 5d8 Leiter Mit Connectors | |
| 1036655 | |
| 2027721 | |
| Wf15-40b410 | |
| Skm36-Hfa0-S05 | previous material number: 6CK-100-200-011 SKM36-HFA0-S05 MOTOR FEEDBACK HIPERFACE 128 sin / cos periods RoHS compliant according to EU Directive 2005/95 (from Date-Code 08/32) Country of origin: DE; Stat. Product number: 90318020 EC dual use / export list number: non; US ECCN: non |
| C40s-0603da040 | |
| 1036098 | |
| 1019244 | |
| 6029514 Sensor Lichtschanke | |
| M40e-034010rr0 | |
| 4043524 | |
| 1042059 | |
| 6033269 Ste-1208-G | |
| 6029215 | |
| WI 130I-32 Sensor | |
| 1040785 Induktiver Sensor | |
| 2015229 | |
| 2024282 | |
| 6044728 Optischer Sensor | |
| 6026006 | |
| 1036013 | |
| Wtb27-3p2411s18 Sensor | |
| 2038993 | |
| WI24-2v530 | |
| Ds50-P1122 | |
| 6011050 Sensor Typ Wt150-P460 (6 011 050) | |
| 1051017 Encoder A3m60b-Bhpb013x13 | |

| |
|---|
| 1211501 |
| 2071778 |
| P/N: 7102164, Type: Dol-Ms10-G20mma3 |
| 6037665 Sensorum30-212112 |
| 6021156 |
| Wt18-2p610 |
| LI3-Dk63z Sensor |
| 6012828 Vtf18-3f1240lichtschränke |
| Ws/We140-2p132 (6024788) Photoelectric Sensor Through-Beam |
| 1029973 |
| 6035497 VI18-4p2240v |
| 1018670 |
| 1064578 Wt2s-P031s13 |
| 1058164 Sensor |
| P/N: 1074221, Type: Vfs60e-Tgak02048 |
| 6013191 Optischer Sensor |
| 6043919 Wfs3-40p415 |
| 1074367 |
| 6048390 |
| Bef-Wn-Dx35 |
| 1059039 |
| WII190t |
| Dfs60b-S4ca02048 |
| Wt23I-F430 |
| 2031086 Dol-0j08-G0m2xb 6, Anschlusskabel |
| 1026031 |
| Dme4000-117 |
| Bef-Kp-W45 (2011435) |
| 1036020 |
| WI250-P430 |

| |
|--|
| Ws45-U260 |
| Gerader Stecker F¼r WII12 |
| 1218237 Licht Schleier Mlg10n-0590n10501 |
| Mm12-60a Ps-Zck Sensor |
| 7900015 Induktiver Sensor |
| 1037685 Sensor |
| 1036078 |
| Wt23lf430 |
| 6025908 Stecker Dol-1205-G10mc |
| 1213200 C2c-Licht Sa03030a10000schleier Sicherheit |
| 6022011 |
| Dt50-P1113 |
| 1050635 |
| 1055503 |
| 1051757 |
| 2062284 |
| 1019246 |
| 1058225 |
| 1215667 |
| 1071843 |
| C2c-Sa06030a10000 |
| Sks36-Hfa0-S01 |
| 1064573 |
| Lichtsensor Wt16p112 |
| 5318680 P55 Reflector |
| 6033207 Lichtschrankewtb8-P2131 |
| 2031079 Bef-Mw-Skx36 |
| 1044442 Lichtschrankewtb11-2p2461 |
| Yg2a14-050vb3xleax |
| WI 12I-2b531 |
| 1023546 |

| |
|---|
| 6041809 Sensor |
| 1018677 C40s-Licht 1804ca010schleier Sicherheit |
| P/N: 1054498 |
| Dbs36e-S3em00500 |
| Kt5w-2p21160 |
| 1042256 Cdb620-001- Kommunikationsmodul |
| 2056306 |
| P/N: 1067934, Type: Ttk50-Hxm0k02 |
| 1040886 |
| Vte18-4p4240 |
| We260-F470 |
| 6033188 Sensor |
| 6013950 Vs18-0d3640 Through-Beam Sens |
| S30a-6011da |
| 6028428 Wf2-40b410 |
| Srm50-Hwz0-S01 |
| 5311138 |
| 6032451 Dol-1208-G20mah1cab.,Fem.St 20m0 M12-8pleiter |
| 1045502 Sensor Lichtschanke ZI1-F2421 |
| 1040288 |
| 2062909 |
| 1042292 C40s-S113 Lightcurtain |
| 1025511 |
| Wt170-P132 |
| Wt2s-P231 |
| 5321625 Pl100 Reflektoren |
| 1036097 |
| Wl12g-P510s10 |
| 1044163 Der Optische Sensor Sickwtb27- 3p2461 |

| |
|--|
| P/N: 1053483 |
| Aq661-466111000000 |
| Wt27p6116910 |
| 1052684 |
| 5308446 |
| 6009383 Connector, M12, 4-Pin |
| C4c-Sa12030a10000 |
| 6013263 |
| 6049969 |
| 2015236 Kabelfiber Optic Lm37-450 |
| 6020422 |
| Dme4000-222 |
| 7900280 |
| Dme4000-219 |
| 6029515 Sensor Lichtschanke |
| 1018044 Sensor Sensick Kt5w-2p 1116 |
| 1037419 Dfs60e-Teek01024 Incremental Encoder |
| Wl273p2451 |
| 1204145 |
| Wl160-E440 |
| 1018587 Sensor Kt5w-2p1126 |
| Wtb 12-3p2431 Sensor |
| 6007303 |
| 2067762 |
| 1062460 |
| Wl24-2v530s04 |
| 1058126 Sensor |
| 1052596 |
| Rt-P2231 |
| 2096235 |
| Dme4000-317 |

| |
|---|
| 1015798 Der Optische Sensor Typ:Wlg12-P537 |
| 1018575 |
| Im12-06bns-Zc1 |
| 1062916 |
| 6024893 |
| 6026568 We190I-P430 Through-Beams. Rcvr |
| P/N: 1054485 |
| 1049045 Sensor Lichtschanke Wtb9-3p2211 |
| Ad-Atm60-Sr2dn - Bus-Adapter |
| Dme4000-224 |
| Dt50-P2113 |
| 1026245 |
| 1040759 Sensor |
| 2046458 |
| 1036114 |
| 1073212 Kontaktloser Sicherheitsschalter |
| 1047402 Ds50-P1112 Distanz Sensor |
| 1017885 Der Optische Sensor Sick Wt24-2b420 Dc 10...30v |
| 2029205 Kabel |
| I12s-B213 Sicherheits-Positionsschalter |
| 1023668 |
| 2048370 |
| 1072635 |
| 6036722 |
| 6012831 |
| 1022949 |
| 6032639 |
| 5322723 |
| 6036351 |

| |
|--|
| 6052386 Miniatur-Lichtschraken, WI100-2p4429 |
| 10556550 Endlosregler |
| 2076230 Spz-58z-010-P Spannzangen |
| 1056222 Dfs60e-Teek00100, Inkrementelles Wegmess |
| 7042400 |
| 6044998 |
| Srm50-Hfao-K21 |
| Iq08-04npoktos Proximity Sensor |
| 1038238 |
| 207654 Dol-127sg15vt25rv0 Starthilfekabel |
| 1062400 Encoder Dfs60b-Beec01024 |
| 2033613 |
| 1019243 |
| 6026216 Lichtschranketyp:Vt12t-2p430 |
| 1 026 822 |
| 2096237 |
| ?T6w-2p5116 1046013 |
| 1066284 Dfs60b-S4em01800 Incremental Encoder |
| 6034482 Ue410-Mm3-Controllersicherheit |
| 6053548 Ultraschallsensor Um12-1192261 |
| 6030709 Sensor Lichtschraken. Typ: WI100I-F2131 |
| C40s-0901aa030 - 1022204 |
| 1037366 |
| Vt180p142 |
| 1029846 Sensor Mz2q-Ftzps-Kp0 |
| 6036917 Ultraschallsensorum30-212113 |
| 1213208 C2c-Sa09030a10000 Lightcurtain Transm. Licht Schleier Sicherheit |
| 6009720 Dos-1205-W Stecker Des Kabelsm12 5-Poligen |

| |
|---|
| Wt24-2b440 |
| 2024489 |
| 6037782 Photoelectric Converter Dc10-30v |
| Clv630-6120 Barcode-Scanner |
| Dme4000-324 |
| WI260-R270 |
| Dme4000-217 |
| 6036630 |
| 2023335 Modular Light Gridmlge5-1450i812 |
| 6011032 Ws/We150-P430 Through-Beam Sens. Sensordie Bestimmungen Optoelektronnyj |
| 1036486 |
| 1040783 |
| 1023009 |
| WII260-F440 |
| 1052684 Abstandssensor DI 100-21 Aa2101 |
| 1055909 Endlosregler |
| Wtt12I-B2538 |
| 1041030 Sensor |
| S3000 51280359 |
| S30b-2011ca |
| L27e-3p2450 |
| 7074074 Der Optische Sensor Gre18-P2412 |
| 1040966 |
| Kt5w-2p1116 1018044 Sensor Q=pnp |
| 1071021 |
| 1072763 |
| P/N: 1055020 |
| 1036733 |
| Im18-12nps-Zc1 |

| |
|---|
| 1036023 |
| 1072687 |
| 2027649 |
| 1036759 Encoder Dfs60b-S1pm10000 (Welle 6 Mm.) |
| 1072560 |
| 1044442 |
| Wtb9-3p1161 |
| 1072555 |
| 1040933 |
| Connector |
| 1030024 Atm60-C4h13x13 Absolute Multi- Turn-Drehgeber |
| 1042084 |
| Um30-214111 Ultraschallsensor |
| 6052373 Lichtschranke Sick Wt100- 2p3439 |
| 1078098 |
| 2095733 Verbindungskabel Mit Stecker |
| Vte 183f4712 Optoelektronische Sensoren |
| 1028106 |
| 1052446 Gse6-P4111 |
| Rt-P3231 |
| Mlg1-0290a412 |
| 6032553 |
| 1086821 |
| 6048416 Ultraschallsensor |
| 1036080 |
| P/N: 1053821 |
| P/N: 1037434, Type: Ttk70-Hxa0-K02 |
| Pm3s11-00330030 |
| 1036026 |
| 2014458 |

| |
|--|
| Dks40-E5l00200 Inkrementaler Drehgeber |
| 7902923 |
| 1052593 |
| 5308082 |
| 1059644 Optischer Sensor |
| 1200150 |
| Wl24-2b440 |
| 2039002 |
| 1061012 |
| 1028099 Wtb4-Optische 3p2161sensor |
| 7902077 |
| Hd32-Do124e0512 Encoder |
| Kd-Lo9n-12111 |
| 1054051 |
| Afs60a-S4nb262144 Wandler Ecken Bewegungen |
| Dfs60e-Teek01000 Dfs60e-Teek01000 |
| 1041322 |
| 2029227 - Bus-Adapterad-Atm60-Sr2dn |
| 6027537 |
| Optischer Sensor |
| 1036017 |
| 6044336 Drucksensor Pbs- Cb2x5g1ssnama0z |
| 6032730 Kabel 5m Sick Dsl-0803-G05nc |
| I17 S?213 |
| Mm12-90aps-200 |
| 1026518 Distanzsensortyp: Dt 500-A 212 |
| 6041816 |
| Bef-2smgeaku4 2030510 Befestigungssystem |
| 1059503 |
| 6024915 Sicherheitsrelais Sick Ue48- |

| |
|--|
| 2os2d2 |
| Wtb27-3r2611 |
| 1030013 Absoluter Drehgebertyp: Atm 60-P 4 H 13 X 13 |
| 1071850 Induktiver Sensor |
| 6010182 |
| Dol-1204-G05m |
| 1051022 |
| 6007302 |
| 1037091 |
| Df S60b-S4 Cl01250 |
| Dfs-60b-S4pc10000 |
| 1042293 |
| 6037661 Sensor Um30-212111 |
| 1059522 WI12I-2b530s06 |
| 1070871 |
| Rtz1-03zrs-Kpo |
| Re11-Sa05 |
| P/N: 1070720, Type: Vfs60e-Bdcj01024 |
| Wtv4-3p3441s38 |
| WI24b4301 (01011463) |
| 1019234 |
| Bef-2smmeaku4 |
| Wse9-3p3430 Optischer Sensor |
| 2017038 |
| 1213184 C2c-Licht Ea03030a10000schleier Sicherheit |
| 6028357 Connector M12 Sick Dos-1204-Gn |
| 1025887 |
| 6025955 |
| 2045339 |
| 6029514 WI170- 2p430fiberoptikoptoelektronische Sensoren |

| |
|--|
| 1079384 |
| 1027982 Stellungsgeber WI27-3p2431 |
| A3m60-S4pb13x13 Absoluter Drehgeber |
| Wtb26i-21161120a00 |
| 1041457 WI12g-3o2431 |
| LI3-Tk75 |
| Wtb12-3p2411 |
| 1041459 |
| 6041751 |
| WI11g-2b2531 |
| Cq4-08epsku |
| Tct-1abzz1006mz Temperatursensor |
| 4063333 |
| 1003546 Reflektor PI22-1 |
| 5310008 |
| 6037322 Ste-0803-G Stecker (Ready-To - Montage) |
| Ue10-2fg |
| M20s-03140a122 Paar (Links Und Rechts) |
| 1045095 |
| Im30-10bus-Zu0 Induktiver Sensor |
| Atm90-Axa12x12 |
| 6020977 Sensor Lichtschanke |
| 1026052 Optische Sensor Wt14-2p422 |
| 1040406 Distanz-Sensor Dt20-P244b (Dt20-Hi) 100-300mm/Dc24v/4-20ma/Pnp |
| C45s-0103aa220 |
| Bef-Ah-Dx50 |
| 1094835 |
| 1038032 Incremental Encoder, 0-5v Ttl (Rs 422), 4096 Rrp, Solid Shaft 6mm, Conne |
| 6033950 Sensor |

| |
|--|
| 1204162 |
| 6052368 Sensor |
| 6048397 |
| 1052594 |
| Wtb27-3 |
| Dme4000-215 |
| Ue410-Mu3t5 |
| Wlq4s-3p3432v |
| 6032869 |
| P/N: 1059265, Type: Vfs60b-Bbaj01024 |
| WI27-2f440 |
| 1040625 |
| 4036250 |
| 1036086 |
| 6048399 |
| 6027522 Im30-40nps-Zc1induktive Sensorenproximity |
| 1052453 |
| 6029832 Sensor |
| 1019236 |
| 2013942 |
| Um18-217161101 Ultraschallsensoren, Um18-217161101 |
| Atm60-A4n12x12 |
| 6053788 |
| 1019229 Sensor Wt34-B410, |
| Gl6-P1111 |
| 1034892 Abstandssensor |
| 6034941 |
| 6036919 |
| Dol-1205-G02m |
| Bks5208pu05 |
| 6009872 |

| |
|--|
| L27s-3d2450 |
| 6048403 |
| 6024908 |
| 6022758 Ws/We160-F440 |
| 6027422 |
| 1054198 |
| 1031548+2029222 |
| P/N: 1078859, Type: Vfs60e-Bgek01024 |
| 1041050 |
| 2096234 |
| Dks40-A5j01024 |
| Wt45-P260s01 |
| 1054706 Sensor |
| 6049458 |
| 5309981 |
| Ref-Plus-R50 Reflektierendes Band |
| 6006821 |
| Mlg2-0880f511 |
| 6013893 Ve18-4p3640 |
| 6026625 |
| 1036643 |
| 1053075 |
| Ime18-08bpozco0s Induktiver Schalter |
| Wt24-2b210 |
| 5321870 |
| Cs81-P1112 |
| Dn400 |
| ?4?-??03030?10000 |
| 1036787 Sensor Dfs60b-Bhpk10000 |
| Wp12-2p730 |
| Dgs60-Aza0-S03 |

| |
|---|
| 2071259 |
| Mlg1-0290f521 |
| 1018040 Kontrasttastertyp: Kt 5 G-2 P 1411 |
| 1063129 |
| 1040696 |
| 1053016 Sensor |
| 1017885 Foto-Sensor Wt24-2b420 |
| Im08-02bpo-Zt1 Inductive Sensor Sick |
| 1017046 Sensor |
| 6052368 Ws/We100-Sensor 2p4439die Bestimmungen Optoelektronnyj |
| 2046172 |
| Bef-Khz-Rt1-63 |
| 5308843 Reflektor |
| 1036748 |
| 6035490 Vte18-4n4240v P. Prox. Sens. Energ. Sensorbestimmungen |
| 1018663 |
| Clv620-1000 |
| 2029178 |
| 1044163 |
| Dol-0612g20m075km0 2022549 Stecker Und Kabel |
| 6041818 |
| 7902078 Dos-0803-W Steckdose (Ready- To -Montage) |
| 1040733 |
| 1075843 |
| 1032665 |
| 6029280 Type: Dsl-1205g01mc; Lead Number / Cross Section: 5-Pole; Length: 1 M |
| 1058181 Wse9l-3p2437photoelectric Switchstellungsgeberoptoelektronnyj |
| 6026220 Optischer Sensor |

| |
|--|
| 2029213 |
| 1028934 Sicherheits-Scanners30a-4011ba |
| 6025900 |
| Wl14p430 1012925 Sensor |
| Ad-Atm60-Ka3pr |
| 6027519 Sensor Im18-20nps-Zc1 |
| 1332 0254 Sensor 1332 0254 2023797 |
| 1213212 Licht Schleier Sicherheitc2c-Sa12030a10000 |
| 6024917 |
| Rt-P2233 Optischer Sensor |
| Sks36-Hfa0-K02 Encoder |
| 1041150 |
| In30-E0407k |
| 1015397 Lut3-620 Sensorenfluoreszierende Etiketten |
| 6026146 |
| 6052616 |
| Ws4-3p2130 |
| 1043916 |
| Drs60-D4a01024 Endlosregler |
| 1028541 |
| Wt34-V210 |
| Ars60-A4a08192 Endlosregler |
| 1041977 Clv630-6120 Barcodecodes |
| 2095836 Stecker Mit Kabel Yi2a14-020ub3xleax |
| 5304549 Reflektor C110a |
| C2mt-06034bbc03fb0 |
| 1028934 |
| 6012822 Optischer Sensor |
| 192290625 |
| 1018678 C40e-Licht 1804ca010schleier |

| |
|--|
| Sicherheit |
| Mzc1-4v3ps-Kp0 |
| 1028232 Kontrastsensoren , Kt10w-2p1115 |
| 6 022 009 Kabel Dol-0803-W05m |
| 5313019 Sensorll3-Dk06 |
| 1058999 |
| Clv450-0010 |
| 6051780 |
| 1000132 Reflektor |
| 1023546 Sicherheits-Scanner S30a-6011ba |
| 1049063 Sensor Lichtschanke |
| 1059521 Der Optische Sensor. Typ: Wl12l-2b530s05 |
| P/N: 1054619 |
| 1301068 |
| Wt18-3n430 |
| 2051612 Befestigungssystem |
| 6044724 |
| 1037419 Encoder Dfs60e-Teek01024 |
| 1036459 |
| 6027529 |
| 2013824 |
| 1027769 Optischer Sensor |
| 1000238 |
| Mzt1-03vps-Kra |
| 1058168 |
| 6025871 |
| 1200131 |
| 1036458 |
| 6039097 |
| 6043208 Um30-213113s07ultraschall-Sensor |

| |
|---|
| 6037824 |
| 1058211 Sensor |
| 1015852 Lichtschanke Mit Reflektorprk 96m/P-1400-22 |
| 1073406 Mzt6-03vps-Kpx |
| 1050618 |
| Vs18I-0d314 |
| 5 305 535 Lichtschanke Wiv-V 180-T 400 |
| 1075638 |
| 1057656 |
| Ds500-P511 |
| 1032954 |
| P/N: 1057791, Type: Ttk50-Hxj0k02 |
| 6035622 |
| 2022545 |
| 1036106 |
| Mcs 100 6023093 |
| 6027531 |
| 104062 Stand |
| 1091393 |
| Wtb26i-1h161120a00 Kompakt- Lichtschraken |
| Clv610-C1000 |
| 1059559 Sensor |
| 1078111 |
| 6027538 |
| Pl240dg |
| Dme4000-127 |
| Wl23-2p2432s02 |
| 1036558 |
| 1036016 |
| 6030589 |

| |
|---|
| 1060529 |
| 1040072 Sensor Magnetisch Mm18-70aps-Zck |
| 1036755 |
| 6063340 |
| 6020688 WI150-P420-Photovoltaik Sensor |
| 6025893 Sensor-Kabel Dol-0803-W10mc |
| 1047782 |
| WI9-2p330s10 |
| P250 |
| 1059035 Afm60a-Bdnb018x12absolute Wegmess |
| 1204161 |
| 1085742 |
| 6036155 |
| We8-P2231v Sensor |
| 2015625 |
| 1041429 |
| Wt18-3p420s12 |
| Nt6-03082 |
| 4003353 |
| Bef-Slit Mask-G |
| 6036386 |
| Die Induktiven Sensoren Ime 12-04bpsc0s |
| 6026555 WI190I-N132 |
| 1028097 Wtb4-3p3161lichtschrinke |
| 1040975 |
| 6043313 |
| 2025241 |
| 2029191 |
| Vtf18-4p1340 |
| 6029515 |
| |

| |
|--|
| 1017853 |
| 5308071 |
| 1047578 |
| 6063335 |
| Dos-1208-Ga01 |
| 6020977 WI260-F470 Fotosensor |
| 5304549 |
| 1200065 Sperre Luminous M40e-025003rb0 |
| 1018045 Optischer Sensor |
| 1047056 |
| 6032451 Kabel |
| Mlg1-0140f521 |
| 6052365 |
| 1040736 Inductive Sensorime 12-02 Bpoz0s |
| Bef-Dkh-W12 |
| 1037555 Dfs60e-S1am01024inkrementelles Wegmess |
| 1053835 |
| 1041029 |
| 5308050 |
| 7901784 Magnet |
| 1012720 |
| 6024915 Ue48-Relais 2os2d2sicherheit |
| WI12g-3v2572 |
| 6034595 |
| 2065223 |
| 1069009 Incremental Encodertyp: Dfs60b-Bdca00s30 |
| 1204936 |
| We160-F132 |
| We272p630 (1007914) |
| |

| |
|---|
| 1026244 |
| Sel37-Hfa0-S01 |
| 1045089 Lichtschanke W114-2p430s07 |
| 1026822 |
| Im18-05bds-Zw1 |
| 1076095 |
| Mpa-179thtpo |
| P/N: 1055021 |
| 1040981 |
| 6026473 Induktiver Sensor Iq80-50bpp-Kc0 |
| 1034892 |
| 6028431 Optischer Sensor. Wf30-40b410 |
| Dsl-8d04g02m025km1 |
| 1211469 |
| Wtb27-3f2611 |
| 6007092 |
| Kt5w-2p1113 Sensor-Kontrast Q=png |
| 6033208 |
| 6032653 |
| 1037077 Endlosregler Srs50-Hqv0-K21 |
| 5308843 Reflektor P250f |
| 1046446 |
| 1044369 Dt50-P1113sensor |
| 1072254 Pgt-10-Pro Toolsprogrammierung Undkonfiguration |
| 6041823 |
| Zt-1200n |
| 1026287 |
| 1071553 |
| 1036092 |
| P/N: 1068879, Type: Ttk70-Hxi0-K02 |
| 6024909 |

| |
|--|
| 6039745 Bcg05-K1km01pp Drehgeber Mit Seilzug Trommel |
| 5308078 |
| Wl9-2n131 |
| 6035225 |
| 1064578 |
| 6039095 |
| 1003865 |
| S30a 7011ea |
| Dos-1205-Ga |
| 1025911 Optische Sensor Wl18-3p430 |
| Dfs60b-S1aa04096 |
| 6043358 Dos-1208-Wa-Steckverbinder M12-8p |
| Vl180-2p42436 Sensor Lichtschanke |
| Dt250 P2113 |
| 1217875 |
| 1028232 |
| ??-Sa09030a10000 |
| Im18-20nps-Zc1 |
| Idm161-300s Lcb-Reading-Scanner |
| 1019229 |
| Dos-1205-W |
| Pe1cne2g |
| 1036022 |
| 6025931 Dsl-1205-G02mc Kabelverbindender |
| 602097 |
| Dl100-21aa2101 Sensor Distanz |
| Wtb27-3p2483 |
| Nav300-2232 |
| Gse6-P1212 Single-Pass-Sensor |
| 6013407 |

| |
|---|
| 6041795 |
| 5310028 |
| 2019506 Type: Bef-1shabazn4 |
| 1038155 Inkremental-Encoder, Dfs60b-Bhek04096 |
| 1066552 Fotosensor Grte18-P246 |
| Wtb27-3p2413s09 |
| 2073543 Bef-1shabbku2 Bracket 2verbindungselemente Aus Kunststoff |
| Dg60-5r4150f00501 |
| Im12-02bcp-Zc1 |
| Wl24-2r230 |
| Clv620-0120 |
| I200 Lock |
| 1064706 Sensorgse10-P4211 Photoelectricswitch |
| Cfs50-Aaz0-S01 |
| 6036918 Sensor |
| Nt6-N112 |
| 6032669 Controller Ue410-Mu4t5 |
| 6009719 |
| 1000132 |
| 1040977 Lichtschranketyp:Ime18-08bnozck |
| 1025994 Lichtschanke Wtb27-3p2411 |
| 6028422 |
| 6048391 Sensor |
| 6048395 |
| Lms500-2000 |
| 1036767 Encoder Dfs60b-Bdpa10000 (Welle 10 Mm.) |
| 1040764 Die Induktiven Sensoren Ime 12-04bpsc0s |
| Wt260-F470-6020980 |

| | |
|---|-----------------------------|
| Im18-12npo-Zc1 | |
| Lut3-650 | |
| 6020685 Sensor Lichtschanke F. Sick Type: WI150-N420 | |
| 1041114 2d-Lidar-Sensoren , Lms111-10100 | |
| 1041376 Wtb11-2p2431lichtschanke | |
| 1025994 | |
| P/N: 6049001, Type: Mvm-1m0-2mc-Mklb | |
| 6041662 | |
| Ime30-20npozco0s Sensoren | |
| PI40a | |
| Elg3-0330p511 Elg3-0330p511 | |
| 1040870 Ime08-02bpszt0s | |
| 6009719 Dos-1205-G-Steckdose (Ready-To -Montage) | |
| 2017550 | |
| Wt2s-P211 | |
| PI80a Reflektor | |
| Dol-0804-G02m | |
| 2055515 | |
| 1045653 | |
| PI100 Reflektor Kv Optische | |
| WI280-2p2431 Sensor | |
| Mht15p2349 | |
| 1018254 Sensor | |
| 6020974 | |
| 1027785 | |
| 1040870 Inductive Sensor _ Sick Ime08-02bpszto | |
| 1036103 | |
| Dfs60, Dfs60e-S4cl01250 | 1054136 Incremental Encoder |
| 1041014 | |
| Ars60-F4a01024 | |

| |
|--|
| Dme4000-223 |
| C4mt-04214abb04de0 |
| Stl-1205-W 10mq |
| 1049062 Sensor Lichtschanke |
| 6037322 Steckverbinder Ste-0803-G |
| Im30-40nps-Nc1 |
| 1037063 Drehgeber |
| WI9-3n1132 |
| 1040887 |
| Vt18-204470s01 |
| Bef-Khs-Kh1 |
| 5311136 |
| 1071552 |
| 1071153 |
| Mzt6-03vps-Kp0 |
| 1041390 WI11g-2b2531 Lichtschanke |
| 6012829 |
| 6048385 |
| Cdm490-0103 Modul Klassifikation |
| Wtb4s-3n1162v |
| Im30-10bds-Zw1 |
| 1036095 |
| Vte18-3f4712 Optischer Sensor |
| 2029225 Ad-Atm60-Ka3pr Adapterreifen |
| P/N: 1053411 |
| 6010193 |
| 1028935 Scanner Laser Sick S30a-4011ca |
| 5311875 |
| 2095898 Kabel Yg2a14-100vb3xleax |
| 1051325 |
| Im08-02bps-Zt1 |
| 6020767 WI260-S270-Photovoltaiksensur |

| |
|---|
| 6037154 |
| 2095962 |
| 2031086 Kabel |
| 2095838 Reflektoren P250 |
| Vte18-4n8240 Optischer Sensor |
| 1018044 Sensor Kontrastierenden Markierungen, 1 018 044, Q=pnp |
| 6033221 |
| Wt12l-2b530 |
| 2076231 Spz-58z-012-P Spannzangen |
| 4056054 Befestigungssystem |
| 1041262 |
| 1074761 Absolut-Encoder, Ahm36a- S4pc014x12 |
| 1028081 |
| 6033188 |
| 6048328 |
| 6020410 |
| Clv650-0000 |
| 1017860 Schalter |
| 6048389 |
| 1071746 Lichtschranketyp:Hte18-P4a1bb |
| 6048062 Wtt280l- 2p2536multifunktionsoptoelektronische Sensoren |
| 6022790 Sensoren Optoelektronische Wt160 Wt160-F420 |
| Wl27-3f2631 |
| 6029282? |
| 5309683 |
| P/N: 1056741 |
| 6025076 |
| P/N: 1057915 |
| 1017910 |

| |
|--|
| 1200120 |
| Ime18-12npszc0s |
| 1040763 |
| 1036113 |
| 1040405 |
| I17 Sa213 Schalter |
| 1085344 |
| 1027754 |
| Vte 180-2p41187 |
| 1064914 |
| Dme4000-123 |
| Ime12-04bnsvcos |
| 1209145 |
| 2015624 |
| 2045891 Screw Terminal Set Kabel- Anschluss |
| Wl12-P4381 |
| 2046579 Connectoh M12.8 Pin:Typ Dsl- 2d08-G0m5ac3 |
| 5308961 |
| 1050541 |
| 1041381 |
| 1036116 |
| 6036841 |
| Wtb27-3r2611 Lichtschanke Schalter |
| 6029514 |
| Atm60-P1h13x13 |
| 1050271 Sensor Sensick Kw5w-2p 1116 Kat. Nr. 1 018 044 |
| Dfs60e-S4ea02000 |
| P/N: 1053494 |
| 1030015 Drehgeber Stegmann Atm60- Pah13x13 |

| |
|---|
| 53009987 |
| Wt45-D260s01 |
| Ws9d430 |
| Ws45r250 |
| Mainhak Rm 210 |
| 6048402 Um18-21812a211 Ultraschall-Sensor |
| 2096236 |
| 1063131 |
| 2045884 |
| Cable |
| Ime12-08npozczok 1040783 |
| Dol-1204-W02mm |
| 1025889 |
| Wtb9-3p2261 Optischer Sensor |
| 1037143 |
| 6063342 Sensor Lichtschanke. Typ: Gll170t-B333 |
| 1019231 |
| 5320017 |
| 5310158 |
| 1049052 Klein-Lichtschrangen , Wtb9-3n11614047084191732 4047084191732 |
| 7901786 Magnet Mag-3015-B |
| Clv622-1120 |
| 1050271 Wl14-2p431 Photovoltaiksensör |
| 6052373 |
| Wl11-2p2432 4-008-61-1456/50 |
| 1301670 |
| Wt18-3p430 |
| 1019245 Sensor Wl34-B430, |
| 1037869 Afm60b-S1ac004096absoluter Drehgeber Ssi |

| |
|---|
| Dbs60e-Thek05000 |
| Gl10-P4151 Kle. Lichtschanke Gl10 |
| Dos-1204-G Stecker |
| Wt9-2p330 |
| Wf80-60b416 Sensor |
| 6034575 Dsl-8u04g10m025km1 Kabel |
| 1013289 |
| 1031495 |
| 6053041 |
| Cs81-P3612 |
| Dos-1205-Wq |
| 1070872 Sensor |
| 2095898 |
| 1027605 |
| Kt5w-2p1116 |
| 1047402 Ds50-P1112 |
| Lgts090-351 |
| 1036787 |
| Wl260-F470 |
| Wl170-P122 |
| 1050571 |
| Im18-08bpszc0s Induktiver Sensor |
| 2034999 |
| 2066614 |
| 6009867 Kabel |
| Kt5g-2p1211 |
| 6012828 Sensor Lichtschanke Sick Vtf18-3f1240 |
| 1064594 Sensor |
| Bcg13-K1km05pp |
| Rt-P3221 |
| 6044738 Wl280-2h4331 Retro-Ref. |

| |
|--|
| Sens. Stellungsgeberoptoelektronnyj |
| P/N: 6037418, Type: Mvm-1m5-2mc-Mklb |
| 2076543 |
| 6025894 |
| 1053536 Optische Sensor |
| 1215668 |
| P/N: 1057772 |
| 1059338 Dfs60b-S4va04096 Incremental Encoder |
| S30b-2011ba |
| LI3-Dm02 |
| 1018044 Sensor |
| P/N: 1057064 |
| 6041823 Fotosensor Pnp24v7m |
| Wt100-N3419 |
| 6011050 Wt150-P460-Photovoltaiksensör |
| 6026548 Photoel.-Proximity-Switch Wtb190I-N430 |
| Im08-04npo-Zw1 |
| 1054155 |
| Atm60p4h13x13 |
| Dmt10-2-1211 |
| 2071332 |
| 5308077 Lichtleiter LI3-Dm02 |
| 1027908 |
| Ssl-2j04-G02mz60 Kabel |
| 6020280 Induktiver Sensor |
| Wtb4s-3p3260s02 Sensor |
| Wtb27-3p2421 |
| 1040878 |
| 1046135 2d-Lidar-Sensortyp: Lms511-10100 Pro |
| 1043006 |

| |
|--|
| Yf2a85-100ub6m2 A85-2096120 Kabel |
| Vfs60a-Bhpsz0-S02 |
| 1065890 |
| 6028428 |
| 1019250 |
| 2025266 |
| Dfs60b-S1pa10000 |
| P/N: 1055606 |
| 2092106 |
| 6013227 Optischer Sensor |
| 1024123 Lut1b-41235 |
| 1042256 |
| Kt5w-2p1216 Contrast Sensor Sick |
| Vte180-2p42447 Sensor Lichtschanke |
| 6053050 |
| Fx0-Gpro00000 |
| WI24-B2301 |
| WI150-P430 |
| Dol-1205-W10mq |
| Wtb4-3p 2261 Sensor Lichtschanke |
| 1041436 |
| Im08-1b5ps-Zc1 |
| Dfs60b-S4eb04000 |
| Bef-Fl-Alupbs-Hldr (5322501) |
| 6052627 |
| 6037496 |
| 1036104 |
| 2021269 Deckel |
| 6058910 Sensor Doppelte Blatt Ud18- 22cc221 Auf Automatik Tetra Pack |
| WI9-3p2232 P/N: 1049060 |
| Dme2000000 |
| |

| |
|--|
| WI 160-F440-9634f 10/30v Dc 102 3958 |
| 6010186 |
| 5313035 |
| 1030015 Atm60-Absolute Pah13x13wegmess |
| 2022547 Dol-0612g10m075km0 Kabel M26*12 |
| 1027787 WI23-2n2430 Lichtschanke |
| 1036093 |
| 1041436 Optische Sensoren Pnp, Reflex (Optoelektronische Sensoren Mit Reflektor).WI12-3p2431 |
| 1003865 PI80a, Reflektor |
| 1044075 Schnittstellenmodul Fx0-Gpro |
| C45e-0303ag220 |
| Dme4000-311s01 |
| P/N: 6037420, Type: Mvm-2m5-2mc-Mklb |
| Pgt-01-S |
| 1059466 |
| 1019229 Wt34-B410- Lichtschrankschalter |
| Kt5w-2n1116 Optischer Sensor |
| 1036110 |
| 6050247 |
| 1044125 |
| Dfs60e-S1ak01024 |
| 1055909 |
| 1010995 |
| 2022548 |
| Kt5w-2n1116 |
| 6012639 |
| 5322778 |
| Dme4000-314 |

| |
|---|
| 6013695 |
| Wtb8-P1111 Sensor |
| C40s-0701ca010 |
| 1054675 |
| 10667183 |
| 2017381 |
| 1041290 |
| 6034582 |
| 1036089 |
| 1025888 |
| 2015623 |
| 1062542 Mit Kabel 200mm |
| 6020598 I10-E0453 Safetyswitch Schalter Sicherheit |
| 6013872 Sensor |
| 6028369 Dos-1208-Ga Steckdose (Fertigezur Montage) |
| Dos-1208-Ga Stecker Pin Geschirmt |
| Dfs60b-S 4 Rk 10000 |
| P/N: 2031070, Type: Dol-2308-G03mjb2 |
| 6049452 |
| Wt45-P260 |
| We12l-2p430 |
| Dme4000-221 |
| Srm50-Hza0-S01 |
| 7902077 Leitungsdosem 8, 3-Polig (Dc), Geradety: Dos-0803-Gartikel-Nr.: 7902077 |
| Mzz1-03v-N-Awo |
| Dme4000-327 |
| Im12-04bns-Zw1 |
| 1074411 |
| Uc12-11231 |
| Clv650-0120 |

| |
|---|
| Cs81-N3612 |
| 1060529 Dbs36e-Bbek00100 İnkrementaler Drehgeber |
| 1066548 |
| Im12-02bpo-Zc1 |
| 2020935 |
| 7028790 Block |
| 6006685 |
| VI18-3p3840 |
| Wt150-P460 |
| T4000-1rca04 Relais |
| 6010190 Sensor Palletizer WI170-P430 |
| Ime12-04bnoz0s Induktiver Sensor |
| Wtb140-P132 |
| 1041381 Wte11-2p2432 Lichtschrinke |
| 1019228 |
| 1061134 |
| 1018594 |
| Wt24-2b410 |
| 1029789 |
| 6044699 Optischer Sensor Mit Reflektor Bis Zu M 13 WI250-P430 Sick 6010610 |
| 1052292 |
| 1049062 |
| Bef-Mr10500apg Weiel |
| VI18-3n3940 |
| 1058174 |
| 6028459 |
| 1059925 Sick Gl6g-N1211 Miniatur Optoelektronische Sensoren, Npn |
| Kt5w-2p1116d Pnp 1026 538 |
| M20z-02550a122 Optoelektronische Schutzeinrichtungen |

| |
|--|
| 2058653 Sensor |
| 1026833 |
| 1059521 |
| 1078884 Ahm36b-Bdcj012x12absolute Wegmess |
| 1018250 Wt12l-2b530lichtschrankeschalter |
| 7900157 Induktiver Sensor > Im30-20nps-Zc1 |
| 1037651 |
| 1037435 Drehgeber Afm60e-S4aa004096 |
| 2096238 |
| P/N: 6037419, Type: Mvm-02m-2mc-Mklb |
| Wl23-2p2430 |
| 2050705 |
| 1050271 |
| 6033188 Miniatur-Lichtschrankenwl8g-P2231 |
| 5304812 |
| 1054675 Sensor W4s-3 Inox |
| Dme4000-213 |
| 1019233 |
| 2032807 |
| Clv610-C0000 |
| 6059177 Dol-0803-G02mnistarthilfekabel Mitweiblicher Teil |
| 1045654 |
| 1223266 |
| 1031427 1031427 Ars60-A4b04096 Absolute Wegmess |
| C40e-0701ca010 |
| 6013407 Encoder |
| Encoder Sick Dgs66-Azzo-S04, 2000 Impulse/Umdrehung, 4-6 Vdc, Ttl. |
| Iq40-20bpp-Kc1 Induktiver Sensor |

| |
|--|
| 1200125 |
| Atm60-P4h13x13 |
| 1067207 |
| 6048416 Sensor |
| 6010544 |
| Plg3-210f431 |
| 6020784 |
| Lichtschrankesick W 11-2wtb11-2p2461 |
| Mlg05s-1195a10501 |