

## Sick Maihak

Garanti: 12 ay  
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Sick Maihak** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

*Firmamız Sick Maihak T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*



¼r¼n	A¼ıklama
<a href="#">1012783</a>	LIGHT CURTAIN SENDER 18MX750MM GUARDED AREA 24V
<a href="#">1015036</a>	RECEIVER: PROTECTED HEIGH
<a href="#">6028693</a>	ETHERNET, 200M, CARRIER FREQUENCY 2
<a href="#">1042124</a>	CLV650-6000 STD. BARCODE, SIDE WINDOW, LINE SCANNER WITH OSCILLATING MIRROR, AUTOFOCUS, SERIAL COMMS, 15 PIN D-SUB HD CONNECTOR, 900MM BLACK CABLE FOR
<a href="#">Fgss-1500-111</a>	FGS SENDER, 1500MM, 14MM RESOLUTION
<a href="#">1018698</a>	C4000 STANDARD/ADVANCED SENDER WITH EXT. PLUG, 1050MM PROTECTIVE HEIGHT, 14MM RESOLUTION
<a href="#">5310016</a>	
<a href="#">1022206</a>	C4000 BASIC SENDER, 1050MM, 14MM RES.
<a href="#">1008615</a>	NTL 6-B11 REGIS SCANNER / FIBER CONTRAST SENSOR, PNP/NPN, CONNECTOR 2M
<a href="#">Fgss-750-25</a>	FGS SENDER, 750MM PROTECTIVE HEIGHT, 30MM

	RESOLUTION
<a href="#">Lvu-706-2212</a>	LIGHT CURTAIN
<a href="#">7073705</a>	
<a href="#">2028360</a>	
<a href="#">Clv 490-0010</a>	(1016958), CLV 490-0010 BAR CODE, LINE SCAN / STANDARD / SOFTWARE SELECTABLE HOST PORT RS 232/422485
<a href="#">Lut3-620</a>	(1015397), LUT 3-620 LUM SCANNER, LUMINESCENCE SENSOR, PNP/NPN OUTPUT, LENS TW 20 (20 MM), 4-PIN 12 CONNECTOR
<a href="#">1035241</a>	BKS09-ATBM0520 ENCODER / SSI MEASURING LENGTH 5M
<a href="#">1024084</a>	DME 5000-122 DIS MEAS / DISTANCE MEASURING DEVICE, REFLEX, 70M PROFI HEAT
<a href="#">1012786</a>	LIGHT CURTAIN RECEIVER 18MX900MM GUARDED AREA
<a href="#">1005936</a>	LUMINESCENCE SENSOR WITH LENS #132 (20 MM), CONNECTOR
<a href="#">Od50-10p850</a>	DISPLACEMENT SENSOR OD-HI SENSING RANGE 50MM +/- 10MM PNP M12-8N
<a href="#">Btf08-D1hm0241</a>	(1034311), BTF08-D1HM0241 ENCODER, BTF WIRE DRAW, DEVICENET, MEASURING LENGTH 2 M
<a href="#">Lut2-711</a>	LUMINESCENCE SENSOR, NPN ANALOG OUTPUT, LENS 148 (
<a href="#">5310022</a>	
<a href="#">1017841</a>	HEIGHT/PROFILE SENSOR, SHINGLE COUNTING, 42 . . .62 MM, NPN OUTPUTS, 8-PIN M12 CONNECTOR
<a href="#">5310602</a>	
<a href="#">Isd300-6212</a>	(6028693), ISD 300-6212, ETHERNET, FREQ 2
<a href="#">Fgse-1350-211</a>	LIGHT CURTAIN 1350MM PROTECT HT 30MM RESOLUTION
<a href="#">1024081</a>	DME 5000-211 DIST MEAS / DISTANCE MEASURING DEVICE, REFLEX, 150M SSI
<a href="#">C40e-0301da010</a>	C4000 STANDARD RECEIVER WITH EXT PLUG, 300MM PROTECTIVE HEIGHT, 14MM RESOLUTION
<a href="#">Lut3-920</a>	(1019286), LUT 3-920 LUM SCANNER, LUMINESCENCE SENSOR, PNP/NPN/ANALOG OUTPUT, LENS TW 20 (20 MM),- PIN M12 CONNECTOR
<a href="#">1026517</a>	DT500-A112 DIST MEAS / DISTANCE MEASURING DEVICE, PROXIMITY, 30M, RS422
<a href="#">Clv631-6120</a>	(1041987), CLV 631-6120, MID RANGE OSCILLATING MIRROR SCANNER, ETHERNET COMMUNICATION

<a href="#">6028692</a>	ETHERNET, 200M, CARRIER FREQUENCY 1
<a href="#">90p1007</a>	
<a href="#">Lms100-10000</a>	(1041113), LMS100-10000, 0-18M RANGE @ 10% REFLECTIVITY, 20M MAX RANGE, 270 DEGREE FIELD OF VIEW, IP65 ENCLOSURE RATING, ETHERNET, 3 OUTPUTS, BLUE
<a href="#">Lut3-890</a>	(1014058), LUT 3-890 LUM SCANNER, LUMINESCENCE SENSOR, PNP/NPN/ANALOG OUTPUT, LENS TW 90 (90 MM),- PIN M12 CONNECTOR
<a href="#">6009345</a>	LIGHT CURTAIN TRANSMITTER
<a href="#">C41e-0401ag-300</a>	C4000 MICRO RECEIVER, SHORT RANGE, 450MM, 14MM RES.
<a href="#">2028465</a>	
<a href="#">1015512</a>	MGS SENDER, 900MM, 30MM RESOLUTION
<a href="#">1012771</a>	FGS SENDER, 1500MM, 14MM RESOLUTION
<a href="#">Agse-450-1211</a>	LIGHT CURTAIN
<a href="#">2032663</a>	
<a href="#">Lut3-610</a>	(1015396), LUT 3-610 LUM SCANNER, LUMINESCENCE SENSOR, PNP/NPN OUTPUT, LENS TW 10 (10 MM), 4-PIN 12 CONNECTOR
<a href="#">1025246</a>	DME 5000-321 DIST MEAS / DISTANCE MEASURING DEVICE, REFLEX, 300M SSI, HEAT
<a href="#">Lms211-30206</a>	1-30 M RANGE, 100 DEGREE FIELD OF VIEW, IP67 ENCLOSURE RATING, INTEGRAL HEATER, FOG CORRECTION
<a href="#">7023255</a>	LIGHT CURTAIN RECEIVER 24VDC 18M WIDE COV 30MM RES
<a href="#">Dt200-111a01</a>	2M RANGE, 0-20MA ANALOG, M12PIN
<a href="#">Lms-211-30106</a>	0-10 M RANGE, 100 DEGREE FIELD OF VIEW, IP67 ENCLOSURE RATING, INTEGRAL HEATER
<a href="#">7073704</a>	
<a href="#">Lms-211-S14</a>	1-30 M RANGE, 90 DEGREE FIELD OF VIEW, IP67 ENCLOSURE RATING, INTEGRAL HEATER, FOG CORRECTION, FAST VERSION
<a href="#">1041788</a>	CLV 621-2000 RIGHT ANGLE / LONG RANGE RIGHT ANGLE LINE SCANNER, SERIAL COMMUNICATION
<a href="#">1015922</a>	DME 3000-211S02 DIST MEAS / DISTANCE MEASURING DEVICE, PROXIMITY, 8 M, SSI, RS422
<a href="#">C40s-0403da010</a>	C4000 STANDARD/ADVANCED SENDER WITH EXT. PLUG, 450MM PROTECTIVE HEIGHT, 30MM RESOLUTION
<a href="#">1023460</a>	LIGHT CURTAIN MICRO SENDER 450MM 14MM RES

<a href="#">Mgse30-12b</a>	LIGHT CURTAIN 24V 20MS TIME WIDTH 18M HEIGHT 300MM
<a href="#">Msc 100e Hw</a>	
<a href="#">5309979</a>	
<a href="#">Clv630-2000</a>	(1041972), CLV 630-2000, LONG RANGE RIGHT ANGLE LINE SCANNER, SERIAL COMMUNICATION
<a href="#">Clv440-6010</a>	OSCILLATING MIRROR / STANDARD / SOFTWARE SELECTABLE HOST PORT R 232/422/485
<a href="#">Nt8-02412</a>	(1005985), NT 8-02412 REGIS SCANNER, CONTRAST SENSOR, NPN, LENS 24 (9 MM), LAMP 1001019, CABLE
<a href="#">1012861</a>	COLOR SENSOR, THREE CHANNEL, PNP OUTPUT, 60 MM SENSING DISTANCE, 8-PIN M12 CONNECTOR
<a href="#">Clv-431-1010</a>	RASTER SCAN / MID-RANGE / SOFTWARE SELECTABLE HOST PORT RS 232/22/485
<a href="#">1013484</a>	DME 2000-000S01 DIST MEAS / DISTANCE MEASURING DEVICE, PROXIMITY (100.2000 MM) OR REFLEX .1.130 M)
<a href="#">Isd250-1111</a>	INFRARED DATA TRANSMISSION 0.4AMP 24VDC
<a href="#">7072298</a>	
<a href="#">Isd300-1112</a>	(6024837), ISD 300-1112, PROFIBUS, RS 485, CARRIER FREQUENCY 2
<a href="#">4036661</a>	
<a href="#">C40s-0603da010</a>	C4000 STANDARD/ADVANCED SENDER WITH EXT. PLUG, 600MM PROTECTIVE HEIGHT, 30MM RESOLUTION
<a href="#">Lms-200-S60</a>	PHOTOELECTRIC LASER 24VDC 36W
<a href="#">2037653</a>	
<a href="#">Vspi-1d111</a>	(1044038), VSPI-1D111, INSPECTOR I10 DOME
<a href="#">Dme-5000-211</a>	(1024081), DME 5000-211 DIST MEAS, DISTANCE MEASURING DEVICE, REFLEX, 150M SSI
<a href="#">1012758</a>	LIGHT CURTAIN RECEIVER 450X6MM GUARDED AREA
<a href="#">C40s-1803ca010</a>	C4000 STANDARD/ADVANCED SENDER, 1800MM PROTECTIVE HEIGHT, 30MM RESOLUTION
<a href="#">Agss900-2121</a>	LIGHT CURTAIN TRANSMITTER
<a href="#">1018735</a>	C4000 STANDARD/ADVANCED SENDER WITH EXT. PLUG, 450MM PROTECTIVE HEIGHT, 30MM RESOLUTION
<a href="#">Isd280-1112</a>	(1017047), ISD 280-1112 DATA TRANS, RS 422/ 458 (2/4), CARRIER FREQUENCY 2
<a href="#">Fgse-600-111</a>	LIGHT CURTAIN RECEIVER 0.6X6M AREA 14MM RESOLUTION

<a href="#">1005933</a>	LUMINESCENCE SENSOR WITH LENS NO 133 50 MM, CONNECTOR
<a href="#">C40s-1302-Ca010</a>	C4000 STANDARD/ADVANCED SENDER, 1350MM PROTECTIVE HEIGHT, 20MM RESOLUTION
<a href="#">2032769-522</a>	
<a href="#">1022583</a>	STRAIGHT READING WINDOW , RS 232/422/485 AND ETHERNET
<a href="#">6009722</a>	RECEIVER: PROTECTED HEIGH
<a href="#">7109278</a>	
<a href="#">Icr-840-0020</a>	BARCODE SCANNER 2D CODE READ STRAIGHT READ WINDOW
<a href="#">Lut1-431</a>	LUMINESCENCE SENSOR WITH LENS NO 133 50 MM, CONNECTOR, WITH OG 70 FILTER
<a href="#">7072283</a>	
<a href="#">Nt8-02512</a>	(1005987), NT 8-02512 REGIS SCANNER, CONTRAST SENSOR, NPN, LENS 25 (18 MM), LAMP 1001019, CABLE
<a href="#">Clv280-2020</a>	BAR CODE SCANNER
<a href="#">Mba220xkf2n5-C0614-A-X</a>	
<a href="#">1017839</a>	HEIGHT/PROFILE SENSOR, 42 . . . 62 MM RANGE, 25 MM LINE, NPN OUTPUTS, 8-PIN M12 CONNECTOR
<a href="#">Isd400-6111</a>	2 OF THE SAME PN REQUIRED PER SYSTEM
<a href="#">2029695</a>	
<a href="#">C40s-1201aa310</a>	1200 MM HEIGHT, 14 MM BEAM RESOLUTION, SENDER, ECO
<a href="#">Dme-2000-000s01</a>	DISTANCE MEASURING DEVICE, PROXIMITY (100.2000 MM) OR REFLEX .1.130 M)
<a href="#">Clv631-6000</a>	(1041986), CLV 631-6000, MID RANGE OSCILLATING MIRROR SCANNER, SERIAL COMMUNICATION
<a href="#">1042280</a>	STANDARD RANGE FRONT READING WINDOW RS232/422/485, ETHERNET TCP/IP
<a href="#">Clv-432-0010</a>	LINE SCAN / CLOSE RANGE / SOFTWARE SELECTABLE HOST PORT RS 232/22/485
<a href="#">Clx-490-0010</a>	(1019318), CLX 490-0010, OMNI DIRECTIONAL / SOFTWARE SELECTABLE RS 232/422/485
<a href="#">Bks09-Atbm0520</a>	(1035241), BKS09-ATBM0520 ENCODER, SSI MEASURING LENGTH 5M
<a href="#">7070621</a>	
<a href="#">Mba220xkf2n5-C0914-A-X</a>	

<a href="#">S10b-9011-Ba</a>	0-4.5M RANGE @ 10% REFLECTIVITY, 10M MAX RANGE, 270 DEGREE FIELD OF VIEW, IP65 ENCLOSURE RATING, 1 FIELD SET, 2 OUTPUTS, BLACK, WITHOUT SYSTEM PLUG OR
<a href="#">7073314</a>	
<a href="#">1-027-452</a>	1200 MM HEIGHT, 14 MM BEAM RESOLUTION, SENDER, ECO
<a href="#">NtI6-B11</a>	(1008615)NTL 6-B11 REGIS SCANNER, FIBER CONTRAST SENSOR, PNP/NPN, CONNECTOR 2M
<a href="#">7122332</a>	PHOTOELECTRIC LASER
<a href="#">7070620</a>	
<a href="#">1027492</a>	1200 MM HEIGHT, 14 MM BEAM RESOLUTION, RECEIVER, 1-5M RANGE, ECO
<a href="#">C40e-0601da010</a>	C4000 STANDARD RECEIVER WITH EXT PLUG, 600MM PROTECTIVE HEIGHT, 14MM RESOLUTION
<a href="#">C45e-0603ag220</a>	600 MM HEIGHT, 30 MM BEAM RESOLUTION, RECEIVER, IP67 HOUSING, 0-4.5M RANGE, 15M CABLE
<a href="#">Fgss-1200-21</a>	LIGHT CURTAIN SENDER 30MM 18MRANGE
<a href="#">C40s-1603aa310</a>	1650 MM HEIGHT, 30 MM BEAM RESOLUTION, SENDER, ECO
<a href="#">5310017</a>	
<a href="#">2028466</a>	
<a href="#">400710</a>	
<a href="#">Rep-400710</a>	
<a href="#">1.018.738</a>	C4000 STANDARD RECEIVER WITH EXT PLUG, 600MM PROTECTIVE HEIGHT, 30MM RESOLUTION
<a href="#">C40e-0601db010</a>	C4000 ADVANCED RECEIVER WITH EXT PLUG, 600MM PROTECTIVE HEIGHT, 14MM RESOLUTION
<a href="#">1042338</a>	ICR 840-2B1020 GEN2, STANDARD RANGE SIDE WINDOW RS232/422/485, ETHERNET TCP/IP
<a href="#">Msls07-11311</a>	LIGHT CURTAIN SENDER 52MM X 55MM 2IN X 2IN
<a href="#">Agss-1200-1141</a>	LIGHT CURTAIN SENDER 1183MM HEIGHT 6M SENSITIVITY
<a href="#">1018-655</a>	C4000 STANDARD/ADVANCED SENDER, 1800MM PROTECTIVE HEIGHT, 30MM RESOLUTION
<a href="#">Mba220xkf2n5-C0414-A-X</a>	
<a href="#">Dme3000-111</a>	PHOTOELECTRIC SWITCH LONG RANGE 18-30VDC
<a href="#">1018653</a>	C4000 STANDARD/ADVANCED SENDER, 1650MM PROTECTIVE HEIGHT, 30MM RESOLUTION

<a href="#">C20e-165303a12</a>	(1016611), C20E-165303A12, TYPE 2 RECEIVER, 1650MM PROTECTIVE HEIGHT, 30MM RESOLUTION, SHOT RANGE
<a href="#">C40e-1503ca010</a>	C4000 STANDARD RECEIVER, 1500MM PROTECTIVE HEIGHT, 30MM RESOLUTION
<a href="#">2024952 (Ex B101 0487)</a>	
<a href="#">C41e-0601ag-300</a>	C4000 MICRO RECEIVER, SHORT RANGE, 600MM, 14MM RES.
<a href="#">2028493</a>	
<a href="#">1047411</a>	OLM100-1001 / OPTICAL LINEAR MEASUREMENT ON BARCODE TAPE, RED LED, 0.10M MEASUREMENT RANGE, 1MM REPEATABILITY , 1MS OUTPUT RATE. SSI
<a href="#">2028604</a>	
<a href="#">Lut2-620</a>	LUMINESCENCE SENSOR, PNP OUTPUT, LENS 211 (20 MM),
<a href="#">2029713</a>	
<a href="#">Fgss-600-13</a>	LIGHT CURTAIN SENDER 6M GUARDED WIDTH 24VDC
<a href="#">1018737</a>	C4000 STANDARD/ADVANCED SENDER WITH EXT. PLUG, 600MM PROTECTIVE HEIGHT, 30MM RESOLUTION
<a href="#">Clv-480-0010</a>	(1024065), CLV 480-0010 BARCODE SCAN, LINE SCAN / STANDARD / SOFTWARE SELECTABLE HOST PORT RS 232/422485
<a href="#">C40s-0902ca010</a>	C4000 STANDARD/ADVANCED SENDER, 900MM PROTECTIVE HEIGHT, 20MM RESOLUTION
<a href="#">7070622</a>	
<a href="#">1016238</a>	DMP 2-N21111 PE SWITCH / FINAL POSITION SENSOR, NPN VERSION, 5 NPN OUTPUTS, 8-PIN M12 CONNECTOR
<a href="#">1027937</a>	900 MM HEIGHT, 30 MM BEAM RESOLUTION, SENDER, BASIC PLUS
<a href="#">Clv-440-0010</a>	LINE SCAN / STANDARD / SOFTWARE SELECTABLE HOST PORT RS 232/422485
<a href="#">7023235</a>	LIGHT CURTAIN RECEIVER 6M GUARDED WIDTH 24V
<a href="#">Clv-422-1010</a>	RASTER SCAN / HIGH DENSITY / HOST PORT RS 232/422/485
<a href="#">Cs-3-P3632</a>	COLOR SENSOR, THREE CHANNEL, PNP OUTPUT, 60 MM SENSING DISTANCE, 8-PIN M12 CONNECTOR
<a href="#">Clv450-6010</a>	OSCILLATING MIRROR / STANDARD / SOFTWARE SELECTABLE HOST PORT R 232/422/485
<a href="#">Icr-850-0020</a>	STRAIGHT READING WINDOW , RS 232/422/485 AND ETHERNET
<a href="#">Isd280-1111</a>	(1017046), ISD 280-1111 DATA TRANS, RS 422/ 458 (2/4), CARRIER FREQUENCY 1

<a href="#">Prf13-A1am0520</a>	(1034324), PRF13-A1AM0520 ENCODER, PRF WIRE DRAW, TTL, 4-6V, MEASURING LENGTH 5 M
<a href="#">Fgse-450-111</a>	LIGHT CURTAIN RECEIVER 450X6MM GUARDED AREA
<a href="#">Mba220xkb2n5-C0314-A-X</a>	
<a href="#">1019285</a>	LUT 3-910 LUM SCANNER / LUMINESCENCE SENSOR, PNP/NPN/ANALOG OUTPUT, LENS TW 10 (10 MM),-PIN M12 CONNECTOR
<a href="#">Lut3-950</a>	(1019287), LUT 3-950 LUM SCANNER, LUMINESCENCE SENSOR, PNP/NPN/ANALOG OUTPUT, LENS TW 50 (50 MM),-PIN M12 CONNECTOR
<a href="#">V40pbe-0700000</a>	V4000 PB RECEIVER
<a href="#">Clv620-1120</a>	(1041549), CLV 620-1120 STRAIGHT, MID RANGE RASTER SCANNER, ETHERNET COMMUNICATION
<a href="#">1015035</a>	SENDER: PROTECTED HEIG
<a href="#">Clv490-1010</a>	(1016959), CLV 490-1010 BAR CODE, OSCILLATING MIRROR / STANDARD / SOFTWARE SELECTABLE HOST PORT R 232/422/485
<a href="#">1015536</a>	MGS RECEIVER, 900MM, 30MM RESOLUTION