



## Simco

Garanti: 12 ay  
Bu ¼r¼ne ait T¼rkiye ii kapı teslim fiyat ve teslim s¼resi ieren teklifimizi almak iin [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Simco** Markası, tedarik s¼resi iin l¼tfen bizimle iletiŐime geiniz.

*Firmamız Simco T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*

¼r¼n	Aıklama
<a href="#">13010198</a>	SIMCO ionization with air knife - Transvector Vortec - Air Knife - Transvector active length 2465.2 mm (96 ") Air connection G 1/4 " mounted on SIMCO anti-static bar type MEB active length 2438.4 mm total length 2505.0 mm incl. 3 m HS cable Country of origin: NL stat. Item no .: 85437090 Net weight: 2.3 kg
<a href="#">12070044</a>	SIMCO power supply type A 2A7 S 230 V / 50 Hz / 7 kV 4 x device connection 7kV max. 12 m (from HS cable including rod length) 1 x high voltage display 1 x power switch with display Tests CE, UL / CSA Protection class IP 54 Country of origin: NL stat. Item no .: 85437090 Net weight: 3.1 kg
<a href="#">A 2A3 S</a>	SIMCO power supply type A 2A3 S 230 V / 50 Hz / 3 kV 4 x device connection 3 kV max. 12 m from HV cable including rod length 1 x high voltage display 1 x power switch with display Tests CE, Protection class IP 54 Without Schuko plug Country of origin: NL stat. Item no .: 85437090 Net weight: 2.8 kg
<a href="#">0207000040</a>	
<a href="#">0209000000</a>	
<a href="#">06.59.20.2000</a>	
<a href="#">09.30.07.6100</a>	
<a href="#">09.32.80.0010</a>	
<a href="#">0928800210</a>	

<a href="#">0932800160</a>	
<a href="#">0932800190</a>	
<a href="#">0974707000</a>	
<a href="#">0974707100</a>	
<a href="#">0974709000</a>	
<a href="#">15.45.00.0160</a>	
<a href="#">17809.</a>	
<a href="#">25-R-1000</a>	
<a href="#">39.30.00.0200</a>	
<a href="#">4002371</a>	
<a href="#">400916301</a>	
<a href="#">4012304</a>	
<a href="#">4012306</a>	
<a href="#">4012474</a>	
<a href="#">4015591</a>	
<a href="#">4015703</a>	
<a href="#">4050661</a>	
<a href="#">4105292</a>	
<a href="#">antistatic for ÅÑİ 60Đ +60kV DC</a>	
<a href="#">DES20424</a>	
<a href="#">EP-SH-N 2115mm x 2245mm</a>	
<a href="#">EP-SH-N 2133mm x 2263mm</a>	
<a href="#">EP-Sh-N eff. 2115 mm/total 2245 mm w</a>	
<a href="#">HD-R Charging Bar</a>	
<a href="#">MEB</a>	
<a href="#">MEB eff. 2286 mm/total 2356 mm</a>	
<a href="#">SIMCO-NETZTEIL TYP LB 2A4 D</a>	
<a href="#">STBAR HD-C 2250x 2325MM OAL</a>	
<a href="#">THUNDERION 2.0</a>	
<a href="#">TT-P-645C</a>	
<a href="#">VCM-30</a>	
<a href="#">02.07.00.0040</a>	Field strength meter FMX-004 with 9V battery and case, optical distance display, including measurement of ion balance
<a href="#">SIMCO CM5-30-N</a>	SIMCO charging generator Operating voltage: 100-240V / 50-60Hz Number of outputs: 4 Output Voltage: 0-30KV Polarity: Negative Output current: 5.0mA max Incl. Power cord 2.5m IEC 320 I/O plug Sub-D 25 pin without cable Country of origin: NL

<a href="#">09.74.70.9081</a>	Supercharging system CM5 60 N for 100/240V, 50/60Hz Output voltage adjustable from 0 - 60 kV negative, current limited remote control connection for voltage, power and on/off including field bus 69.72.70.4800
<a href="#">09.74.70.9181</a>	Supercharging system CM5 60 P for 100/240V, 50/60Hz Output voltage adjustable from 0 - 60 kV positive, current limited remote control connection for voltage, power and on/off including field bus 69.72.70.4800
<a href="#">45.09.00.1035</a>	Emitter ThunderIon 2.0
<a href="#">75.10.99.000</a>	
<a href="#">75.10.99.0020</a>	
<a href="#">45.10.90.3920</a>	
<a href="#">45.09.00.1035</a>	
<a href="#">45.09.00.1030</a>	
<a href="#">Typ A 2A7 S</a>	12070044 230V / 50Hz / 7kV 4 x device connection 7kV max. 12 m (above HS cable incl. rod length) 1 * High Voltage Indicator 1 x power switch with indicator Tests CE, UL/CSA Degree of protection IP 54
<a href="#">Typ FMX-004</a>	15010026 including case and 9 V battery Measuring distance 25 mm Setting via 2 LED light marks on the object to be measured Measuring ranges Electrostatic field Measuring range Low +/- 1.5kV High +/-30.0 kV Ion balance measurement, with the built-in ion adapter Measuring range Low +/- 300 V High +/- 2.0 kV LCD display -- bar graph + / - Digital -- battery -- display 4 digits The measuring device for the commissioning engineer - maintenance. including calibration and calibration certificate
<a href="#">ion FMX-004</a>	
<a href="#">1531011710 Static Neutrolising Busbar</a>	
<a href="#">09.74.70.7000</a>	Charging system CM5 30 N for 100/240V, 50/60Hz Output voltage adjustable from 0 - 30 kV negative, current limited Remote control connection for voltage, current and On off
<a href="#">09.74.70.9081</a>	CM5 60 N charging system for 100/240 V, 50/60 Hz Output voltage adjustable from 0 - 60 kV negative, current limited Remote control connection for voltage, current and On off including fieldbus 69.72.70.4800
<a href="#">09.74.70.9181</a>	CM5 60 P charging system for 100/240 V, 50/60 Hz Output voltage adjustable from 0 - 60 kV positive, current limited Remote control connection for voltage, current and On off including fieldbus 69.72.70.4800
<a href="#">09.74.70.7000</a>	CM5 30 N charging system for 100/240 V, 50/60 Hz Output voltage adjustable from 0 - 30 kV negative, current limited Remote control connection for voltage, current and On off
<a href="#">02.07.00.0040</a>	Field strength meter FMX-004 with 9V battery and case, optical distance display, including measurement of ion balance
<a href="#">02.07.00.0040</a>	Field strength meter FMX-004 with 9V battery and case, optical distance display, including measurement of ion balance
<a href="#">08.05.25.7000</a>	A2A7S f¼r 230 V, 50 Hz, 7 kV
<a href="#">4004261</a>	(PRICE/EA) AEROSTAT GUARDIAN 3-FAN OVERHEAD IONIZER, 230V, 50 HZ CE-EU
<a href="#">Mcm30</a>	CHARGER
<a href="#">4008832</a>	VISION CONTROLLER 120-240VAC 50/60HZ 22W

<a href="#">4001995</a>	HOOD
<a href="#">12010707</a>	
<a href="#">1511000100</a>	
<a href="#">Ch30-N</a>	CHARGER 2.5A 115VAC 50/60HZ 30KV 5MA 6MA SCC MAX
<a href="#">4003337</a>	CHARGER
<a href="#">R50-Blue-Bar-20.5in</a>	STATIC NEUTRALIZING BAR 20.5IN OVERALL LENGTH
<a href="#">Hd-C Charging Bar 2200/2275 Mm. + 14 M Cable</a>	
<a href="#">14-21570</a>	
<a href="#">R51-Blue-Bar-27in</a>	STATIC NEUTRALIZING BAR 5800VAC 50/60HZ
<a href="#">As-10</a>	
<a href="#">4010442</a>	POWER SUPPLY, LINEAR, 7KV, POWER SUPPLY OUTPUT TYPE:FIXED, NO. OF OUTPUTS:1, OUTPUT VOLTAGE:7KV, POWER RATING:20VA, INPUT VOLTAGE VAC:120V, LENGTH:6.4
<a href="#">08.05.10.7000</a>	
<a href="#">Type Cm5 60 N</a>	High voltage generator type CM5 60 N 100-240V, 50/60Hz Output voltage 60 kV DC
<a href="#">4005105</a>	AIR IONIZER, IONIZING AIR GUN, APPROVAL BODIES:CE / UL, FEATURES:OSHA COMPLIANT, OPERATES ON COMPRESSED AIR OR NITROGEN, STATIC DISSIPATIVE GUN AND 7
<a href="#">4011281</a>	(PRICE/EA) AEROSTAT FPD HIGH OUTPUT 3-FAN OVERHEAD IONIZER, 120/230V, 50/60 HZ, CE-EU
<a href="#">4006599</a>	(PRICE/EA) TOP GUN 3 IONIZING BLOW-OFF GUN, 120V, 14-FOOT CABLE/HOSE ASSEMBLY, N.A.
<a href="#">13200037</a>	
<a href="#">R50-Blue-Bar-20in</a>	NEUTRALIZER BAR 8KV BAR 20IN W/CORD
<a href="#">94-156250</a>	PC BOARD ASSEMBLY ADC/GAIN MEMORY
<a href="#">12070135</a>	
<a href="#">Hd-R 1313/1388</a>	
<a href="#">11020308</a>	
<a href="#">4012557</a>	CONTROL
<a href="#">23040001</a>	
<a href="#">64-08.0525.7000</a>	
<a href="#">4012199</a>	(PRICE/EA) TOP GUN 3 IONIZING BLOW-OFF GUN, 120V, 5 CABLE/HOSE ASSEMBLY, OPTICAL SENSOR, N.A.
<a href="#">08.34.62.5480</a>	
<a href="#">13040005</a>	
<a href="#">4004175</a>	BLOWER STATIC ELIMINATION 2AMP 120VAC 50/60HZ
<a href="#">4010018</a>	NEUTRALIZER BAR 8KV BAR 29IN W/CORD

<a href="#">Simco-Netzteil Typ Lb 2a4 D</a>	
<a href="#">23040002</a>	
<a href="#">4011009</a>	(PRICE/EA) AEROSTAT FPD HIGH OUTPUT 4-FAN OVERHEAD IONIZER, 120/230V, 50/60 HZ, NAM
<a href="#">4002549</a>	IONIZED AIR BLOWER MODEL AS30 2AMP 120VAC 50/60HZ
<a href="#">4088022</a>	STBAR R50 1710X1795MM OAL WITH 7 FOOT HV CABLE
<a href="#">03.20.06.1003</a>	
<a href="#">08.05.25.7900 - A2a7bhr</a>	
<a href="#">4010608</a>	POWER SUPPLY DC HIGH VOLTAGE .6AMP 120VAC 50/60HZ
<a href="#">12010766 Typ P-Sh-N</a>	
<a href="#">Cm5 30n</a>	
<a href="#">4012250</a>	CENTURION SINGLE-FAN DC IONIZING AIR BLOWER, IONIZER TYPE:BENCHTOP, FLOW RATE MAX:90CFM, DEPTH:3.375, WIDTH:8, HEIGHT:9.375, SUPPLY VOLTAGE VAC:120
<a href="#">4011549</a>	IONIZING BAR, POWER SOURCE:BATTERY, SUPPLY VOLTAGE:9V
<a href="#">Electrode For A6c7s</a>	
<a href="#">A2a7s 230v 50hz 7 Kv</a>	
<a href="#">4012210</a>	ORION IONIZING AIR NOZZLE, 230V, 7 CABLE/HOSE ASSEMBLY, OPTICAL SENSOR, EU CE
<a href="#">4011546cald</a>	IONIZATION BAR, LENGTH:457MM, POWER SOURCE:BATTERY, SUPPLY VOLTAGE:9V
<a href="#">As-20af</a>	IONIZED BLOWER 9KS RMS MAX 120VAC 60HZ
<a href="#">A2a7s</a>	
<a href="#">05.06.20.0010</a>	
<a href="#">12011804 - Performax Easy</a>	
<a href="#">R50-Blue-Bar-26.5inch</a>	STATIC NEUTRALIZER BAR SHOCKLESS 6INCH RANGE
<a href="#">4050202</a>	MOTOR
<a href="#">4012556</a>	CHARGEMASTER GENERATOR NEGATIVE POLARITY 115/230V
<a href="#">R50-Blue-Bar-14-1/2in</a>	NEUTRALIZER BAR 8KV BAR W/CORD 14-1/2IN
<a href="#">4011154</a>	VISIONI CONTROLLER, 120V, 50 HZ
<a href="#">Vcmbp30</a>	CHARGER
<a href="#">4011547cald</a>	IONIZING BAR, POWER SOURCE:BATTERY, SUPPLY VOLTAGE:9V
<a href="#">4016015c</a>	CHARGER BOARD
<a href="#">4008404</a>	CHARGER
<a href="#">08.05.25.7000 - A2a7s Power</a>	
<a href="#">Vcm30-N</a>	CHARGEMASTER GENERATOR NEGATIVE POLARITY 115/230V
<a href="#">0805257000</a>	
<a href="#">Ivse300</a>	STATIC ELIMINATOR VOLUME 115VAC 435W 5AMP
<a href="#">13200038</a>	

<a href="#">4008729</a>	(PRICE/EA) AEROSTAT GUARDIAN CR2000 2-FAN CLEANROOM OVERHEAD IONIZER, 120V, 60 HZ
<a href="#">R50-Blue-Bar-53in</a>	STATIC NEUTRALIZER BAR SHOCKLESS 8KVAC
<a href="#">Ch25-N</a>	ELECTROSTATIC GENERATOR 2/3MA 25KV OUTPUT
<a href="#">4012229</a>	(PRICE/EA) FUSION IN-LINE LOCALIZED IONIZER, TUNGSTEN (W) EMITTERS
<a href="#">Sdvp</a>	PERFORATION DETECTOR CHARGING UNIT
<a href="#">P-Sh The Upper Electrode Is Double</a>	
<a href="#">Hd-C 2500mm</a>	
<a href="#">Vcmbp60</a>	CONTROLLER
<a href="#">4004063</a>	IONIZING AIR BLOWER, APPROVAL BODIES:CE / UL, DEPTH:17.1CM, EXTERNAL DEPTH:6.75, EXTERNAL HEIGHT:4, EXTERNAL WIDTH:42.75, FEATURES:PATENTED POINT C
<a href="#">4088013</a>	R50 BLUE BAR, 41.1" OL W/7FT CABLE
<a href="#">4014683</a>	POWER SUPPLY
<a href="#">0805254000</a>	
<a href="#">4012563</a>	GENERATOR
<a href="#">4012022</a>	PC2 IONIZING AIR BLOWER, MANUAL EMITTER CLEANER, IONIZER TYPE:BENCHTOP, FLOW RATE MAX:100CFM, DEPTH:3.5, WIDTH:6, HEIGHT:7.8, SUPPLY VOLTAGE VAC:24
<a href="#">4012245cald</a>	PC2 IONIZING AIR BLOWER, AUTOMATIC EMITTER CLEANER, IONIZER TYPE:BENCHTOP, FLOW
<a href="#">17809</a>	
<a href="#">As20a W/Oplt, Part Number-4100735as 20 Bar &amp; Block Zus</a>	
<a href="#">11179001</a>	POWER SUPPLE DUAL POLARITY 1AMP 120V 50/60HZ
<a href="#">11040040 - Cm5 30 Negativ</a>	
<a href="#">4050230</a>	POWER SUPPLY FOR IONIZATION BARS 230V 50HZ
<a href="#">A6c7s,Art. Nr. : 08.05.60.7000</a>	
<a href="#">Pshnex-230-50hz.</a>	
<a href="#">T780 80x66</a>	
<a href="#">4012245</a>	PC2 IONIZING AIR BLOWER, AUTOMATIC EMITTER CLEANER, IONIZER TYPE:BENCHTOP, FLOW RATE MAX:100CFM, DEPTH:3.5, WIDTH:6, HEIGHT:7.8, SUPPLY VOLTAGE VAC
<a href="#">4002321</a>	POWER SUPPLY MODEL N167 0.24A 120VAC 60HZ
<a href="#">4005106</a>	(PRICE/EA) TOP GUN 3 IONIZING BLOW-OFF GUN, 230V, 7 CABLE/HOSE ASSEMBLY, EU CE
<a href="#">Hd-R</a>	
<a href="#">4009245</a>	(PRICE/EA) ORION IONIZING AIR NOZZLE, 120V, SIDEKICK (HANDS-FREE STAND), N.A
<a href="#">Ecm 30 N 85-265v/50-60 Hz</a>	

<a href="#">4012555</a>	GENERATOR
<a href="#">11020307</a>	
<a href="#">4012212</a>	(PRICE/EA) ORION IONIZING AIR NOZZLE, 120V, SIDEKICK (HANDS-FREE STAND), OPTICAL SENSOR, N.A
<a href="#">13040006</a>	
<a href="#">4008630</a>	GUARDIAN CR2000 3-FAN OVERHEAD IONIZING AIR BLOWER, APPROVAL BODIES:CULUS, CE, DEPTH:6.75
<a href="#">4006992</a>	(PRICE/EA) AIR IONIZER, BENCHTOP, 120VAC, IONIZER TYPE:BENCHTOP, SUPPLY VOLTAGE VAC:120V, PRODUCT RANGE:-
<a href="#">4011550</a>	IONIZING BAR, POWER SOURCE:BATTERY, SUPPLY VOLTAGE:9V
<a href="#">Worksurface Tester Model St 4</a>	
<a href="#">Pn25a</a>	STATIC GENERTR
<a href="#">4011007</a>	(PRICE/EA) AEROSTAT FPD HIGH OUTPUT 3-FAN OVERHEAD IONIZER, 120/230V, 50/60 HZ, NAM
<a href="#">A157c2</a>	
<a href="#">4007059</a>	TOP GUN SIDEKICK (FOR HANDS-FREE OPERATION)
<a href="#">Valve Type 16 Offset Design, Female Npt</a>	
<a href="#">10742-001</a>	(PRICE/EA) I-VSE 5000 STATIC CONTROL BLOWER
<a href="#">4012209</a>	(PRICE/EA) ORION IONIZING AIR NOZZLE, 120V, 5 CABLE/HOSE ASSEMBLY, OPTICAL SENSOR, N.A
<a href="#">Aerostat As-10</a>	
<a href="#">Vcm60n</a>	CHARGER
<a href="#">4012206</a>	(PRICE/EA) TOP GUN 3 IONIZING BLOW-OFF GUN, 230V, SIDEKICK (HANDS-FREE STAND), OPTICAL SENSOR, EU
<a href="#">4011726</a>	PREFORMAX IQ POWER SUPPLY 24VDC 1.5AMP INPUT
<a href="#">4011548</a>	IONIZING BAR, POWER SOURCE:BATTERY, SUPPLY VOLTAGE:9V
<a href="#">Spring Connector/Federkonnektor Hv 30/60kv 5050328(91.46.87.3900)</a>	
<a href="#">4011282</a>	(PRICE/EA) AEROSTAT FPD HIGH OUTPUT 3-FAN OVERHEAD IONIZER, 120/230V, 50/60 HZ, CE-UK
<a href="#">12011403</a>	
<a href="#">4000048</a>	4 RING
<a href="#">4012205</a>	TOP GUN 3 IONIZING BLOW-OFF GUN, 120V, SIDEKICK (HANDS-FREE STAND), OPTICAL SENSOR
<a href="#">11010012</a>	
<a href="#">As-20</a>	IONIZER BLOWER 230V
<a href="#">4011547</a>	IONIZING BAR, POWER SOURCE:BATTERY, SUPPLY VOLTAGE:9V
<a href="#">4088028c</a>	BAR
<a href="#">91-6115- Nxfmr</a>	
<a href="#">03.20.06.0623</a>	

<a href="#">Meb-229-299</a>	
<a href="#">Cm5 60 P</a>	
<a href="#">R50-Blue-Bar</a>	STATIC NEUTRALIZER BAR SHOCKLESS 6INCH RANGE
<a href="#">10735-015</a>	(PRICE/EA) VOLUME STATIC ELIMINATOR (VSE) 3000, 230V, 50HZ CE-UK
<a href="#">Meb 7kv Lendth:375mm</a>	
<a href="#">1500000240</a>	
<a href="#">A2a7bhr 230v 5-Hz 7kv</a>	
<a href="#">4011546</a>	IONIZATION BAR, LENGTH:457MM, POWER SOURCE:BATTERY, SUPPLY VOLTAGE:9V
<a href="#">29t1-1000</a>	
<a href="#">P-Sh-N-Ex</a>	
<a href="#">91-0280a-C</a>	(PRICE/EA) DIGITAL CHARGED PLATE MONITOR, MODEL 280A FOR HIGH FREQUENCY IONIZERS (MP TECHNOLOGY), SOFTWARE AND CARRYING CASE INCLUDED, CALIBRATION CER
<a href="#">C1750</a>	CABLE CUTTER
<a href="#">14020005</a>	
<a href="#">Ch-20-Ni</a>	CHARGING UNIT .3AMP 230VAC 50/60HZ
<a href="#">4009894</a>	TOP GUN 3 IONIZING BLOW-OFF GUN, 120V, 7 CABLE/HOSE ASSEMBLY, UK CE
<a href="#">Es2j</a>	
<a href="#">25- R-1000</a>	
<a href="#">4008804</a>	(PRICE/EA) AEROSTAT GUARDIAN CR2000 2-FAN CLEANROOM OVERHEAD IONIZER, 230V, 50 HZ CE-UK
<a href="#">92-6115-Us</a>	AIR FORCE BLOW-OFF GUN, 65PSI, PLUG TYPE:US, AIR PRESSURE MAX:65PSI
<a href="#">He3</a>	
<a href="#">Fmx-002(Replacemont)fmx-004</a>	