

## Sitec-Sieber

Garanti: 12 ay  
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Sitec-Sieber** Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

*Firmamız Sitec-Sieber Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.*



rn	Aıklama
<a href="#">7200211</a>	Pressure screw 3/8 "and 10 mm HP Vibro according to drawing: 720.0211 Nominal width 1.6, 3 and 5 mm M 20 x 1.5 Width across flats 22 Anti-Vibro
<a href="#">7200221</a>	Pressure ring 3/8 "HP VIBRO according to drawing: 720.0221 Internal thread 3/8 "- 24 UNF LH Anti-Vibro Material: 1.4104 Goods no .: 84818099; Country of origin: CH
<a href="#">7190116-R-NHEP</a>	Through valve NC, 500 bar, G1 / 4 ", DN = 4 with pneumatic drive Spindle made of 1.4542 with ceramic ball and interchangeable seat for N-heptane commitment O-ring in Viton in contact with the medium Medium temp .: -15 ° C to + 200 ° C with magnet and guide on the cylinder prepared for inductive position indication without reed contact switch
<a href="#">7190101-LD4R</a>	Test bench valve NO, 400 bar, DN = 4mm with O-ring connection Spindle made of 1.4542 with ceramic ball and interchangeable seat 17 -4PH Test pressure 450 bar, compressed air requirement: 6 bar Medium: n - Heptane O-rings in the drive in MVQ O-rings in Viton in contact with the medium with magnet and guide on the cylinder prepared for inductive position indication without reed contact switch Item no .: 84814090; Country of origin: CH Replacement for: 719.0101-LD4RK
<a href="#">720.1511</a>	Bulkhead fitting 4000bar, 9/16HP, DN5
<a href="#">720.1512 / a</a>	Elbow 4000bar, 9/16HP, DN5

<a href="#">7105310</a>	Valve 4000 bar 1/4" HP, T1, shut-off Material: 1.4571 Drawing: 710.5310 Nominal diameter 3 mm, type 1, shut-off valve
<a href="#">720.0211</a>	Thrust screw 3/8 "and 10 mm HP Vibro Nominal width 1,6, 3 and 5 mm M 20 x 1.5 Spanner size 22 Anti-Vibro
<a href="#">771,1001</a>	
<a href="#">720.0221</a>	Thrust ring 3/8 "HP VIBRO 5% / -2.40 according to drawing: 720.0221 Internal thread 3/8 "- 24 UNF LH Anti - vibro
<a href="#">720.0330</a>	Plug 1/4 "HP Standard + Anti-Vibro
<a href="#">771,1009</a>	
<a href="#">729.5024-2</a>	
<a href="#">720.0311</a>	Thrust screw 1/4 "and 6 mm HP VIBRO according to drawing: 720.0311 Nominal width 1.6 and 3 mm M 16 x 1.5 Spanner size 17 Anti-Vibro
<a href="#">771,1006</a>	
<a href="#">720.0321</a>	Thrust ring 1/4 "HP VIBRO according to drawing: 720.0321 Internal thread UNF 1 / 4-28 Anti-Vibro
<a href="#">719.0116-K</a>	
<a href="#">719.0115-K</a>	
<a href="#">771,1002</a>	
<a href="#">7280300-10</a>	
<a href="#">7280722</a>	
<a href="#">770,2100</a>	
<a href="#">771,1017</a>	
<a href="#">7700,1100</a>	