



Skum

Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Skum** Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Skum Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
Mlr-40a	Skum Foam nozzle MLR-40A, 400 Ltr., 5 bar, 1.1/2" ball valve with Storz coupling C; 8 kg each, made in Sweden
Fire Hydrant Angle Valve	Fire Hydrant angle valve with 1 flange DN 40, PN 16 x outlet C-storz coupling Ms, je 5 kg, made in Germany
Bladder Tank	Bladder Tank, 1500 lt.
Typ FJM-80	SKUM monitor type FJM-80 DIN / ANSI 3700 l / min at 10 bar max range 75 m Rotation 360 °, elevation -60 ° - + 90 ° material Stainless steel / bronze
BLADDER TANK 1500 LT	PED APPROVED (CE MARKED),RED EPOXY FINISH,DN 50 PN16 DIN FLANGED CONNECTIONS,INC.LEVEL HOSE INDICATOR,DRAIN VALVE,VENT AND FILL VALVES
SKUM ARC	3 X 3 AR-AFFF FOAM CONCENTRATE EN 1568 & UL-162 GRADE % 3 1500LT
WIDE RANGE RATIO,	VARIABLE FLOW , SUITABLE TO WORK WITH 3% AR-AFFF FOAM, SUITABLE TO USE IN SPRINKLER SYSTEM, 100-5000 L/MIN CAPACITY
WATER ACTUATED FOAM	VALVE MODEL WAFV-40 MK2,FOAM LINE CONNECTION DN40 BSP FEMALE,DA ACTUATOR/SS-316 BALL VALVE INCL.LEVER FOR MANUAL RESETTİNG
SKUM Monitor Tp FJM-80 DIN / ANSI 3700 l/min	max range 75 m Rotation 360 ° Elevation -60 ° - + 90 ° Metrial stainless steel, bronze

foam gun applicator	For 6 circuit
SKUM MLB	Heavy foam pipe MLB-40 F DIN Expansion rate up to 15: 1 K-factor 224/500 L / min protection area 4-6 m Connection DN40 PN16 Material: stainless steel
FJM-80 model	O-RING KIT- There is a leak in the foam guns on our ship because there is no suitable o-ring. Ribbon o-rings were tried but no result could be obtained because the same thickness could not be obtained. There are 6 foam guns in total on board. Each of them must have 2 o-rings. For this reason, 3 spares are required for 12 existing foam guns. Inner Diameter :93 mm Outer Diameter : 96 mm Wall Thickness: 3 mm
FJM-150 EL/MV M	
TYP FJM-100	KUM MONITOR TYPE FJM-100 DIN / ANSI6000 LITER / MINUTE AT 10 BAR MAXIMUM RANGE 80 METERS ROTATION 360°, ELEVATION - 60° + 90° MATERIAL: STAINLESS STEEL, BRONZE"
FOAM PUMP PROPORȚIONER	FOAM CONN. DN20 / WATER CONN DN80
WET ALARM VALVE DN80	
ppw 150/50 (tyco,Skum) dosing mixer	
FOAM PUMP PROPORȚIONER	FOAM CONN. DN20 / WATER CONN DN80
FOAM PUMP PROPORȚIONER -	FOAM CONN. DN20 / WATER CONN DN80
123008108	SKUM FOAM PUMP MIXER TYPE PP 80 INTERMEDIATE FLANGE DN 80, FOAM INLET 3/4" IT CAPACITY 300 - 2000 LITERS/ MINUTE ADJUSTABLE MIXING RATE FROM 1% - 6% MATERIAL BODY: BRONZE
Pp-100/50 din/ansi	Order 2560649c
MONITOR TYPE FJM-100 DIN / ANSI6000	LITER / MINUTE AT 10 BAR MAXIMUM REACH 80 METERS ROTATION 360°, ELEVATION - 60° + 90° MATERIAL: STAINLESS STEEL, BRONZE"
FOG/JET MONITOR MANUAL FJM-80 DIN/ANSI	FLANGED DN80 UP TO 3700 L/MIN CAPACITY @ 10BAR
DN80 PN16 foam gun	SKUM MONITOR TYPE FJM-80 DIN / ANSI3700 LITER / MINUTE AT 10 BAR MAXIMUM RANGE 75 METERS ROTATION 360°, ELEVATION - 60° + 90° MATERIAL: STAINLESS STEEL, BRONZE
FJM-80 WTO	Skum monitor type FJM-80 WTO 3700l/min at 10 bar max. range 75 m Material stainless steel, bronze
FJM 80	10 bar range 75m Rotation 360, elevation -60 +90 Material stainless steel/bronze
O-RING KIT FJM-80 169108201	PACKAGE CONTAINING NITRILE O-RINGS: 1 PCE 94,5X3 1 PCE 84,5X3 1PCE 114,5X3 2 PCE 10,3X2,4 5 PCE 84,1X5,7 SILICONE GREASE AND INSTRUCTIONS
FOG/JET (FJM-80 DIN/ANSİ 9 BAR)	
FJM 100"	Flench 100 DIN PN 16,8 Holes)