



Sodeco

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye ii kapı teslim fiyat ve teslim s¼resi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Sodeco** Markası, tedarik s¼resi iin l¼tfen bizimle iletiŐime geiniz.

Firmamız Sodeco T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	Aıklama
34579	Double-acting pneumatic actuator type ADA Double-acting pneumatic actuator Rack & pinion Housing made of aluminum Swivel movement: 90 ° ± 5 ° Stroke limitation: ± 5 ° Operating temperature: -30 ° C ~ 100 ° C Operating pressure: 3 - 8 bar
2 APA4-BB05	UGELLO PE
16234ETR DN 300	Butterfly valve Fig. 16234 ET / R Ring body butterfly valve Housing made of nodular cast iron EN GJS-400-15 ASTM A351 CF8M stainless steel flap AISI 416 stainless steel shaft EPDM seat, for high temperatures, max. 130 ° C Max. Operating pressure: 16 bar (DN 32 - DN 300), 10 bar (DN 350 - DN 600) Installation length: ISO 5752 Connection: flange PN 10, PN 16 and ANSI 150 ISO mounting flange for direct mounting With worm gear
16234ETR-0303 DN 400	Butterfly valve Fig. 16234 ET / R Ring body butterfly valve Housing made of nodular cast iron EN GJS-400-15 ASTM A351 CF8M stainless steel flap AISI 416 stainless steel shaft EPDM seat, for high temperatures, max. 130 ° C Max. Operating pressure: 16 bar (DN 32 - DN 300), 10 bar (DN 350 - DN 600) Installation length: ISO 5752 Connection: flange PN 10, PN 16 and ANSI 150 ISO mounting flange for direct mounting With worm gear
16234ETR-0303 DN 450	
16234ETR-0303 DN 600	
	Ring body butterfly valve Housing made of nodular cast iron EN GJS-400-15 ASTM A351 CF8M stainless steel flap AISI 416 stainless steel shaft

16234ETH DN 100	EPDM seat, for high temperatures, max. 130 ° C Max. Operating pressure: 16 bar Installation length: ISO 5752 Connection: flange PN 10, PN 16 and ANSI 150 ISO mounting flange for direct mounting With aluminum hand lever, adjustable in steps of 10 ° (DN 32 - DN 200) With steel hand lever, adjustable in steps of 10 ° (DN 250 - DN 300)
16234ETH DN 150	
16234ETR DN 200	Butterfly valve Fig. 16234 ET / R Ring body butterfly valve Housing made of nodular cast iron EN GJS-400-15 ASTM A351 CF8M stainless steel flap AISI 416 stainless steel shaft EPDM seat, for high temperatures, max. 130 ° C Max. Operating pressure: 16 bar (DN 32 - DN 300), 10 bar (DN 350 - DN 600) Installation length: ISO 5752 Connection: flange PN 10, PN 16 and ANSI 150 ISO mounting flange for direct mounting With worm gear
530AIT diam. 1 1/2"	Ball valve Fig. 530 AIT - ANSI 300 Flanged ball valve with floating ball Housing made of steel A216 Gr. WCB Ball made of stainless steel A 351 Gr. CF8M PTFE seats Max. Operating pressure: 50 bar Installation length: ASME B16.10 long pattern Connection: flanged ANSI 300 Lbs ISO mounting flange Fire safe according to ISO 10497 With hand lever made of nodular cast iron (free shaft end from 8 ')
530AIT diam. 1"	
530AIT diam. 1/2"	
530AIT diam. 2"	
530AIT diam. 3"	
530AIT diam. 3/4"	
530AIT diam. 4"	
530AIT diam. 6"	
530AIT diam. 8"	
364BAAITIFS diam. 1 1/2"	Ball valve Fig. 364 BA AIT / I / FS Three-part ball valve with floating ball, full passage Housing made of steel A216 Gr. WCB AISI 316 stainless steel ball Seats made of PTFE + 15% glass fiber Max. Operating pressure: 138 bar (1/4 'to 1'), 103 bar (1 1/4 'to 2') Connection: NPT internal thread ISO mounting flange Fire-safe according to API 607, Part 4 With hand lever made of stainless steel and locking device
364BAAITIFS diam. 1"	
364BAAITIFS diam. 1/2"	
364BAAITIFS diam. 1"	
364BAAITIFS diam. 2"	
222AIIT-0303 diam. 1/4"	Ball valve Fig. 222 A IIT Two-part ball valve with floating ball ASTM A351 Gr. CF8M Stainless steel ball ASTM A351 Gr. CF8M Seats made of PTFE + 15% glass fiber Max. Operating pressure: 63 bar Connection: NPT internal thread With hand lever made of stainless steel and locking device
363/4BAAITIFS DN15	Ball valve Fig. 363/4 BA AIT / I / FS Three-part ball valve with floating ball, full passage Housing made of steel A216 Gr. WCB AISI 316 stainless steel ball Seats made of PTFE + 15% glass fiber Max. Operating pressure: 138 bar (DN 8 to DN 25), 103 bar (DN 32 to DN 50) Connection: weld-in / NPT internal thread ISO mounting flange Fire-safe according to API 607, Part 4 With hand lever made of stainless steel and locking device
	Piston Check Valve - Class 800 # API602 Lid with bolt - reduced

BFE-S24A8 diam. 1"	passage Housing made of A105N Trim 8 (13Cr / HF) NPT thread NACE MR-0175 & ATEX
VR300BCA8-0303 diam. 2"	Check valve - Class 300 # Check valve ANSI 300, full passage Body made of ASTM A216 WCB steel ASTM A216 WCB + 13Cr flap ASTM A105 + Stellite size 6 seat Max. Working pressure: 51 bar Installation length: ISO 5752 Connection: flanged ANSI 300
VR300BCA8-0303 diam. 3"	
VR300BCA8-0303 diam. 4"	
VR300BCA8-0303 diam. 8"	
BFE-S24A8 diam. 1 1/2"	Check valve Fig.S24A8 - Class 800 (marking: BFE) Piston Check Valve - Class 800 # API602 Lid with bolt - reduced passage Housing made of A105N Trim 8 (13Cr / HF) NPT thread NACE MR-0175 & ATEX
VR300BCA8-0303 diam. 12"	Check valve - Class 300 # Check valve ANSI 300, full passage Body made of ASTM A216 WCB steel ASTM A216 WCB + 13Cr flap ASTM A105 + Stellite size 6 seat Max. Working pressure: 51 bar Installation length: ISO 5752 Connection: flanged ANSI 300
VC150BBA8-0303 diam. 14"	Gate valve Fig. VC 150-BB-A-8 - 150 Lbs Gate valve ANSI 150 Housing made of steel A 216 Gr. WCB Slider made of steel A 216 Gr. WCB + ER410 Seat made of A 105 + stellite Max. Working pressure: 19.6 bar Installation length: ISO 5752 Connection: flanged ANSI 150 Lbs With gray cast iron handwheel (2' ~ 14') With worm gear (16' ~ 20')
VC150BBA8-0303 diam. 4"	
BAV2P000107 diam. 2"	Ball valve Fig. 730 AIT / AS / SXM9XXT - ANSI 300: 050 + 16-5966 + 16-5967 + 16-6891
BAV2P000107 diam. 3"	
BAV2P000107 diam. 4"	
BAV2P000107 diam. 6"	
BAV3P000090 diam. 8" x 6"	Ball valve Fig. 7030J A I CG RF / AS / SXM9XXT - 300 # RF: 200 + DIVSO000007 + 16-5967 + DIVXX000034
STRYFI000055 diam. 2"	Inclined seat strainer - A216WCB - mesh size 1 mm - 300RF
STRYFI000055 diam. 6"	
1003A-1528 diam. 1 1/2"	Angular seat strainer Fig. 1003A - NPT - Class 800 Made of A105N steel, support and inner sieve made of AISI 304 stainless steel Connection: NPT internal thread
STRYFI000056 diam. 16"	Inclined seat strainer - A216WCB - mesh size mm - 150 RF
V33H9IIRL diam. 3/4"	Ball valve Fig. V33H-9-IIR / L - Class 300 Three-way ball valve, horizontal, L-borehole Made of stainless steel, seat rings made of PTFE, reinforced Flanged to ANSI 300 Lbs With hand lever
Type 500	Article number : ADA Double-acting pneumatic actuator type ADA Double-acting pneumatic drive Rack & pinion Aluminum body Pivoting movement: 90° ±5° Stroke limitation: ±5° Operating Temperature: - 30°C ~ 100°C Operating pressure: 3 - 8 bar
ES428	
Tht/Cl-90-4t-5.5-120-F-300	
Hct-90-4t-10/Al	
Tht/Cl-90-4t-7.5-140-F-300	

1001a40
Tht/CI-90-4t-4-100-F-300
Hct-100-4t-10/Al
Aba4bb1000583103
Hct-80-4t-5.5/Al
Ckn 322 M4 Noda
Apa1.Aa03cp
Tht/CI-90-4t-10-200-F-300
H412148230
Apa3.Aa3-1
Zlvtf
450148150
Tht/Imp-C-Ini-38-2/4t-1.5-F-300
Dmm362m4s2n0v00(Excpn312m4n0n0e0024vdc
Hgt/CI-125-4t/6-30-180
Hct-90-4t-7.5/Al
Es2153-24vdc
Tht/CI-100-4t-20-240-F-300
Hct-90-4t-4/Al
Type: Dn150 Pn16 Mat C: 1.4408 .:300c
Hc-40-4m/L
Tht/CI-125-4t/6-30-180-F-300
42864800
Hc-35-4m/H
Tht/CI-100-4t-15-220-F-300
H2 811 8812 0
Apa4bb05
Jc516set
Tht/CI-100-4t-10-160-F-300
6.132.012.863
Apa4.Bb10
465 Kc/Pe Pn 16 Dn 25
412148230
Hct-80-4t-4/Al
082d1nonoe
Apa3.B3

Tht/CI-71-4/8t-4-240-F-300
Tht/CI-90-4/8t-5.5-120-F-300
Apa3aa11
Tht/CI-100-4t-15-200-F-300
428648000
Cnp312d1n0n0e
Apa1aa003cp
H4-503-4801-0
150hit
Tht/CI-80-4t-160-F-300
Apa4bd10
Apa3-Aa-5-1
Fig.90 R2\
Tcr/R-2271-4t-F-300
Zl24vdc
Hgt/CI-125-4t/6-75-300
Cnp312d1n0n0e11000vac
Rg865e 15is 100/115
Es423
Type: 1/2 Rg 161 24 Vdc, 25 Imp/Sec, 180 Ohms, 6 Digits
Tht/CI-71-4t-1.5-80-F-300
Apa3-B-5
428648050
Hct-100-4t-15/Al
Zlvt
Hct-100-4t-20/Al
Hct-100-4t-7.5/Al
Kod2 E15
Hct-71-4t-4/Al
281188120
Tht/CI-160-6t/6-40-220-F-300
Saia E15.Z25