

Soemer

Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Soemer Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Soemer Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunulmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.



rn	Aıklama
DAD142.2	measuring amplifier Digital strain gauge measuring amplifier with digital display for DIN rail mounting and the following equipment: Single-channel precision strain gauge measuring amplifier, accuracy 0.001% Approval according to EN 45501:2015 and OIML R76:2006 for 10000d 600 digitizations per second, 2,400 measurements internally Profibus DP interface Dimensioned for up to 6 strain gauge sensors (parallel) with 350 ohms (min. 58 ohms) 6-digit, 5.1 mm LED display and 8 status LEDs mV/V calibration possible, no weights required, accuracy 0.03% 3 optically isolated semiconductor relays, max. load 36 VDC/AC 0.5A 2 optically isolated inputs, 18 ... 36 VDC logic level extensive "free" analysis software (DOP) Power supply: 10 - 30 V DC (4 W) Dimensions: 120 x 105 x 22.5 mm, weight approx. 170 g
3510-C3-500kg-T-10m	Measuring range: 0...500kg Accuracy: C3, custody transfer Resolution: 50g typical (accuracy approx. +/- 50g) Force application: blind hole (option T) Material: stainless steel Protection class: IP68 Cable length: 10m
	Height-adjustable rubber-metal base, consisting of: Stand made of neoprene/stainless steel with M12 fine thread

EBH-SFE-3510-2t	Height adjustable up to 8 mm Ball head force introduction made of hardened stainless steel Safety bracket/loss protection made of stainless steel
Ebh-Sfm-3510	
355-C3	
Qlj	
Lac 65.1	
1020	
Modell 3510-C3	
Pc 3105	