

Solcon

Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Solcon Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Solcon Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunulmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.



rn

Aıklama

[Msr-Hd-P-V-1p-2-0-M-I](#)

Artikelnr.: 700500 Fully equipped, digital, microprocessor-based motor protection relay with 10 PT 100 inputs. Separate alarm and trigger relay for separate detection and MODBUS communication. Occurring Faults that are not recognized by the soft starter are recognized by the MSR. This then opens the Line contactors. With a high short-circuit current that is above the breaking capacity of the contactor, the line contactor remains switched on so that the upstream fuse can switch off the fault current. integrated contacts Programmable multifunction inputs and outputs (optically isolated) - 4 digital inputs - 4 changeover contacts 8A / 250 V. - 4 analog outputs - 4 analog inputs - Modbus - LEDs on, stop, start, run - LED triggering, alarm, relay, A, B, The motor protection relay has the following protective functions:

- (51R) Overcurrent (overload) with adjustable delay
- (50) Overcurrent (short circuit) with adjustable delay (only in connection with circuit breaker and Protective transformers)
- (37) undercurrent with adjustable delay
- (46) current unbalance
- (27) undervoltage with adjustable delay
- (59) Overvoltage with adjustable delay
- (32L) under current release with adjustable delay
- (50G) earth fault alarm with adjustable delay
- (50N) earth fault tripping with adjustable

	delay • (47) phase error • (47) phase sequence • (48) Start time too long • (66) Too many starts • (51L) load increase • (49/51) Thermal overload • (49S / 51) blocked rotor • (49R) Motor overtemperature - thermistor input (Pt100) • (55) Low power factor • (86/94) External error • (3) Internal error • (3) Communication error MSR-HD and MPS 3000 are identical units. It is a motor protection relay.
TSR-K 6	115/230VAC Temperature Protection Relay TSR-K-6 (exchangeable with type Solcon TPR 6/6)
MPS3000	
TPR-6 Temperature Protection Relay	
58-400-E-S	
DIGITAL CARD FOR RVS-DX	
HRVS-DN 140-6300V	
RVS DX 580 400-230-S	
RVS-AX 58 400-N	
RVS-AX 58-400-0-S	
RVS-DN 58	
RVS-DN 580-400-230-0-RU	
RVS-DN 820-230-230-3M-4-9-R-S	
RVS-DN 950	
RVS-DN-1400-230-230-M-R-4-R-U	
RVSDN-170-400-230-230-9-S	
RVS-DN-72-400-230-230-3M+4+9-S	
RVSDXM-590-400-230-S	
RVS DX 72 400-230-H-S	
RVS-DX 460	
Vin: 2x120V / 50-60Hz. Vout: 24V / 250VA	
YUNPEN EMI FILTER YE10T11L2	
ISA HD	
MSR HD	
JCZ5-7.2D/400 IGEL 72D400A230AC	
ETI Un:7.2kV In:125A 004226516	

ETI Un:7.2kV In:125A 004226516	
WO1384282069	
UVC64CD-1F600A	
Vmax	Vmax 12.06.16 16P150+MSM01MCBB1BB2BB3BS2BT1BT2
Rvx-Dx	
Rvs-Dn-72	SOFT START 72AMP
Rvs-Dx 210-400-230-3m 5-8-S Obsolete, Alternative Isa-Ds 210-400-230-3m-5-8- I (Brand Igel Electric)	
Rvs Dx 250kw	
Agma 80r 1 Drum X 210 Kg	
Rvsax-58-400-U-S	
Rvs-Ax 44 400v	
Rvsdx-44-400-230-3m-8-U-S	
Isa-D 72-400-230-230-9-I	
Fsc-T03-2 D24-50-Nc	
Rvs-Dxm 414 - Obsolete, Replaced By Isa-SI3 430-480-230-230-I	
Rvsdx-72-400-115-3m-8-U-S	
Mv05112001 Phase Module	
Rvs-Ax 44 400-N Alternative Isa-A 44- 400 (Another Brand Igel Electric)	
Model: Rvs Ax 145 400s	
Agma Solcon 80r 1 Drum X 210 Kg	
Rvsdx-310-400-230-8-S	
Tpr-6-14-M-O-S	TEMPERATURE PROTECTION RELAY
Fsc-T03-2-200-50-Nc	
Rvs-Dn-145	SOFT START 145AMP
Rvs-Dn 310	
Digital Card For Rvs-Dx	
Dpm 10 (Obsolete - No Replacement)	
Rvs-Ax 31	ANALOG SOFT STARTER, 15KW/31A
Rvsdn-170-400-230-230-9-S	

833455	MOTOR PROTECTION RELAY MPR6 SERIES
Isa-SI3 430-480-230-230-I Ig0021085sl0004	
Dpm 10 (Obsolete - No Replacement) Digital Power Meter	
Rvs-Ax 58 400-N (Alternatives Are Rvsax-58-400-U-S And Rvsdx-72-400- 115-3m-8-U-S)	
Rvs-Dn-1400	SOFT START 1400AMP
Mpr6-5-2-3t-M-S	MOTOR PROTECTION RELAY MPR6 SERIES
Imb 10-400	
Rvs-Dx-44-400-115-0-S	CONTROLLER SOFT START 44AMP 3PH 400V 115V CONTROL
Mv05112001	
Rvs-Dx	
Rvsdx-950 400-230-3m-5-S	
Mpr6-5-1t-0-M-S	MOTOR PROTECTION RELAY MPR6 SERIES