

Sor

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Sor Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Sor T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
9NN-K5-N4-C1A	ADJ. RANGE = 200-1000 PSI OVERRANGE = 2500 PSI PROOF = 6000 PSI ELECTRICAL RATING: 15 AMPS 250 VAC, 5 AMPS 30 VDC 9 = NO. 9 PISTON NN = NEMA 4X (IP65) ALUMINUM HOUSING 3/4 INCH NPT (F) CONDUIT CONN. (CSA ENCLOSURE 4 IF 'CS' OPTION SELECTED). K = SPDT, DEAD BAND FIXED 5 = NO. 5 SPRING N4 = TCP DIAPHRAGM/BUNA-N O-RING C = 316/316LSST PROCESS CONNECTION 1A = 1/4 INCH NPT (F) Weight/approx. 1 kgs/each
101NN-KK45-N4-C1A	SOR DIFFERENTIAL PRESSURE SWITCH ADJ. RANGE = 10-75 PSID OVERRANGE = 500 PSI PROOF = 1000 PSI ELECTRICAL RATING: 15 AMPS 250 VAC, .5 AMPS 125 VDC 101 = NO. 101 PISTON NN = NEMA 4X (IP65) ALUMINUM HOUSING 3/4 INCH NPT (F) CONDUIT CONN. (CSA ENCLOSURE 4 IF 'CS' OPTION SELECTED). KK = DPDT, DEAD BAND FIXED. 45 = NO. 45 SPRING N4 = TCP DIAPHRAGM/BUNA-N O-RING C = 316LSS PROCESS CONNECTION 1A = 1/4 INCH NPT (F) Weight: approx. 1,5 kgs/each Guarantee: 36 months after date of manufacture Customs tariff no.: 90262080
	SOR PRESSURE SWITCH ADJ. RANGE = 45-550 PSI OVERRANGE = 1500 PSI PROOF = 2500 PSI ELECTRICAL

5NN-K45-M1-C2A-TT	RATING: 15 AMPS 250 VAC, 5 AMPS 30 VDC 5 = NO. 5 PISTON NN = NEMA 4X (IP65) ALUMINUM HOUSING 3/4 INCH NPT (F) CONDUIT CONN. (CSA ENCLOSURE 4 IF 'CS' OPTION SELECTED). K = SPDT, DEAD BAND FIXED 45 = NO. 45 SPRING M1 = 316L SS DIAPHRAGM/VITON GLT O-RING C = 316/316LSST PROCESS CONNECTION 2A = 1/2 INCH NPT (F) TT = STAINLESS TAG PERMANENTLY ATTACHED TO HOUSING
17RB-K2-N4-C1A	SOR DIFF. PRESSURE SWITCH - OPPOSED PISTON ADJ. RANGE = 4-15 PSID OVERRANGE = 500 PSI PROOF = 1000 PSI ELECTRICAL RATING: 15 AMPS 250 VAC, 5 AMPS 30 VDC 17 = NO. 17 PISTON RB = NEMA 4X (IP65) ALUMINUM HOUSING WITH ONE 3/4 INCH NPT (F) CONDUIT CONNECTIONS, TERMINAL BLOCK (CSA ENCLOSURE 4 IF 'CS' OPTION SELECTED). K = SPDT, DEAD BAND FIXED 2 = NO. 2 SPRING N4 = TCP DIAPHRAGM/BUNA-N O-RING C = 316/316LSST PROCESS CONNECTION 1A = 1/4 INCH NPT (F) Weight: approx. 1,5 kgs/each
203NN-K105-U9-C7A	SOR TEMPERATURE SWITCH ADJ. RANGE = 300-1000 DEG F OVERRANGE = 1100 DEG F PROOF = 1000 PSI ELECTRICAL RATING: 15 AMPS 250 VAC, 5 AMPS 30 VDC 203 = 6 FEET (1.8 METERS) 316SS CAPILLARY WITH 304SS ARMOUR, 316SS SENSING BULB 0.38 X 4.41 INCHES (9.7 X 112 MM) NN = NEMA 4X (IP65) ALUMINUM HOUSING 3/4 INCH NPT (F) CONDUIT CONN. (CSA ENCLOSURE 4 IF 'CS' OPTION SELECTED). K = SPDT, DEAD BAND FIXED 105 = FILL FLUID NITROGEN, BULB DIMENSIONS CHANGE TO 0.63 X 5.84 INCHES (16 X 148.3MM) ON SENSORS 203, 205, 207, 209. U9 = WELDED DIAPHRAGM (MATCHES PRESSURE PORT MATERIAL) C = 316SS PROCESS CONNECTION 7A = 1/2 INCH NPT (M) Weight: approx. 3 kgs/each Guarantee: 36 months after date of manufacture Customs tariff no.: 90262080
201NN-K115-U9-C7A-TT	SOR TEMPERATURE SWITCH ADJ. RANGE = 150-375 DEG F OVERRANGE = 520 DEG F PROOF = 2300 PSI ELECTRICAL RATING: 15 AMPS 250 VAC, 5 AMPS 30 VDC 201 = DIRECT MOUNT, 316SS SENSING BULB 0.38 X 4.16 INCHES (9.7 X 105.7MM) NN = NEMA 4X (IP65) ALUMINUM HOUSING 3/4 INCH NPT (F) CONDUIT CONN. (CSA ENCLOSURE 4 IF 'CS' OPTION SELECTED). K = SPDT, DEAD BAND FIXED 115 = FILL FLUID FREON U9 = WELDED DIAPHRAGM (MATCHES PRESSURE PORT MATERIAL) C = 316SS PROCESS CONNECTION 7A = 1/2 INCH NPT (M) TT = STAINLESS TAG PERMANENTLY ATTACHED TO HOUSING Weight: approx. 1 kgs/each
BH-023006-023	SOR 101 / 121 DIFFERENTIAL PRESSURE ADJ. RANGE = 3-30 PSID OVERRANGE = 500 PSI PROOF = 1000 PSI ELECTRICAL RATING 15 AMPS AT 250 VAC & 5 AMPS AT 30 VDC Customs tariff no.: 90262080
BH-036001-036	SOR 101 / 121 DIFFERENTIAL PRESSURE SWITCH ADJ. RANGE = 3-30 PSID OVERRANGE = 500 PSIPROOF = 1000 PSI ELECTRICAL RATING 5 AMPS AT 250 VAC & 5 AMPS AT 30 VDC
BH-036006-036	SOR 2-PISTON DIFFERENTIAL PRESSURE SWITCH ADJ. RANGE = 5-60 PSID OVERRANGE = 500 PSIPROOF = 1000 PSI ELECTRICAL RATING 5 AMPS AT 250 VAC & 5 AMPS AT 30 VDC

101NN-K3-H4-C1A	SOR 101 / 121 DIFFERENTIAL PRESSURE SWITCH ADJUSTABLE RANGE = 3-30 PSID OVERRANGE = 500 PSI PROOF = 1000 PSI ELECTRICAL RATING 15 AMPS AT 250 VAC & 5 AMPS AT 30 VDC ----- 101 (Piston) = NO. 101 PISTON NN (Housing) = NEMA 4X (IP65) ALUMINUM HOUSING 3/4 INCH NPT (F) CONDUIT CONN. (CSA ENCLOSURE 4 IF 'CS' OPTION SELECTED). K (Switch) = SPDT, DEAD BAND FIXED. 3 (Spring) = NO. 3 SPRING H4 (Diaphragm and O-Ring) = HAST B DIAPHRAGM/ VITON O- RING C (Pressure Port Material) = 316/316LSST PROCESS CONNECTION 1A (Pressure Port Size and Type) = 1/4 INCH NPT (F)
PRESSURE SWITCH 403213 090069	
SOR PRESSURE SWITCH 6NN-K3-N4-C1A	
SWITCH PRESSURE 1NN EE45 M4 C2A	
SWITCH PRESSURE 74V1 K118 N4 B1A	
SWITCH TEMPERATURE 101NN K3 N4 C1A TTVVPK	
SWITCH PRESSURE 9NN KK5 N4 C1A	
Xts203	DC PWR SUPPLY
403213 090069 107al-N40-P1-F1a	
Dcr40-60a	POWER SUPPLY
Bh 013045 013	
201rn-Ee115-U9-C7a-Tt	
5ah-Ef3-M2-C2a-Yy	MINI-HERMET PRESSURE SWITCH
403212 Q9c069	
Xg150-11.2	1690W DC POWER SUPPLY
Dcr600-3b	POWER SUPPLY
103ad-Eg805-N1-C2a	PRESSURE SWITCH DIFFERENTIAL 100-1000 INCHES WC
6nn-K3-N4-F1a-Ttx371	
5nn K45 M1 C2a Tt	
12b4-Ee4-U9-C2a-Cl	
Dcr16-310t	POWER SUPPLY 0-16V 0-325A DC
44v1-K4-N4	
205lcee125u9c7ay	TEMP SWITCH

Dlm30010e	POWER SUPPLY
Dcrt16625t5	DC PWR SUPPLY
Sga40025c1aaa	POWER SUPPLY
12b4ee4u9c2a	SWITCH
6nn-Ee45-M4-Cia-Ttx	
Srl6035a	POWER SUPPLY
Sga-160/31d0-Oaaaab	POWER SUPPLY
303-14-3x S/N 331480102	
54rm-K118m4	
101nn-K3-M4-C1a-Tt	
103ad-Af212-N4-C1a	PRESSURE SWITCH DIFFERENTIAL
Qrd601	POWER SUPPLY
44v1-K4t-N4-C1a	
Ptm-15-.8d	POWER SUPPLY
5nn-K45-N4-F1a	
103ad-Eg805-N5-C1a-Rr	PRESSURE SWITCH DIFFERENTIAL
6nn-K3-M4-C2a	
12nn K614 N4 B1a	
03572020001	CONTROL
Dcs8037e	POWER SUPPLY
1nn-K45-54-C1a	
Xts154m5	DC PWR SUPPLY
101nn-K3-N4-C1a-Rr	
403213 090069	
Dcs20-150e	POWER SUPPLY RACK MOUNT 150AMP 20V
201nn-125-U9-C7a	
4nn-K5-M4-C2a	
101l-K3-N4c1a	
Dcr300-9b	POWER SUPPLY DC 0-300V
12b4ee4u9c2acl	SWITCH
203sck125u9c7att	TEMP SWITCH

Xts302	DC PWR SUPPLY
6nn-K3-N4-Tin	
Dcr6004	POWER SUPPLY
17rb-Ee3-N4-C1a	SOR DIFF. PRESSURE SWITCH - OPPOSED PISTON RANGE: 5-60 PSID OVERRANGE: 500 PSI PROOF: 1000 PSI ELECTRICAL RATING: 5 AMPS 250 VAC, 5 AMPS 30 VDC 17 = NO. 17 PISTON RB = NEMA 4X (IP66) ALUMINUM HOUSING WITH ONE 3/4 INCH NPT (F) CONDUIT CONNECTIONS, TERMINAL BLOCK (CSA ENCLOSURE 4 IF 'CS' OPTION SELECTED). EE = DPDT, DEAD BAND FIXED. 3 = NO. 3 SPRING N4 = TCP DIAPHRAGM/BUNA-N O-RING C = 316/316LSST PROCESS CONNECTION 1A = 1/4 INCH NPT (F)
Sgi600x25e-1caa	POWER SUPPLY DC RACK MOUNT 25AMP 15KW 0-600VDC
Dcr150-12m35	POWER SUPPLY 198-242 V 50-63 HZ 14.5
Dlm150-4m9g	POWER SUPPLY LINEAR BENCHTOP 600W 0-4AMP 0-150V
205lcee115u9c7ay	TEMP SWITCH
Dcs-150-7e	POWER SUPPLY DIGITAL 0-150V 0-7AMP
12nn K4 N1 C2a	
4nn-K5-M4-C2a-Tt	
1nn-K45-M4-C1a	
201nn-K115-U9-C7a-Tt	
209lcee115u9c7ay	TEMP SWITCH
Dlm22180	POWER SUPPLY
99v2ef5m4c2att	PRESSURE SW
522cr-Tc51-P6-C2a-Vt	ELECTRONIC PRESSURE SWITCH
Dcr600	POWER SUPPLY
10nn-K3-M4-C1a	
371u-1.16-C3a	
12l-K614-U8-C2a-Cgx	PRESSURE SWITCH
Xts154	DC PWR SUPPLY
6nn-K3-N4-F1a	
5nn-K45-N4-F1a-Rr	
4nn-Ee-4-N4-C2a	
Dcs3004e	POWER SUPPLY

54nn-Ee118-M4-C2a	
Bh009046009	CONTROLLER
203nn-K105-U9-C7a	
6bh-Eg-3-U8-C2a-Ttx	
Xts302m5	DC PWR SUPPLY
6bh-Jf3-M1-C2a-Hbme	
205b3-Eg115-U8-C7a-Ttyyvw	TEMPERATURE SWITCH 5AMP 250V 150-375DEG F 2300PSI
17b-K5-N4-C2a	OPPOSED PISTON DIFFERENTIAL PRESSURE SWITCH
3aheg45s1c1a	PRESSURE SW
4nn-K4-M4-C2a-Tt	
6nn-K3-M4-C2a-Tt	
Dcr150-6b	POWER SUPPLY 103-127V 50-60HZ 15.5AMP INPUT
Dcr10-120b	POWER SUPPLY
12l-K614-U8-C2a-Cg-C1	PRESSURE SWITCH
Xts76	DC PWR SUPPLY
Dcr-40-20a	POWER SUPPLY 0-40V 0-20AMP
205a-A1b-B-Y4-N4-Fe-Tt	
22tak2n4c1a	SWITCH
403213 Q8f018- Alternative- 107al-N40-P1-F1a	
1520b-F5a-C-W9-Ef	
201v1-Aa125-U9-C7a-Cs	TEMP SWITCH
9013013	CONTROL
Dcr208ob	DC PWR SUPPLY
Dcr150-15a	POWER SUPPLY
Bh 013011 013	
103ad-Ef212-N4-C1a-Tt-Tb	PRESSURE SWITCH DIFFERENTIAL 7-100 INCHES WC
124ba-Kb4-U9-C6a	PRESSURE SWITCH
Dcs2050em1m130	POWER SUPPLY
Xfr10028	POWER SUPPLY
Xt 250-0.25/Mga/M13a/M2 Cal Du	XT 250-0.25/MGA/M13A/M2 CALIBRATED W/ DATA + UNCERT

101b3p45m4c1xttw	DIFF PRESS SW
6nn-K2-M4-C1a	
12nn-K4-N4-B1a	
44v1 K4 N4 C1a	
54nn-K118-M1-C2a-Tt	
101nn-Ee3-M4-C1a	
403213 090069	
403213 Q9c069 107al-N40-P1-F1a-	
101rm-Ee45	
101rm-K3-N4-C1a-X	
4v3-Ag4-N4-C1a-Yy	PRESSURE SWITCH 5-25PSI OVRRG 750PSI PROOF 1000PSI
55v2-Af45-M1-Cia-Tt	PRESSURE SWITCH
15rb-K2-M4-C2a	
103w1ee212n1c	SWITCH
9bh-Jf5-M1-C2a-Hbme	
209lckk105u9c7a	SWITCH
107al-N40-P1-F1a-	
103ad-Eg212-N1-C2a	PRESSURE SWITCH DIFFERENTIAL 7-100 INCHES WC