

Sor Inc

Garanti: 12 ay

Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

Sor Inc Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Sor Inc Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

| rn | Aıklama |
|----------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 4NN-K45-N4-B1A | SOR PRESSURE SWITCH ADJ. RANGE = 0.3-5 BAR OVERRANGE = 50 BAR PROOF = 70 BAR ELECTRICAL RATING: 15 AMPS 250 VAC, 5 AMPS 30 VDC 4 = NO. 4 PISTON NN = NEMA 4X (IP65) ALUMINUM HOUSING 3/4 INCH NPT (F) CONDUIT CONN. (CSA ENCLOSURE 4 IF 'CS' OPTION SELECTED). K = SPDT, DEAD BAND FIXED 45 = NO. 45 SPRING N4 = TCP DIAPHRAGM/BUNA-N O-RING B = ALUMINUM PROCESS CONNECTION 1A = 1/4 INCH NPT (F) Weight: approx. 1 kgs/each |
| 4NN-K45-N4-C1A | SOR PRESSURE SWITCH ADJ. RANGE = 4-75 PSI OVERRANGE = 750 PSI PROOF = 1000 PSI ELECTRICAL RATING: 15 AMPS 250 VAC, 5 AMPS 30 VDC 4 = NO. 4 PISTON NN = NEMA 4X (IP65) ALUMINUM HOUSING 3/4 INCH NPT (F) CONDUIT CONN. (CSA ENCLOSURE 4 IF 'CS' OPTION SELECTED). K = SPDT, DEAD BAND FIXED 45 = NO. 45 SPRING N4 = TCP DIAPHRAGM/BUNA-N O-RING C = 316/316LSST PROCESS CONNECTION 1A = 1/4 INCH NPT (F) Weight: approx. 1 kgs/each |
| 101L-K3-N4C1A | |
| 101NN K45 N4 C1A | |
| 101NN-K3-M4-C1A-TT | |
| 101NN-K3-N4-C1A | |
| 101NN-K3-N4-C1A-RR | |
| 101RN-EE3-M4-C1A-TTB1X | |
| 101RN-EE3-N4-C1A- | |
| 101RN-EE45 | |
| 101RN-K3-N4-C1A-X | |
| 103W1-EE212-N1-C1A-TT | |
| 103W1-K502-N4-C1A-RRC1 | |

| |
|-----------------------------------------|
| 107AL-K12-P1-F1A- |
| 107AL-N40-P1-F1A |
| 10NN-K3-M4-C1A |
| 12B4-EE4-U9-C2A-CL |
| 12B4-JF2-M4-C2A-TTCLA5 |
| 12LC-KK5-N4-C2A-TT |
| 12LC-KL-M2-C2A |
| 12NN-K4-N1-C2A |
| 12NN-K614-M4-C1A-X |
| 12NN-K614-N4-B1A-C1 |
| 12RN-EE45-M4-C2A-TTB1X |
| 1530B-G2A-C-J0-PS-TT |
| 15RB-K2-M4-C2A |
| 1B4-K45-M4-C1A-PBTTCLA5 |
| 1NN-K45-N4-F1A-YY |
| 201NN K125U9 C7A |
| 201RN-EE115-U9-C7A-TT |
| 203NN-K105-U9-C7A |
| 206A A1B B Y4 N4 TTX |
| 221A A1B B B4 N4 TTX |
| 221A-A1B-B-B4-N4 |
| 403212-08F019 |
| 403213-Q8F019 |
| 44V1-K4T-N4-C1A |
| 4LC-K4-M2-C2A |
| 4NN - K4 - N4 - B1A |
| 4NN-K5-N4-B1A |
| 4NN-K5-N4-C2A |
| 54NN - K118 - M4 - B1A |
| 5B3 K3 N4 C2A CL |
| 5LC-EE45-M2-C2A |

| |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 5L-EE5-M4-C7A-TTNCC4X |
| 5NN-K3-N4-C2A |
| 6LC-K3-N4-F1A- |
| 6N6-T2-M2-C2A |
| 6N6-T45-M2-C2A |
| 6NN K45 M1 C2A TT |
| 6NN-K2-N4-C1A |
| 6NN-K2-N4-F1A |
| 6NN-K3-M4-C2A-TT |
| 6NN-K3-M9-C2A-PKX3 |
| 6NN-K3-N4-C2A |
| 6NN-K3-N4-F1A |
| 6NN-K3-N4-F1A-TT |
| SOR PRESSURE SWITCH ADJ. RANGE = 12-100 PSI OVERRANGE = 1500 PSI PROOF = 2500 PSI ELECTRICAL RATING 15 AMPS AT 250 VAC & 5 AMPS AT 30 VDC 6 = NO. 6 PISTON NN = NEMA 4X (IP65) ALUMINUM HOUSING 3/4 INCH NPT (F) CONDUIT CONN. (CSA ENCLOSURE 4 IF 'CS' OPTION SELECTED). K = SPDT, DEAD BAND FIXED. 3 = NO. 3 SPRING N4 = TCP DIAPHRAGM/BUNA-N O-RING F = CARBON STEEL PROCESS CONNECTION 1A = 1/4 INCH NPT (F) TT = STAINLESS TAG PERMANENTLY ATTACHED TO HOUSING Weight: approx. 1 kgs/each |
| 6NN-K3-N4-TIN |
| 6NN-K45-N4-F1A |
| 6NN-K5-M4E2A-TT |
| 6NN-T2-M2-C2A-PBMMYYRR |
| 6RN-T2-M2-C2A-PBMMYYRR |
| 701K1-U-P6-C-CS -X |
| 701K1-U-P6-C-CSC |
| 733A-F4C-T6-TTNCMR-X |
| 74V1-K118-N4-C1A |
| 99V1- K5 - N4 - B1A |
| 99V1-K45-S1-C1A |
| 9NN - K45- N4 - F1A |

| | |
|-------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 9NN - K5- N4 - F1A | |
| BBH-02202-022 | |
| BH 009047 009 | |
| BH 013017-013 | |
| BH-001007-001 | |
| BH-003001-003 | |
| BH-003011-003 | |
| BH-013008-013 | |
| BH-022005-022 | |
| BH-023047-023 | |
| BH-031001-031 | |
| BH-031058-031 | |
| BH-048015-048 | |
| BH-048022-048 | |
| BH-412002-412 | |
| BH-417011-417 | |
| BH-003013-003 | SOR PRESSURE SWITCH (GENERAL) SET POINT = MID RANGE KPA ADJ. RANGE = 170-1655 KPA OVERRANGE = 10340 KPA PROOF = 17235 KPA ELECTRICAL RATING 5 AMPS AT 250 VAC & 5 AMPS AT 30 VDC |
| 3rs-Ka45-P1-C2a-Tt | |
| 104a-C1p-B-X4-N4-Etmrttx8 | |
| 5nn Kk45 N4 C1a | |
| 104a-Aip-B-X4-Etmrttx8 | |
| 101nn-Ee3-M4-C1a-Tt | |
| 101nn-Kk3-N4-C1a | |
| 104a-A1xb-X4-N4-Mrttx7 | |
| 6104a-A1pb-X4-N4-Emrttx8 | |
| 6nn K2 N1 F1a | |
| 103-Aic-B-X4-N4-Etmrttx8 | |
| 122a-A1d-B-X4-N4-Mrttx7 | |
| 5nn K45 M1 C2a | |

| | |
|-------------------------------------------|------------------------------------------------------------------------------------------------------------|
| 121a-A1c-B-S4-N4-Mrttx8 | |
| 6rn-Jx3-M4-C2a-Pkpyc1c4x3 | |
| 4405-120-3s | |
| 4l-K5-N4-C2a-Tt | |
| 103a-A1d-B-X4-N4-Bqmrmtx8 | |
| 5104a-Aie-B-X4-N4-Emrttx8 | |
| 414841-Zxsg08 | |
| 103a-A1c-B-X4-N4-Bpmrttx8 | |
| 6nn-Kk5-N4-C1a-Yyffts | |
| 9nn-K5-N4-C1a | |
| 6nn-K3-N4-C1a | |
| 12nn-T614-M4-B1a | |
| BH-003010-003 | SOR RF LEVEL TRANSMITTER - MULTIPOINT LEVEL (660) PROBE LENGTH = 25 INCHES Weight: approx. 7,5 kgs/each |
| 83414841-Zxsg08 | |
| 4nn-Kk45-N4-C1a-Sytl | |
| Bh-023016-023 | |
| 4nn-K45-N4-C1a | |