

## Sor Inc

Garanti: 12 ay

Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

**Sor Inc** Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

*Firmamız Sor Inc Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.*

rn	Aıklama
<a href="#">4NN-K45-N4-B1A</a>	SOR PRESSURE SWITCH ADJ. RANGE = 0.3-5 BAR OVERRANGE = 50 BAR PROOF = 70 BAR ELECTRICAL RATING: 15 AMPS 250 VAC, 5 AMPS 30 VDC 4 = NO. 4 PISTON NN = NEMA 4X (IP65) ALUMINUM HOUSING 3/4 INCH NPT (F) CONDUIT CONN. (CSA ENCLOSURE 4 IF 'CS' OPTION SELECTED). K = SPDT, DEAD BAND FIXED 45 = NO. 45 SPRING N4 = TCP DIAPHRAGM/BUNA-N O-RING B = ALUMINUM PROCESS CONNECTION 1A = 1/4 INCH NPT (F) Weight: approx. 1 kgs/each
<a href="#">4NN-K45-N4-C1A</a>	SOR PRESSURE SWITCH ADJ. RANGE = 4-75 PSI OVERRANGE = 750 PSI PROOF = 1000 PSI ELECTRICAL RATING: 15 AMPS 250 VAC, 5 AMPS 30 VDC 4 = NO. 4 PISTON NN = NEMA 4X (IP65) ALUMINUM HOUSING 3/4 INCH NPT (F) CONDUIT CONN. (CSA ENCLOSURE 4 IF 'CS' OPTION SELECTED). K = SPDT, DEAD BAND FIXED 45 = NO. 45 SPRING N4 = TCP DIAPHRAGM/BUNA-N O-RING C = 316/316LSST PROCESS CONNECTION 1A = 1/4 INCH NPT (F) Weight: approx. 1 kgs/each
<a href="#">101L-K3-N4C1A</a>	
<a href="#">101NN K45 N4 C1A</a>	
<a href="#">101NN-K3-M4-C1A-TT</a>	
<a href="#">101NN-K3-N4-C1A</a>	
<a href="#">101NN-K3-N4-C1A-RR</a>	
<a href="#">101RN-EE3-M4-C1A-TTB1X</a>	
<a href="#">101RN-EE3-N4-C1A-</a>	
<a href="#">101RN-EE45</a>	
<a href="#">101RN-K3-N4-C1A-X</a>	
<a href="#">103W1-EE212-N1-C1A-TT</a>	
<a href="#">103W1-K502-N4-C1A-RRC1</a>	

[107AL-K12-P1-F1A-](#)

[107AL-N40-P1-F1A](#)

[10NN-K3-M4-C1A](#)

[12B4-EE4-U9-C2A-CL](#)

[12B4-JF2-M4-C2A-TTCLA5](#)

[12LC-KK5-N4-C2A-TT](#)

[12LC-KL-M2-C2A](#)

[12NN-K4-N1-C2A](#)

[12NN-K614-M4-C1A-X](#)

[12NN-K614-N4-B1A-C1](#)

[12RN-EE45-M4-C2A-TTB1X](#)

[1530B-G2A-C-J0-PS-TT](#)

[15RB-K2-M4-C2A](#)

[1B4-K45-M4-C1A-PBTTCLA5](#)

[1NN-K45-N4-F1A-YY](#)

[201NN K125U9 C7A](#)

[201RN-EE115-U9-C7A-TT](#)

[203NN-K105-U9-C7A](#)

[206A A1B B Y4 N4 TTX](#)

[221A A1B B B4 N4 TTX](#)

[221A-A1B-B-B4-N4](#)

[403212-08F019](#)

[403213-Q8F019](#)

[44V1-K4T-N4-C1A](#)

[4LC-K4-M2-C2A](#)

[4NN - K4 - N4 - B1A](#)

[4NN-K5-N4-B1A](#)

[4NN-K5-N4-C2A](#)

[54NN - K118 - M4 - B1A](#)

[5B3 K3 N4 C2A CL](#)

[5LC-EE45-M2-C2A](#)

<a href="#">5L-EE5-M4-C7A-TTNCC4X</a>
<a href="#">5NN-K3-N4-C2A</a>
<a href="#">6LC-K3-N4-F1A-</a>
<a href="#">6N6-T2-M2-C2A</a>
<a href="#">6N6-T45-M2-C2A</a>
<a href="#">6NN K45 M1 C2A TT</a>
<a href="#">6NN-K2-N4-C1A</a>
<a href="#">6NN-K2-N4-F1A</a>
<a href="#">6NN-K3-M4-C2A-TT</a>
<a href="#">6NN-K3-M9-C2A-PKX3</a>
<a href="#">6NN-K3-N4-C2A</a>
<a href="#">6NN-K3-N4-F1A</a>
<a href="#">6NN-K3-N4-F1A-TT</a>
SOR PRESSURE SWITCH ADJ. RANGE = 12-100 PSI OVERRANGE = 1500 PSI PROOF = 2500 PSI ELECTRICAL RATING 15 AMPS AT 250 VAC & 5 AMPS AT 30 VDC 6 = NO. 6 PISTON NN = NEMA 4X (IP65) ALUMINUM HOUSING 3/4 INCH NPT (F) CONDUIT CONN. (CSA ENCLOSURE 4 IF 'CS' OPTION SELECTED). K = SPDT, DEAD BAND FIXED. 3 = NO. 3 SPRING N4 = TCP DIAPHRAGM/BUNA-N O-RING F = CARBON STEEL PROCESS CONNECTION 1A = 1/4 INCH NPT (F) TT = STAINLESS TAG PERMANENTLY ATTACHED TO HOUSING Weight: approx. 1 kgs/each
<a href="#">6NN-K3-N4-TIN</a>
<a href="#">6NN-K45-N4-F1A</a>
<a href="#">6NN-K5-M4E2A-TT</a>
<a href="#">6NN-T2-M2-C2A-PBMMYYRR</a>
<a href="#">6RN-T2-M2-C2A-PBMMYYRR</a>
<a href="#">701K1-U-P6-C-CS -X</a>
<a href="#">701K1-U-P6-C-CSC</a>
<a href="#">733A-F4C-T6-TTNCMR-X</a>
<a href="#">74V1-K118-N4-C1A</a>
<a href="#">99V1- K5 - N4 - B1A</a>
<a href="#">99V1-K45-S1-C1A</a>
<a href="#">9NN - K45- N4 - F1A</a>

<a href="#">9NN - K5- N4 - F1A</a>	
<a href="#">BBH-02202-022</a>	
<a href="#">BH 009047 009</a>	
<a href="#">BH 013017-013</a>	
<a href="#">BH-001007-001</a>	
<a href="#">BH-003001-003</a>	
<a href="#">BH-003011-003</a>	
<a href="#">BH-013008-013</a>	
<a href="#">BH-022005-022</a>	
<a href="#">BH-023047-023</a>	
<a href="#">BH-031001-031</a>	
<a href="#">BH-031058-031</a>	
<a href="#">BH-048015-048</a>	
<a href="#">BH-048022-048</a>	
<a href="#">BH-412002-412</a>	
<a href="#">BH-417011-417</a>	
<a href="#">BH-003013-003</a>	SOR PRESSURE SWITCH (GENERAL) SET POINT = MID RANGE KPA ADJ. RANGE = 170-1655 KPA OVERRANGE = 10340 KPA PROOF = 17235 KPA ELECTRICAL RATING 5 AMPS AT 250 VAC & 5 AMPS AT 30 VDC
<a href="#">3rs-Ka45-P1-C2a-Tt</a>	
<a href="#">104a-C1p-B-X4-N4-Etmrttx8</a>	
<a href="#">5nn Kk45 N4 C1a</a>	
<a href="#">104a-Aip-B-X4-Etmrttx8</a>	
<a href="#">101nn-Ee3-M4-C1a-Tt</a>	
<a href="#">101nn-Kk3-N4-C1a</a>	
<a href="#">104a-A1xb-X4-N4-Mrttx7</a>	
<a href="#">6104a-A1pb-X4-N4-Emrttx8</a>	
<a href="#">6nn K2 N1 F1a</a>	
<a href="#">103-Aic-B-X4-N4-Etmrttx8</a>	
<a href="#">122a-A1d-B-X4-N4-Mrttx7</a>	
<a href="#">5nn K45 M1 C2a</a>	

<a href="#">121a-A1c-B-S4-N4-Mrttx8</a>	
<a href="#">6rn-Jx3-M4-C2a-Pkpyc1c4x3</a>	
<a href="#">4405-120-3s</a>	
<a href="#">4l-K5-N4-C2a-Tt</a>	
<a href="#">103a-A1d-B-X4-N4-Bqmrmtx8</a>	
<a href="#">5104a-Aie-B-X4-N4-Emrttx8</a>	
<a href="#">414841-Zxsg08</a>	
<a href="#">103a-A1c-B-X4-N4-Bpmrttx8</a>	
<a href="#">6nn-Kk5-N4-C1a-Yyffts</a>	
<a href="#">9nn-K5-N4-C1a</a>	
<a href="#">6nn-K3-N4-C1a</a>	
<a href="#">12nn-T614-M4-B1a</a>	
<a href="#">BH-003010-003</a>	SOR RF LEVEL TRANSMITTER - MULTIPOINT LEVEL (660) PROBE LENGTH = 25 INCHES Weight: approx. 7,5 kgs/each
<a href="#">83414841-Zxsg08</a>	
<a href="#">4nn-Kk45-N4-C1a-Sytl</a>	
<a href="#">Bh-023016-023</a>	
<a href="#">4nn-K45-N4-C1a</a>	