

## Standard Pump

Garanti: 12 ay  
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Standard Pump** Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

*Firmamız Standard Pump Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.*



rn	Aıklama
<a href="#">1608</a>	
<a href="#">833</a>	
<a href="#">P-280P-2</a>	
<a href="#">SP-ENC-2-V</a>	
<a href="#">SP-PP-HH</a>	
<a href="#">SP-PVDF-47</a>	
<a href="#">SP-SS-39</a>	
<a href="#">st 1.8-85</a>	
<a href="#">SP-280P-2</a>	electric motor 230-240V, 50-60Hz, 825W IP44 USP, with undervoltage release, without speed control, with motor cable with plug Electric Motor 230-240V, 50-60HZ, 825W IP44 LVR With low voltage release Without speed control With motor cable and plug HS code 8413.406040
	Electric Motor 230-240V, 50-60HZ, 825W IP44 LVR With low

### Standard Pump

YURSAT yedek para tedariki yapan bir Őirkettir. Sitemizde bulunan markaların yetkili distribtr yada temsilcisi deĐildir.

<a href="#">SP-280P-2</a>	voltage release Without speed control With motor cable and plug
<a href="#">SP-7600-47</a>	Pump tube 1200 mm - 47" Shaft Stainless Steel, Hose connection 1 1/4" for 1" hose, max. Temp. 80°C, AtEx 40°C Pump mechanism stainless steel 1200 mm Shaft stainless steel, connection 1 1/4" for hose1"
<a href="#">SP-280P-2-V</a>	electric motor 230-240V, 50-60Hz, 825W IP44 USP, with undervoltage release, with speed control, with motor cable with plug Electric Motor 230-240V, 50-60HZ, 825W IP44 With low voltage release With speed control With motor cable and plug HS code 8413.406040
<a href="#">SP-280P-2-V</a>	Electric Motor 230-240V, 50-60HZ, 825W IP44 With low voltage release With speed control With motor cable and plug
<a href="#">SP-PVDF-39</a>	Pump tube PVDF 1000 mm - 39" Shaft Hastelloy, Hose connection 1 1/4" for 1" hose, max. Temp. 80°C,
<a href="#">Sp-280p-2 Drum-Pump-Motor, Open Drip Proof (Ip44), 220-240v/1/50-60hz, 825 Watts, Lvr</a>	
<a href="#">Sp-Pp-39</a>	
<a href="#">Sp-Pvdf-39</a>	
<a href="#">Sp-800sr-751p-39</a>	
<a href="#">Snm 32-125 Snã 11114</a>	
<a href="#">Sp-Enc-2-V Drum-Pump-Motor, 230-240v/50-60hz, Tefc (Ip54), 825 Watts, Variable Speed</a>	
<a href="#">1608 Impeller For Pp-Pipeteil</a>	
<a href="#">Sp-Pp-39 Die Pumpe Drum-Pump, Polypropylene, 39 (1000 Mm), Hastelloy-Shaft, High Volume Version</a>	
<a href="#">Sp-Enc-2-V Motor (Ip54) With Variable Speed</a>	
<a href="#">Sp-Pvdf-47 Pump Tube</a>	
<a href="#">Type: Snm 32-125</a>	
<a href="#">Lh-9032</a>	
<a href="#">Sp-Ss-39 Pumpe (1000mm, Aisi316)</a>	
<a href="#">Sp-Ss-39 Pumpe Sp-Ss-39 (1000mm, Aisi316)</a>	
<a href="#">835</a>	
<a href="#">Sp-280p-2 Motor Ip44, 825vt, 220v</a>	

<a href="#">835 Installation</a>
<a href="#">9034m-A</a>
<a href="#">P-280p-2 Standard Pump Motor, Open Drip Proof, Ip44220-240v, 1-Phase, 50-60hz, 825 Wattssingle Speed</a>
<a href="#">Sp-Pvdf-47 Pumpe (1200mm, Pvdf)</a>
<a href="#">Sp-800sr</a>
<a href="#">Sp-Pp-39 Sp-Pp-39 (Length 1000mm)</a>
<a href="#">833 Tri-Clamp</a>
<a href="#">Sp-280p-2</a>
<a href="#">Sp-Ss-39 Pumpe (Length 1000mm)</a>
<a href="#">Dd700-181-39-T</a>
<a href="#">Sp-Pp-39 Drum-Pump, Polypropylene, 39" (1000 Mm), Hastelloy-Shaft, High Volume Version</a>
<a href="#">Sp-280p-2 Motor Sp-280p-2 (Ip44, 825 0,825 Kw 220v)</a>
<a href="#">Sp-800sr-751p-39 Pumpwerk Edelstahl Ss316l, 3a, 39" (1000 Mm), Stator Ptfe, 9,0 Kg</a>