

Standard Pump Inc

Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Standard Pump Inc Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Standard Pump Inc Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.



rn	Aıklama
Sp-502	STANDARD SANITARY ELECTRIC MOTOR TEFC (IP55), FOOD PROCESSING EPOXYPAINT- 230/460V/3/60 HZ., 0.75 HP, 900 RPM, 380-415V/3/50 HZ., 0.55 KW, 750 RPM, 90
9510	STANDARD PUMP PACKAGE 5 FOR CONCENTRATED ACIDS ALKALIES MEASUREMENT 110-120V PACKAGE (1)SP-ENC-V MOTOR, (1)SP-PVDF-39 POLYPRO PUMP TUBE, (1) 9028 HA
Sp-700sr-1851-P-39	47 INCHES LONG. BUNA STATOR. 7000 CPS VISCOSITY MAX.SPEC
9610exp	XP MOTOR TYPE: EXP (IP 54)PUMP ASSEMBLY: SS316PUMP LENGTH: 39 (1000 MM) OR 47 (1200 MM)HOSE: 6 FT. (1,8M), I.D. 1" (25 MM)
9415	STANDARD PUMP PACKAGE 6 SP-280P-2-V ELECTRIC MOTOR WITH 316SS 39 INCH DRUM PUMP TUBE.INCLUDES 6 FT PVC HOSE, 1 INCH SS DISPENSING NOZZLE, 304SS BARREL
Sp-700sr-752p-39	39 INCHES LONG. VITON STATOR. 25,000 CPS VISCOSITY M
	STANDARD FLOW METER ASSEMBLY BATTERY-OPERATED 9 VDC IN-LINE F200 PADDLEWHEEL FLOW METER ASSEMBLY

F200kitss	WITH 316 SS FLOW CHAMBER 1 INCH HOSE BARB CONNECTIONS
Sp-700dd-752-B-47	47 INCHES LONG. BUNA STATOR. 100,000 CPS VISCO
Bc-Enc-Pp-47	STANDARD BATCH CONTROL SYSTEM POLYPRO 47 INCH LONG DRUM PUMP TUBE WITH TEFC 115 VAC 60 HZ MOTOR RATED 825 W.INCLUDES 16 FT POWER CORD WITH US 115 VAC
Bc-Enc-Pp-27	STANDARD BATCH CONTROL SYSTEM POLYPRO 27 INCH LONG DRUM PUMP TUBE WITH TEFC 115 VAC 60 HZ MOTOR RATED 825 W.INCLUDES 16 FT POWER CORD WITH US 115 VAC
9611_Standardpumppackage9	STANDARD PUMP PACKAGE 9 (220-240V) (1) SP-SS-39, (1) SP-420EX, (1) 9026 316SS HAND NOZZLE, (1) 9006 WALL BRACKET, (1) 9002 304SS BARRELADAPTOR, (6 FT)
Sp-420ex	STANDARD DRUM PUMP MOTOR EXPLOSION-PROOF MOTOR 600 WATT 220-240V, SINGLE PHASE, 50-60 HZ, 0.3 HP.FOR USE WITH STAINLESS STEEL PUMP TUBES ONLY. ATEX/CE
Sp-700dd-1851p-39	39 INCHES LONG. PTFE STATOR. 10,000 CPS VISCO
F200pp-B	STANDARD PUMP DIGITAL FLOW METER BATTERY-OPERATED 9 VDC DIGITAL IN-LINE F200 FLOW METER WITH 1 INCH BARBED CONNECTIONS. POLYPROPYLENE FLOW CHAMBER
Sp-700dd-752-P-39	39 INCHES LONG. PTFE STATOR. 100,000 CPS VISCO
Bc-Enc-Pp-39	STANDARD BATCH CONTROL SYSTEM POLYPRO 39 INCH LONG DRUM PUMP TUBE WITH TEFC 115 VAC 60 HZ MOTOR RATED 825 W.INCLUDES 16 FT POWER CORD WITH US 115 VAC
7610	STANDARD BATCH CONTROLLER
Sp-Ss-72	STANDARD DRUM PUMP TUBE STAINLESS STEEL HIGH VOLUME 39 INCHES LONG, FLOUROPOLYMER BEARINGS, HIGH VOLUME, SEAL-LESS DESIGN, SS316 SHAFT
Sp-700dd-751-P-39	39 INCHES LONG. PTFE STATOR. 100,000 CPS VISCO
Sp-700sr-751p-39	39 INCHES LONG. BUNA STATOR. 25,000 CPS VISCOSITY M
Sp-700dd-752-P-47	47 INCHES LONG. FLOUROPOLYMER (PTFE) STATOR. 100,000
Sp-522	STANDARD SANITARY ELECTRIC MOTOR TEFC (IP55), FOOD PROCESSING EPOXY PAINT- 230/460V/3/60 HZ., 1.5 HP, 900RPM, 380-415V/3/50 HZ., 1.1 KW, 750RPM, 100LC
9422	SPECIAL FOR AGGRESSIVE LIQUIDS AND CONCENTRATED ACIDS AND ALKALIS.SP-ENC-V VARIABLE SPEED 115 VAC ELECTRIC MOTOR,SP-PVDF-39
9430	STANDARD PUMP PACKAGE 1(110-120V) (1) SP-CPVC-39, (1) SP-280P-V, (1) 9017 HAND NOZZLE, (1) 9006 WALL BRACKET, (1) 9015ADAPTOR, (2) 9001 CLAMPS, (6 FT)

Sp-700sr-1851-P-47	STANDARD HIGH VISCOSITY DRUM PUMP INDUSTRIAL, PROGRESSIVE CAVITY PUMP, PTFE STATOR, 1851 SERIES, 39 (1000MM) LENGTH, 1 1/2 (38 MM)HOSE BARB DISCHARGE
Sp-410ex	EXPLOSION-PROOF MOTOR 230 WATT 110-120V, SINGLE PHASE, 50-60 HZ, 0.3 HP.FOR USE WITH STAINLESS STEEL PUMP TUBES ONLY .CSA CERTIFIED
Sp-700dd-751-B-39	39 INCHES LONG. BUNA STATOR. 100,000 CPS VISCO
Sp-A8	STANDARD INDUSTRIAL PNEUMATIC MOTOR PNEUMATIC MOTOR, DD SERIES, FOOD PROCESSING EPOXY PAINT, 2 HP
Sp-700sr-751b-39	47 INCHES LONG. VITON STATOR. 7000 CPS VISCOSITY MA
Bc-Enc-Pvdf-39	STANDARD BATCH CONTROL SYSTEM PVDF 39 INCH LONG DRUM PUMP TUBE WITH TEFC 115 VAC 60 HZ MOTOR RATED 825 W .INCLUDES 16 FT POWER CORD WITH US 115 VAC PLU
Bc-280-Pp-39	STANDARD BATCH CONTROL SYSTEM POLYPRO 39 INCH LONG DRUM PUMP TUBE WITH ODP 115 VAC 60 HZ MOTOR RATED 825 W .INCLUDES 16 FT POWER CORD WITH US 115 VAC P
Sp-700dd-751-B-47	47 INCHES LONG. BUNA STATOR. 100,000 CPS VISCO
F201-M10ssp-2ez	STANDARD OVAL GEAR FLOW METER
F201-M10ssp-2ehz	STANDARD OVAL GEAR FLOW METER
9420	STANDARD PUMP PACKAGE 3 SP-ENC ELECTRIC MOTOR WITH PVDF 39 INCH DRUM PUMP TUBE.INCLUDES 6 FT VIPER HOSE, 1 INCH PVDF DISPENSING NOZZLE, POLYPRO BARREL
Sp-700sr-751v-39	39 INCHES LONG. VITON STATOR. 25,000 CPS VISCOSITY MAX.SPECIFY APPLICABLE AIR- OR ELECTRIC
Sp-700sr-1851-B-47	39 INCHES LONG. BUNA STATOR. 7000 CPS VISCOSITY MAX.SPEC
F200kitpvdf	BATTERY-OPERATED 9 VDC IN-LINE F200 PADDLEWHEEL FLOW METER ASSEMBLY WITH PVDF FLOW CHAMBER 1 INCH HOSE BARB CONNECTIONS.INCLUDES PVDF HAND NOZZLE.
Sp-700sr-1851b-39	39 INCHES LONG. PTFE STATOR. 7000 CPS VISCOSITY MAX.SPEC
Sp-512	STANDARD SANITARY ELECTRIC MOTOR TEFC (IP55), FOOD PROCESSING EPOXY PAINT- 230/460V/3/60 HZ., 1.0 HP, 900RPM, 380-415V/3/50 HZ., 0.75 KW, 750RPM, 100L
F101	120 / 220-240