



Start Elevator

Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Start Elevator Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Start Elevator Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
HOME-LIFT (2006/42/EC)	<p>Piston Type 80 x 5 SL x 5000 - SINGLE INDIRECT 2:1 Min length of piston 5200 mm Max length of piston 10200 mm Rod weight 57 kg Total weight of piston 110 kg Filling oil 11 lt Oil in circulation 25.1 lt Safety valve type LOCKING N. ONE In.Position BOTTOM Connection 3/4 Pump Unit Type 21EHSL4C - 34 LT/1' 3 KW THREE-PHASE 50 Hz Starting type DIRECT Voltage 400 Motor 230/400 Tank type HSL/02 Available oil 40 lt Motor starting/h 410 Over heat 0 kCAL/h Pump unit pipe connection 3/4-90° Min necessary oil 58 lt 0 Weight and Dimensions 55 kg - 250x220xh1225 mm Max Pressure 0.16 Mpa Min pressure 0.11 < 1.00 Mpa On piston load 0.00 kg Stability admissible load 2109.39 kg Pressure admissible load 2505.97 kg Deflection lenght 5410.00 mm Coefficient KE (stability) 165.12 Pressure limiting device coefficient 1.40 Compression force 49.96 daN Admissible force 2946.01 daN Minimum thickness 0.57 mm Cabin Speed 0.23 m/s Max Pressure 4.2 Mpa Motor Inputs Nominal current : 7.2 A Maximum current / Expected: 9.4 / 2.9 A Direct Starting current : 22 A</p>