

Stasto



Garanti: 12 ay

Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Stasto** Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Stasto Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
BAW1-002-BLTT-MZL	Brass ball valve; with drainage hole; Inner thread; Seal PTFE; Medium temperature -10 ... + 100 ° C; Hand lever Stole; Pressure range 0 ... 14bar; with shut-off device; RP 1/4 "; Nominal diameter 8mm; Installation length 45mm Weight / pc: 0.173 kg
SV02-12-14-X	Safety valve; with rotary lift; Body brass; Stainless steel compression spring; Seal FKM; Application: compressed air, non-toxic, non-flammable gases that are allowed to escape freely; Medium temperature -20... + 200 ° C; possible set pressures in 0.1 bar steps; G 1/2 "; DN 14mm; set pressure 0.2 ... 40bar; Blow-off capacity at 6bar (g) air 613Nm3 / h
110VA-1/2"	Needle valve; Body stainless steel 1.4571; Spindle seal PTFE; Medium temperature -20 ... + 250 ° C; G 1/2 "; DN 7mm; Pressure range 0-400bar; Overall length 60mm; Material handwheel polyamide Weight / pc: 0.422 kg
GDV14024CY	Solenoid type GDV / GDH; for higher pressures / temperatures; Connector width 32mm; Voltage 24VDC; Approval CSA / UL / VDE Weight / pc: 0.379 kg
21HT4K0Y160-GDV	2/2-way solenoid valve; forced control; NC; Body brass; Stainless steel guide tube; Seal NBR; Medium temperature - 10 ... +90; Connector width 32mm; G 1/2 "; DN 16mm; pressure AC 0-14bar; Pressure DC 0-14bar; Overall length 70mm; Standard coil GDV Weight / pc: 0.960 kg
21A2KV30-M	2/2-way solenoid valve with manual actuation, body brass, DN 3 mm, direct operated, seal FKM, NC, 1/4 " + BDA08024CS Magnetic coil type BDA; Default; Connector width 32mm; Voltage 24VDC or BDA08223DS Magnetic coil type BDA; Default; Connector width 32mm; Voltage 220-230V / 50-60Hz + C003-32-6 Device socket; Connector width 32mm; Default; tension 0 ... 250VAC / DC
	BA086-125-S0-ABS54-EB0X03-FR STASTO automation package Ball valve with built-on rotary drive; single acting PAS1605; material 1.4401; ball seal off graphite reinforced

AND011	PTFE; DN125, PN16; built up limit switch box EBOX03; constructed 5/2-way control valve ABS54, 24VDC, LED, VDR; including speed control; including filter pressure regulator FR01-14-0.5/8; NO; BA086-125-S0-ABS54-EB0X03-FR Weight/piece: 73.213 kg
9016/ES	MSV01-12-U1
1821-1/2"	
1821-1"	
710060-1"	
710000-2"	
100000 - 1/2"	BRASS/NBR NON RETURN CHECK VALVE
100001 - 3/8"	BRASS/FKM NON RETURN CHECK VALVE
MV21-00-14-U	block throttle check valve; Connection 1/4"; nominal flow 650 NI/min
3830-1/4"	BALL VALVE
0518/1218	SOLENOID VALF
STASTO MK20 NO	NO (normally open), 220V DC supply, G 1" diameter connection (New series CVT20 models are not suitable for us due to size difference)
C-VSTIR1/4ED	Sealing plug series C-VSTI-R-ED; Galvanized steel; hexagon socket; BSP thread; elastic seal; Thread 1/4
BDA08024CS	Solenoid coil type BDA; Default; plug width 32mm; Voltage 24VDC
SL200-38-BDA08024CS-C003-32-LV-2	2/2-way solenoid valve series SL200, 21H; pilot controlled; NC; Body Brass; NBR seal; Medium temperature -10...+90°C; Standard coil BDA; plug width 32mm; G 3/8"; DN 12mm; pressure AC 0.1...20bar; pressure DC 0.1...10bar; Length 50mm BDA08024CS Solenoid coil type BDA; Default; plug width 32mm; Voltage 24VDC C003-32-LV-2 device socket; plug width 32mm; with built-in LED yellow and VDR; Voltage 24VAC/DC
21W4KB250-MR	2/2-way solenoid valve series 21W-MR; pilot-operated; NC; body brass; guide tube stainless steel one-piece; seal NBR; medium temperature -10...+90°C; with adjustable closing delay; manual operation; standard coil BDA; plug width 32mm; G 1"; DN 25mm; pressure AC/DC 0.2-16bar; length 104mm
KTG0W3KB19	Seal kit; suitable for series 21W-NC; size 3/4", 1"; Seal NBR
PR02-12-1.5/6	Pressure regulator series PR02/PR10; housing brass; fine sieve stainless steel; spring cap, sieve cup polyamide; seals NBR/EPDM; mesh size 0.5mm; max. inlet pressure 30bar; working pressure range 1.5...6bar; medium temperature -10...+70°C; R 1/2"; matching pressure gauge MA001-50R-10-D

3" Class 150 -valf	190168_4Serie_6209_EN_V2
CY52502S 110VDC	
EBOX03	
Ga015-Dn20	
Rcp1-448,3x Schelle Zur Befestigung Des Rohres Dn48	
Se01-12-Rt51 Druckgesteuertes Sitzventil(Innengewinde, Dn15)alte Nummer 015v101000	
Pr04-65-1/8	
Vnpr2	
1800-2" Ball Valve Full Bore, Female/Female, G2"	
Rcp1-228 Schelle Zur Befestigung Von Rohr Dn28	
Es-2305-11/2 Es-2305-11/2 Indus. Nr. 58182974 Typ Es-2305-11/2	
2/2-Wege-Magnetventil	
A-Ew22171	
21a2ke25	
21h8ke120 Electrovalve Coil 24vdc G 1/2	
22 520 4	
Rcp1-332	
Rpe3 062h51 02400e1t1	
C0f-60n250	
21h9kb180 2/2-Wege-Magnetventil 21h9kb180	
Rvm/U-L40006-Ms	
Pds-1-016-M-2-1 Druckschalter	
21h7ke120	
21a5zv45 2/2-Wege-Magnetventil	
3303.	
21a2kv30 2/2-Wege-Magnetventil+ Bda08223ds (220-230v/50-60hz)+ 6-41142-2000-S	

Pr08-112-1/8
Ns320 Nosr 0-10 Bar 220/50hz
2203
110st- 3/4 Ventil Nadelventil
21h7ke120 Electrovalve Coil 24vdc G 3/8
Gdv14024cy Magnetspule Typ Gdv/Gdh24vdc
772000-1/2" T- Bore
Cs11050
Ma001-63b-25 Manometer Ma001-63b- 25 + Ma001-63b-10
015v1020c11--1-S--3
Cp-6/4-Na
Rcp1-448,3 Schelle Zur Befestigung Des Rohres Dn48
Re07-114-0,5/16-Ma
850c
Fr01-14-0,5/8
Bdv08230ay Elektromagnetische Spule
Vcml53614
Rcp 228 Befestigung Rohrkupplung Dn20
21x3kv190 2/2-Wege-Magnetventil
Pr08-12-1/8
1810-1" Messingkugelhahn
K52w1014
Re23-12-0,5/25-Ma Druckregler
21x2kv120 2/2-Wege-Magnetventil 21x2kv120
4059074
Re13-20-0,5/10-Ma
Fi03-12
21w3kb190 2/2-Wege-Magnetventil

Pds-1-016-M-2-1	
21wa4k0b130 2/2-Wege-Magnetventil	
6 51022 9002	
1810-11/2" Messingkugelhahn	
1810-1/2" Messingkugelhahn	
60001031211	
Gdv14024dy	
6 14123 0000 S	
Sv06-34-12,5-9-V	
Fr03-34-0,5/10-P Filter Pressure Regulator	
Bdv08230ay Solenoidmagnetspule Typ Bdv Bdv08230ay	
Re07-10h-0,5/16	
Ri1080 Reparatursatz	
21a2kv20-Bdv 24 ?	
721000-100 Flanschkuhgelhahndn100, Pn16	
Bda08223ds Magnetspule Typ Bda; Standard; Steckerbreite 32mm;Spannung 220-230v/50-60hz	
21a3kv20	
Bdv08024dy Spule 24v/50-60hz	
Rcp 448,3 Befestigung Rohrkupplung Dn40	
Fr03-34-0,5/10	
BDV08230AY	magnetic coil type BDV; for humid environment; Approval CSA/ UL/VDE; connector width 32mm; Voltage 230V/50Hz, 240V/ 60Hz Weight/pc: 0.136 kg
Msl03-12-03 Elektrisches Absperrventil	
Nm52w1s-Pr Wegeventil Mit Spule Und Stecker	
6-51022-9002	
737.705/S	
C11-K 10-A-X, Dn6 Druckminderventil	

6-42143-2000-S
Lu04-12h - Yađlayici
100.101-Dn80-Pn10
Magnetventil 21ht4k0y160
21ht6k0y250-Gdv 2/2-Wege- Magnetventil
Bda08223ds Spulemagnetspule Typ Bda, Standard, Steckerbreite 32mm,Spannung 220-230v/50-60hz
Ba233-38-D0 Kugelhahn Mit Pneumatischem Antrieb 500bar Dn10 G3/8"
Sf01-114w-30-X Vollhubsicherheitsventil 6bar
Bda08223dv Coil
Sv01-14-7.5-20 Sicherheitsventileinstelldruck 20 Bar
A-G20s71
Bda08024cs Magnetspule Typ Bda, Standard, Steckerbreite 32mm,Spannung 24vdc
Sve552100
R3121-04dtrg
Eb0x01-Nm
21a2zr30(Ex20b-2r-30n)
Pds-1-016-M-2-1 Drucksensor Pressure Switch
Pds-1-016-M2-1pds-1-016-M2-1
Ma001-50r-16-D
21ht6k0y250-Gdv 2/2-Wege- Magnetventi
6-14123-0000-S
Re07-34h-0,5/25-Ma
1810-1/2quot;
21w7kb500 2/2-Wege-Magnetventil
21ht6k0y250-Gdv 2/2-Wege-

Magnetventilwith Coil Gdv14230ay (Old Number: Gdh14223dv)	
Rcp1-228x Schelle Zur Befestigung Von Rohr Dn28	
Se06-20-Gt51-01 Druckgesteuertes Sitzventil(Dn20, Flansch)alte Nummer 020v213000---H	
Bdv08024dy Magnetspule 24v/50-60hz	
Rpe3-062j15	
Rcp 335 Befestigung Rohrkupplung Dn25	
21hf8k0v400 2/2-Wege-Magnetventil	
Bdv08110ay	
Gdv14230ay Magnetspule Typ Gdv/Gdh230v/50hz	
Sf01-34w-18-7	
21?8??120	
316-3/8	
1810-11/4quot;	
Rvm/U-2/13-Ms	
21a16kv25	
Sv06-34-12,5-10-V	
21ht4k0y160	
Fi04-12h	Filter; Semi-automatic drain valve; Form max. 16bar; Plastic containers; Port 1/2 "; flow at 6bar / $\Delta p = 1$ bar 4000NI / min; Filter insert 5 μ m Weight / piece: 0.840 kg Tariff: 84213925
Sc13-10-14-N Gerade Aufschraubverschraubung	
21a2kv30 2/2-Wege-Magnetventil+ Bda08223ds Magnetspule 220-230v/50-60hz + 6-41142-2000-S	
Drvb-1/4-V-N	
Bda08223ds	
Bda08024cs Magnetspule Typ Bda; Standard; Steckerbreite 32mm;Spannung 24vdcgewicht/Stk: 0,136 Kg	

737.503/S	
K52w1018	
Pr08-12-1/8 6bar-1bar Druckregler	
710060-2 Kugelventil	
Se06-40-Gt81-04 Flanschventil(Dn40)alte Nummer 040v2130014--H-S-----9	
Pds-1-016-M-2-1.	
C33-S	
C001-22 Magnetspule Typ C001; Steckerbreite 22mm; Spannung 230v/50-60hz	
21a2kv30 Ventil Magnetventil	
Bdv08024dy Coil Type Bdv Bdv08024dy24v/50-60hz	
A-T20s71	
100 101 Dn80 Pn10	
Nsk100-Sg Dichtsatz Pu; Zylinder Serie Nsk; Durchmesser 100mm	
C003-32-6	
D06fh Mb=1,5-12 ??? R3/4 Pressure Regulator	
1810-1quot;	
21w6kb400 2/2-Wege-Magnetventil	
R450 466 B	
Se01-10-Re51-01	
Rcp1-460.3	
21w4kb250-Mr	2/2-way solenoid valve; servo-assisted; NC; Body brass; Guide tube stainless steel one-piece; Seal NBR; Medium temperature -10 ... + 90 ° C; with adjustable Delayed action; Manual operation; Standard coil BDA; Connector width 32mm; G 1 "; DN 25mm; Pressure AC / DC 0.2-16bar; Overall length 104mm Weight / piece: 1,063 kg
1-6bar Dc 1-12bar Solenoid Valve Water	
8p0045-100 Flanschkuigelhahn Mit Druckluftdrehantrieb	
21ht6k0y250-Gdv	

A1n2h3-5v-100-B
21w3kb190
Pr04-40-1/8 Flanschdruckregler 8bar-7bar
- Handpumpe Stasto PI132
21pw4k0t120bda 0,5-18 Bar Ac
Ktght6k0y25
Hds-1-320-K-7-1
21ht4z0v160-Gdv 2/2-Wege-Magnetventil
1800-3/4" Ball Valve Full Bore, Female/Female, G3/4"
Pv-10/4-Na
Sq6-0b6-Q11
3303
Bda08223ds Coilmagnetspule Typ Bda
600 010 311 11
Sv06-10-16-9-V
21a2kv30 2/2-Wege-Magnetventil
4166
K32wis612cs-24vdc
Bda08223ds Magnetspule Typ Bda, Standard, Steckerbreite 32mm,Spannung 220-230v/50-60hz
E52w1sm12-02400
21a16kv25-Xv Ventil
Rcp1-116
1810-2" Messingkugelhahn
Bac1-004-Sstv-D0b
21h8ke120
Bdv08024cy Magnetspule Typ Bdv
21a2y0f55-Pwb
Ms02400 24vdc, 3 W

[Sc13-10-14-N Direkter Anschluss Mit
Innengewinde](#)

[680.26](#)

[Cs02400](#)

[680.26 Dn40 Pn25](#)

[Es-2305-11/2](#)

[Hds-1-250-K-7-1 Pressure Regulator](#)

[Sv06 10 16 9 V](#)

[Sv01-14-7.5-10](#)

[21a8zv55+bdp08223ds-2](#)

[704000-1/2"](#)

[Sv01-12-11-1](#)

[VcmI52014](#)

[Bab1-006-Bltv-D0b Kugelhahn Mit
Pneumatischem Antrieb](#)

[Fr03-34-0,5/10-P Pressure Regulator
With Filter](#)

[22.520.4](#)

[21ht6k0y250-Gdv 2/2-Wege-
Magnetventilmit Spule \(24v Oder 230v\)
Und Einer Steckdose \(6-41142-2000-S\)](#)

[21ih6k1v250-Gdv](#)

[Bac1-009-Sstv-D0](#)

[Gdv14230ay Magnetspule Typ
Gdv/Gdh230v/50hz-240v/60hz](#)

[Bdv08024dy](#)

[Mmb04-38h/10](#)

Holder kit; suitable for series FI04-38H / 10, LU04-38H / 10
Tariff: 84129080

[0010 Kit Db 114/C](#)

[Bab1-006-Bltv-D0b- Stasto](#)

[A-G22I71](#)

[21a2kv20-Bdv220-230](#)

[640/2](#)

1810-11/4" Messingkugelhahn
Dkm-1/60 G1
687.6.050
721000-50 FlanschKugelhahndn50, Pn16
Sf01-34w-18-X Vollhubsicherheitsventil 7bar
Pr04-40-1/8
640 2
Nsku100-60-F
21h8kb120
Nm52w1s-Pr
21a2kv25
650 C / K
Rcp1-460.3x
21w6kb400-Mr
2/2 21??4zov 160-Gdv Control Valve
21h8kb120-220-230v/50-60hz
578.020k
Pr04-65-1/8 Flanschdruckregler 8bar- 6bar
Sf01-114w-30-6
Re06-38h-0,5/16-Ma
21ht6k0y250gdv Membrane Zum Ventil0-12 Bar (Ac) 0-6 Bar (Dc)
Ma001-63r-10-D Manometer
Re06-14h-0,5/10-Ma Konstantdruckregler
21h8kb120bda Ventil G1/2 Bp 24dc
Sc13-10-14-N Verbindung, Innengewinde 1/4"x D=10
21a16kv25 Ventil Magnetventil
Bdv08230ay
21h9kb180 Ventil Magnetventil

Spule Netzteil 220v Bda08223ds	
Rv2i	
Sv11-12-14-8	
Pkh-113-Sgv-Ipn64-F1-Da75 Ventil Mit Pneumatischem Antrieb (Dn50, Pn64 Valve With Endswitch)	
21w7kb500	
Lu04-12h	Oiler, inlet pressure max. 16bar, plastic container, connection 1/2 ", flow at 6bar / $\Delta p = 1\text{bar}$ 4000NI / min Weight / piece: 0.750 kg Tarif: 84248970
Beim-2nc	
4166 Manometer	
Ba233-38-D0	
Bdv08230ay Elektromagnetische Spule230v 50hz - 240v 60hz, 16 Va, Ed 100%	
90166	
Maintainance Unit 850c, G1/2"	
Bab1-006-Bltv-D0b	
316-11/2quot;	
C11-S	
21ht4k0y160-Gdv	
Bda08230cs	
1810- 1/2" Messingkugelhahn	
578 020k	
21w4kb250 Magnetventil	
A-T22I71	
Bda08024cs	
21a2kv30	
Rpe3-062h51/02400e1t1	
Fr03-12-0,5/10	
Rcp1-220	
21wa4k0b130	

[316-3/8 Axial Check Valve 0.1-16 Bar](#)

[6-41142-2000-S](#)

[Sv01-14-7.5-X](#)

[760 K](#)

[VcmI53914](#)