

Stemmann Technik

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Stemmann Technik Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Stemmann Technik T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
111016	
111205	
119155	
1206011	
1215381	
1507186	
1507187	
20 A	
2206571	
2209276	
2209284	
2209286	

25/50C-52000316
5020002
5020087
5020091
5020132
5030027
5030028
5030105
5040113
5040272
52000326
52000396
52000669
5201152
5201153
5202475 (310)
5202995
5202995 (310)
5203024
6251682
6253117
6253506
6263675 (345)
6604046
6610003
6610049
6699
6710182
6716
6860085

7910146	
8010006 (310)	
8560100.B2612	
AV28361810C-1002	
BAK018	
CRL-1/2 (52671)	
D5411040	
D7910008	
D7910014	
D7910064	
D7910065	
D7910070	
D7910086	
D7910087	
D7910094	
D7910095	
D7910237	
D7910624	
D930139	
GK13E-02	
KONTAKTKOHLER P25/200 A	
LTTR FED TLF 400 N.ZG. 3KF213/1A00	
MP 297 876 72 044	
P25/50-100 -5200326	
TLF 190 19361420BA-BAKO 07	
GD.1.B.03.01.01.004	STEMMANN TECHNIK REVISIONKIT FB700.69
6264053 (345)	LP60GL 37 WEGE PE+4X10A/230V+24X10A/24V+9XPROFIB Replacement of 6262233 Designed for: 1-way grounding (50A) 1 way PE 4-way 230 V / 10 A 24 way 24 V / 10 A 9-way bus signal (incl. shield) Drawing no.: SRK0060.334Ä00 The protection class of the housing is IP65. The housing parts are made of aluminum. The device is pre-wired with 10 m of cable on the rotor and stator side. On the ring side (rotor), the slip ring is pre-wired with single cores, but Profibus with

	Profibus cables. On the brush side (stator), the slip ring is pre-wired with sheathed cables. The maximum speed is 30 rpm. The minimum lifetime of the slip ring contact technology is 3.5 million turns. 4E00 Packaging dimensions: (approx.) 1 box 75x52x60cm Net. 20 kg brood. 26kg
7787	CONTACT CARBON P25/200 A (310) METAL GRAPHITE N6
690W 64A	+3 pcs. busbar covers
TLF400	
1140	
D7910600	SLIDING CONTACT SCL SET 4 6-7P ; BZ 40 AMP ONLY FOR 70 SQMM
MP297-87672044;	
6264053 (345)	LP60GL 37 WEGE PE+4X10A/230V+24X10A/24V+9XPROFIB Successor to 6262233! Designed for: 1 way PE (50 A) 1 way PE 4 ways 230 V / 10 A 24 ways 24 V / 10 A 9-way Profibus signal (including shield) Drawing number: SRK0060.334Ä00 The protection class of the housing is IP65. The housing parts are made of aluminum. The device is pre-wired with 10 m of cable on the rotor and stator sides. On the ring side (rotor), the slip ring is pre-wired with individual wires, The Profibus signal is transmitted using a Unitronic cable. On the brush side (stator), the slip ring is pre-wired with sheathed cables. The maximum speed is 30 rpm. The service life of the slip ring contact technology is 3.5 million revolutions.
6264154 (345)	LP60G 60 WEGE 60XMA-10A/24V Successor to 6261656! Designed for: 14x 24V/mA (incl. shield) 2xPE 6x 24V/0.5-1A 6x 24V/0.5-3A 12x 24V/0.5A 6x 24V/0.5-1.5A 6x 24V/1-2A 6x 24V/1.5A 2x save Based on drawing: SRK0060.372Ä00 The housing is designed for protection class IP 65. All housing parts that are visible to the outside are made of either aluminum or cast aluminum manufactured. The device is pre-wired with 5m sheathed cable on the ring and housing side, the two reserve paths are pre-wired with single AWG20 wires. The service life of the slip rings is 3.5 million revolutions.
6264142	SLIP RING U:480V I:10A SERIAL NO:1 IP 54 (A WABTEC SUBSIDIARY)
5200668 CURRENT COLLECTOR PHASE BLUE PSW 25/400A	
5200669 CURRENT COLLECTOR GROUND GREEN PSW 25/400A P25	
5203024 (310)	CURRENT COLLECTOR SICL25 - MAX.400 AMP PE "DOUBLE ARMED" WITHOUT WIRE, INSTALLATION POSITION 160
CI7-7-70s-----	
5200696	

6602601
0077741
5050090
2103677
5050115
5050066
1112-S
2009149
6602598
2009289
2103558
5050078
6602599