

Strack

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Strack Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Strack T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunulmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
SN5650-PMO-0230-15-M-N-V03	Standard slide hanging above PowerMax
SN5650-PMO-0230-30-M-N-V03	Standard slide hanging above PowerMax
SN5650-PMO-0065-45-M-N-V03	Standard slide hanging above PowerMax
SN5650-PMO-0330-15-M-N-V03	Standard slide hanging above PowerMax
SN5650-PMO-0165-20-M-N-V03	Standard slide hanging above PowerMax
SN5650-PMO-0125-70-M-N-V03	Standard slide hanging above PowerMax
SN5650-PMO-0065-10-M-N-V03	Standard slide hanging above PowerMax
SN5650-PMO-0090-5-M-N-V03	Standard slide hanging above PowerMax
SN5650-PMO-0260-20-M-N-V03	PowerMax above
SN5650-PMO-0260-25-M-N-V03	PowerMax above
SN5650-PMO-0090-10-M-N-V03	Standard slide hanging above PowerMax
SN5650-PMO-0065-75-M-N-V03	Standard slide hanging above PowerMax

SN5650-PMO-0330-30-M-N-V03	Standard slide hanging above PowerMax
Z4-21-0-0	latch lock
Globe valve S24.056	Globe valve DN 100, PN 40 type S24.056, welding connection, manual actuator type, working medium temperature 160
Globe valve S24.056	Globe valve DN100, PN 40 type S24.056, welding connection, with electric actuator AUMA SA 10.1, temperature of working medium 160 C
Check valve Type S70.056	Check valve DN 100, Pworking 52 type S70.056, welding connection, temperature of the working medium 158 C
check valve Type S72.021	Check valve DN 200, PN 16 type S72.021, welding connection, temperature of the working medium 158 C
check valve Type S72.021	Check valve DN 100, PN 16 type S72.021, welding connection, temperature of the working medium 158 C
STRACK Type S17, DN50 PN250, with actuator	STRACK Type S17, DN50 PN250, with actuator AUMA SA
STRACK Type S21, DN50 PN250, with actuator	STRACK Type S21, DN50 PN250, with actuator AUMA SA
Globe valve S20.013	Globe valve DN 40, P working 8 type S20.013, welding connection, with electric actuator AUMA SA 07.1, temperature of working medium 163 C
Globe valve S20.013	Globe valve DN 50, PN 25 type S20.013, welding connection, with electric actuator AUMA SA 07.1, temperature of working medium 163 C
Globe valve S21.021	Globe valve DN 50, Pworking 91 type S21.021, welding connection, with electric actuator AUMA SA 10.1, medium temperature 297 C
Globe valve S21.021	Globe valve DN 65, PN 160 type S21.021, welding connection, with electric actuator AUMA SA 10.1, medium temperature 504 C
Globe valve S21.021	Globe valve DN 20, PN 160 type S21.021, welding connection, manual actuator, working medium temperature 504 C
Globe valve S21.024	Globe valve DN 50, P working 89 type S21.024, welding connection, with electric actuator AUMA SA 10.1, temperature of working medium 536 C
Z3-31-50-125	151923 round latch lock Set consisting of: 141699 Z3-3-01-125 1 pc draw bolt 151892 Z3-31-50 1 pc complete housing
Z3-31-50	complete housing
VANA GATE 4" 2500 CLASS //	TECHNICAL DRAWING IS ATTACHED. OPERATION PRESSURE: 280 BAR OPERATION TEMPERATURE: 350 C FLUID: BROWN WATER STEAM DIMENSIONS: 114X20
SN4321-63-200	guide column with waistband DIN 9825-4, ISO 9182-5

Z4416-63-75	guide bush with waistband rolling guide ~DIN 9831-2, ISO 9448
SN1798-63-148	ball cage made of brass
SN4321-40-125	guide column with waistband DIN 9825-4, ISO 9182-5
Z4411-40-50-B	guide bush with waistband CuSn12 ~DIN 9831-1 / ISO 9448
SN2808-VS-920-32	gas spring MICROseries VDI 3003
SN2808-V-470-25	gas spring MICROseries ~VDI 3003
SN1515-17.5-M12-90	screw with spacer tube
SN1591-50	Tragzapfen VDI 3366
SN1860B-HSS-6.1-80-10	cutting stamp cylindrical head discontinued ISO 8020 Form B
SN1860B-HSS-8.1-80-13	cutting stamp cylindrical head discontinued ISO 8020 Form B
SN1860B-HSS-5.6-80-8	cutting stamp cylindrical head discontinued ISO 8020 Form B
APX 8 19 80 P5.6 M2	
512030/4 Size 65	Body 1.0460 Trim Stell?
12606	Z5260-50-38-24.5 Counter Mechanical
600780	Z5263-38-24.5-48 Counter Mechanical
Z7415-16	
P/N: 151225 Type: Z7602-2-3000	
Z4-2-07	
Sn2540-20-25	
Z7618-500	
Z7565	
Z7675	
Z68-25-160	
Z5106-Ds-Z5101-12	
250165 Sn5650-Pmo-0330-10-M-N-V02	
Z7769-10-1,5 141487	
Z 7600-4	
Z7609	
P/N: 181899 Type: Z7616-2	
35063 Klinkenz¼ge Z5 - 2	

[P/N: 73835 Type: R523-10-40](#)

[Z5140-1](#)

[Z68-16-63](#)

[R1031-6-40](#)

[Sn1709-2](#)

[Z7769-10-3,2 141489](#)

[Z5130-18](#)

[Z4-2-02](#)

[Z7750-8](#)

[Sn1598-M20](#)

[162647](#)

[Z5101-12-12](#)

[P/N: 73823 Type: R523-8-30](#)

[123972 Z75-32-76](#)

[182696](#)

[Z7410-16](#)

[Z7408-16](#)

[37773 Z81-42-150](#)

[Z4-15-03](#)

[P/N: 73815 Type: R523-6-30](#)

[37771 Z81-42-110](#)

[Z7600](#)

[Z5140-0](#)

[127445](#)

[Bp25c25x32x25](#)

[Z 5-31](#)

[Z 5-32](#)

[Z3-3-125](#)

[Z6040-1](#)

[84572 Z81-42-200](#)

R1031-6-25
Z5130-13 182692
Z7769-10-2,5 141488
Z7433-3
P/N: 37192 Type: Z75-50-76
Z6040-3
Z7608
Z50093 Sn5650-Pmo-0230-5-M-N-V02
Z5130-27
Z7433-2
Z5177-10-1-12-13 = Z5176-10-1-12 + Z5174-6-13 + Z5173-6
Z7616-2
Z4-15-0-0
Z5-32 -162,5
Z5-31 -162,5
R523-20-60
Z7416-16
S17rks
P/N: 140309 Type: Z7662
Z5-0
Z 50-1 / Z51-1
Z3-2-100-220
Z4315-25-300
Z7678-500
150975
Z7665-3000
Z5-4
145218 Z4310-25-190
Z4-2-06
10060216 Z20-40-117

Z4-15-02
P/N: 73852 Type: R523-16-60
Z624-2
Sn4322-80-224
Z51-02
P/N: 26711 Type: Z148-16-120
Z3-1-40-125
Z68-20-100
221057 Sn5650-Pmo-0400-20-M-N
P/N: 73845 Type: R523-12-50
Z5085-22
Z5134-7
P/N: 73851 Type: R523-16-50
Z48-30/26/40
Sn 2500-17-85 Stat. Warennummer:7320 20 81
Z5260-50-38-24,5
Z5260-50-38-24.5
W25-18-160
Z5129-13
Z5129-27
Sn1598-M30
Z3-2-01-120
Sn1763-80-150-C
35317 Z15-125-20
Z5129-18
Z5-1
Z3-11-40-100
Z5-2
Z57-25 / Z56-25
181906 / Z7618-500

250099 Sn5650-Pmo-0330-5-M-N-V02
R523-5-30
Z68-25-250
P/N: 181302 Type: Z7615
P/N: 165874 Type: W 32-16-22
Z4078-R-25-76
10100473 Klinkenzug Z5 - 4
Z4325-2
Z68-25-200
Wz8031/B-20-025
R523-13-50
Z68-12-63
250819 Sn5650-Pmo-0230-60-M-N-V02
Z20/40(30)-117
Z7602-2
151794
P/N: 40020 Type: Z56-25
P/N: 35063 Type: Z5-2
Strack Z5-0
Z4320-20-100
Z68-16-160
Z7538re-14
Z3-2-25-170
Z7685
Z4-32-189-290
1855a-Hss-5,0-90
Z3-2-75-120
Z5-0-06
Z5101-12-24
Z4-15-0-0

[85533 Z78-25-49](#)

[Z7606-40](#)

[Z7604](#)

[P/N: 600019 Type: Z51-1](#)

[Z7616-1](#)