

Straub

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Straub Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Straub T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
Eco Grip Ø88.9 - Stainless Steel A4	
100695	
103519	
103537	
1105	
1110	
1112	
13146	
481-525-300	
G20206	
G20351	
G20450	

G20550	
G20551	
G20558	
G20601	
G20650	
G20900	
G21051	
STRLE48	
WGR560	Item No.: G21107 STRAUB-GRIP FF 133.0 mm NBR/ES W5 Clamping range 131.7 - 134.3 Housing 1.4404 or equivalent Screws A4-80 Bolt 1.4404 or equivalent Sealing sleeve NBR Operating pressure (Ind.) 21.00 Temperature -20°C - +80°C
article_code=6829/0612	name plate=6620M0016 NORMA Grip-E-FP-W5-NBR ø133.0
article_code=6829/0612	name plate=6620M0018 NORMA Grip-E-FP-W5-NBR ø133.0
OPEN-FLEX 1 □ 114.3mm EPDM/ES PN20 W5	35650 Sealing Sleeve :EPDM Clamping Range :112,5. - 116.0 Temperature : -20 C to +100C CAsing : 1.4404 o. equivalent Bars : A4-80 Bolts : 1.4404 o.rquivalent Pressure (Ind.) :20
OPEN-FLEX 1 □ 76.1mm EPDM/ES PN25 W5	35250 Sealing Sleeve :EPDM Clamping Range : 74.5-77.5 Temperature : -20 C to +100C CAsing : 1.4404 o. equivalent Bars : A4-80 Bolts : 1.4404 o.rquivalent Pressure (Ind.) :25
OPEN-FLEX 1 □ 88.9mm EPDM/ES PN25 W5	35350 Sealing Sleeve :EPDM Clamping Range :87.5-90.5 Temperature : -20 C to +100C CAsing : 1.4404 o. equivalent Bars : A4-80 Bolts : 1.4404 o.rquivalent Pressure (Ind.) :25
OPEN-FLEX 1 □ 48.3mm EPDM/ES PN25 W5	35000 Sealing Sleeve :EPDM Clamping Range :47.0 - 49.5 Temperature : -20 C to +100C CAsing : 1.4404 o. equivalent Bars : A4-80 Bolts : 1.4404 o.rquivalent Pressure (Ind.) :25
OPEN-FLEX 1 □ 60.3mm EPDM/ES PN25 W5	35150 Sealing Sleeve :EPDM Clamping Range :59.0-63.0 Temperature : -20 C to +100C CAsing : 1.4404 o. equivalent Bars : A4-80 Bolts : 1.4404 o.rquivalent Pressure (Ind.) :25
GRIP 33.7 mm EPDM/ES W5	ALTERNATIVE (Bu boyuttaki OpenFlex modeli retimden kaldırılmıŐtır) G20100 Sealing Sleeve :EPDM Clamping Range :33.2-34.2 Temperature : -20 C to +100C CAsing : 1.4404 o. equivalent Bars : A4-80 Bolts : 1.4404 o.rquivalent Pressure (Ind.) :39
30600	108.0mm EPDM/W5 /PN20 Clamping range 106.5-110.0 Pressure ind. 20 EPDM Casing 1.4404 Bars A4-80
30800	133.0mm EPDM/W5 / PN16 Clamping range 131.0-135 Pressure ind. 16 Sealing sleeve : EPDM Casing 1.4404 Bars A4-80
3" SCH40 304L	

Grip-L 33.7mm NBR/W5	claming range 33.2-34.2 pressure :39 sealing sleeve NBR Casing 1.44044 Bars A-4-80 Bolts1.4404
1017 Marquardt 648 1264.3501	
36050	STRAUP-OPEN-FLEX 1Ø168,3mm EPDM/W5 I PN16
35350	STRAUP-OPEN-FLEX 1Ø 89.9 mm EPDM/W5 I PN25
STR30250	76.1 mm Pipe Outer Diameter, EPDM Gasket, SS Bolt
PN16 DN40 FLEXIBLE HOSE DIN2633	1 METER LENGTH, 1 END FLANGED, 1 END UNION CONNECTION
Grip-L 166,6 - 170,0mm	
Grip-L 166,6-170,0mm	
491-625-300	
41681663	
Grip W5 114,3mm	NBR PN bar 22
42218654	
Grip-L 47,8 - 48,8mm	
41806532	
S30651/1-L-114,3	
381-215-200	
S30251/1-L-76,1	
42216950	
Grip-L 138,3-141,1mm	
Grip-L 33,2 - 34,2mm	
392-420-400	
381-108-200	
Grip-L 59,7 - 60,9mm	
500246716	
Grip W5 168,3mm	NBR PN Bar 16
491-525-300	
Grip-L 113,2-115,4mm	
500246715	
Grip-L 113,2 - 115,4mm	

[Rep-Flex Kupplung Reparaturd525mm
\(525-535\) L=300mm Nbr/Es](#)

[Grip-L 26,4 - 27,4mm](#)

[Grip-L 273,0mm](#)

[41625338](#)

[Grip-L 138,3 - 141,1mm](#)

[Grip-L 216,9 - 221,3mm](#)

[Grip-L 59,7-60,9mm](#)

[Grip-L 88,0 - 89,8mm](#)

[Grip-L 33,2-34,2mm](#)

[381-269-300](#)

[Grip-L 75,3-76,9mm](#)

[381-159-200](#)

[Grip-L 41,9-42,9mm](#)

[Grip-L 48.3 Kupplung](#)

[S30151/1-L-60,3](#)