

## Stuvex

Garanti: 12 ay  
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Stuvex** Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

*Firmamız Stuvex Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.*



rn	Aıklama
<a href="#">503-1050-003</a>	
<a href="#">503-1500-000</a>	
<a href="#">651-1100-040</a>	
<a href="#">651-1100-075</a>	
<a href="#">651-1100-080</a>	
<a href="#">663-0410-020</a>	
<a href="#">SG/E-TES01-V2/IP</a>	Earth Monitoring System for Trucks Brand: Stuvex * Type: Capacitive + Resistive * Material: Body in AISI304 stainless steel * Dimensions: 200x300x155mm * Assembly: wall mounting ... cable glands: 3x M20 incl. (1D/2G) ... equipped with an earth connection * Voltage supply: 110-240VAC +10%/-15%, 50-60Hz 24VDC, +/-20% * Output contacts: potential-free, NO, 1A @ 250 VAC / 30 VDC potential free, SPDT, 6A @ 250 VAC / 30 VDC * Indication: ... Power supply: 24 VDC, max. 100 mA Grounding OK: 1x green Grounding NOT OK: 1x red * Equipped with a key switch Truck detection on/off" * Protection class: IP66 * Temperature: -30°C to

	+54°C * Humidity: max. 95% at 20°C, non-condensing * ATEX ITS18ATEX103783 EX II 2 (1) D Ex tb [ia Da] IIIC T135°C Db * IECEx ITS 18.0042
<a href="#">CR1/65V15</a>	Cable reel aluminium Cable: : H05VV-F 2x1.5 + 1.5mm <sup>2</sup> , 15M Length 15 meters Connection length: 2 meters Automatic blocking mechanism Cable line Seal kit: IP65 Housing: aluminum Pivoting attachment Weight: 10kg Assembled including connector (F). Cable: H05RN-F 2x1.5 + 1.5mm <sup>2</sup> - Length 15 meters - Connection length 1.7 meter Assembled including connector (F). Automatic blocking mechanism (default setting: braked) Cable management system with rollers Seal kit: IP65 Behuizing: aluminum Ground connection housing Pivoting attachment (in stainless steel) Weight: 10kg Mark: CE0344 Ex II 2GD ISSeP 04 ATEX 084X ATEX ITS18ATEX103783 ITS 18.0042
<a href="#">SG/B-CMS1-SCM</a>	Clamp Medium StuvEx, incl. M connector In stainless steel 1.4401 (AISI 316) Size: 210mm Opening: 3±mm Temperature range: -40°C to +80°C Weight: 0.6kg Including integrated strain relief Suitable for use in ...of zones 20, 21, 22 ...of zones 0, 1, 2 Cable ...Type: H07RN-F 2x1.5 + 1.5 mm <sup>2</sup> ...Length: 0.2 m ...water and oil resistant Connector, M ...PA6.6, blue
<a href="#">651-1100-080 Fc Ar-01 Alarm Relay For Fcu Rp01</a>	
<a href="#">651-1100-075 Fc Rp-01 Firing Card Rp - Squib</a>	
<a href="#">503-1050-003 Cm1 - Erdungszange Ss</a>	
<a href="#">503-1500-000 Set Of Plugs (M+f)</a>	
<a href="#">503-3250-010</a>	
<a href="#">651-1100-040 Em-01 Earth Monitor</a>	