

## Svecom

Garanti: 12 ay  
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Svecom** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

*Firmamız Svecom T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*



¼r¼n	A¼ıklama
<a href="#">RPLM00020</a>	Springback type B 20mm
<a href="#">RPLN07008</a>	Brass blade B / code RPLN07008
<a href="#">3400334.00.1</a>	pneum. Clamping heads type 716/PK with wedges on the circumference for HID 76.20 mm, in steel version Body diameter 74.50mm Clamping length 981 mm Total length 1010mm Roll weight max. 150 kg Roll width max. 150 mm Roll diameter max. 1500 mm Speed V max. 500 m/min. with flange according to code no. 3400334.00.1 as supplied with no. 0603.04 03/17
<a href="#">3400333.00.02</a>	pneum. Clamping heads type 716/PK with wedges on the circumference for HID 152.20 mm, in steel version Body diameter 150 mm Clamping length 321 mm Total length 350mm Roll weight max. 150 kg Roll width max. 250 mm Roll diameter max. 1500 mm Speed V max. 500 m/min. with flange according to code no. 3400333.00.02 as supplied with no. 0603.01 03/17

<a href="#">3400336.00.00</a>	pneum. Clamping heads type 716/PK with wedges on the circumference for HID 76.20 mm, in steel version Body diameter 74.50mm Clamping length 401 mm Total length 430mm Roll weight max. 150 kg Roll width max. 250 mm Roll diameter max. 1500 mm Speed V max. 500 m/min. with flange according to code no. 3400336.00.00 as supplied with no. 3411.01 11/19
<a href="#">Svecom locking bearing square:30 mm 905 KLPF.0</a>	
<a href="#">Svecom locking bearing square:30 mm 905 KLPF.1</a>	
<a href="#">Code-Nr. PLF 02000</a>	Type B rubber flat hose, 20 mm wide Suitable for 30 hoses with a length of 2800 mm (necessary to cut it yourself)
<a href="#">PLF 02001</a>	PU flat hose type B, 20 mm wide Version: white-transparent Suitable for 30 pieces of hose each 2800 mm long (requires cutting yourself)
<a href="#">New</a>	For a project that is in the design phase, we need an Air expanded shaft on the opener side and a Friction Shaft on the winder side.
<a href="#">RPLF02002 SHORE:80/85</a>	PU flat hose type B, 20 mm wide Version: white-transparent Suitable for 30 pieces of hose each 2800 mm long (requires cutting yourself)
<a href="#">Rubber bellows 105 x 105 x 85 mm</a>	PDK 21137B
<a href="#">Steel ring for rubber bellows</a>	PMM 10825
<a href="#">Rubber wedge for clamping head</a>	PDK 21308B
<a href="#">PDK21308/01</a>	SVECOM SHAFT SHOSE_ 3 INCHES _PDK21308/01 STEEL-RUBBER LUG 155*15
<a href="#">Rubber wedge for clamping head</a>	PDK 21308B
<a href="#">Rubber bellows 105 x 105 x 85 mm</a>	PDK 21137B Steel ring for rubber bellows PMM 10825
<a href="#">PDK21308/01</a>	SVECOM SHAFT SHOSE_ 3 INCHES _PDK21308/01 STEEL-RUBBER LUG 155*15
<a href="#">Pneum. Clamping heads type 716/PK</a>	with rubber wedges on the circumference, for HID 152 mm, in steel version Clamping range 150 - 158 mm Span width 900 mm Total length 930 mm Roll weight max. 150 kg Roll width max. 800 mm Roll diameter max. 1220 mm V max. 250 m/min. Article code 3400335.00-03
<a href="#">outer diameter 75 x inner</a>	diameter x 55 x length 1550 mm
<a href="#">PNEUMECANICAL CHUCK WITH LEAVES</a>	714MZ OUT OF STEEL EXTERNAL DIAMETER: 149MM TABLE WIDTH: 160MM TOT WIDTH: 232MM 6' CORES SPRING EXPANSION, AIR RETRACTION 2130 RPM MAX TORQUE 330NM MAX WEIGHT: 2000KG
	Mounting: Square 35 mm / Round 50 mm With plastic finger

<a href="#">Bearing 926 KLLF0 according to drawing</a>	protection With sensor preparation: M8 2 buttons for opening / sliding ring According to K¼nig & Bauer Zng.-No. 1002264814 / W5526689
<a href="#">Bearing 926 KLLF1 according to drawing</a>	Mounting: square 35 mm / round 50 mm Pin Ø 45x35 / Ø 48x106 / Ø 50x24 mm Pin length 165 mm With plastic finger protection With sensor preparation: M8 2 buttons for opening / sliding ring According to K¼nig & Bauer Zng.-No. 1002264815 / W5526688
<a href="#">Rpfb 00000</a>	
<a href="#">Model: 714 Mlz</a>	
<a href="#">Repair Kit For Chuck 740/PI</a>	
<a href="#">Rplq 20045</a>	
<a href="#">69x1350x1000mm</a>	
<a href="#">Rplm 00020</a>	
<a href="#">Rpla 01509 780mm</a>	
<a href="#">900 Klpf0</a>	SVECOM VERSCHLOSSENES BETT 900 KLPF0 (Leerlauf)
<a href="#">Gummi-Flachschlauch Typ A,15 Mm Breit</a>	
<a href="#">Klapplager Typ 925/KI.P.P.0 Q</a>	
<a href="#">Typ Pd/14 , Cod. Rplv 00014</a>	
<a href="#">Rplm 00120</a>	
<a href="#">Pla01509c (Gummileiste Schnitt Gleichmã196;Ssig B.15 H.9 Die Leistne Sind In Rollen Je 11 Meter Lang)</a>	
<a href="#">1607/02</a>	
<a href="#">Klapplager Typ 900/KI.S.P.2</a>	
<a href="#">Typ 715/Pg</a>	
<a href="#">36075</a>	
<a href="#">Klapplager Typ 925/KI.P.F.1 Q</a>	
<a href="#">Rbas 4608</a>	
<a href="#">Cod. Rplv 00014</a>	
<a href="#">1607/01</a>	
<a href="#">900 Klpf1</a>	SVECOM GESPERRTES LAGER 900 KLPF1 (Wellenseite)
<a href="#">Type: Ep 300 Series</a>	
<a href="#">Fullspitze Fur Luftfullpistole, Gemã196;ã223; Foto Cod. Rpfb 00000</a>	

<a href="#">Svecom-Pe Rpla 01509</a>	
<a href="#">Pd14 Rplv00014</a>	
<a href="#">74x255x200 Mm.</a>	
<a href="#">Klapplager Typ 925/Kl.P.F.0 Q</a>	
<a href="#">Gd/29 Rplv00029</a>	
<a href="#">65 1001 01/14</a>	
<a href="#">Rpla 01509 1370mm</a>	
<a href="#">Code Rpkf25035</a>	SVECOM round hose for tension shafts Size ID = 25 mm / AD = 35 mm
<a href="#">Rpla 01509 1150mm</a>	
<a href="#">Klapplager Typ 925/Kl.P.P.1 Q</a>	
<a href="#">Rpla 01509 960mm</a>	
<a href="#">Luftfullpistole Komplett Mit Manometer Und Fullspitze, Gemã196;Å223; Foto Cod. Rpfb 00053b</a>	
<a href="#">Code-Nr. Rplm 00150</a>	
<a href="#">21844019dl150</a>	
<a href="#">1060;69x1350x100</a>	
<a href="#">Rplv00014 Svecom</a>	