

Sycon

Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine bařvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulařabilirsiniz.
Sycon Markası, tedarik sresi iin ltfen bizimle iletiřime geiniz.

Firmamız Sycon Trkiye Distribtr veya temsilcisi deęildir. Firmamız sipariř durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.



rn	Aıklama
SYCON 2602	SYCON 2602 analyzer in a housing, 110/230 V. 30-210160 Compact and fully automatic online analyzer for limit value monitoring of the Total hardness: - Easy commissioning with the configuration assistant - low indicator consumption (5,000 analyzes per bottle) - tool-free maintenance and easy cleaning - high measuring accuracy through self-calibration - Monitoring of a limit value - 2 relay outputs for limit value and device error - 1 input contact - SD card for storage of measured values - Software updates via SD card - no condensation on the optics - compact design 280x250x135 mm - multicolored, multilingual graphic display - Supply voltage 85-264 VAC - in the housing
SYCON 2802	Analyzer, on wall bracket, 110/230 V. Item no .: 30-010164 Reliable, accurate and fully automatic online analyzer for measuring the Total hardness in the range 0.02-30 ° dH (0.35-534 ppm CaCO3): - Easy commissioning with the configuration assistant - low indicator consumption - tool-free maintenance and easy cleaning - high measuring accuracy through self-calibration - Monitoring of 2 limit values - Indicator level monitoring - 4 programmable relay outputs for limit values, pre-cooler, flushing valves, pumps,

Errors, lack of indicators, rear derailleurs - 1 current interface
0 / 4-20 mA - 2 digital inputs for water meters, turbines, flow
monitors, external controls - SD card for storage of measured
values - Software updates via SD card - no condensation on
the optics - multicolored, multilingual graphic display -
compact design 280x250x135 mm - Supply voltage 85-264
VAC - on wall bracket

[33-099005](#)

Housing for SYCON series (with wall mounting set)

[Profibus-Dp-Configurator](#)

[Generator Tachometer 6v D.C.Per 1000
R.P.M. Open Ckt. 50 Ma Max](#)

[Shaft Flexible Drive-2.62 In. Long](#)