



Tapeswitch

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Tapeswitch Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Tapeswitch T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	A¼ıklama
PRSU/4	PRSU / 4 evaluation device Supply voltage: 24V AC / DC Mounting: DIN mounting on top hat rail Contacts: 3 NO contacts, 1 NC contact Reset: aut. / Ext. Temperature range: -25 ° C to + 55 ° C Safety category: EN ISO 13849-1 PL "d" Customs tariff number: 85364190 country of origin: Germany Net weight: 0.2kg
121BP/0100/2	
121BP/0250/1	
CKP/C1/0175/0120/1	
CKP/S1/0600/0500/4	
GS140/S/4/15/LED	
M12/5/20	
M12/8/20	
PSSZ/4	

TS26C/0805/3	
TS26C/1270/1	
TS26C/5000/7	
TS28	
TS-46-AL FC - VAL0044325	
PRSU/4	PRSU/4 evaluation device Supply voltage: 24V AC/DC Mounting: DIN mounting on top-hat rail Contact equipment: 3 NO contacts, 1 NC contact Reset: aut. / ext. Temperature range: -25°C to +55°C Safety category: EN ISO 13849-1 PL"d" Customs tariff number: 85364190
Ts28/1060/4 Ts28/1060/F/A/B/Fs/Ee/0500/ 0500/N	
Ts3/0558/1	
Ts26c/0750/9	
Ts-46d - Val0044338	
B1230	SAFETY UNIT
800-234-8273	
B3230	LIGHT CURTAIN
Ckps1sesrs100009003000	
Ts26c/0805/3	
Pssu/2.	
Ts6/2235/1	TS6/2235/F/A/R/FS/EE/5000/ 2000/N/AC Safety Edge Type: TS6 Length: 2,235mm Profile rail: aluminum, flat Profile color: red Material: EPDM / PP Band switch: 107BPE IP67 Wiring: Fail-Safe (4-wire) Cable outlet: two-sided (EE) Cable length: 1 x 5,000mm, 1 x 2,000mm Cable type: Ölflex Robust 210; 2 x 0.5mm² Connection: make contact max. 30V @ 1A loadable End cap version: without Special feature: At the beginning and end has the safety edge is not active Range of max. 50mm. Drawing: ---- Tariff No .: 85365019
B0830r	LIGHT CURTAIN RECEIVER 808MM 18MS 24VDC
0921m	LIGHT CURTAIN
B0830r0905	B SERIES LIGHTCURRENT
0930	LIGHT CURTAIN
Ts-26p	
0906	LIGHT CURTAIN
Ts26/Lca/0620/4w	

E3049-119-004	
B/S/1200/30/15/Cb	LIGHT CURTAIN RECEIVER 12V 24VDC
Prsu/2	
Ts26c/1700/1	
Ts26c/0750/F/A/B/Fs/Oe/2000/ 2000/N	
Pssu/2	
Prsu/4	
B830	RECTIFIER
Ts26/Lca/1000/4w	
121- Val0008760	
Ckp/S1/Se/Srs/1600/1100/3000	
0904	LIGHT CURTAIN 608MM 30MM 24VDC
Ts6/860	
B0630e	LIGHT CURTAIN EMITTER
Sp-1324-1	
Ts-46-AI Fc ? Val0044325	
B0630r	LIGHT CURTAIN RECEIVER
Bs0330r	LIGHT CURTAIN RECEIVER 0.5-15M RANGE 24VDC
Sensing Edge Ts-26p 750 Mm	
Ts-26p 750 Mm In Length	
121bp/0270/1	
920022	
B/S/0800/70/15/Cb	LIGHT CURTAIN
121-Bp	CABLE LENGHT 8m 8m TO OTHER END+LENGHT OF RİBBON SWITCH
Mes0628	LIGHT CURTAIN RANGE .3-6M CAP 28MM P.HEIGHT 630MM
Ckp/S1/2000/1200/7	
Sab Tx 116/Sd Range 6m	
Sp-3291-1	