

Tecnomagnete

Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Tecnomagnete Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Tecnomagnete Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.



rn	Aıklama
St 200 Fb	
St211r 400v	Control unit ST211R 400V, 1CH, incl. FB 8 level and DB-9
41758.00	Exchange kit for Dautanac Ademco (drawing no. 41758.00)
Exchange kit for Dautanac Ademco	(drawing no. 41758.00)
MaxX 500	Max. Load 500 Holding force 1,500 Min material thickness 25 15kg
CNR4BFH04	Control unit ST214FB 400V, 4CH 7x4 PVC / met / PVC 7PFV Feme 5 m, incl.TCF4 and DB-9
MTG 406 HD	Permanent electro magnetic chuck, dimensions 405 x 600 x 42 mm, 24 PoleERGON plug-in contact and transport plate
ST 200 SK	1 channel control ST 200SK, 400V-50Hz, with cable (5m) for control and power supply cable (4m) without mains plug
maxx 3ton	
Control unit ST212FA	230V, 2CH 4x2.5 PVC / met / PVC 4PFV 18/10 6m, DB-9
TPF/C 0500	Permanent electro magnetic chuck dimensions Ø 500 x 51 mm, open cable outlet on the underside of the plate according to drawing TPF-C-500-54
ST 200 R	1 channel control ST 200 R, 400V - 50Hz, complete Mag / Demag, 8 holding force levels. Cable with plug contact to the plate (6m) and power supply cable (4m), without mains plug
FH	Mounting holes for magnetic chuck

ST211R	control device ST211R 400V, 1CH, incl. FB 8 level and DB-9 CNR1BRH04
T1050100T-51	0006 180 KG 50/60 HZ 50X100
T1040080T	0001 125 KG 50/60 HZ - 40X80
QX303HD50	
20401130/1	Relay board SR04
PT 050/HD	For IMM 500 Ton, Krauss-Maffei
Maxx 250	
QX 508 HE50 T51	Permanent electric magnetic chuck, dimensions 470 x 780 x 51 mm, 60 poles, maximum clamping force 235 kN. With ERGON plug contact (5-PIN).
ECPM4/ V3	4-channel control ST 214F, 400V-50Hz complete with Mag/Demag, with TCF 4 with channel selection and distribution box, 4 outputs to the panel with cable (6m) and 1 input to the control (6m), power supply cable (4m) without mains plug
HABE KEH PLUS 04 - 5METER OHNE HAFTKRAFTREGULIERUN	
VBK 1XILME PLUS - 4X4PIN 5 METER KEH	
PMQ 50/32	mobile pole extensions, square, 50 x 50 x 32 mm
C.O 50812	Vers. 000100 PLC box for ST 210 (PLC) Version 7 (33324-E) 6mtr cable
TM 4/100X	Permanent electro lifting beam TM 4/100X for the transport of individual sheets with dimensions Length: 3,000 - 12,000mm Width: 500 - 3,500mm Thickness: 5 - 80 mm Max. load: 10 tons
AVC 1	Spring cable reel with 12m cable length including plug for Fastening on the crane 5 x 6mm ² (without installation)
MaxX 125	
20401130/1	relay board SR04
TM 4/100X	Permanent electric lifting traverse TM 4/100X for the transport of individual sheets Dimensions Length: 3,000 - 12,000 mm Width: 500 - 3,500 mm Thickness: 5 - 80 mm Max. load: 10 tons Technical information on dimensions, weight and Load specifications according to technical drawings
Maxx250	
MaxX 500	
TM 4/100X	Permanent electric lifting beam TM 4/100X for transporting individual sheets with dimensions Length: 3,000 - 12,000 mm Width: 500 - 3,500 mm Thickness: 5 - 80 mm Max. load: 10 tons Technical information on dimensions, weight and load specifications according to technical drawings
Maxx 500	
Qx303umk6 / 00270	
30408172	Lid for 5/10 pin CML socket (IP68)
St211fb - V3	
Maxx 300	
St500 T 12.2009 00256	
Qx408umk6 / 00577	
St200	Control unit ST200 > 400V / 50Hz to drive a magnetic chuck > 5m cable between control unit and magnetic chuck > 4m supply cable without mains plug

St100	Please see attached Photo
Sq 306 St70/Tá;Á;300x605	
Control Unit For Sq24784.00 01036 - Obsolete, Replacement St211fb - V3	
10403037	
St100sk	
295010504	Adapter kit from 7Pin to 10Pin connector system (with 4 x M4 x 20 screw + gasket)
Mte Tm4/075-N	
Mte Mt 4.120.K4 Smh/30	
Qx 509 He50	We need an electromagnetic table to be used on the Lagun BM2 machine. The new model of the electromagnetic table is attached and its dimensions are 470mm x 910mm with the "509 model number".
20401123/1	
Cnl07ch02	
St100f	
Qx 303 Hd50	Permanent electric chuck QX 303 HD50 Dimensions 310 x 340 x 51 mm, 16 poles 5-pin ERGON plug-in contact, design according to drawing > Replaceable threaded bush M 8 made of high - strength material in every pole > maximum rigidity through monoblock construction
Mtg 610 Hd - Manyetik Tabla 600x1100mm	
Sq 404 Hd70/T 400x415	
Sq 405 St50/T 400x480	
Shaft For Maxx 500	
Maxx 1000	
St100f 3kva	
203019167.3	
30408179	Sealing ring for CML connector female
Max X 1000	
BAT-GRIP 250/N	LifLifting magnet type BAT-GRIP 250 / N for flat material up to 2.5 tons Technical information on dimensions, weight and load specifications according to technical drawings
St120f / V2 4 Ch	
St120f / V2	
Sq 304 Hd70/T 310x415	
St210r 2 Sch	
St120f / V2 (2ch)	
20407014	
1500 Kg Kaldirma Magneti	
Mtg406 405x600	
30408177	CML 10Pin male (female-IP68) with 10mtr. Metal coated (10x2mm ²) 4,4 Kg

Maxx 250	
Sq 506 St70/T Á:460x605	
Maxx 125	the lifting magnet MaxX 125.
20407015	
1 Maxx 2000	
St100r / V2	
30408174	CML 10Pin male (female-IP68) with 3mtr. Metal coated (10x2mm ²) 1,4 Kg
Maxx 2000	
20401120/11	Control board ST200-7 (ST210) FW: 7.5noIFC HW: 11 (milling / grinding)
Mtg405 405x500	
Sq 306 Hd70/T 310x605	
30408175	CML 10Pin male (female-IP68) with 5mtr. Metal coated (10x2mm ²) 2.2 Kg
Mte-Tm4/80	
295010170	
30408171	CML 10Pin socket on the plate (male / male) (IP68 only with cover)
Sq 403 St50/T 400x330	