

## Thomas Betts

Garanti: 12 ay  
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Thomas Betts** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

*Firmamız Thomas Betts T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*



¼r¼n	A¼ıklama
<a href="#">Wiring Duct Covers 3"</a>	TY3CP6
<a href="#">Wiring Duct 3wx4d</a>	TY3X4W PG6
<a href="#">Wiring Duct Covers 4"</a>	TY4CP6
<a href="#">Wiring Duct 4wx4d</a>	TY4X4W PG6
<a href="#">TY27MX</a>	BLACK CABLE TIES, UV-RESISTANT ABM. 7.6 X 338 MM ROHS COMPLIANT Price per p100 (100 pieces)
<a href="#">TYL546MX-</a>	CABLE TIE, 250 LB, L> 342 MM, UV RESISTANT, NYLON Minimum order quantity: 50 pieces Packaging unit: 50 pieces
<a href="#">SMNY-001-0-D</a>	Kabelbindersockel Ty-Fast B=15.2, L=9.8, H=7.1 PA 6.6 schwarz Befestigungsbohrung D=4.2 / UV-bestaendig 12082258
<a href="#">TB-YLS-4,6-520-B</a>	STAINLESS STEEL CABLE TIES 4,6X520MM STAINLESS STEEL 316 UNCOATED Price per p100 (100 pieces) Packaging unit: 100 pieces
<a href="#">TBM15 15 Ton Hydraulic Crimper Head</a>	
<a href="#">Adapter 15500-TB or U-Die Adapter for TBM 15i</a>	Crimp Head

<a href="#">Set of Dies that include: Black Die Cat No.</a>	15515-CK, Die Code No. 106H; Purple Die Cat No. 15609, Die Code No. 112H, if no set available then just these dies at present.
<a href="#">TB-TY27MX</a>	BLACK CABLE TIES, UV-RESISTANT ABM. 7.6 X 338 MM ROHS COMPLIANT Packaging unit: 500 pieces
<a href="#">E23018 (M)</a>	
<a href="#">41400 serie</a>	unser Kunde m¼chte den Hersteller wechseln und m¼chte f¼r diese produkte wenn sie haben einen Angebot (Jahres bedarf 45.000 Stk.) 6-10-16-25-35-50 mm2
<a href="#">TB-TY27MX-A</a>	TY-RAP STEEL NOSE CABLE TIES STANDARD, 340X6.86MM, 540N, BLACK PA6.6, UV-RESISTANT, HEAT STABILIZED ROHS COMPLIANT
<a href="#">TB-TYC25MX</a>	CABLE TIE, BLACK POLYAMIDE (NYLON 12) FOR TEMPERATURES UP TO 85 DEGREES CELSIUS (185F), WEATHER AND ULTRAVIOLET RESISTANT FOR INDOOR AND OUTDOOR APPLICATIONS, LENGTH OF 184.45MM (7.25 INCHES), WIDTH OF 4.52MM (0.178 INCHES), THICKNESS OF 1.021MM (0.04 INCHES), TENSILE STRENGTH RATING OF 155 Price per p100 (100 pieces) Packaging unit: 1,000 pieces
<a href="#">TB-TYC-27MX</a>	CABLE TIES ABM. 7.6 X 338 MM ROHS COMPLIANT Price per p100 (100 pieces) Packaging unit: 500 pieces
<a href="#">TB-TY528MXR</a>	UV-RESISTANT CABLE TIES ABM. 4.8 X 360 MM ROHS COMPLIANT Price per p100 (100 pieces) Packaging unit: 100 pieces
<a href="#">TB-ERG4007</a>	HAND TOOLS ERGONOMIC INSULATED / UNINSULATED CONNECTORS
<a href="#">TB-TC-347</a>	FASTENING BASE ROHS COMPLIANT Price per p100 (100 pieces)
<a href="#">CABLE TIE,T&amp;B,RSTY23MFR,POLYAMIDE6.6</a>	
<a href="#">RSK301 7TCI029060R0029</a>	
<a href="#">RSK201 7TCI029060R0027</a>	
<a href="#">TB-TC-105</a>	MOUNTING BASE (VPE 100 pieces)
<a href="#">TB-TYL546MX</a>	TY-FAST CABLE TIES HEAVY DUTY 546X13.2MM PA 6.6, BLACK UV-RESISTANT, 5 ROHS COMPLIANT
<a href="#">TB-TY528MR-NDT</a>	CABLE TIES TY-RAP WITH DETECTABLE METAL COMPONENT 360 X 4.67MM, POLYAMIDE 6.6 MP, 222N, BLUE Packing unit 100 pieces
<a href="#">0.194672.D</a>	WATER PROOF STRAIGHT COUPLING 5332 D.1/2 NPT M
<a href="#">WATER PROOF STRAIGHT COUPLING 5332 D.1/2 NPT M</a>	
<a href="#">FLEXIBLE SHURESEAL TBDL 0500-60</a>	

<a href="#">D.1/2"</a>	-40Å°-105Å°C "THOMAS & BETTS"
<a href="#">FLEXIBLE SHURESEAL TBDL 0375-75 D.3/8"</a>	-40Å°-105Å°C
<a href="#">WATER PROOF STRAIGHT COUPLING 5332 D.1/2 NPT M</a>	
<a href="#">NPT 1/2"90Å°ANGLE CONNECT. FOR FLEX 1/2"</a>	COD T&B 5352
<a href="#">NPT 1/2" THREAD LIQUIDTIG FITTING STRAIGHT</a>	CONNECT COD T&B 5331
<a href="#">NPT 1/2"90Å°ANGLE CONNECT. FOR FLEX 3/8"</a>	COD T&B 5351
<a href="#">COUNTER RING NUT FOR COUPLING NPT 1/2"NPT</a>	
<a href="#">HSTW 20</a>	
<a href="#">Befestigungssockel,H=8.5 L=29.0 B=29.0</a>	PA 6.6/ THOMAS+BETTS/ TC347A
<a href="#">COUNTER RING NUT FOR COUPLING NPT 1/2"NPT</a>	
<a href="#">COUNTER RING NUT FOR COUPLING NPT 1" NPT</a>	
<a href="#">EZ-WHS14</a>	
<a href="#">EZ-WHS38</a>	
<a href="#">EZ-YHS14</a>	
<a href="#">EZ-YHS14</a>	
<a href="#">STX050- 462</a>	
<a href="#">STX050-464</a>	
<a href="#">STX075-465v</a>	
<a href="#">STX075-466</a>	
<a href="#">9362 M20x1.5</a>	WATER PROOF STRAIGHT COUPLING 9362 M20X1,5
<a href="#">484 9411</a>	
<a href="#">2 0 Sol 1 0 Str P N 8t</a>	
<a href="#">1 5 8 X 1 5 8 Flat Fitting Ab241 5 8 Superstrut</a>	
<a href="#">15504</a>	
<a href="#">5332 D.1/2 Npt M</a>	WATER PROOF STRAIGHT COUPLING 5332 D.1/2 NPT M

<a href="#">166lr-C-5260</a>	CONNECTOR ELBOW , LOADBREAK, W/TEST POINT, 15 KV, 200 A
<a href="#">171 14</a>	
<a href="#">Tc 347</a>	Mounting base m. 2 inputs 28.6 mm x 28.6 mm, binder width: 7,6mm Pack of 1000 pieces
<a href="#">Tbdl 0500-60 D.1/2" -40°-105°c (3.000mm)</a>	FLEXIBLE SHURESEAL TBDL 0500-60 D.1/2" -40°-105°C
<a href="#">1/2" Iso7/1-228/1 Ch.30° C</a>	FLEX END NIPPLE 1/2" ISO7/1 - 228/1 CH.30° C STEEL ZINC COAT. EN 10204/2.2
<a href="#">484 9405</a>	
<a href="#">171 14 14p 14m</a>	
<a href="#">146 Tb</a>	
<a href="#">01901470</a>	