

Thomas Betts

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Thomas Betts Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Thomas Betts T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
Wiring Duct Covers 3"	TY3CP6
Wiring Duct 3wx4d	TY3X4W PG6
Wiring Duct Covers 4"	TY4CP6
Wiring Duct 4wx4d	TY4X4W PG6
TY27MX	BLACK CABLE TIES, UV-RESISTANT ABM. 7.6 X 338 MM ROHS COMPLIANT Price per p100 (100 pieces)
TYL546MX-	CABLE TIE, 250 LB, L> 342 MM, UV RESISTANT, NYLON Minimum order quantity: 50 pieces Packaging unit: 50 pieces
SMNY-001-0-D	Kabelbindersockel Ty-Fast B=15.2, L=9.8, H=7.1 PA 6.6 schwarz Befestigungsbohrung D=4.2 / UV-bestaendig 12082258
TB-YLS-4,6-520-B	STAINLESS STEEL CABLE TIES 4,6X520MM STAINLESS STEEL 316 UNCOATED Price per p100 (100 pieces) Packaging unit: 100 pieces
TBM15 15 Ton Hydraulic Crimper Head	
Adapter 15500-TB or U-Die Adapter for TBM 15i	Crimp Head

Set of Dies that include: Black Die Cat No.	15515-CK, Die Code No. 106H; Purple Die Cat No. 15609, Die Code No. 112H, if no set available then just these dies at present.
TB-TY27MX	BLACK CABLE TIES, UV-RESISTANT ABM. 7.6 X 338 MM ROHS COMPLIANT Packaging unit: 500 pieces
E23018 (M)	
41400 serie	unser Kunde m¼chte den Hersteller wechseln und m¼chte f¼r diese produkte wenn sie haben einen Angebot (Jahres bedarf 45.000 Stk.) 6-10-16-25-35-50 mm2
TB-TY27MX-A	TY-RAP STEEL NOSE CABLE TIES STANDARD, 340X6.86MM, 540N, BLACK PA6.6, UV-RESISTANT, HEAT STABILIZED ROHS COMPLIANT
TB-TYC25MX	CABLE TIE, BLACK POLYAMIDE (NYLON 12) FOR TEMPERATURES UP TO 85 DEGREES CELSIUS (185F), WEATHER AND ULTRAVIOLET RESISTANT FOR INDOOR AND OUTDOOR APPLICATIONS, LENGTH OF 184.45MM (7.25 INCHES), WIDTH OF 4.52MM (0.178 INCHES), THICKNESS OF 1.021MM (0.04 INCHES), TENSILE STRENGTH RATING OF 155 Price per p100 (100 pieces) Packaging unit: 1,000 pieces
TB-TYC-27MX	CABLE TIES ABM. 7.6 X 338 MM ROHS COMPLIANT Price per p100 (100 pieces) Packaging unit: 500 pieces
TB-TY528MXR	UV-RESISTANT CABLE TIES ABM. 4.8 X 360 MM ROHS COMPLIANT Price per p100 (100 pieces) Packaging unit: 100 pieces
TB-ERG4007	HAND TOOLS ERGONOMIC INSULATED / UNINSULATED CONNECTORS
TB-TC-347	FASTENING BASE ROHS COMPLIANT Price per p100 (100 pieces)
CABLE TIE,T&B,RSTY23MFR,POLYAMIDE6.6	
RSK301 7TCI029060R0029	
RSK201 7TCI029060R0027	
TB-TC-105	MOUNTING BASE (VPE 100 pieces)
TB-TYL546MX	TY-FAST CABLE TIES HEAVY DUTY 546X13.2MM PA 6.6, BLACK UV-RESISTANT, 5 ROHS COMPLIANT
TB-TY528MR-NDT	CABLE TIES TY-RAP WITH DETECTABLE METAL COMPONENT 360 X 4.67MM, POLYAMIDE 6.6 MP, 222N, BLUE Packing unit 100 pieces
0.194672.D	WATER PROOF STRAIGHT COUPLING 5332 D.1/2 NPT M
WATER PROOF STRAIGHT COUPLING 5332 D.1/2 NPT M	
FLEXIBLE SHURESEAL TBDL 0500-60	

D.1/2"	-40Å°-105Å°C "THOMAS & BETTS"
FLEXIBLE SHURESEAL TBDL 0375-75 D.3/8"	-40Å°-105Å°C
WATER PROOF STRAIGHT COUPLING 5332 D.1/2 NPT M	
NPT 1/2"90Å°ANGLE CONNECT. FOR FLEX 1/2"	COD T&B 5352
NPT 1/2" THREAD LIQUIDTIG FITTING STRAIGHT	CONNECT COD T&B 5331
NPT 1/2"90Å°ANGLE CONNECT. FOR FLEX 3/8"	COD T&B 5351
COUNTER RING NUT FOR COUPLING NPT 1/2"NPT	
HSTW 20	
Befestigungssockel,H=8.5 L=29.0 B=29.0	PA 6.6/ THOMAS+BETTS/ TC347A
COUNTER RING NUT FOR COUPLING NPT 1/2"NPT	
COUNTER RING NUT FOR COUPLING NPT 1" NPT	
EZ-WHS14	
EZ-WHS38	
EZ-YHS14	
EZ-YHS14	
STX050- 462	
STX050-464	
STX075-465v	
STX075-466	
9362 M20x1.5	WATER PROOF STRAIGHT COUPLING 9362 M20X1,5
484 9411	
2 0 Sol 1 0 Str P N 8t	
1 5 8 X 1 5 8 Flat Fitting Ab241 5 8 Superstrut	
15504	
5332 D.1/2 Npt M	WATER PROOF STRAIGHT COUPLING 5332 D.1/2 NPT M

166lr-C-5260	CONNECTOR ELBOW , LOADBREAK, W/TEST POINT, 15 KV, 200 A
171 14	
Tc 347	Mounting base m. 2 inputs 28.6 mm x 28.6 mm, binder width: 7,6mm Pack of 1000 pieces
Tbdl 0500-60 D.1/2" -40°-105°c (3.000mm)	FLEXIBLE SHURESEAL TBDL 0500-60 D.1/2" -40°-105°C
1/2" Iso7/1-228/1 Ch.30° C	FLEX END NIPPLE 1/2" ISO7/1 - 228/1 CH.30° C STEEL ZINC COAT. EN 10204/2.2
484 9405	
171 14 14p 14m	
146 Tb	
01901470	