



Thyracont

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye ii kapı teslim fiyat ve teslim s¼resi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Thyracont Markası, tedarik s¼resi iin l¼tfen bizimle iletiŐime geiniz.

Firmamız Thyracont T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	Aıklama
B_VSM77	
SLKBT	
SLKUSB	
SLN4	
VD85M	
VSM77D	
VSP63MA4	
W1515010	
XB15SL05	
ZSR2025	
ZZCH025	
ZZR025	
VSP63MV	Pirani vacuum transmitter Absolute pressure 1.0e-4 - 1000 hPa Output signal 1.5 - 8.5 V logarithmic Electrical connection: Hirschmann 6-pin male. Stainless steel flange DN 16 ISO-KF
W0600002	Measuring cable with open ends, 2 m

DCERT	Factory calibration digital
VCP63MV Vacuum transmitter Pirani	absolute pressure 5.0e-4 - 1000 hPa, Corrosive gas version, platinum-rhodium filament Output signal: 2.2-8.5 V (logarithmic) Electrical connection: Hirschmann 6-pin male. Stainless steel flange DN16 KF
XB0600002	Line socket 6-pin. GO 6 WF Mating connector for analog line transmitter 0-10 V
DCERT - Factory calibration digital	four-page calibration certificate as a PDF DOCUMENT for documentation, 4 reference points per printing decade (traceable to national ODAKS standards)
VD85	Compact vacuum gauge Piezo / Pirani Absolute pressure 5.0e-4 - 1200 hPa, combination sensor Data logger function, min/max memory USB interface for battery (9 V) or ext. Power adapter (15V) Stainless steel flange DN 16 ISO-KF
VD8ZUB	Accessory set VD8 consisting of: VD8CASE protective case VD8, with foam insert, 275 x 230 x 83 mm; VD8N4 plug-in power supply 15 V, input plug: AC plug, EURO, US, UK, AUS Output: 15 VDC / 200 mA, DC jack connector: 2.5 x 5.5 x 10 mm; VD8ALK alkaline block battery 9 V (vacuum tested); WUSB0002 Interface cable, 2 m, USB; VGR VacuGraph 11 software, for Windows Vista / 7 / 8 / 10 / 11
VCP63MA4	Vakuumtransmitter Pirani
XB0500004	Angle socket 5-pin, series 713 Mating connector, 5-pin for analog line transmitters 4-20 mA
DCERT	Factory calibration digital
SP363MV	Pirani vacuum transmitter Absolute pressure 1.0e-4 - 1000 hPa Output signal 1.0 - 10 V logarithmic (1.286 V/decade) Electrical connection: FCC68 8-pin female. Stainless steel flange DN 16 ISO-KF
VSP63MV	Pirani vacuum transmitter Absolute pressure 1.0e-4 - 1000 hPa Output signal 1.5 - 8.5 V logarithmic Electrical connection: Hirschmann 6-pin male. Stainless steel flange DN 16 ISO-KF
VD85	Compact vacuum gauge piezo / Pirani Absolute pressure 5.0e-4 - 1200 hPa, combination sensor Data logger function, min/max memory USB interface for battery (9 V) or ext. Power supply (15V) Stainless steel flange DN 16 ISO-KF
VD8ZUB	Accessory set VD8 consisting of: VD8CASE VD8 protective case, with foam insert, 275 x 230 x 83 mm; VD8N4 plug-in power supply 15 V, input plug: AC change-over plug, EURO, US, UK, AUS Output: 15 VDC / 200 mA, DC jack plug: 2.5 x 5.5 x 10 mm; VD8ALK alkaline block battery 9 V (vacuum tested); WUSB0002 interface cable, 2 m, USB; VGR VacuGraph 11 Software, for Windows Vista / 7 / 8 / 10 / 11
VD8ANS	Connection set consisting of: - 1 piece ZTS016 DN 16 ISO-KF T-piece, stainless steel - 2 pieces ZZR016 DN 16 ISO-KF centering sealing ring, stainless steel / Viton - 2 pieces ZSR1016 DN 10/16 ISO-KF clamping ring, aluminum
VCP63MA4	Pirani vacuum transmitter
VSP63MV	Absolute pressure 5.0e-4 - 1000 hPa Corrosive gas version, platinum-rhodium filament Output signal 4-20 mA logarithmic Electrical connection: M12 A, 5-pin male Stainless steel flange DN 16 ISO-KF
Vd8alk	
Vsp62mvsww	
Wusb0002	

Vd85
Vd8case
Vgr
Vd8ans
W 1500002
Zzr016
Vd81
Vd8n4
Vd84
W 0606002
Adjcert
Vsr53d
Zsr1016
Vd81sw1
Vd85m Obsolete/Replacement Vd85
Vd83
Vsp63mv
Vsp52_Ma4
Vcc200ma4
Vsh88d
Vd84/1
Vsm77dl