

Tidland

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Tidland Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Tidland T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
M189076	Tidland Roll Saver Mark II A hydraulic precision device for the Restoration of pressed cardboard tubes in paper rolls. Standard model for HID 70 + 76mm Max. Penetration depth 250 mm Max. Roll width 500 mm Max. Roller diameter 1100 mm 8.5000 kg
Chuck M203615	SN 6439,7357,25581
M000005	11946 + 11947
	TIDLAND paper cut knife holder: The patented TIDLAND 'Performance' knife holder has a unique 3-function Selector switch [only in the automatic version] equipped for easy handling. Thanks to The additional automatic half-stroke function can make the knife safe, quick and can easily be delivered to the bedknife. The handling of the knife holder is explained above In addition, thanks to the easily replaceable connecting wedge, a quick and safe option changing the cutting head and the dust-protected design make it even easier. Through the Combining these features with the optional 360° knife protection makes it possible To improve service life and safety when changing knives. TIDLAND knife

[PSA2\(0.50\)Tm-A?-M](#)

holder 'Performance-Scissor Cut', 'Automatic' - Class 'II' Knife holder type: A automatic Knife diameter: 2 class 2 = 150 mm Cutting angle: 0.50 Cutting head: Tm swing + 360° mechanical protection Web direction: A Cutting edge: L / R left / right of the bottom knife ??? Clamping: M manual Mounting bracket: _ Standard guide rail Blade material: 1.2379 (X155 CrVMo 121 standard) -profile: 25° GDF Additional special knives for special applications can be added as an option. Minimum cutting width: 49.0 mm (knife holder) Max. speed: 1680 m/min (knife holder) At least 5µm filtered, oil and water-free, regulated air must be used. More Functional data and information can be found in the technical instructions.

[1-800-426-1000 S/N 767291 Replaced By Css-01 \(M258915\)](#)

[M147550](#)

[M186456](#)

[091245-004ã542000](#)

[04545-002](#)

[Mark Ii](#)

[M230119](#)

[Pneumatic Core Holder For 840699](#)
[Obsolete](#)

[201338-Tid](#)

[M266336](#)

[Holder Pins For 62045135/F/78750](#)

[Hv-13](#)

[131393](#)

[Se-44rm289867](#)

[M187198](#)

[M441466](#)

[M186443](#)

[M255217](#)

[M289899](#)

[536160](#)

CONTROL ASSY

[M000005](#)

[M397275](#)

[Se-24](#)

[Se-44](#)

[M258915](#)