

Timotion

Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Timotion Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Timotion Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.



rn	Aıklama
LINEER ACTUATOR, TA2P-2K	Model: TA2P-2K Part No: TA2P-2100-001 Spec code: TA2P-2K-100246-2211-523-3 Serial No: 201508031774 IP66 DC24V Max. 3,0 Amp
TA7-2100-005	
TA2P-IP66 D	
TA2P-2K-100246-2211-523-3	Voltage(24V DC), Load & Speed(6600RPM, Load>Push:1500/Pull:1500 ,speed:10mm/s), Stroke(Stroke:100 mm), Retracted Length(Retracted length:246 mm), Rear attachment(mm)(Aluminum casting, hole 8.0, one piece casting with gear box), Front attachment(mm)(Aluminum casting, hole 8.0), Direction of rear attachment (counterclockwise)(90°), Functions for limit switches(Two switches at full retracted/extended positions to cut current), Output signal(Hall sensor*2), Connector(Tinned leads), Cable length(Straight, 1000mm), IP rating(IP66)
TA7-2100-030	
TA2P-Series IP66	
TA7-2L-300485-27121-01013-M	DC24 max %10 max2min /18min pushl 6000N max 5, 5 amp TA7-2100-027
TA2P-2K-100246-2211-523-3	Voltage(24V DC), Load & Speed(6600RPM, Load>Push:1500/Pull:1500 ,speed:10mm/s), Stroke(Stroke:100 mm), Retracted Length(Retracted length:246 mm), Rear attachment(mm)(Aluminum casting, hole 8.0, one piece casting with gear box), Front attachment(mm)(Aluminum casting, hole 8.0), Direction of rear attachment (counterclockwise)(90°), Functions for limit switches(Two switches at full retracted/extended

	positions to cut current), Output signal(Hall sensor*2), Connector(Tinned leads), Cable length(Straight, 1000mm), IP rating(IP66)
TA2P-2100-005	IP66 DC 24V
LINEER ACTUATOR, TA2P	
MA2 2 G 360 564 4 5 2 6 0 0 2 3 3 1 0	
TA2P.2100.004 TA2P 1500N 200mm	
TA7-Series	
TA2P-2C-050174-4421-022-1	Voltage(24V DC), Load & Speed(5200RPM, Load>Push:1000/Pull:1000,speed:11.8mm/s), Stroke(Stroke:050 mm), Retracted Length(Retracted length:174 mm), Rear attachment(mm) (Aluminum, U clevis, slot 6.0, depth 10.5, hole 6.4, one piece casting with gearbox), Front attachment(mm)(Aluminum, U clevis, slot 6.0, depth 16.0, hole 6.4), Direction of rear attachment (counterclockwise) (0°), Function of limit switches(Two micro switches cut off the actuator at end of stroke (EOS)), Output signal(Without), Connector(Tinned leads), Cable length(Straight, 600mm), IP rating(Without)
TA2-2100-001 100N 50 mm 24VDC LINEER AKT¼	
TA7-2LM	
TA2P.2100.004	Linear Actuator
Ta2-2100-003	
Ta23	
Ta7-2100-004	
Ta2-Series	
Tc1-S3na-4 Oem	
Ta7-2lm Oem	
Ta1	
Ta7-5lm Oem	