

Tival Sensors



Garanti: 12 ay

Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

Tival Sensors Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Tival Sensors Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
Pressure Switch Tival Ff4-4dah 0,22-4bar	
Ff4- 4 Dah	Pressure switch with Perbunan membrane Setting range: 0.07 ... 4 bar Pressure connection: 3/8 "inside (silumin) Tariff number 90322000
Ff4- 16 Vds Dai	Pressure switch with Perbunan membrane Setting range: 0.5 ... 16 bar Pressure connection: 1/2 "inside (silumin) VdS approval Product number 90322000
16-120 BAR 3/8 - FF4-120 PAH	
3/8" 0,5-8 BAR - TIVAL FF4-8 DAH	
FF4- 4 DAY A	Pressure switch with Perbunan membrane Setting range: 0.07 ... 4 bar Pressure connection: 3/8 "inside (polyamide) Lot number 90322000
FF4- 30 AAG	Pressure switch with corrugated stainless steel pipe Setting range: 1 ... 30 bar Pressure connection: 1/4 "inside (stainless steel) Max. Medium temperature: 200 ° C Lot number 90322000
FF4- 10 VdS DAI	Pressure switch with Perbunan membrane Setting range: 0 ... 10 bar Pressure connection: 1/2 "inside (Silumin) VdS approval Lot number 90322000
FF4- 60 PAH G	Setting range: 4 ... 60 bar Pressure connection: 3/8 "inside (stainless steel) Gold-plated contacts Lot number 90322000
TS-UNS-*-02-...	Zone 0 -- Ex II 1G Ex ia IIB T5 Ga
FF4- 250 AB PAH	Pressure switch with plastic piston Setting range: 14 ... 250 bar Pressure connection: 3/8 "inside (stainless steel) Approval ATEX EN 60079

PRJ000360 MISC-0014	TS-EX
EWTSB.4x44.3.1PtM-4.0.G1/4"(10mm) 1110539	Screw-in resistance thermometer with Binder M12x1 round connector Sensor: 1 x Pt1000 Accuracy: class B according to DIN EN 60751 Connection type: 4-wire circuit Connector: Binder Round connector M12x1 (max. 90 ° C), 4-pin, pin assignment: 1.3 & 2.4 Measuring range: -50 ... +250 ° C Protection tube: Ø 4 mm Process connection: G 1/4 ", HEX SW 22 Installation length: 44 mm, including the thread of the G 1/4 "process connection (10 mm) Height including M12x1 connector: 56 mm Case diameter: 18 mm Material: stainless steel 1.4301 Lot number 90251900
EWTSB.4x39.3.1PtM-4.0.G1/4" (10mm)1110540	Screw-in resistance thermometer with Binder M12x1 round connector Sensor: 1 x Pt1000 Accuracy: class B according to DIN EN 60751 Connection type: 4-wire circuit Connector: Binder Round connector M12x1 (max. 90 ° C), 4-pin, pin assignment: 1.3 & 2.4 Measuring range: -50 ... +250 ° C Protection tube: Ø 4 mm Process connection: G 1/4 ", HEX SW 22 Installation length: 39 mm, including the thread of the G 1/4 "process connection (10 mm) Height including M12x1 connector: 56 mm Case diameter: 18 mm Material: stainless steel 1.4301 Lot number 90251900 country of origin: Germany
1010 003	
1010 016	
1010 062	
1010 063	
1010 069	
1010 072	
1010 073	
1010 074	
1010 087	
1010 094	
1010 096	
1010 100	
1010 109	
1010 117	
1010 122	
1010 299	
1010 300	

[1010026](#)

[1010076](#)

[1010078](#)

[1010081](#)

[1010084](#)

[1011 002](#)

[1011 003](#)

[1011 004](#)

[1020 068](#)

[1020 070](#)

[1020067](#)

[1020080](#)

[1030 131](#)

[1030 132](#)

[1030 134](#)

[1030 139](#)

[1030 141](#)

[1030 144](#)

[1030 149](#)

[1040 007](#)

[1040 011](#)

[1050 003](#)

[1050 005](#)

[1050 009](#)

[1050 026](#)

[1050 027](#)

[1050 028](#)

[1051 006](#)

[1070 025](#)

[1071 008](#)

[1071 009](#)

1071 042
1080 001
1080 002
1080 008
1080 014
1090 001
1090 002
1090 200
1090 202
1090 203
1090 205
1090 223
1090 224
1090 225
1090 226
1090 241
1090 242
1090 245
1090 600
1090 603
1090 620
1091 003
1091 006
1120194
1120198
1120201
1121007
23E01 LISTED:297E
5357
FF 142-8 DAH

FF 4 - 2 Vds DRI	
FF 4-250 GL PAH	
FF 4-4 AB DAH G3/8"	
FF 4-4ACDAH 1030142	
FF4- 250	
FF4-4 DAH	
FF4-4 AB DAH I	
FF4-8 DAH	
TS-KGS-W1222-PL	
TST-DD 10.0	
TST-DD 10.0-25-D	
TST-DD 10.0-2-D	
TST-DD 10.0-5-D	
TST-DD 20.0-25-D	
TST-DD 20.0-2-D	
FF4- 120 PAH	Pressure switch with plastic piston Setting range: 8...120 bar Pressure connection: 3/8" inside (stainless steel) Commodity number 90322000 Country of origin: CZ/EEC
AIR FRESHER SENSOR FF4-32	Pressure switch with Perbunan membrane Setting range: 0.8...32 bar Pressure connection: 3/8" inside (Silumin) Commodity number 90322000
FF4-8 DAH	Pressure switch with Perbunan membrane Setting range: 0.2...8 bar Pressure connection: 3/8" inside (Silumin)
Ex21A.3,2x11.3.2Pt-3.0.2000/8000TTDT	System type: KF EC certificate no.: IBExU 09 ATEX1143 X Degree of protection: intrinsic safety Classification: EX II 2G Ex ia IIC T6-T2 according to DIN EN 60079-0:2012 according to DIN EN 60079-11:2012 Insulation class: H Sensor: 2 x Pt100 Accuracy: Class B according to DIN EN 60751 Connection type: 3-wire circuit (from transition sleeve) Measuring range: -50°C...+180°C Protective tube: Ø 3.2 mm L1: 2,000mm Material: VA connecting cable: FEP / FEP / wire mesh / FEP 6*AWG24 Sheath color: blue Wire colors: red, red, white, black, black yellow L2: 8,000mm Line between protective tube and transition sleeve: FEP / Cu braid / PFA 4*AWG26 Sheath color: transparent Wire colors: red, red, white, white Shield placed on transition sleeve Shield: 50 mm brought out Pressure resistance: 3 bar (oil pressure) High voltage test: 250V/AC above 1 at least Incl. documentation / operating instructions EC Certificate No.: IBExU 09 ATEX1143 X Degree of protection: intrinsic safety Classification: EX II 2G Ex ia IIC T6-T2, Ex II 2G Ex ia IIIC Tx

	Db
1020080	FF4- 10 VdS DAI Pressure switch with Perbunan membrane Setting range: 0...10 bar Pressure connection: 1/2" inside (Silumin) VdS approval
FF4- 16 DAH	Pressure switch with Perbunan membrane less 15.00% -31.68 Setting range: 0.4...16 bar Pressure connection: 3/8" inside (Silumin)
FF4- 4 DAH	Pressure switch with Perbunan membrane Setting range: 0.07...4 bar Pressure connection: 3/8" inside (silumin)
FF4- 12 AAG	Pressure switch with stainless steel corrugated tube Setting range: 0.5...12 bar Pressure connection: 1/4" inside (stainless steel)
FF4- 10 VdS DAI	Pressure switch with Perbunan membrane Setting range: 0...10 bar Pressure connection: 1/2" inside (Silumin) VdS approval
FF4-4-AB DAH	PRESSURE SWITCH / FF4-4 AB DAH / BVS 06 ATEX E 056 / TYP:1030134 / I M2 Ex ia I Mb / TIVAL SENSOR
Ff4- 8 Dah	Sensor
Ff4- 250 Ab Pah	Pressure switch with plastic piston Adjustment range: 14 ... 250 bar Pressure connection: 3/8 "inside (stainless steel) Approval ATEX EN 60079 Lot number 90322000 Origin: EEC / DE
Ff4- 120 Pah	1010079 Pressure switch with plastic piston Adjustment range: 8 ... 120 bar Pressure connection: 3/8 "inside (stainless steel) Lot number 90322000
Ff4- 32 Gl Dah	Pressure switch with Perbunan membrane Adjustment range: 0.2 ... 32 bar Pressure connection: 3/8 "inside (silumin) GL approval Lot number 90322000
Ps1-A3a	
FF4- 4 AB DAH	Pressure switch with Perbunan membrane Adjustment range: 0.07 ... 4 bar Pressure connection: 3/8 "inside (zinc die-cast) Approval ATEX EN 60079 Lot number 90322000 Origin: EEC / DE