



## TLV

Garanti: 12 ay

Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

**TLV** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

*Firmamız TLV T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*

¼r¼n	A¼ıklama
<a href="#">Druckreduzierendes Dampfventil Dn50 Pn40 Cs</a>	angeflanscht Fl¼ssigkeit: Wasserdampf; Auslegungsdruck und -temperatur: 26 bar.g @ 230 derC; Arbeitsbedingungen in der Sattedampfphase; Arbeitsdruck: 18-20 bar.g; Ausgangsdrucksollwert: 3-5 bar.g; Kapazit¼t: 13-14 TPH
<a href="#">1/2 "800lb Sw Astm A105 Absperrschieber</a>	
<a href="#">1 "300lb Kondensatableiterflansch</a>	(Beispiel: Modell P46SRN der Marke TLV)
<a href="#">1/2 "thermodynamischer</a>	Kondensatableiteranschluss (z. B. TLV-Marke P46SRN-Modell)
<a href="#">Dn40 Pn40 Vollhub-Sicherheitsventil</a>	(Fl¼ssigkeit: Wasserdampf-Einstelldruck: min. 4,5 bar.g)
<a href="#">JF3X-8 DN25 PN16 GGG40.3</a>	Free float steam trap Material: ductile iron (GGG40.3) Nominal width: DN 25/1 "/ 25 mm Connection type: flange PN 16 Installation position: horizontal PMA (maximum allowable pressure): 13barG TMO (max. Permissible operating temperature): 200 ° C Vent: X element Max. Differential pressure: 8 bar HS code: 84818061 Country of origin: JP Item weight: 19.12 kg
<a href="#">J3X-8 3/4" Rp (BSP) GGG40.3</a>	Free float steam trap Material: ductile iron (GGG40.3) Nominal width: DN 20 / 3/4 "/ 20 mm Connection type: threaded socket BSP Installation position: horizontal PMA (maximum allowable pressure): 13barG TMO (max. Permissible operating temperature): 200 ° C Vent: X element Max. Differential pressure: 8 bar HS code: 84818061 Country of origin: JP Item weight: 6 kg

<a href="#">JF3X-8 DN15 PN16 GGG40.3</a>	Free float steam trap Material: ductile iron (GGG40.3) Nominal width: DN 15 / 1/2 " / 15 mm Connection type: flange PN 16 Installation position: horizontal PMA (maximum allowable pressure): 13barG TMO (max. Permissible operating temperature): 200 ° C Vent: X element Max. Differential pressure: 8 bar HS code: 84818061 Country of origin: JP Item weight: 14.24 kg
<a href="#">LV13N 1/2" Rp (BSP) C3771</a>	Thermal capsule steam trap Material: brass (C3771) Nominal width: DN 15 / 1/2 " / 15 mm Connection type: threaded socket BSP PMO (max. Permissible operating pressure): 13barG TMO (max. Permissible operating temperature): 200 ° C HS code: 84818069 Country of origin: JP Item weight: 0.72 kg
<a href="#">VENKAVA VSR8</a>	
<a href="#">1041525</a>	
<a href="#">1083533</a>	
<a href="#">1285064</a>	
<a href="#">1295927</a>	
<a href="#">1295933</a>	
<a href="#">1295973</a>	
<a href="#">1295990</a>	
<a href="#">1296074</a>	
<a href="#">1338207</a>	
<a href="#">1340466</a>	
<a href="#">1342807</a>	
<a href="#">1343342</a>	
<a href="#">3000356</a>	
<a href="#">3004365</a>	
<a href="#">3050167</a>	
<a href="#">5110182</a>	
<a href="#">COSR-16</a>	
<a href="#">SJ5FNX-5</a>	
<a href="#">PN16-DN20</a>	
<a href="#">J3S-X-10 3/4" Rp (BSP) CF8</a>	Free-float steam trap Material: stainless steel (CF8) Nominal width: DN 20 / 3/4" / 20 mm Type of connection: threaded socket BSP Installation position: horizontal PMA (maximum pressure): 21barG TMO (max. allowable operating temperature): 220°C Vent: X element max. differential

	pressure: 10 bar
<a href="#">J3X-10 1" Rp (BSP) GGG40.3</a>	Free-float steam trap Material: nodular cast iron (GGG40.3) Nominal width: DN 25 / 1" / 25 mm Type of connection: threaded socket BSP Installation position: horizontal PMA (maximum pressure): 13barG TMO (max. allowable operating temperature): 200°C Vent: X element max. differential pressure: 10 bar
<a href="#">P46SRN DN20 PN63 A105 (L=210mm)</a>	Thermodynamic condensate drain Material: carbon steel (A105) Nominal width: DN 20 / 3/4" / 20 mm Type of connection: Flange PN 63 PMO (max. allowable operating pressure): 46barG TMO (max. allowable operating temperature): 400°C
<a href="#">TLV LV21 Repair Kit</a>	
<a href="#">5330103</a>	dirt sieve
<a href="#">5338285</a>	X element
<a href="#">5330149</a>	Tension bracket
<a href="#">JF3X-10 DN25 PN16 GGG40.3</a>	1343303 Free-float steam trap Material: nodular cast iron (EN 5.3103) Nominal width: DN 25 / 1" / 25 mm Connection type: flange PN 16 Installation position: horizontal PMA (maximum permissible pressure): 13barG TMO (max. permitted operating temperature): 200°C Venting: X element
<a href="#">L21S DN25 PN40 A105</a>	1295918 Thermal capsule steam trap Material: carbon steel (A105) Nominal width: DN 25 / 1" / 25 mm Connection type: flange PN 40 PMO (max. permitted operating pressure): 21barG TMO (max. permitted operating temperature): 235°C
<a href="#">Repair kit P65SRN A105</a>	3000145
<a href="#">Repair kit P65SRN A105</a>	3000145
<a href="#">V2P-RB 15mm SW ASME F304</a>	1033481 Base unit for drainage station with 2xASV Material: stainless steel (F304) Nominal width: DN 15 / 1/2" / 15 mm Connection type: S.W. ASME welding socket PMO (max. permissible operating pressure): 50barG TMO (max. permitted operating temperature): 425°C
<a href="#">V2P-LB 15mm SW ASME F304</a>	1033509 Base unit for drainage station with 2xASV Material: stainless steel (F304) Nominal width: DN 15 / 1/2" / 15 mm Connection type: S.W. ASME welding socket PMO (max. permissible operating pressure): 50barG TMO (max. permitted operating temperature): 425°C
<a href="#">L21C</a>	1079855 Thermal capsule steam trap unit Material: stainless steel (CF8) Installation position: universal PMA (maximum permissible pressure): 21barG TMO (max. permitted operating temperature): 235°C
<a href="#">Universal connector:</a>	F46 DN20 PN40 CF8 Universal connector Material: stainless steel (CF8) Nominal width: DN 20 / 3/4" / 20 mm Connection type: flange PN 40 Installation position: universal PMA (maximum permissible pressure): 50barG TMO (max. permitted operating temperature): 400°C

<a href="#">Free-float steam trap unit:</a>	S5-10 316L Free-float steam trap unit Material: Type316L Installation position: universal PMA (maximum permissible pressure): 32barG TMO (max. permitted operating temperature): 400°C max. differential pressure: 10 bar
<a href="#">1295980 - COS-16 DN50 PN40 CF8M</a>	Pressure reducer pilot-tested with cyclone dryer + KA Material: stainless steel Nominal diameter: DN 50 / 2" / 50 mm Connection type: flange PN 40 PMO (max. permissible operating pressure): 16 barG TMO (max. permissible operating temperature): 220°C Setting range: 0.3 - 13.4 barG
<a href="#">1295640 / J7x-10 Dn40 Pn16rf</a>	
<a href="#">Ef73 Dn80 Pn40</a>	
<a href="#">J3x-10</a>	
<a href="#">J5x-10</a>	
<a href="#">Jh7rlx-14 Dn50 Pn40</a>	
<a href="#">Sf1 Jis10kff 40a Scs13a 0.5um</a>	
<a href="#">P46sm C22.8</a>	
<a href="#">1338149</a>	
<a href="#">Mc-Cosr-16 Jis10kff 25a Fc250</a>	
<a href="#">Bbf1n Jis10kff 40a Cac407</a>	
<a href="#">P46sm</a>	
<a href="#">901100000000</a>	
<a href="#">Sc-F70-7-N-N-0</a>	
<a href="#">Cosr-16 Jis10kff 25a Fc250</a>	
<a href="#">745000110416</a>	
<a href="#">J3x-8 25a Fcd450</a>	
<a href="#">Bb1n Rc 15a Cac407 Long Handle</a>	
<a href="#">P46sm A105</a>	
<a href="#">29121085</a>	
<a href="#">745050140000</a>	
<a href="#">Y3 25a Sc13a</a>	
<a href="#">Dc3a</a>	
<a href="#">1342561, Jf3x-5 Dn15 Pn16rf</a>	
<a href="#">729000000001</a>	
<a href="#">J7x-10 Dn40 Pn16rf</a>	

<a href="#">Bbfin Jis10kff 40a Cac 407</a>
<a href="#">Tm5/Trapmanager</a>
<a href="#">Dc3s</a>
<a href="#">J8x-10 Dn100 Pn16</a>
<a href="#">J3x-J5x-J7x</a>
<a href="#">1342807, Jf3x-5 Dn20 Pn16rf</a>
<a href="#">J8sn-8-100a- Obsolete, Replaced By J8x-10 Dn100 Pn16</a>
<a href="#">Ja3-16 Bsp 1/2quot;</a>
<a href="#">Ckf3mg-Dn80 Pn40 Cf8</a>
<a href="#">745050080002</a>
<a href="#">Ck3m-A</a>
<a href="#">Bbin Rc 25a C377i</a>
<a href="#">Cos-16 4quot; Jis 20k Rf</a>
<a href="#">1343575 Ja3-16 Bsp R 1/2quot;</a>
<a href="#">Ef73</a>