



TLV

Garanti: 12 ay

Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

TLV Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız TLV T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	A¼ıklama
Druckreduzierendes Dampfventil Dn50 Pn40 Cs	angeflanscht Fl¼ssigkeit: Wasserdampf; Auslegungsdruck und -temperatur: 26 bar.g @ 230 derC; Arbeitsbedingungen in der Sattedampfphase; Arbeitsdruck: 18-20 bar.g; Ausgangsdrucksollwert: 3-5 bar.g; Kapazit¼t: 13-14 TPH
1/2 "800lb Sw Astm A105 Absperrschieber	
1 "300lb Kondensatableiterflansch	(Beispiel: Modell P46SRN der Marke TLV)
1/2 "thermodynamischer	Kondensatableiteranschluss (z. B. TLV-Marke P46SRN-Modell)
Dn40 Pn40 Vollhub-Sicherheitsventil	(Fl¼ssigkeit: Wasserdampf-Einstelldruck: min. 4,5 bar.g)
JF3X-8 DN25 PN16 GGG40.3	Free float steam trap Material: ductile iron (GGG40.3) Nominal width: DN 25/1 "/ 25 mm Connection type: flange PN 16 Installation position: horizontal PMA (maximum allowable pressure): 13barG TMO (max. Permissible operating temperature): 200 ° C Vent: X element Max. Differential pressure: 8 bar HS code: 84818061 Country of origin: JP Item weight: 19.12 kg
J3X-8 3/4" Rp (BSP) GGG40.3	Free float steam trap Material: ductile iron (GGG40.3) Nominal width: DN 20 / 3/4 "/ 20 mm Connection type: threaded socket BSP Installation position: horizontal PMA (maximum allowable pressure): 13barG TMO (max. Permissible operating temperature): 200 ° C Vent: X element Max. Differential pressure: 8 bar HS code: 84818061 Country of origin: JP Item weight: 6 kg

JF3X-8 DN15 PN16 GGG40.3	Free float steam trap Material: ductile iron (GGG40.3) Nominal width: DN 15 / 1/2 " / 15 mm Connection type: flange PN 16 Installation position: horizontal PMA (maximum allowable pressure): 13barG TMO (max. Permissible operating temperature): 200 ° C Vent: X element Max. Differential pressure: 8 bar HS code: 84818061 Country of origin: JP Item weight: 14.24 kg
LV13N 1/2" Rp (BSP) C3771	Thermal capsule steam trap Material: brass (C3771) Nominal width: DN 15 / 1/2 " / 15 mm Connection type: threaded socket BSP PMO (max. Permissible operating pressure): 13barG TMO (max. Permissible operating temperature): 200 ° C HS code: 84818069 Country of origin: JP Item weight: 0.72 kg
VENKAVA VSR8	
1041525	
1083533	
1285064	
1295927	
1295933	
1295973	
1295990	
1296074	
1338207	
1340466	
1342807	
1343342	
3000356	
3004365	
3050167	
5110182	
COSR-16	
SJ5FNX-5	
PN16-DN20	
J3S-X-10 3/4" Rp (BSP) CF8	Free-float steam trap Material: stainless steel (CF8) Nominal width: DN 20 / 3/4" / 20 mm Type of connection: threaded socket BSP Installation position: horizontal PMA (maximum pressure): 21barG TMO (max. allowable operating temperature): 220°C Vent: X element max. differential

	pressure: 10 bar
J3X-10 1" Rp (BSP) GGG40.3	Free-float steam trap Material: nodular cast iron (GGG40.3) Nominal width: DN 25 / 1" / 25 mm Type of connection: threaded socket BSP Installation position: horizontal PMA (maximum pressure): 13barG TMO (max. allowable operating temperature): 200°C Vent: X element max. differential pressure: 10 bar
P46SRN DN20 PN63 A105 (L=210mm)	Thermodynamic condensate drain Material: carbon steel (A105) Nominal width: DN 20 / 3/4" / 20 mm Type of connection: Flange PN 63 PMO (max. allowable operating pressure): 46barG TMO (max. allowable operating temperature): 400°C
TLV LV21 Repair Kit	
5330103	dirt sieve
5338285	X element
5330149	Tension bracket
JF3X-10 DN25 PN16 GGG40.3	1343303 Free-float steam trap Material: nodular cast iron (EN 5.3103) Nominal width: DN 25 / 1" / 25 mm Connection type: flange PN 16 Installation position: horizontal PMA (maximum permissible pressure): 13barG TMO (max. permitted operating temperature): 200°C Venting: X element
L21S DN25 PN40 A105	1295918 Thermal capsule steam trap Material: carbon steel (A105) Nominal width: DN 25 / 1" / 25 mm Connection type: flange PN 40 PMO (max. permitted operating pressure): 21barG TMO (max. permitted operating temperature): 235°C
Repair kit P65SRN A105	3000145
Repair kit P65SRN A105	3000145
V2P-RB 15mm SW ASME F304	1033481 Base unit for drainage station with 2xASV Material: stainless steel (F304) Nominal width: DN 15 / 1/2" / 15 mm Connection type: S.W. ASME welding socket PMO (max. permissible operating pressure): 50barG TMO (max. permitted operating temperature): 425°C
V2P-LB 15mm SW ASME F304	1033509 Base unit for drainage station with 2xASV Material: stainless steel (F304) Nominal width: DN 15 / 1/2" / 15 mm Connection type: S.W. ASME welding socket PMO (max. permissible operating pressure): 50barG TMO (max. permitted operating temperature): 425°C
L21C	1079855 Thermal capsule steam trap unit Material: stainless steel (CF8) Installation position: universal PMA (maximum permissible pressure): 21barG TMO (max. permitted operating temperature): 235°C
Universal connector:	F46 DN20 PN40 CF8 Universal connector Material: stainless steel (CF8) Nominal width: DN 20 / 3/4" / 20 mm Connection type: flange PN 40 Installation position: universal PMA (maximum permissible pressure): 50barG TMO (max. permitted operating temperature): 400°C

Free-float steam trap unit:	S5-10 316L Free-float steam trap unit Material: Type316L Installation position: universal PMA (maximum permissible pressure): 32barG TMO (max. permitted operating temperature): 400°C max. differential pressure: 10 bar
1295980 - COS-16 DN50 PN40 CF8M	Pressure reducer pilot-tested with cyclone dryer + KA Material: stainless steel Nominal diameter: DN 50 / 2" / 50 mm Connection type: flange PN 40 PMO (max. permissible operating pressure): 16 barG TMO (max. permissible operating temperature): 220°C Setting range: 0.3 - 13.4 barG
1295640 / J7x-10 Dn40 Pn16rf	
Ef73 Dn80 Pn40	
J3x-10	
J5x-10	
Jh7rlx-14 Dn50 Pn40	
Sf1 Jis10kff 40a Scs13a 0.5um	
P46sm C22.8	
1338149	
Mc-Cosr-16 Jis10kff 25a Fc250	
Bbf1n Jis10kff 40a Cac407	
P46sm	
901100000000	
Sc-F70-7-N-N-0	
Cosr-16 Jis10kff 25a Fc250	
745000110416	
J3x-8 25a Fcd450	
Bb1n Rc 15a Cac407 Long Handle	
P46sm A105	
29121085	
745050140000	
Y3 25a Sc13a	
Dc3a	
1342561, Jf3x-5 Dn15 Pn16rf	
729000000001	
J7x-10 Dn40 Pn16rf	

Bbfin Jis10kff 40a Cac 407
Tm5/Trapmanager
Dc3s
J8x-10 Dn100 Pn16
J3x-J5x-J7x
1342807, Jf3x-5 Dn20 Pn16rf
J8sn-8-100a- Obsolete, Replaced By J8x-10 Dn100 Pn16
Ja3-16 Bsp 1/2quot;
Ckf3mg-Dn80 Pn40 Cf8
745050080002
Ck3m-A
Bbin Rc 25a C377i
Cos-16 4quot; Jis 20k Rf
1343575 Ja3-16 Bsp R 1/2quot;
Ef73