

Unitronics

Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Unitronics** Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Unitronics Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.



rn	Aıklama
Vision V430-J-T2	
V120-22-UN2	V120-22 OPLC,12/12IO,2 UNIV
V200-18-E3XB	IO MODULE,18/17IN/OUT,4UNI/AN,IS
450.72.UNT.10	USL-070-B05 HMI 7"
450.71.UNT.10	USC-B5-TR22 PLS 2 AI-10DI , 12 TO- 8 RO
1X2X0,34MM2 BUS CAN UNITRO.2170263	Cable
V570-57-T20B-J	Vision V570 COLOR OPLC, WL,5.7", TOUCH, no Frame
V1210-T20BJ	V1210 COLOR OPLC,12.1", TOUCH, NoB
V570-57-T20-B	V570 COLOR OPLC, WL,5.7", TOUCH
EX-A2X	Expansion adapter, isolated
IO-AI8	8 Analog Input module
IO-TO16	16 digital outputs module
SM35-J-R20	SM35-R20,3.5",12/8 I/O,2A,1HS
SM35-J-T20	SM35-T20,3.5",12/8 I/O,2A,3HS
V200-18-E3XB	IO MODULE,18/17IN/OUT,4UNI/AN,IS

V200-18-E1B	IO MODULE,16/10 IN/RELAY OUT,ISO
V200-18-E1B	IO MODULE,16/10 IN/RELAY OUT,ISO
V130-33-RA22	V130-RA22 OPLC,WL DIS,12/8 IO
V100-17-CAN	MODULE,CANbusINTERFACE FORV130
V200-18-E3XB	IO MODULE,18/17IN/OUT,4UNI/AN,IS
UIA-0800N	UniStream IO, 8AI,NO ISO
UID-0808T	UniStream IO 8DI,8TO,24V
V570-57-T20B-J	V570 COLOR OPLC,WL,5.7",TOUCH - NO LCD FRAME
EXL-CAB1000	CABLE,XL-EXP-PLC,RJ45-RJ45,10m
BUS PB FD P A - : 2170822	
V130-33-T38	V130-T38 OPLC,WL DIS,22I,16O,2A
EX-RC1	REMOTE I/O ADAPTER
UNITRONİCS V200-18-E3/4XB	
V200-18-E3XB	IO MODULE,18/17IN/OUT,4UNI/AN,IS
V200-18-E4XB	IO MODULE,18/17IN/TOUT,4UN/AN,IS
IO-D16A3-TO16	XL-EXP,16I,3AI,16TO
IO-TO16	16 digital outputs module
EX-D16A3-TO16	XL-EXP,ADPTER,16I,3AI,16O
IO-AI4-AO2	4 in / 2 out analog module
EX-A2X	Expansion adapter,Isolated
V200-18-E3XB	IO MODULE,18/17IN/OUT,4UNI/AN,IS
V200-18-E4XB	IO MODULE,18/17IN/TOUT,4UN/AN,IS
USP-070-B08	UniStream 7" HMI PANEL B08
UIS-04PTN	UniStream IO, 4PT100
UID-0808R	UniStream IO 8DI,8RO,24V
UIA-0006	UniStream IO, 6AO,NO ISO, 24V
V700	
V570 TOUCH SCREEN	
X-A2X I/O EXPANSİON MODULE	
Io-T016 I/O	
Ex-D16a3-To16 I/O.	
280-18-B20b Plc	
280-18-B20b	
M90-R1-Can	Operator Panel
V290-19-B20b	5.7" Monochrome Touchscreen
Eu210154 Ex-A2x	

Vision120-22-R34	PLC, Vision, 2.4 "b / w LCD, 20DI, 12RO, 2AI 11.04.19 Item No .: 111473 µ-PLC with graphic display and keyboard: - Display: FSTN LCD (128x64) 8x20 characters Keyboard: 16 membrane keys - Program size: 448 kWorte, real-time clock - 1 RS-232 (RJ11), 1 RS-485 (RJ11) - I / O extension (RJ45), MODBUS and GSM support Zung - Panel or DIN rail mounting, front IP65 - Including programming software and serial cable - 20 digital inputs (24VDC), of which 3 as counter (10kHz, 32 bit) - 12 relay outputs (230VAC / 5A, 10Hz) - 2 inputs as analog inputs (10Bit; 0-10V, 0 / 4-20mA) or as 2 additional digital inputs (24VDC) - Power supply 24 VDC - incl. programming software and cable, assembly instructions erial
Io-Ao6x	
Jz10-11-R16 - Obsolete , Alternative Is Jz20-J-R16	
I0-Di16 I/O	
V130-33-R34	
V280-18-B20b	Product: Unitronics Vision V280-18-B20B
Io-Di8-Ro8	
V130-33-T2	10 DIGITAL INPUTS
111625	
112270 Jz-Prg	
109564	
107881	
Acs355-03e-12a5-4.3f/3f	DRIVER
V200-18-E2b	PLC I / O module, 16DI, 10RO, 4TO, 2AI, 2AO Item No .: 106929 Snap-in I / O Module: - 16 digital inputs (24VDC) of which 2 as Counter (10kHz, 16 bit) isolated in groups of 8 inputs. Isolation 1KV - 4 digital outputs (24VDC / 0.5A) thereof 2 as high speed output (max. 50kHz) isolated in a group of 4 outputs , Isolation 1KV - 10 relay outputs (230VAC / 5A, 10Hz) - 2 analog inputs 10bit (0-10V, 0 (4) -20mA) - 2 analog outputs 12bit (0-10V, 0 (4) -20mA)
M91-2-R2c	
2170334	
V120-22-R1	
Eu210068 Io-Pt400	
Io-Lc1	
Io-Ro16	PLC remote I / O, 16RO (24VDC) Item No .: 106948 - Relay outputs (230VAC / 24VDC, 10Hz): 16 outputs - Relay type: SPST-NO - 5A resistive load, 1A inductive load - DIN rail mounting - Dimensions: 80mm x 93mm x 60mm, 125g - only in conjunction with EX-A1, EX-2AX u. EX-Maxi Modules - Supply voltage 24VDC
117824 Vision130-33-Ta24	
121358	
101262	
V200-18-E3xb I/O	
120336 Jz10-11-Un20	

Jz-Rs4	
Sm35-J-R20	
Io-Di16	PLC remote I / O, 16DI (24VDC) Item No .: 101262 - Digital inputs (24VDC): 16; - counter (10kHz, 16 bit): 1; - DIN rail mounting - only in conjunction with EX-A1, EX-2AX u. EX-Maxi Modules - Supply voltage 24VDC - Dimensions: 80mm x 93mm x 60mm, 141g
M91-2-R1	
126642	
101264	
107882	
Eu210045 , V200-18-E3xb	
V130	PLC Operator Panel
01 M91-2-R34 Serie Oplc	
Io-Ai8	
Io-Atc8	
Li2ycy Pimf 3x2x0,Lapp0034041	
Ex-A2x (Successor To Ex-A1)	PLC expansion adapter, for PLC I / O module, insulated Art. No .: 126453 - Extension adapter for M90 / 91 / Vision series - incl. cable (1,0m) - supports up to 8 extensions - Connect using the supplied cable proprietary bus - Supply voltage 12 / 24VDC - Dimensions: 80mm x 93mm x 60mm, 125g
114157 Jz-Rs4	
Jz10-11-T40	
V1040-T20b	10.4" COLOR TOUCH SCREEN, TFT, USB PROGRAMMING PORT, MICRO SD CARD SLOT, 800 X 600 RESOLUTION (SVGA), 65K COLORS, WHITE LED-ILLUMINATED BACKLIGHT,9 PROGRAMMABLE FUNCTION KEYS, UP TO 1024 I/OS
121354	