

Valmatic

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Valmatic Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Valmatic T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
3420-Ar-Hp500	INlet size : 2" Outlet size : 1" Orifice size : 7/32" GPM : 2200 - 50000 MWP : 500 Height : 132" Width : 12" Weight : 135 P/N : 21056722E
3410ar-116.3	INlet size : 1-"NPTF Outlet size : 1/2" NPTF (1" Size Supplies Std. with 1/2" & 3/4" Bushing Included) Orifice size : 1/16" Pressure rating : 300 psi Cast iron ASTM A126 body fusion bounded epoxy coated blue (ext) Stainless steel triem & float FM approved
15A.3 1"	
1906A.1XP	
201C.2	
8812W.1	
9808T	
9810T	
9820T	

API 594/ASME B 16.34	
ASV-T-015-AL050	
ASV-T-025-AL063	
Model 22.3	
SPK1-108S	
VM-8800W 1 1/4"	
VM-8800W 2"	
VM-8800W 6"	
8804w	
7208	VALVE
Å8803w.1gcc	
Vm-8800w 2ã39;Å39;	
A510hp-3gcc	
8806w.1	
Vm-8800w 6quot;	
Model: 22.7 (Obsolete - Replaced By 22.9)	
Vmc-25 Size: ¥; Quot; Max. Pressure: 300 Psi	
Vm-8800w 4quot;	
¥8a.1xp	
8800 Dual Disc® Grooved End - UI/Fm Approved "12	
Val-Matic 22.4	
Vm-8800w 2 1/2ã39;Å39;	
Vm-8800w 1 1/4ã39;Å39;	
22.9	
21056108j	582 Two-door wafer check valve size 8" / ANSI Class 150 Body : Ductile iron with Buna-N resilient seat molded to body Doors : Aluminum Bronze ASTM B148 Disc, Seat : Stainless Steel Spring: Stainless Steel
22.7gcc	
22.7	

Val Matic 7225	
Val Matic 7203	
Ã8804w.1gcc	
8808w.1	
Val Matic 7204	
A512hp-3gcc	
8808w	
5806rxp	
202c.2	VALVE AIR RELEASE AND VACUUM 20-300PSI
Trim :S.S 316 Body :A 216	
Ã189;? Aus Edelstahl	