

Valves

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Valves Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Valves T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunulmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
Electric motor for shut-off valves - electric driv	(electric motor asynchronous), 3-phase, AC Explosion-proof hydrogen-rich gas / synchronous generator - 0.37 kW, 1500 rpm, star connection For adjustable shut-off valves of tank farms type: OPEN FIELD (3791-41-07503715-98; connection dimensions 100 * 100.) Purpose and working environment: open valves, close. Petroleum products, gas reduction; for shut-off valves DN 50 mm Degree of protection IP65, explosion-proof 1ExdIICT1 / 1ExdIIBT5
Electric motor for shut-off valves - electric driv	(electric motor asynchronous), 3Phase, AC; 5.5 kW, Explosion-proof-Hydrogen-rich gas / Synchronous Generator - 1500 rpm, Star connection type For adjustable shut-off valves of tank farm Type: OPEN FIELD (3791-41-07503715-98; connection dimensions 285*285 Purpose and working environment: Opening, closing valves. Petroleum products, gas reduction; For shut-off valves DN 500, DN 400 Degree of protection IP65, Explosion proof 1ExdIICT1/1ExdIIBT5
Electric motor for shut-off valves -	(electric motor asynchronous), 3Phase, AC; Explosion-proof-Hydrogen-rich gas / Synchronous Generator - 4kW; 1500 rpm, Star connection type For adjustable shut-off valves of tank farm Type: OPEN FIELD (3791-41-07503715-98; connection

electric driv	dimensions 200*200 Purpose and working environment: Opening, closing valves. Petroleum products, gas reduction; DN 350 mm for shut-off valves Degree of protection IP65, Explosion proof 1ExdIICT1/1ExdIIBT5
Electric motor for shut-off valves - electric driv	(electric motor asynchronous), 3Phase, AC; Explosion-proof-Hydrogen-rich gas / Synchronous Generator - 1.5kW; 1500 rpm, Star connection type For adjustable shut-off valves of tank farm Type: OPEN FIELD (3791-41-07503715-98; connection dimensions 122*122 Purpose and working environment: Opening, closing valves. Petroleum products, gas reduction; For shut-off valves DN 100 mm, DN 250 mm Degree of protection IP65, Explosion proof 1ExdIICT1/1ExdIIBT5
BVW-1-050	Butterfly valve BVW-1 Zw.Fl. DN50 21bar
BVW-1-065	Butterfly valve BVW-1 Zw.Fl. DN65 21bar
BVW-1-150	Butterfly valve BVW-1 Zw.Fl. DN150 21bar
Butterfly valve BVT-1-025	
Butterfly valve BVT-1-032	
Butterfly valve BVT-1-040	
BALL VALVE VSP/2V" (DN50) PN16	AISI 316L / AISI 316L -FF GAS -PTFE/VITON -max 120 C -for. " I " -ATT. 63/90 -DE -DX- CA code 3KFC1QA2AEE3
Db-Da71f/24	