

Valvole Hofmann

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Valvole Hofmann Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Valvole Hofmann T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
FP940406CG	VALV.FP94 DN040 SERV. 70 NC BSPP P.max:8 bar-T.max:195 C°- Rating:PN25 << If ATEX required, CERT.ATEX must be bought separately Pressure & temperature limited by body rating
FP940155CS	VALV.FP94 DN015 SERV. 50 NC SOCKET WELD P.max:21 bar-T.max:195 C°-Rating:PN25 << If ATEX required, CERT.ATEX must be bought separately >> Pressure & temperature limited by body rating
01-FP-02BP DN25 PN16	
01-FP-02BP DN15 PN16	
KIT.M8080	KIT GUARN.M8 DN080 WITHOUT MEMBRANE
MD2040-2	MEMBRANES SS2 430 mm NBR 70 SHORE SV5639NB (20 holes) CLOTH ON THE LOWER SIDE
FP940255CG	VALV.FP94 DN025 SERV. 50 NC BSPP P.max:8 bar-T.max:195 C°- Rating:PN25 << If ATEX required, CERT.ATEX must be bought separately >> Pressure & temperature limited by body rating
KIT.M8065	KIT GUARN.M8 DN065 WITHOUT MEMBRANE
MD4795-3	MEMBRANES SS3 360 mm NBR 70 SHORE SV5639NB (16 holes) CANVAS ON THE LOWER SIDE
	VALV.M9S DN040 3WAY SERV.360 NC straight way SEGN.6-30 GGG40.3

M9S04033CT/L	LIN. SOFT DIVERTING EU NC 84818071 P.max:25 bar-T.max:210 C-Rating:PN25 -T.min:-15 C -Class:VI << If ATEX required, CERT.ATEX must be bought separately >> KV straight way:24-KV angle way:24 Pressioni e temperature limitate da rating del corpo/Pressure & temperature limited by body rating
LC0155SCG	VALV.LC DN15 SERV. 50S NC SS316 BODY BSPP P.max:16 bar-T.max:185 C-Rating:PN16 << If ATEX required, CERT.ATEX must be bought separately >> Pressioni e temperature limitate da rating del corpo/Pressure & temperature limited by body rating
M802013C	VALV.M8 DN020 2WAY SERV. 275 NC SEGN.6-30 BODY GJS-500-7 EQP SOFT P.max:25 bar-T.max:210 C-Rating:PN25 -KV:6,4-T.min:-10 C -Class:VI << If ATEX required, CERT.ATEX must be bought separately >> Pressioni e temperature limitate da rating del corpo/Pressure & temperature limited by body rating
Ersatzteile	POS. 3+4+5 und 7 je 1 Stk.
FP940407CB	VALV.FP94 DN040 SERV.100 NC FLG DRILL PN25 P.max:21 bar-T.max:195 C-Rating:PN40 << If ATEX required, CERT.ATEX must be bought separately >> Pressioni e temperature limitate da rating del corpo/Pressure & temperature limited by body rating
10300AM-5063+SVEL24V	SOLENOID VALVE 3/2 AA-0184C NC 1/8 W/O COIL MANUAL DRIVE CLOSE TAP + REG.UNID.CARICO + DOS.SVE SCARICO+LED
SRD991-BDFT7EA4NY-V06	POSIT.LIN.SMART IN: 4-20mA w/o communication ATEX:II 2G EEx ia IIC T4, IP66 +FEEDBACK 4-20mA +Inductive switches
LEXG-J	MANIFOLD + GAUGES FOR SA POSIT. SRD991/SRI990
EBZG-K+EBZG-A	STAFFA POSIZ. AL PILLAR YOKE SRI990/SRD991/SRD960 + FEEDBACK LEVER STROKE 8 - 70 mm (EBZG-A INCLUS DANS EBZG-K)
DA-0051	BOBINA / COIL U1 3,5 W 24VDC
FP940407AB	VALV.FP94 DN040 SERV.100 NO FLG DRILL PN25 T.max:195 C-Rating:PN25 << If ATEX required, CERT.ATEX must be bought separately >> Pressioni e temperature limitate da rating del corpo/Pressure & temperature limited by body rating
CL-302A18T6+AM-5063-2L24V	SOLENOID VALVE 3/2 CL-302A NC 1/8 AL - RILSAN PIPE 4x6 W/O COIL CLOSE CAP + UNID.REG.1/8 INPUT & OUTPUT ON VALVE NC or NO +LED024VAC/DC +MANUAL OVERRIDE
LC01658CG / DN15 PN16	
FP940657CS / DN65	
FP940255CG / DN15 PN17	
FP940406CG / DN40 PN25	
M806533C	
FP940155AG	VALV.FP94 DN015 SERV. 50 NO BSPP T.max:195 C-Rating:PN25 << If ATEX required, CERT.ATEX must be bought separately >> Pressioni e temperature limitate da rating del corpo/Pressure & temperature limited by body rating
M808023C	VALV.M8 DN080 2WAY SERV. 430 NC SEGN.6-30 BODY GJS-500-7 EQP SOFT P.max:8,6 bar-T.max:210 C-Rating:PN25 -KV:100-T.min:-10 C -Class:VI << If ATEX required, CERT.ATEX must be bought separately >> Pressioni e temperature limitate da rating del corpo/Pressure & temperature limited by body rating
I/P converter IPN420-0220	
	SERV.100 NC FLG DRILL PN25 FP940407CB 18 bar ACTUATOR AISI 304

VALV.FP94 DN040	heavy work to the conditions should be appropriate PTFE AND FPM
VALV.FP94 DN040	SERV.100 NC FLG DRILL PN25 FP940407AB 18 bar ACTUATOR AISI 304 heavy work to the conditions should be appropriate PTFE AND FPM
M9S10021AD/PROSM	VALV.M9S DN100 2WAY SERV.430 NO SEGN.3-15 GGG40.3 EQP MET. BELLOW EU NC 84818071 T.max:350 C°-Rating:PN16 -KV:150-T.min:-20 C° -Class:IV << If ATEX required, CERT.ATEX must be bought separately >> Pressioni e temperature limitate da rating del corpo/Pressure & temperature limited by body rating ==Tag PCV-400==
SRD998-HBD0B0S1SA17A1	POSIT.LIN.SMART SA IN: 4-20mA HART BASIC DIAGN. STD PNEU. FS 1/4N-M20x1.5 ATEX:II 2G Ex ia IIC T4/T6 Gb, II 1D Ex ia IIIC T100 C Da, IP66 +GAUGES
KIT.RER	KIT ASSEMBLY+SET POSITIONER (COPPER PIPE+BRASS FITTINGS)
KIT.FRAWR	KIT FILTER REG.1/4GAS AL+PLASTIC COPPER PIPE ASSEMBLED
HZ9P400618	GAUGE 3240 P1/8 GC 0-6 BAR-M / PLASTIC
PP12X A0VB	PL2006030
M803213C	VALV.M8 DN032 2WAY SERV. 275 NC SEGN.6-30 BODY GJS-500-7 EQP SOFT EU NC 84818071 P.max:23,6 bar-T.max:210 C°-Rating:PN25 -KV:17-T.min:-10 C° -Class:VI << If ATEX required, CERT.ATEX must be bought separately >> Pressioni e temperature limitate da rating del corpo/Pressure & temperature limited by body rating
FP940325CG	VALV.FP94 DN032 SERV. 50 NC BSPP P.max:5,2 bar-T.max:195 C°-Rating:PN25 << If ATEX required, CERT.ATEX must be bought separately >> Pressioni e temperature limitate da rating del corpo/Pressure & temperature limited by body rating
M805033C	VALV.M8 DN050 2WAY SERV. 360 NC SEGN.6-30 BODY GJS-500-7 EQP SOFT EU NC 84818071 P.max:19 bar-T.max:210 C°-Rating:PN25 -KV:39-T.min:-10 C° -Class:VI << If ATEX required, CERT.ATEX must be bought separately >> Pressioni e temperature limitate da rating del corpo/Pressure & temperature limited by body rating
KIT.M8050	KIT GUARN.M8 DN050 stem Ø12mm new & stem Ø10mm old WITHOUT MEMBRANE
MD4795-3	MEMBRANE SERV.618cm2 360mm (16 holes) SS3 NBR 70 SHORE +INSERTO TESSILE
M9S04011CD	VALV.M9S DN040 2WAY SERV.275 NC SEGN.3-15 GGG40.3 EQP SOFT EU NC 84818071 P.max:8,5 bar-T.max:210 C°-Rating:PN25 -KV:24-T.min:-15 C° -Class:VI << If ATEX required, CERT.ATEX must be bought separately >> Pressioni e temperature limitate da rating del corpo/Pressure & temperature limited by body rating
Pneumatic Control Valve	M9S04011CD DN40 PN25 air supply 3÷15 psi
GP0156C	VALV.GP DN015 SERV. 70 NC BODY GJS-500-7 FLG PN25 P.max:25 bar-T.max:195 C°-Rating:PN25 << If ATEX required, CERT.ATEX must be bought separately >> Pressioni e temperature limitate da rating del corpo/Pressure & temperature limited by body rating
KIT.M8025 VALVOLE HOFMANN REPAIR KIT	
HOFMANN M80 PROPORTIONAL VALVE DIAPHRAGM	
M808023C	VALV.M8 DN080 2WAY SERV. 430 NC SEGN.6-30 BODY GJS-500-7 EQP SOFT P.max:8,6 bar-T.max:210 C°-Rating:PN25 -KV:100-T.min:-10 C° -Class:VI << If ATEX required, CERT.ATEX must be bought separately >> Pressioni e temperature limitate da rating del corpo/Pressure & temperature limited by body rating

FP940255CG	VALV.FP94 DN025 SERV. 50 NC BSPP P.max:8 bar-T.max:195 C°- Rating:PN25 << If ATEX required, CERT.ATEX must be bought separately Pressure & temperatures limited by body rating
MD2040-2	MEMBRANE SERV.791cm2 430mm (20 holes) SS2 NBR 70 SHORE +INSERTO TESSILE
KIT.M8050	KIT GUARN.M8 DN050 stem Ø12mm new & stem Ø10mm old WITHOUT MEMBRANE
MD2039-1	MEMBRANE SERV.306cm2 275mm (12 holes) SS1 NBR 70 SHORE +INSERTO TESSILE
1204-599	
KIT.M8050	KIT GUARN.M8 DN050 stem Ø12mm new & stem Ø10mm old WITHOUT MEMBRANE
DIAPHRAGM SEAL WITH BLUE CLOTH DIAMETER: 280 MM WITH 12 HOLES	
Mnt005g1/4	
Fpmd02003cg	
Fv 1302	
Fp940155cs/K	
Fp940406cg	VALV.FP94 DN040 SERV. 70 NC BSPP P.max:8 bar-T.max:195 C°- Rating:PN25 << If supplied with CERT.ATEX - To be bought separately - T.max: 180 C°>> Pressioni e temperature limitate da rating del corpo/Pressure & temperature limited by body rating
Sv 1312	
Service Kit For M803213c	
Ma005g1/4pro/Ener	
Lv 1927a	
M804013c	
M801511c	
Fv 2405	
Sv 2408-3	
Fp940326cg	
Sv 241a-13	
Lc0155cg	
M802511c	
Md2038-0	
Lexg-Xn	
Sv 130-6	
Fp940506cg	
Sv 2408-1	
Sv 120-2	
Fv 1309	

Fa0206ct/T
Gm9s032+lh016/24d/M Kv:10 - On/Off Vana Dn32
M805013c Dn 50
Sv 2411c-12
M803213c
Sv 1302-1
117843
Fp940255cs/P S/L
Service Kit For M9504013cd
M802013c
Dn025
Sv 2401-4
Lh010/230/Ip65
Sv 2405-3
Sv 130-4
Fp94 Dn025
01fp
117886
01fp Dn40
Lv 1927b
Sv 2411a-12
Lc0205cg
Sv 2401-2
Fp940205cg
Res1 4-20 Ma
Service Kit For M806533c
Gm9s040+lh016/24d/M Kv:16 - On/Off Vana Dn32
Fp940508cg
Kit.Bfp94.50.7
Shaft (Axle) For Dn 32 Cod : M803213c
Fp94 Dn80
Sv 130-8
Shaft (Axle) For Dn 65 Cod : M806533c
Mp9-2 Nc

Sv 130-3	
Fp940206cg	
Epc010-244 W/Y 52/10 6-8 Bar	
Sv 2411b-1	
Fp940256cg	
Sv 2411c-3	
Sv 2411a-3	
08400/2004 Cod:Fp940205 Cg Valv Fp 94 Dn 25 Serv 50 Nc Psmx 12 Bar Tmax190 C	
Gp0156c/T	
Sv 2411c-8	
M802011c	
Gm9s020+lh010/24d/M Kv:6 - On/Off Vana Dn20	
Fv 141-1	
Gp0326c	
Kit.M9025t/Es	
Sv 2411c-16	
Dn25 Fp94 4-20ma Ip 24vdc, 0-10v	
M9s1252l4cd/P	
Md4795-3	
Kit.Bpfp94.15.5	
Sv 2411a-4	
Kit.M8032	
Fv 2411a	
Fp940256dg	VALV.FP94 DN025 SERV. 70 DE BSPP T.max:195 C°-Rating:PN25 << If supplied with CERT.ATEX - To be bought separately - T.max: 180 C°>> Pressioni e temperature limitate da rating del corpo/Pressure & temperature limited by body rating
243332	
Kit.Bpfp94.32.6	
Fp940407cg	
Lv 2920	
Fv2414c-1	
Fp940507cs/T	
Fp 940155 Cs / K	
Shaft (Axle) For Valvole Hofmann Dn 50 Cod : M805013c	
Fp94 Dn65	

Sv 1302-2	
Sv 2408-4	
Sv 2411b-13	
Din:2633 Pn16 Flanch	
Fp940507cg	
Sv 2411c-11	
Sv 130-10	
Sv 2401-3	
Kit.M8065	
Gm.Rm.1/4	
117868	
Sv 130-5	
Ap0d	
Sv 2411c-2	
Fp94 Dn020	
M805013c Dn 15	
Kit.Bfp94.25.6	
Sv 2411c-13	
Eqweqwe	
Sv 2401-1	
Kit.Bfp94.40.7	
Fv 120	
Kit.Bfp94.20.6	
M803211a	
Sv 2411a-1	
Fv 2401	
Lh025/230	
Fv 2408	
Md2039-1	MEMBRANE SERV.306cm2 275mm (12 holes) SS1 NBR 70 SHORE +INSERTO TESSILE
Sv 2405-4	
Sv 2405-2	
M9s05031cdm	
Sv 130-9	
Sv 2411b-11	
Fa0807ct/T 666.40.3	

01 Fp 02 Bp Dn32
Fp940255cg/Tke
Sv 2411c-5
Sv 2411a-15
Shaft (Axle) For Dn 40 Cod : M9504013cd
Sv 2411a-11
Sv 2411b-14
Riii0201r/Cx6ep
Fa0807ct/T
Fv2414b-1
Kit.M9040
Sv 2411c-6
Kit.Bpfp94.65.7
Sv 2408-2
Fp940155cg/K
M801513c
Kit.M8050
M9s1502l4cd/P
401.
M9s08023cd
600
M802503c
Fp940406cs
M9s15012l4cd/P
Eqweqwe/Dsad
M805033c
Sv 2411c-15
Sv 2411c-14
Ap3d
Mn005g1/4
117853
Sv 2411b-15
Sv 2411a-16
Sv 2411c-4
Sv 2405-1

Pd
Fp940325cg
Sv 130-1
Sv 2411a-2
Sv 2411b-2
Shaft (Axle) For Dn 50 Cod : M805013c
M803213c (S/N:07677/2014)
Sv 2411b-16
Sv 2411c-1
Service Kit For M805013c
Ipn420-0212
Sv 130-2
Sv 2411a-14