

Vem Motors

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Vem Motors Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Vem Motors T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
B5 Ff215	
K210 100L	
185567	Elektromotor
K20R 80 K 2	
K21R 112 M8	
MEL 2-3-4-5 VEMTYP:K21R 200 L4HW HID.MOT	
	Technical specifications: Pos. 10 - your pos. 1 LEWA metering pump type LDB2 Element: a, b Request data Delivery fluid carbon dioxide Operating temperature [° C] 10 Density [g / cm³] 0.89 Viscosity [mPas] 0.09 Steam pressure [bara] 45.10 Solids (proportion / grain size max.). [%] / [mm] - / - required dosing flow

Dosierpumpe LDB2

[l / h] 4.00 total Operating pressure
pressure side [bar] 200.00
Operating pressure suction side [bar]
..... 60.00 Environmental conditions
..... Installation in the
explosion-proof Area Constructive
execution Engine
..... LDB Gear reduction
..... 1: 12.50 Eccentric
offset [°] 0/180
Stroke frequency [min-1]
..... 22 - 109 Stroke length
..... [mm] 15
Stroke adjustment type
..... manually Pump head
..... 2 x
membrane pump head heatable M910S Displacer Ø
..... [mm] 2 x 8 Dosing
flow at operating pressure [l / h]
5.58 max. permissible operating pressure
[bar] 200.00 Diaphragm rupture signaling
..... CONTACT MANOMETER CO2
Valves suction side [Type / DN]
..... 1 ball valve / 5 Valves pressure side
..... [Type / DN] 1 ball valve / 5
Setting internal DBV [bar]
250.00 Minimum design pressure pressure line [bar]
..... 200.00 Required minimum suction flange
pressure [bara] 45.1 Pipe connection
suction side [DN / PN] ISO G 3/8
fem. Pipe connection pressure side [DN / PN]
..... ISO G 3/8 fem. Connection heating / cooling
jacket G 3/8 Materials in
contact with the fluid Pump body
..... 316 / 316L
Membrane PTFE
Valve seat suction side
1.4122 Ball valve suction side
1.3541 Valve seat pressure side
..... 1.4122 Ball valve pressure
side 1.3541 Page 5 of 5 Offer
no. P12-1003758-00 LEWA GmbH, Ulmer Strasse 10, 71229
Leonberg, Phone +49 7152 14-0, lewa@lewa.de,
www.lewa.com Drive.....
..... DS engine Make
..... VEM
Nominal power [kW]
..... 0.55 Nominal speed [1 /
min] 1360 Type of protection (explosion
protection) - Degree of
protection
..... IP55 Mains voltage
..... [V] 400 Mains
frequency [Hz]
50 Size
080 Design
..... B14 / V18 FU - operation
..... [Hz] 10.1- 50.0
Miscellaneous

 approx. Weight pump [kg] 90
B21R 8 G 2 MLEN VB IGR115 TPM140	
K21 R 160L 6 model	-FRONT COVER IMB5: 4 pieces - -BACK COVER IMB5: 4 pcs
SRPZH76B	No : 611337 / 026-07 n2(min-1) : 50 / Mb2=3666N ISD : V6 680 SHC/PAO 29L MATERIAL NR : 7669601 Engine Label Information: TYPE : SRPZH 76B ARG 180S 6 TWS WE KR HW 9,0 PS / 6,6 kW cos 0.80 Y 400 V 14A I _{max} 38 985/50 min- 1/r.p.m. 50Hz/c/s IP 55 M _{max} = 190/3666Nm I=19,69 Rt.60 C
SRPZH 76B ARG 180S 6 TWS WE KR HW 9,0 PS	6,6 kW cos 0.80 Y 400 V 14A I _{max} 38 985/50 min-1/r.p.m. 50Hz/c/s IP 55 M _{max} = 190/3666Nm I=19,69 Rt.60 C
K21r 112 M4. By W41r112m4h	
Srifn46c71-B21g100 L6	
W21rá;63á;Ká;2	
Vem Kr21r315l6-4 L Ns LI Hw Engine Front Cover	
W21rá;71á;Ká;6	
P/N K21r100l4	
W21rá;280á;S8	
W21rá;71á;Ká;2	
530441	
B21r90s4 H Keb/1 Dod / 9985	Please look at the attachement
K21r 63 K 4 H Dod / 6840	
Repair Kit And Springs (For Pneumatic Valve Vem214)	
03944103 Spen 160l 4 Tpm	
Vem S11p315lx6 Ns VI Hb Hw Engine Front Cover	
099 603/0005 H K21r	
W21rá;90á;L8	
W21rá;71á;Gá;6	
Asenkron	ASENKRON MOTOIR IP55 50 HZ S1 1.1 KW 955 RPM-IE3 W41R 90LHRHPTC IMB14FT115
W21rá;160á;M8	
Kmer B90l4 347743	

N-Ls Kpr 180	
Ie2-We1r 90 Lw4	
Arc315I8 LI Tws II Hw	
4846 413 3640	
Kunststofflufter 3.02 Mit Befestigungsteil Fur Motor K21r 132 Sx 2	
W21rá;100á;Lá;8	
Vem K21r 112 M4 H 5081	
W21rá;90á;Sá;8	
0102942f Type:Y21r315mn9vltwsil	
Mot. Nr: 5716987/739 Type: Kmer 132 M4 Ac P	
Type: K11r 315 S4 LI Hw 175 Ps / 132 Kw - Cos 0,86 - ? 440v ? 216a ? 1780 Rpm ? 60 Hz ? Ip 55	
Kper 80 G4 5031	
B21r 80 G4 Str Mb Dsd	
Kper 90 L2 Ex E Ii T3	
Repair Kit And Springs (For Electrovalve Vem306)	
W22rá;355á;L2	
Ie3-W43r 225 S4 Tpm Hw	IE3-W43R 225 S4 TPM HW 37kW, 1475min-1, 400 / 690V, D / Y, 50Hz, IN B3 - IP55, Th. Class 155 (F / B), operating mode S1, rating plate de / en, available power at Coolant temperature 45 ° C and installation altitude 1000m: 35.1 kW Color system 01 moderate (KK C2), RAL 7031 blue gray IEC / EN 60034-1 Coolant temperature 45 ° C Vibration severity level A 1 set of PTC thermistors Easy storage Fixed bearing N side Balance with half feather key standard documentation Engine no. 9053203 with + 45 ° C ambient temperature
W21rá;315á;Lx8	
177b8313 1.5kw	
S11h 280s 6 VI Hw	
Mm11044-Pp	
W21rá;280á;M8	
K21r 225 M4 Tws Hw , Vem Ie3-W41r 225 M4 Tpm Hw B3	

W 21rá;80á;Gá;8	
M21r 90 S2t	
Kmr 90 L4r	
Mot.Nr: 15119322 Type: K11r180l4 1765 U/Min	
W 21rá;315á;My8	
Type :K210 112 M 12-6l	
W 21rá;225á;M8	
Kper 225 M4 P Fws Ns,45kw,1465 Rpm	
W 21rá;56á;Ká;2	
Vem K21r 80 G 4 H 0,75 Kw	
601 8742 E1	
M21r 90 L 4t	
Ie211404030001	
Fbi Bg 200	
K21o 80 G 4 Bah Fds-K Ts140/2306	
K21r 90 L4 - , By Ie211004030001	
22 Kw 300 U / Min	Flanged
Vem-Motors-Verlõ;Ngerung-F3;R-Fbi-Zarge-Istanbul-Turkiye	
W 21rá;56á;Ká;4	
Vem Ie3-W41r 225 S4c Tpm Hw B3	
W 21rá;180á;L8	
7aa100l04k 2.2 Kw 1420	
Typ (Vem): K21r 63 G 4	Modification.3: H Th.K.155 TS140 El.Ausf. : 230: 220-240 / 400: 380-420 V 275: 255-290 / 480: 440-500 V D / Y 50/60 Hz Design: IP55 IM B14 FT75 Power: 0.18 kW 0.21 kW S1 n (syn): 1500 min ⁻¹ 1800 min ⁻¹ Color: FS01: KK C 2 RAL 7031: blue gray silk matt Power-Sch: VEM ALU
5783302	
Vem Ie3-W41r 225 M4 Tpm Hw B3	
K21r 132 Sx 2t Fds Ts140/3931	
Ie3-W41r 250 M4 Ee Tpm Hw	

W21rá;71á;Gá;4	
Kper90I2	
K21r 71 G4h	
Ie1 K21r 132 S4	
21r 90lv4 / B62 230/400v, 7.4/4.3a	
Ie2-We2r 180l 6 Tpm Hw	
4301 373741-13 Å 9978	
Maã223;E: 20x12,5x32	
180436 / 0034	
V1ff215 Ip55 /Mbr/	
W21rá;315á;M8	
Srifn86c22.4 Motor Bu1g 225 M4	
Vem Ie3-W41r 160 M4 Tpm Hw	
0-342-A-12	
Keper225 S4 Tws	
K11r 200 Lx2 Tpm Hb Kv Hw	
W21rá;315á;S8	
43219103 / Ie3-W41r 180m 2 C St Tpm Hw	22.00 kW, 2975 rpm, 400/690 V D / Y, 50 Hz, IM B5 / V1, IP55, th.K.155 (F / B) Rating plate German / Engl. Rating plate: 400 / 690V (zone B) 50Hz 22,0kW 460V (Zone B) 60Hz 26,0kW therm. winding protection 1 set of PTC thermistors copper rotors Housing with 8 threaded holes D-side Color System 01 moderate (KK C2), RAL 7031 blue gray Balance with half feather key according ident.No. 41585003
W21rá;315á;Mx8	
K21r 250m 4 Tws Hw- Ie3-W41r 250 M4 Ee Tpm Hw	
Weir-160-M4 B5ie2 , Ie3-W41r 160 M4 Hw!!!	
Maã223;E: 16x12,5x32	
Arc 315 L8	
Ie3-W41r 225s 4 C St Tpm Hw	Ar nr. 41682603 37.00 kW, 1490 rpm, 400/690 V D / Y, 50 Hz, IM B3, IP55, th.K.155 (F / B) Rating plate German / Engl. Rating plate: 400 / 690V (zone B) 50Hz 37,0kW 460V (Zone B) 60Hz 40,0kW therm. winding protection 1 set of PTC thermistors copper rotors Housing with 8 threaded holes D-

	side Color System 01 moderate (KK C2), RAL 7031 blue gray Balance with half feather key
8221301	
W21r 80 G 4 Ie2	
W21rá;315á;L8	
L11/1 B5rdn For K21r 112 M4 , By W41r112m4h	
W21rá;100á;Lx8	
Front Cover For Mt 315 La-2	
Fbi-Zarge	
Ie2-We2r 132 M6	
K21f 90 L2 Tk	
Ie3-W41r 90 L4.	
0 342 A 15	
K21r 225 S4 Hw , Vem Ie3-W41r 225 S4c Tpm Hw B3	
0102201 A05f	
Ie2-We1r 112 M4 Hw	
W21rá;250á;M8	
No:167171/0012h Type:K21v 315m 4 Ll Tws Hb Il Dl Kv Hw	
Srifn26b9 Motor B21g 90 L4	
W21rá;80á;Ká;4	
W21rá;200á;L8	
W21rá;56á;Gá;2	
Spare Foot For Ie2-W21r 200 Lx6 Tpm Hw	
3 Typ K21r 100 Lz4/8840	
60034 - 1	
Ku2r355m2	
5433502 (2.02)	
K21r 100 L6	
W21rá;132á;S8	

W21rá;225á;S8	
Vem Kr21r315l6-4 L Ns Ll Hw Engine Back Cover	
Voltage: 575/3/60hz. Rpm: 3460 Amps: 5.65- 3.25	
Ie3-W41r 225 M2 Hw	IE3-W41R 225 M2 HW 45kW, 2960min-1, 400 / 690V, D / Y, 50Hz, IM B3 IP55, Th. Cl. 155 (F / B), Operating mode S1, Nameplate de / en, Color system 01 moderate (KK C2), RAL 7031 blue gray IEC / EN 60034-1 Vibration severity level A Easy storage Fixed bearing N side Balancing with half feather key standard documentation
13611403 (K21r 160l 4 Kv Hw)	
W21rá;63á;Gá;4	
Srifn56b8 Motor Arg 160 M-6	
5795802 Zu Motor K21r 315m 4 Il Kty Ll Hw / 193487-03	
K21r 112 M4. By W41r112m4h	
(Ie1)-K21r 132 Sx2t	
W21rá;132á;M8	
W21rá;71á;Ká;4	
Nr: 135908/0020h K21r 132s 4 Hw , Ie211404030001	
W21rá;56á;Gá;4	
W21rá;63á;Gá;2	
P/N K21r315mx4/Ns Ll Tws Kv Hw	
Srifn56c16b200 Motor B21g 90 L6	
Ie3-W41r 80 G2	
K21r 160m 4 Tws Hw Alte Typenbezeichnung/Neue Typenbezeichnung Vem Ie3-W41r 160 M4 Tpm Hw B3/B5	
24035/0037 F Type K11r 280 84 Ns 0w	
Ie3-W41r 160 M4 Hw	
W41r112m4h	
W21rá;80á;Ká;6	
Sped 200 L For Din En 60034-1 Motor No:149017 002 H 28.5 Ps/21 Kw 1465 D/Dk 50 Hzsped 200 L 4 Hw 220	

5433602
5952302 (1.03)
Ie2-We1r 132s 4 Hw
Vem Ie3-W41r 160 M4 Tpm Hw B3/B5
W21rá;160á;Mx8
7718702 Zu Motor K21r 315m 4 Il Kty Ll Hw / 193487-03
5089 K21r 112 M4 Tpm
W21rá;71á;Gá;2
5085 Vem K21r 71 G4 Culus 0815324025904h
0 342 A 07
Kmr 90 L4r By K20r 90 L4
Kper 90 L4 H Ex Ii 2d Extda21
0102201-A05f Type: Y21r280s4nsvltws
Exproof K21r 80 G 2, By Ie3-W41r 80 G2
W21rá;80á;Ká;8
D-Ls Kpr 180/2
79343/0017 F Type K11r 225 M4 0w
K21r 200 L4 - , - Vem Ie3-W41r 225 S4c Tpm Hw B3
Kper 100 L 4 Tpm 140, 217970405
W21rá;63á;Ká;4
K21r 160 L4 Tpm Hw
Motortyp: (Ie1)-K21r 90 L2
Sph 200 M 6
Vem S11p315lx6 Ns VI Hb Hw Engine Back Cover
Srifn56c71 Motor B21g 132 S6
Srifn96c100-A21g 160 L6
W21r 80 G6
136114/ 0019 H K21r 160 L 4 Kv Hw ,

By 13611403 (K21r 160l 4 Kv Hw)
K21r 100 L6-4l
W21rá;112á;Mv8
W21rá;160á;L8
Thermal Board For Motor K21r 180l 4kv VI Hw
Gmfw 1416-32
K21r 80 K 4 1xm20
0-342-A-07
Kper 63 G 4 H Dsd Kns Laip10/ 7679
5,5 Kw 1400 Devirá;
Per 90 S4 Kal140 Tlb960 Codeh/G
Srifn36c45 B21g 112 M 6
(Ie1)-K21r 132 S4 T